


A close-up photograph of two braided sleeves. One is orange and the other is black, both with a distinct woven texture. They are arranged in a way that shows their flexibility and the intricate pattern of the braiding. The background is a plain, light color.

Routing, Protection & Insulation

Braided Sleeving

**HellermannTyton**

## Braided Sleeving

HellermannTyton braided sleeving products provide abrasion and damage protection for hoses, cable assemblies and wire bundles. Braided sleeving products are made in a variety of materials including general purpose polyester, PA66 nylon, flame retardant, fray resistant, high temperature and materials that provide electromagnetic protection.

Available in non-expandable, expandable, split wrap and hook and loop styles, HellermannTyton offers a braided sleeving option for every application. Many sleeving products are also resistant to harsh environments such as chemicals, salts, solvents, de-icing fluids and petroleum products as well as being resilient against UV light. The unique physical weave of braided sleeving makes it flexible but provides enough airflow as to not trap moisture or humidity. Expandable braided sleeving products are designed to expand beyond their nominal size to fit varying bundle sizes and shapes.

Most braided sleeving products are designed to be cut with a hot knife, which sears the edges and reduces the amount of fraying that occurs during the lifetime of the product. For applications that do not allow access to a hot knife, fray resistant versions are available that can be cut with ordinary scissors with minimal fraying. Ends are easily secured with cable ties, electrical tape or heat shrink materials.

### Market Applications

Automotive, Transportation, Industrial Equipment, Electronics, Automation/Robotics, Control Panels, Marine, Machine Tools, General Manufacturing/OEM

### Product Applications

Hose Assemblies, Cable Bundles, Wire Harnesses, Electrical Cables

### SELECTION GUIDE

| Materials Comparison | General Purpose                             |                                                                       |                                            | Flame Retardant                             |                                                              |                                                         |                                             |                                           |
|----------------------|---------------------------------------------|-----------------------------------------------------------------------|--------------------------------------------|---------------------------------------------|--------------------------------------------------------------|---------------------------------------------------------|---------------------------------------------|-------------------------------------------|
|                      | General Purpose Expandable Braided Sleeving | General Purpose Expandable Braided Sleeving Helagaine Dispenser Packs | Fray Resistant Expandable Braided Sleeving | Flame Retardant Expandable Braided Sleeving | Flame Retardant + Fray Resistant Expandable Braided Sleeving | Hook & Loop Flame Retardant Expandable Braided Sleeving | Split Wrap Flame Retardant Braided Sleeving | Electromagnetic Flame Retardant Helagaine |
| Color                | Black or Orange                             | Black                                                                 | Black                                      | Black or Gray                               | Black                                                        | Black                                                   | Black                                       | Tin Colored & Black                       |
| Temperature Range    | -94°F to 257°F                              | -58°F to 230°F                                                        | -94°F to 257°F                             | -94°F to 257°F                              | -94°F to 257°F                                               | -94°F to 257°F                                          | -94°F to 257°F                              | -40°F to 347°F                            |
|                      | -70°C to 125°C                              | -50°C to 150°C                                                        | -70°C to 125°C                             | -70°C to 125°C                              | -70°C to 125°C                                               | -70°C to 125°C                                          | -70°C to 125°C                              | -40°C to 175°C                            |
| Melt Point           | 482°F / 250°C                               | 482°F / 250°C                                                         | 482°F / 250°C                              | 482°F / 250°C                               | 482°F / 250°C                                                | 482°F / 250°C                                           | 446°F / 230°C                               | 392°F / 200°C                             |
| Flammability Rating  | UL 94-V0                                    | —                                                                     | UL 94-V0                                   | UL VW-1                                     | UL VW-1                                                      | UL VW-1                                                 | UL VW-1                                     | UL94-V0                                   |
| ROHS                 | •                                           | •                                                                     | •                                          | •                                           | •                                                            | •                                                       | •                                           | •                                         |
| UL / CSA             | •                                           | —                                                                     | •                                          | •                                           | •                                                            | •                                                       | •                                           | —                                         |
| Other Certifications | FMVSS 302, FAR-25                           | —                                                                     | —                                          | FMVSS 302, Mil-202 FAR-25                   | Mil-202                                                      | Mil-202                                                 | FAR-25                                      | FMVSS 302                                 |
| Recommended Cutting  | Hot Knife                                   | Hot Knife                                                             | Scissors                                   | Hot Knife                                   | Scissors                                                     | Hot Knife                                               | Hot Knife                                   | Shears                                    |
| Abrasion Protection  | M                                           | M                                                                     | M                                          | M                                           | M                                                            | M                                                       | H                                           | H                                         |
| Outgassing           | M                                           | M                                                                     | M                                          | M                                           | M                                                            | M                                                       | M                                           | M                                         |
| Cut Resistance       | M                                           | M                                                                     | H                                          | M                                           | H                                                            | M                                                       | H                                           | H                                         |
| Chemical Resistance  | M                                           | M                                                                     | M                                          | M                                           | M                                                            | M                                                       | H                                           | H                                         |
| UV Resistance        | •                                           | •                                                                     | •                                          | •                                           | •                                                            | •                                                       | •                                           | •                                         |
| Halogen Free         | •                                           | •                                                                     | •                                          | •                                           | •                                                            | •                                                       | •                                           |                                           |
| Expandable           | •                                           | •                                                                     | •                                          | •                                           | •                                                            | •                                                       | —                                           | •                                         |
| Page                 | 4, 6                                        | 5                                                                     | 7                                          | 8                                           | 9                                                            | 10                                                      | 11                                          | 12                                        |


VH = Very High H = High M = Medium L = Low

## Key Benefits

**Easy Application** All braided sleeving products are designed for easy application on bundles while adjusting to fluctuations in bundle size and shape.

**Superior Protection** In addition to abrasion protection, most braided sleeving products also provide protection against chemicals, salts, solvents, de-icing fluids and petroleum products. Specialty braided sleeving models also provide protection against flame, heat and/or electromagnetic interference.

**Enhanced Appearance** Braided sleeving products wrap around varying bundle shapes, sizes and colors to provide an aesthetically pleasing uniform look and appearance.



| Specialty                 |                                           |                                                     |                                                 | Wrap Sleeving               |                                         |                                   | High Temperature                                                                |                                                     |                                                         |
|---------------------------|-------------------------------------------|-----------------------------------------------------|-------------------------------------------------|-----------------------------|-----------------------------------------|-----------------------------------|---------------------------------------------------------------------------------|-----------------------------------------------------|---------------------------------------------------------|
| Electromagnetic Helagaïne | Polyamide 6.6 Expandable Braided Sleeving | Polyamide 6.6 Helagaïne Expandable Braided Sleeving | Plenum Rated Halar® Expandable Braided Sleeving | Split Wrap Braided Sleeving | Hook & Loop Expandable Braided Sleeving | Split Wrap Woven Braided Sleeving | Extreme High Temperature Resin Saturated Fiberglass Expandable Braided Sleeving | High Temperature Nomex® Expandable Braided Sleeving | High Temperature Aluminum Laminated Fiberglass Sleeving |
| Tin Colored & Black       | Black                                     | Gray                                                | Black or White                                  | Black or Orange             | Black                                   | Black                             | Black                                                                           | Green                                               | Silver                                                  |
| -40°F to 347°F            | -49°F to 302°F                            | -76°F to 302°F                                      | -103°F to 302°F                                 | -94°F to 257°F              | -94°F to 257°F                          | -94°F to 257°F                    | -94°F to 1,202°F                                                                | -320°F to 662°F                                     | -76°F to 491°F                                          |
| -40°C to 175°C            | -45°C to 150°C                            | -60°C to 150°C                                      | -75°C to 150°C                                  | -70°C to 125°C              | -70°C to 125°C                          | -70°C to 125°C                    | -70°C to 650°C                                                                  | -196°C to 350°C                                     | -60°C to 255°C                                          |
| 392°F / 200°C             | 491°F / 255°C                             | 491°F / 255°C                                       | 482°F / 250°C                                   | 482°F / 250°C               | 482°F / 250°C                           | 482°F / 250°C                     | 2,048°F / 1,120°C                                                               | NA                                                  | 2,048°F / 1,120°C                                       |
| UL94-V2                   | Non Flammable                             | UL 94-V2                                            | UL VW-1                                         | UL 94-V0                    | UL 94-V0                                | UL 94-V0                          | UL VW-1                                                                         | Non Flammable                                       | Non Flammable                                           |
| •                         | •                                         | •                                                   | •                                               | •                           | •                                       | •                                 | •                                                                               | •                                                   | •                                                       |
| —                         | —                                         | •                                                   | •                                               | •                           | •                                       | •                                 | •                                                                               | —                                                   | —                                                       |
| FMVSS 302                 | —                                         | FMVSS 302                                           | UL 2024, NFPA 262, FAR-25, FMVSS 302            | —                           | FAR-25                                  | —                                 | —                                                                               | —                                                   | —                                                       |
| Shears                    | Hot Knife                                 | Hot Knife                                           | Hot Knife                                       | Hot Knife                   | Hot Knife                               | Hot Knife                         | Scissors                                                                        | Scissors                                            | Scissors                                                |
| H                         | H                                         | H                                                   | M                                               | M                           | M                                       | M                                 | VH                                                                              | L                                                   | NA                                                      |
| M                         | H                                         | H                                                   | L                                               | M                           | M                                       | M                                 | L                                                                               | NA                                                  | NA                                                      |
| H                         | H                                         | H                                                   | M                                               | M                           | M                                       | M                                 | VH                                                                              | L                                                   | H                                                       |
| H                         | H                                         | H                                                   | M                                               | M                           | M                                       | M                                 | H                                                                               | M                                                   | H                                                       |
| •                         | •                                         | •                                                   | •                                               | •                           | •                                       | •                                 | •                                                                               | —                                                   | •                                                       |
| •                         | •                                         | •                                                   | —                                               | •                           | —                                       | •                                 | •                                                                               | •                                                   | •                                                       |
| •                         | •                                         | •                                                   | •                                               | —                           | •                                       | —                                 | •                                                                               | •                                                   | —                                                       |
| 13                        | 14                                        | 15                                                  | 16                                              | 17, 18                      | 19                                      | 20                                | 21                                                                              | 22                                                  | 23                                                      |

Nomex® is a registered trademark of the DuPont Corporation. Halar® is a registered trademark of the Solvay Solexis Corporation.

## Braided Sleeving

General Purpose  
Expandable Braided Sleeving

Designed to adjust and expand to irregular shapes, this general purpose sleeving is lightweight and offers a high tensile strength while still maintaining flexibility. This sleeving is an excellent choice for protecting wire and cable bundles from abrasion, chafing and heat degradation.

## Application

Commonly used in electrical and industrial wire harnessing applications where economy and durability are required for the protection of wires, cables, tubing, bundles and pneumatic hoses.

## Benefits

- Adjusts to twisting and flexing without creating wrinkles, bends or bulges.
- Provides tough, durable protection through a wide range of temperatures.
- Expands up to 150% of flat diameter for easy installation.
- Offers excellent abrasion and cut-through resistance as well as inertness to most chemicals and fungus.



## Material Data


|                       |                                |
|-----------------------|--------------------------------|
| Material              | PET (Polyester)                |
| Flammability          | UL 94-V0                       |
| Operating Temperature | -94°F to 257°F, -70°C to 125°C |
| Melt Point            | 482°F / 250°C                  |
| Abrasion Protection   | Medium                         |
| Recommended Cutting   | Hot Knife                      |



## Product Selection

| Part No.                | Nominal Size |      | Type     | Expansion Range |            |            |            | Color | Reel Length* |       | Weight |       |
|-------------------------|--------------|------|----------|-----------------|------------|------------|------------|-------|--------------|-------|--------|-------|
|                         | in.          | mm.  |          | (Min.) in.      | (Max.) in. | (Min.) mm. | (Max.) mm. |       | ft.          | m.    | lbs.   | kg.   |
| 170-03177               | 1/8          | 3.2  | BSP180   | 0.094           | 0.25       | 2.4        | 6.4        | Black | 225          | 68.6  | 0.41   | 0.19  |
| 170-03000               | 1/4          | 6.4  | BSP140   | 0.125           | 0.437      | 3.2        | 11.1       | Black | 200          | 61    | 0.52   | 0.24  |
| 170-03001               | 1/2          | 12.7 | BSP120   | 0.25            | 0.75       | 6.4        | 19.1       | Black | 100          | 3.5   | 0.77   | 0.35  |
| 170-03002               | 3/4          | 19.1 | BSP340   | 0.5             | 1.25       | 12.7       | 31.8       | Black | 75           | 22.9  | 0.9    | 0.41  |
| 170-03003               | 1            | 25.4 | BSP100   | 0.625           | 1.625      | 15.9       | 41.3       | Black | 65           | 19.8  | 0.87   | 0.4   |
| 170-03004               | 1-1/4        | 31.8 | BSP1140  | 0.75            | 1.75       | 19.1       | 44.5       | Black | 50           | 15.2  | 0.8    | 0.363 |
| 170-03005               | 1-1/2        | 38.1 | BSP1120  | 1.0             | 2.125      | 25.4       | 54.0       | Black | 40           | 12.2  | 0.79   | 0.358 |
| <b>Bulk Sized Reels</b> |              |      |          |                 |            |            |            |       |              |       |        |       |
| 170-03174               | 1/8          | 3.2  | BSP180B  | 0.094           | 0.25       | 2.4        | 6.4        | Black | 1000         | 304.8 | 1.8    | 0.82  |
| 170-03041               | 1/4          | 6.4  | BSP140B  | 0.125           | 0.437      | 3.2        | 11.1       | Black | 1000         | 304.8 | 2.6    | 1.18  |
| 170-03042               | 1/2          | 12.7 | BSP120B  | 0.25            | 0.75       | 6.4        | 19.1       | Black | 500          | 152.4 | 3.85   | 1.75  |
| 170-03043               | 3/4          | 19.1 | BSP340B  | 0.5             | 1.25       | 12.7       | 31.8       | Black | 250          | 76.2  | 3.0    | 1.36  |
| 170-03044               | 1            | 25.4 | BSP100B  | 0.625           | 1.625      | 15.9       | 41.3       | Black | 250          | 76.2  | 3.35   | 1.52  |
| 170-03045               | 1-1/4        | 31.8 | BSP1140B | 0.75            | 1.75       | 19.1       | 44.5       | Black | 250          | 76.2  | 4.0    | 1.81  |
| 170-03178               | 2            | 50.8 | BSP200B  | 1.5             | 3.5        | 38.1       | 88.9       | Black | 200          | 61.0  | 6.6    | 2.99  |

Use Part No. for ordering and Type for specification purposes. \* Pre-cut lengths available upon request.



## Braided Sleeving

## General Purpose Expandable Braided Sleeving Helagaine Dispenser Packs

This convenient package holds mini spools of expandable braided sleeving. Designed to save space and provide easy access when dispensing, this unit allows for the efficient handling and management of sleeving.

## Application

The perfect solution for use in field-service applications where a large spool of braided sleeving is not feasible or when only a small amount of sleeving is required for a quick-fix project.

## Benefits

- Expands (3:1 ratio) to allow for a wide range of bundle sizes.
- Dispenser box protects sleeving from dirt and keeps it from unraveling.



## Material Data

|                       |                                |
|-----------------------|--------------------------------|
| Material              | PET (Polyester)                |
| Operating Temperature | -58°F to 230°F, -50°C to 150°C |
| Melt Point            | 482°F / 250°C                  |
| Abrasion Protection   | Medium                         |
| Recommended Cutting   | Hot Knife                      |



## Product Selection

| Part No.  | Nominal Size |      | Type  | Expansion Range |            |            |            | Color | Reel Length |      | Weight |      |
|-----------|--------------|------|-------|-----------------|------------|------------|------------|-------|-------------|------|--------|------|
|           | in.          | mm.  |       | (Min.) in.      | (Max.) in. | (Min.) mm. | (Max.) mm. |       | ft.         | m.   | lbs.   | kg.  |
| 170-80150 | 1/4          | 6.4  | HLB15 | 0.2             | 0.83       | 5.1        | 21.1       | Black | 32.8        | 10.0 | 0.45   | 0.2  |
| 170-80250 | 1/2          | 12.7 | HLB25 | 0.4             | 1.18       | 10.2       | 30.0       | Black | 32.8        | 10.0 | 0.56   | 0.25 |
| 170-80350 | 1            | 25.4 | HLB35 | 0.71            | 2.13       | 18.0       | 54.1       | Black | 32.8        | 10.0 | 0.67   | 0.3  |

Use Part No. for ordering and Type for specification purposes.

## Braided Sleeving

## General Purpose Expandable Braided Sleeving - Orange

Orange PET braided sleeving is an extremely flexible, general purpose option for bundling and protecting wires and cables in abrasive type applications. Its color makes it ideal for systematic color coding of complex wiring installations.

## Application

Commonly used to shield cable harnesses in battery-powered vehicles, such as hybrid cars, golf carts, and light trucks.

## Benefits

- Provides easy visual and safety identification of critical wiring components.
- Offers high tensile strength while maintaining extreme flexibility.
- Expands up to 150% of flat diameter for easy installation.
- Does not trap heat and humidity.
- Installs quickly and accommodates expansions and varying cable assembly shapes, reducing installation costs.



## Material Data

|                       |                                |
|-----------------------|--------------------------------|
| Material              | PET (Polyester)                |
| Flammability          | UL 94-V0                       |
| Operating Temperature | -94°F to 257°F, -70°C to 125°C |
| Melt Point            | 482°F / 250°C                  |
| Abrasion Protection   | Medium                         |
| Recommended Cutting   | Hot Knife                      |



## Product Selection

| Part No.  | Nominal Size |      | Type     | Expansion Range |            |            |            | Color  | Reel Length* |       | Weight |      |
|-----------|--------------|------|----------|-----------------|------------|------------|------------|--------|--------------|-------|--------|------|
|           | in.          | mm.  |          | (Min.) in.      | (Max.) in. | (Min.) mm. | (Max.) mm. |        | ft.          | m.    | lbs.   | kg.  |
| 170-03076 | 1/4          | 6.4  | BSP143B  | 0.125           | 0.437      | 3.2        | 11.1       | Orange | 1000         | 304.8 | 2.6    | 1.18 |
| 170-03077 | 1/2          | 12.7 | BSP123B  | 0.25            | 0.75       | 6.4        | 19.1       | Orange | 500          | 152.4 | 3.9    | 1.75 |
| 170-03078 | 3/4          | 19.1 | BSP343B  | 0.5             | 1.25       | 12.7       | 31.8       | Orange | 250          | 76.2  | 3.0    | 1.36 |
| 170-03079 | 1            | 25.4 | BSP103B  | 0.625           | 1.625      | 15.9       | 41.3       | Orange | 250          | 76.2  | 3.35   | 1.52 |
| 170-03080 | 1-1/4        | 31.8 | BSP1143B | 0.75            | 1.75       | 19.1       | 44.5       | Orange | 250          | 76.2  | 4.0    | 1.81 |
| 170-03081 | 1-1/2        | 38.1 | BSP1123B | 1.0             | 2.125      | 25.4       | 54.0       | Orange | 200          | 61.0  | 6.6    | 3.0  |

Use Part No. for ordering and Type for specification purposes. \* Pre-cut lengths available upon request.



## Braided Sleeving

Fray Resistant Expandable  
Braided Sleeving

A versatile and economical general purpose sleeving that resists fraying when cut with ordinary scissors.

## Application

For use in automotive, industrial and computer applications where the wires, cables and hoses being covered endure frequent handling.

## Benefits

- Enables field installations without a hot knife thus reducing time and assembly costs.
- Expands up to 150% of flat diameter for easy installation.
- Offers excellent abrasion and cut-through resistance as well as inertness to most chemicals and fungus.



## Material Data

|                       |                                |
|-----------------------|--------------------------------|
| Material              | PET (Polyester)                |
| Flammability          | UL 94-V0                       |
| Operating Temperature | -94°F to 257°F, -70°C to 125°C |
| Melt Point            | 482°F / 250°C                  |
| Abrasion Protection   | Medium                         |
| Recommended Cutting   | Scissors                       |



## Product Selection

| Part No.  | Nominal Size |      | Type      | Expansion Range |            |            |            | Color | Reel Length* |      | Weight |      |
|-----------|--------------|------|-----------|-----------------|------------|------------|------------|-------|--------------|------|--------|------|
|           | in.          | mm.  |           | (Min.) in.      | (Max.) in. | (Min.) mm. | (Max.) mm. |       | ft.          | m.   | lbs.   | kg.  |
| 170-03123 | 1/8          | 3.3  | BSPSC180  | 0.125           | 0.25       | 3.2        | 6.4        | Black | 100          | 30.5 | 0.4    | 0.18 |
| 170-03035 | 1/4          | 6.4  | BSPSC140  | 0.156           | 0.437      | 4.0        | 11.1       | Black | 100          | 30.5 | 0.46   | 0.21 |
| 170-03012 | 1/2          | 12.7 | BSPSC120  | 0.25            | 0.75       | 6.4        | 19.1       | Black | 100          | 30.5 | 0.82   | 0.37 |
| 170-03013 | 3/4          | 19.1 | BSPSC340  | 0.625           | 1.0        | 15.9       | 25.4       | Black | 75           | 22.9 | 0.83   | 0.38 |
| 170-03014 | 1            | 25.4 | BSPSC100  | 0.75            | 1.19       | 19.1       | 30.2       | Black | 50           | 15.2 | 0.62   | 0.28 |
| 170-03015 | 1-1/4        | 31.8 | BSPSC1140 | 1.0             | 1.5        | 25.4       | 38.1       | Black | 50           | 15.2 | 0.78   | 0.35 |
| 170-03016 | 1-1/2        | 38.1 | BSPSC1120 | 1.25            | 2.0        | 31.8       | 50.8       | Black | 50           | 15.2 | 0.93   | 0.42 |

Use Part No. for ordering and Type for specification purposes. \* Pre-cut lengths available upon request.



# Braided Sleeving

## Flame Retardant Expandable Braided Sleeving

A flame retardant woven (threaded) polyester sleeving that is resistant to cuts and abrasion, and contains a combustion inhibitor allowing it to achieve a UL and CSA flame-resistance rating of VW-1.

### Application

This fire extinguishing braided sleeving is ideal for electronic and high tech applications because of its light weight and durable qualities.

### Benefits

- Resists gasoline, engine fluids, chemicals and cleaning solvents.
- Expands up to 150% of flat diameter for easy installation.
- Enables quick and easy installation over large connectors.



### Material Data

|                       |                                |
|-----------------------|--------------------------------|
| Material              | Treated PET (Polyester)        |
| Flammability          | UL VW-1                        |
| Operating Temperature | -94°F to 257°F, -70°C to 125°C |
| Melt Point            | 482°F / 250°C                  |
| Abrasion Protection   | Medium                         |
| Recommended Cutting   | Hot Knife                      |



### Product Selection

| Part No.                | Nominal Size |      | Type       | Expansion Range |            |            |            | Color | Reel Length* |       | Weight |       |
|-------------------------|--------------|------|------------|-----------------|------------|------------|------------|-------|--------------|-------|--------|-------|
|                         | in.          | mm.  |            | (Min.) in.      | (Max.) in. | (Min.) mm. | (Max.) mm. |       | ft.          | m.    | lbs.   | kg.   |
| 170-03006               | 1/4          | 6.4  | BSPFR140   | 0.125           | 0.437      | 3.2        | 11.1       | Black | 200          | 61    | 0.48   | 0.22  |
| 170-03007               | 1/2          | 12.7 | BSPFR120   | 0.25            | 0.75       | 6.4        | 19.1       | Black | 100          | 30.5  | 0.72   | 0.33  |
| 170-03008               | 3/4          | 19.1 | BSPFR340   | 0.5             | 1.25       | 12.7       | 31.8       | Black | 75           | 22.9  | 0.65   | 0.3   |
| 170-03010               | 1-1/4        | 31.8 | BSPFR1140  | 0.75            | 1.75       | 19.1       | 44.5       | Black | 50           | 15.3  | 0.8    | 0.363 |
| 170-03011               | 1-1/2        | 38.1 | BSPFR1120  | 1.0             | 2.125      | 25.4       | 54.0       | Black | 40           | 12.2  | 0.79   | 0.358 |
| 170-03071               | 1/8          | 3.2  | BSPFR188   | 0.094           | 0.25       | 2.4        | 6.4        | Gray  | 225          | 68.6  | 0.4    | 0.18  |
| 170-03072               | 1/4          | 6.4  | BSPFR148   | 0.125           | 0.437      | 3.2        | 11.1       | Gray  | 200          | 61    | 0.48   | 0.22  |
| 170-03073               | 1/2          | 12.7 | BSPFR128   | 0.25            | 0.75       | 6.4        | 19.1       | Gray  | 100          | 30.5  | 0.72   | 0.33  |
| 170-03074               | 3/4          | 19.1 | BSPFR348   | 0.5             | 1.25       | 12.7       | 31.8       | Gray  | 75           | 22.9  | 0.63   | 0.29  |
| 170-03066               | 1-1/2        | 38.1 | BSPFR1128  | 1.0             | 2.125      | 25.4       | 54.0       | Gray  | 40           | 12.2  | 0.79   | 0.358 |
| <b>Bulk Sized Reels</b> |              |      |            |                 |            |            |            |       |              |       |        |       |
| 170-03089               | 1/8          | 3.2  | BSPFR180B  | 0.094           | 0.25       | 2.4        | 6.4        | Black | 1000         | 304.8 | 1.6    | 0.73  |
| 170-03090               | 1/4          | 6.4  | BSPFR140B  | 0.125           | 0.437      | 3.2        | 11.1       | Black | 1000         | 304.8 | 2.4    | 1.1   |
| 170-03187               | 3/8          | 9.5  | BSPFR380   | 0.188           | 0.5        | 4.8        | 12.7       | Black | 500          | 152.4 | 2.85   | 1.29  |
| 170-03091               | 1/2          | 12.7 | BSPFR120B  | 0.25            | 0.75       | 6.4        | 19.1       | Black | 500          | 152.4 | 3.6    | 1.6   |
| 170-03092               | 3/4          | 19.1 | BSPFR340B  | 0.5             | 1.25       | 12.7       | 31.8       | Black | 250          | 76.2  | 2.2    | 1.0   |
| 170-03093               | 1            | 25.4 | BSPFR100B  | 0.625           | 1.625      | 15.9       | 41.3       | Black | 250          | 76.2  | 3.4    | 1.5   |
| 170-03094               | 1-1/4        | 31.8 | BSPFR1140B | 0.75            | 1.75       | 19.1       | 44.5       | Black | 250          | 76.2  | 4.0    | 1.8   |
| 170-03095               | 1-1/2        | 38.1 | BSPFR1120B | 1.0             | 2.125      | 25.4       | 54.0       | Black | 200          | 61.0  | 3.9    | 1.77  |

Use Part No. for ordering and Type for specification purposes. \* Pre-cut lengths available upon request.



## Flame Retardant + Fray Resistant Expandable Braided Sleeving

This protective sleeving is self-extinguishing and can be cut with sharp scissors instead of a hot knife for fray-resistant ends.

### Application

Readily used in the automotive, audiovisual, industrial, wire, cable and computer industries where flame retardancy is required to reduce the likelihood of ignition and/or reduce the rate of flame spread. It is suited for situations where access to a hot knife is either impractical or impossible.

### Benefits

- Provides fuller coverage and a medium-to-high abrasion resistance.
- Expands for ease of installation in the shop or the field.
- Offers increased braid density without loss of flexibility.
- Contains white tracer thread for simple identification of flame retardancy.
- Extinguishes quickly and reduces flame spread to surrounding components.



#### Material Data

|                       |                                |
|-----------------------|--------------------------------|
| Material              | Treated PET (Polyester)        |
| Flammability          | UL VW-1                        |
| Operating Temperature | -94°F to 257°F, -70°C to 125°C |
| Melt Point            | 482°F / 250°C                  |
| Abrasion Protection   | Medium                         |
| Recommended Cutting   | Scissors                       |



#### Product Selection

| Part No.                | Nominal Size |      | Type        | Expansion Range |            |            |            | Color | Reel Length* |       | Weight |      |
|-------------------------|--------------|------|-------------|-----------------|------------|------------|------------|-------|--------------|-------|--------|------|
|                         | in.          | mm.  |             | (Min.) in.      | (Max.) in. | (Min.) mm. | (Max.) mm. |       | ft.          | m.    | lbs.   | kg.  |
| 170-03036               | 1/4          | 6.4  | BSSCFR140   | 0.156           | 0.437      | 4.0        | 11.1       | Black | 100          | 30.5  | 0.4    | 0.18 |
| 170-03017               | 1/2          | 12.7 | BSSCFR120   | 0.25            | 0.75       | 6.4        | 19.1       | Black | 100          | 30.5  | 0.82   | 0.37 |
| 170-03018               | 3/4          | 19.1 | BSSCFR340   | 0.625           | 1.0        | 15.9       | 25.4       | Black | 75           | 22.9  | 0.833  | 0.38 |
| 170-03019               | 1            | 25.4 | BSSCFR100   | 0.75            | 1.188      | 19.1       | 30.1       | Black | 50           | 15.2  | 0.62   | 0.28 |
| 170-03020               | 1-1/4        | 31.8 | BSSCFR1140  | 1.0             | 1.5        | 25.4       | 38.1       | Black | 50           | 15.2  | 0.78   | 0.35 |
| 170-03021               | 1-1/2        | 38.1 | BSSCFR1120  | 1.25            | 2.0        | 31.8       | 50.8       | Black | 50           | 15.2  | 0.925  | 0.42 |
| <b>Bulk Sized Reels</b> |              |      |             |                 |            |            |            |       |              |       |        |      |
| 170-03116               | 1/4          | 3.3  | BSSCFR180B  | 0.125           | 0.25       | 3.2        | 6.4        | Black | 1000         | 304.8 | 4.0    | 1.8  |
| 170-03117               | 1/4          | 6.4  | BSSCFR140B  | 0.156           | 0.437      | 4.0        | 11.1       | Black | 1000         | 304.8 | 4.6    | 2.1  |
| 170-03118               | 1/2          | 12.7 | BSSCFR120B  | 0.25            | 0.75       | 6.4        | 19.1       | Black | 500          | 152.4 | 4.1    | 1.9  |
| 170-03119               | 3/4          | 19.1 | BSSCFR340B  | 0.625           | 1.0        | 15.9       | 25.4       | Black | 250          | 76.2  | 2.78   | 1.3  |
| 170-03120               | 1            | 25.4 | BSSCFR100B  | 0.75            | 1.9        | 19.1       | 48.3       | Black | 250          | 76.2  | 3.1    | 1.4  |
| 170-03121               | 1-1/4        | 31.8 | BSSCFR1140B | 1.0             | 1.5        | 25.4       | 38.1       | Black | 250          | 76.2  | 3.9    | 1.8  |
| 170-03122               | 1-1/2        | 38.1 | BSSCFR1120B | 1.25            | 2.0        | 31.8       | 50.8       | Black | 250          | 76.2  | 4.63   | 2.1  |

Use Part No. for ordering and Type for specification purposes. \* Pre-cut lengths available upon request.



## Braided Sleeving

### Hook & Loop Flame Retardant Expandable Braided Sleeving

Hook and loop edging keeps this flame retardant sleeving securely wrapped around cables, but allows for easy access when maintenance is necessary.

#### Application

Ideal for high-technology applications, especially operating environments where harsh fluids are present.

#### Benefits

- Conforms to irregular shapes and contours.
- Meets military specifications (Mil-202 approved).
- Cuts easily with a bench-mount hot knife.
- Resists chemicals and cleaning solvents.



#### Material Data

|                       |                                |
|-----------------------|--------------------------------|
| Material              | Treated PET (Polyester)        |
| Flammability          | UL VW-1                        |
| Operating Temperature | -94°F to 257°F, -70°C to 125°C |
| Melt Point            | 482°F / 250°C                  |
| Abrasion Protection   | Medium                         |
| Recommended Cutting   | Hot Knife                      |



#### Product Selection

| Part No.  | Nominal Size |      | Type          | Wall Thickness |     | Color | Reel Length* |      | Weight |      |
|-----------|--------------|------|---------------|----------------|-----|-------|--------------|------|--------|------|
|           | in.          | mm.  |               | in.            | mm. |       | ft.          | m.   | lbs.   | kg.  |
| 170-03153 | 1/2          | 12.7 | BSHKLPFR120B  | 0.063          | 1.6 | Black | 100          | 30.5 | 1.3    | 0.6  |
| 170-03154 | 3/4          | 19.1 | BSHKLPFR340B  | 0.063          | 1.6 | Black | 100          | 30.5 | 1.8    | 0.8  |
| 170-03155 | 1-1/4        | 31.8 | BSHKLPFR1140B | 0.063          | 1.6 | Black | 100          | 30.5 | 2.3    | 1.04 |
| 170-03156 | 2            | 50.8 | BSHKLPFR200B  | 0.063          | 1.6 | Black | 100          | 30.5 | 3.2    | 1.45 |
| 170-03157 | 2-1/2        | 63.5 | BSHKLPFR212B  | 0.063          | 1.6 | Black | 100          | 30.5 | 3.75   | 1.7  |

Use Part No. for ordering and Type for specification purposes. \* Pre-cut lengths available upon request.



## Split Wrap Flame Retardant Braided Sleeving

Used when flame retardancy is a primary requirement, this protection option incorporates a lateral split that opens to accommodate a variety of bundling requirements. The semi-rigid braid configuration simply closes around the entire installation without the need for any additional fasteners.

### Application

Use this self-extinguishing product that complies with UL VW-1 standards where cables exit a wall and need to be managed for an uncluttered, clean appearance.

### Benefits

- Installs easily, saving assembly time.
- Allows for future accessibility without disassembly.
- Needs no fasteners (i.e., tape, hook and loop, etc.).
- Provides greater flexibility than spiral wraps or convoluted tubing.
- Retains shape and rigidity throughout operating temperature range.

See installation tool on back cover.



#### Material Data

|                       |                                |
|-----------------------|--------------------------------|
| Material              | Treated PET (Polyester)        |
| Flammability          | UL VW-1                        |
| Operating Temperature | -94°F to 257°F, -70°C to 125°C |
| Melt Point            | 446°F / 230°C                  |
| Abrasion Protection   | High                           |
| Recommended Cutting   | Hot Knife                      |



#### Product Selection

| Part No.  | Nominal Size |      | Type        | Wall Thickness |            | Color | Reel Length* |       | Weight |      |
|-----------|--------------|------|-------------|----------------|------------|-------|--------------|-------|--------|------|
|           | in.          | mm.  |             | (Min.) in.     | (Max.) in. |       | ft.          | m.    | lbs.   | kg.  |
| 170-03140 | 1/8          | 3.1  | BSSWFR180B  | 0.024          | 0.61       | Black | 400          | 121.9 | 0.8    | 0.36 |
| 170-03141 | 1/4          | 6.4  | BSSWFR140B  | 0.025          | 0.64       | Black | 200          | 61.0  | 1.2    | 0.54 |
| 170-03142 | 1/2          | 12.7 | BSSWFR120B  | 0.025          | 0.64       | Black | 150          | 45.7  | 2.1    | 0.95 |
| 170-03143 | 3/4          | 19.1 | BSSWFR340B  | 0.025          | 0.64       | Black | 100          | 30.5  | 1.6    | 0.73 |
| 170-03144 | 1            | 25.4 | BSSWFR100B  | 0.038          | 0.97       | Black | 100          | 30.5  | 2.0    | 0.91 |
| 170-03145 | 1-1/4        | 31.8 | BSSWFR1140B | 0.038          | 0.97       | Black | 75           | 22.9  | 1.8    | 0.82 |
| 170-03146 | 1-1/2        | 38.1 | BSSWFR1120B | 0.038          | 0.97       | Black | 75           | 22.9  | 2.1    | 0.95 |
| 170-03147 | 2            | 50.8 | BSSWFR200B  | 0.038          | 0.97       | Black | 50           | 15.2  | 1.8    | 0.82 |

Use Part No. for ordering and Type for specification purposes. \* Pre-cut lengths available upon request.



## Braided Sleeving

### Electromagnetic Flame Retardant Helagaine

Helagaine VO (HEGEMIPVO) is tubular braided sleeving made from Polyester PBT monofilaments. The raw material is treated with non-burning agents so it has flame retardant and self-extinguishing properties. Rated VO by Underwriters Laboratories.

#### Application

Excellent for use where flame can cause damage to highly sensitive wiring in critical applications, such as laboratories, computer rooms, satellites, mass transit and airplanes.

#### Benefits

- Shields or dissipates wire and cables from electromagnetic interference.
- Resists most chemicals.
- Expands (ratio 2:1) to allow for easy placement over bundles.



#### Material Data

|                       |                                          |
|-----------------------|------------------------------------------|
| Material              | Polyester (PBT)/Tin-plated copper (TNCU) |
| Flammability          | UL 94-V0                                 |
| Operating Temperature | -40 °F to 347 °F -40 °C to 175 °C        |
| Melt Point            | 329 °F / 200 °C                          |
| Abrasion Protection   | High                                     |
| Recommended Cutting   | Shears                                   |
| EMI Requirements      | 10 KHz to 1 GHz according to CISPR25     |



#### Product Selection

| Part No.  | Nominal Size |      | Type        | Expansion Range |            |            |            | Color       | Reel Length |     | Weight |      |
|-----------|--------------|------|-------------|-----------------|------------|------------|------------|-------------|-------------|-----|--------|------|
|           | in.          | mm.  |             | (Min.) in.      | (Max.) in. | (Min.) mm. | (Max.) mm. |             | ft.         | m.  | lbs.   | kg.  |
| 173-60400 | 1/8          | 3.2  | HEGEMIPV004 | 0.16            | 0.26       | 4.0        | 6.0        | Tin + Black | 328         | 100 | 4.74   | 2.2  |
| 173-60600 | 1/4          | 6.4  | HEGEMIPV006 | 0.2             | 0.39       | 5.0        | 10.0       | Tin + Black | 328         | 100 | 6.28   | 2.8  |
| 173-60800 | 5/16         | 7.9  | HEGEMIPV008 | 0.32            | 0.45       | 8.0        | 11.0       | Tin + Black | 328         | 100 | 5.84   | 2.6  |
| 173-61000 | 3/8          | 9.5  | HEGEMIPV010 | 0.32            | 0.52       | 8.0        | 13.0       | Tin + Black | 164         | 50  | 9.6    | 4.4  |
| 173-61200 | 7/16         | 11.1 | HEGEMIPV012 | 0.39            | 0.59       | 10.0       | 15.0       | Tin + Black | 164         | 50  | 10.6   | 4.8  |
| 173-61400 | 1/2          | 12.7 | HEGEMIPV014 | 0.47            | 0.71       | 12.0       | 18.0       | Tin + Black | 328         | 100 | 12.8   | 5.8  |
| 173-61600 | 9/16         | 14.3 | HEGEMIPV016 | 0.55            | 0.79       | 14.0       | 20.0       | Tin + Black | 328         | 100 | 15.9   | 7.2  |
| 173-61800 | 5/8          | 15.9 | HEGEMIPV018 | 0.63            | 0.87       | 16.0       | 22.0       | Tin + Black | 164         | 50  | 17.3   | 7.8  |
| 173-62000 | 3/4          | 19.1 | HEGEMIPV020 | 0.71            | 0.98       | 18.0       | 25.0       | Tin + Black | 164         | 50  | 22.1   | 10.0 |

Use Part No. for ordering and Type for specification purposes.

## Electromagnetic Helagaine


Helagaine (HEGEMIP) is a sleeving created from tin-plated copper and polyester threads that offers not only secure cable bundling but electromagnetic protection as well. The formulated mix of materials offers inside and outside abrasion resistance.

### Application

Particularly suitable for applications with movement and little space; ideal for short-run cables found in electrical appliances and radio equipment.

### Benefits

- Features a supporting inner tube that makes insertion of cable easier and protects the sleeve from deformation during transport.
- Attenuates electrical field interference.
- Provides electromagnetic and electrostatic shielding.
- Delivers added shielding in retrofit applications.
- Retains original form even when bent and twisted, unlike pure copper braids.



#### Material Data

|                       |                                               |
|-----------------------|-----------------------------------------------|
| Material              | PET (Polyester) /<br>Tin-Plated Copper (TNCU) |
| Flammability          | UL 94-V2                                      |
| Operating Temperature | -40°F to 347°F, -40°C to 175°C                |
| Melt Point            | 392°F / 200°C                                 |
| Abrasion Protection   | High                                          |
| Recommended Cutting   | Shears                                        |
| EMI Requirements      | 10 KHz to 1 GHz according<br>to CISPR25       |



#### Product Selection

| Part No.  | Nominal Size |      | Type      | Expansion Range |               |               |               | Color       | Reel Length |     | Weight |      |
|-----------|--------------|------|-----------|-----------------|---------------|---------------|---------------|-------------|-------------|-----|--------|------|
|           | in.          | mm.  |           | (Min.)<br>in.   | (Max.)<br>in. | (Min.)<br>mm. | (Max.)<br>mm. |             | ft.         | m.  | lbs.   | kg.  |
| 173-00400 | 1/8          | 3.2  | HEGEMIP04 | 0.16            | 0.26          | 4.0           | 6.0           | Tin + Black | 328         | 100 | 4.74   | 2.2  |
| 173-00600 | 1/4          | 6.4  | HEGEMIP06 | 0.2             | 0.39          | 5.0           | 10.0          | Tin + Black | 328         | 100 | 6.28   | 2.8  |
| 173-00800 | 5/16         | 7.9  | HEGEMIP08 | 0.32            | 0.45          | 8.0           | 11.0          | Tin + Black | 328         | 100 | 5.84   | 2.6  |
| 173-01000 | 3/8          | 9.5  | HEGEMIP10 | 0.32            | 0.52          | 8.0           | 13.0          | Tin + Black | 164         | 50  | 9.6    | 4.4  |
| 173-01200 | 7/16         | 11.1 | HEGEMIP12 | 0.39            | 0.59          | 10.0          | 15.0          | Tin + Black | 164         | 50  | 10.6   | 4.8  |
| 173-01400 | 1/2          | 12.7 | HEGEMIP14 | 0.47            | 0.71          | 12.0          | 18.0          | Tin + Black | 328         | 100 | 12.8   | 5.8  |
| 173-01600 | 9/16         | 14.3 | HEGEMIP16 | 0.55            | 0.79          | 14.0          | 20.0          | Tin + Black | 328         | 100 | 15.9   | 7.2  |
| 173-01800 | 5/8          | 15.9 | HEGEMIP18 | 0.63            | 0.87          | 16.0          | 22.0          | Tin + Black | 164         | 50  | 17.3   | 7.8  |
| 173-02000 | 3/4          | 19.1 | HEGEMIP20 | 0.71            | 0.98          | 18.0          | 25.0          | Tin + Black | 164         | 50  | 22.1   | 10.0 |

Use Part No. for ordering and Type for specification purposes.

# Braided Sleeving

## Polyamide 6.6 Expandable Braided Sleeving - Black

A pliable yet durable nylon sleeve that delivers excellent protection against cuts, abrasions and excessive wear caused by repetitive motion.

### Application

Used on hoses, pipes, wiring harnesses and cables installed in cars, trucks, military vehicles, trains and industrial equipment. Protects delicate wiring in engine compartments and near exhaust systems. Also organizes wires and breakouts in electrical harnesses.

### Benefits

- Resists fuels, salts, solvents, gasoline and other common contaminants.
- Offers a tight, 12 mil braid that provides full coverage but will not rot or retain moisture.
- Performs well in wet applications and where abiding substrate has a smooth surface.
- Expands up to 150% of flat diameter for easy installation.



### Material Data

|                       |                                |
|-----------------------|--------------------------------|
| Material              | Polyamide 6.6 (Nylon)          |
| Flammability          | Non-Flammable                  |
| Operating Temperature | -49°F to 302°F, -45°C to 150°C |
| Melt Point            | 491°F / 255°C                  |
| Abrasion Protection   | High                           |
| Recommended Cutting   | Hot Knife                      |



### Product Selection

| Part No.                | Nominal Size |      | Type        | Expansion Range |            |            |            | Color | Reel Length* |       | Weight |      |
|-------------------------|--------------|------|-------------|-----------------|------------|------------|------------|-------|--------------|-------|--------|------|
|                         | in.          | mm.  |             | (Min.) in.      | (Max.) in. | (Min.) mm. | (Max.) mm. |       | ft.          | m.    | lbs.   | kg.  |
| 170-03069               | 1/4          | 6.4  | BSPA66140   | 0.125           | 0.375      | 3.2        | 9.5        | Black | 200          | 61.0  | 0.6    | 0.27 |
| 170-03027               | 1/2          | 12.7 | BSPA66120   | 0.375           | 0.75       | 9.5        | 19.1       | Black | 100          | 30.5  | 1.03   | 0.47 |
| 170-03028               | 3/4          | 19.1 | BSPA66340   | 0.5             | 1.25       | 12.7       | 31.8       | Black | 75           | 22.9  | 1.103  | 0.5  |
| 170-03029               | 1            | 25.4 | BSPA66100   | 0.625           | 1.375      | 15.9       | 35.0       | Black | 50           | 15.2  | 0.8    | 0.36 |
| 170-03030               | 1-1/4        | 31.8 | BSPA661140  | 0.75            | 1.5        | 19.1       | 38.1       | Black | 50           | 15.2  | 0.89   | 0.4  |
| <b>Bulk Sized Reels</b> |              |      |             |                 |            |            |            |       |              |       |        |      |
| 170-03070               | 1/4          | 6.4  | BSPA66140B  | 0.125           | 0.375      | 3.2        | 9.5        | Black | 1000         | 304.8 | 3.1    | 1.41 |
| 170-03046               | 1/2          | 12.7 | BSPA66120B  | 0.375           | 0.75       | 9.5        | 19.1       | Black | 500          | 152.4 | 5.15   | 2.34 |
| 170-03047               | 3/4          | 19.1 | BSPA66340B  | 0.5             | 1.25       | 12.7       | 31.8       | Black | 250          | 76.2  | 3.68   | 1.67 |
| 170-03048               | 1            | 25.4 | BSPA66100B  | 0.625           | 1.375      | 15.9       | 35.0       | Black | 250          | 76.2  | 4.0    | 1.81 |
| 170-03049               | 1-1/4        | 31.8 | BSPA661140B | 0.75            | 1.5        | 19.1       | 38.1       | Black | 250          | 76.2  | 4.5    | 2.04 |

Use Part No. for ordering and Type for specification purposes. \* Pre-cut lengths available upon request.

## Braided Sleeving

## Polyamide 6.6 Helagaine Expandable Braided Sleeving - Gray

Made from heat-stabilized monofilament strands, this lightweight sleeving provides tough protection with excellent resistance to abrasion. Despite its sturdy composition, Helagaine is expandable and durable, and can be easily applied over irregular surfaces.

## Application

Suitable for automotive and transportation industry applications for abrasion protection of sensitive cables and wires.

## Benefits

- Offers a strand diameter that is approximately 10% larger than that of polyester, allowing for greater expandability.
- Resists fuels, salts, solvents, gasoline and other common contaminants.
- Performs well in wet applications and where abiding substrate has a smooth surface.



## Material Data

|                       |                                |
|-----------------------|--------------------------------|
| Material              | Polyamide 6.6 (PA66)           |
| Flammability          | UL 94-V2                       |
| Operating Temperature | -76°F to 302°F, -60°C to 150°C |
| Melt Point            | 491°F / 255°C                  |
| Abrasion Protection   | High                           |
| Recommended Cutting   | Hot Knife                      |



## Product Selection

| Part No.  | Nominal Size |      | Type      | Expansion Range |            |            |            | Color | Reel Length |     | Weight |      |
|-----------|--------------|------|-----------|-----------------|------------|------------|------------|-------|-------------|-----|--------|------|
|           | in.          | mm.  |           | (Min.) in.      | (Max.) in. | (Min.) mm. | (Max.) mm. |       | ft.         | m.  | lbs.   | kg.  |
| 170-20400 | 1/8          | 3.2  | HEGPA6604 | 0.12            | 0.24       | 3.0        | 6.1        | Gray  | 656         | 200 | 1.1    | 0.5  |
| 170-20600 | 3/16         | 4.76 | HEGPA6606 | 0.16            | 0.32       | 4.1        | 8.1        | Gray  | 328         | 100 | 1.3    | 0.59 |
| 170-20800 | 1/4          | 6.4  | HEGPA6608 | 0.2             | 0.4        | 5.1        | 10.2       | Gray  | 328         | 100 | 1.1    | 0.5  |
| 170-21000 | 3/8          | 9.5  | HEGPA6610 | 0.28            | 0.47       | 7.0        | 12.0       | Gray  | 328         | 100 | 2.09   | 0.95 |
| 170-21200 | 1/2          | 12.7 | HEGPA6612 | 0.32            | 0.55       | 8.1        | 14.0       | Gray  | 328         | 100 | 2.4    | 1.1  |
| 170-21500 | 5/8          | 15.9 | HEGPA6616 | 0.47            | 0.71       | 12.0       | 18.0       | Gray  | 164         | 50  | 2.76   | 1.25 |
| 170-22000 | 3/4          | 19.1 | HEGPA6620 | 0.59            | 0.91       | 15.0       | 23.1       | Gray  | 164         | 50  | 3.1    | 1.41 |
| 170-22500 | 1            | 25.4 | HEGPA6625 | 0.71            | 1.1        | 18.0       | 28.0       | Gray  | 164         | 50  | 3.9    | 1.77 |
| 170-23000 | 1-1/4        | 31.8 | HEGPA6630 | 0.98            | 1.26       | 24.9       | 32.0       | Gray  | 164         | 50  | 4.9    | 2.22 |
| 170-25000 | 2            | 50.8 | HEGPA6650 | 1.58            | 2.17       | 40.1       | 55.1       | Gray  | 164         | 50  | 10.4   | 4.72 |

Use Part No. for ordering and Type for specification purposes.



# Braided Sleeving

## Plenum Rated Halar® Expandable Braided Sleeving

Halar® self-extinguishing sleeving is used where flammability, high temperature endurance and low outgassing are concerns. This sleeving is made from strands of high temperature, flame resistant Halar monofilaments that are able to resist a wide range of corrosive chemicals and organic solvents.

### Application

Its low flame spread and smoke generation properties make it the perfect option for use in technologically-advanced applications, such as those in the automotive, aerospace and vital military markets.

### Benefits

- Resists gasoline and engine chemicals.
- Exceeds automotive industry requirements of FMVSS 302 as well as aviation industry requirements of FAR 25.
- Expands up to 150% for economical and expeditious installation.
- Withstands abrasion and won't degrade when exposed to Cobalt 60 radiation conditions.
- Meets UL 2024 and NFPA 262 specifications for plenum applications.



### Material Data

|                       |                                                       |
|-----------------------|-------------------------------------------------------|
| Material              | Ethylene Chlorotrifluoroethylene Monofilament (ECTFE) |
| Flammability          | UL VW-1                                               |
| Operating Temperature | -103°F to 302°F, -75°C to 150°C                       |
| Melt Point            | 482°F / 250°C                                         |
| Abrasion Protection   | Medium                                                |
| Recommended Cutting   | Hot Knife                                             |



### Product Selection

| Part No.  | Nominal Size |      | Type       | Expansion Range |            |            |            | Color | Reel Length* |      | Weight |      |
|-----------|--------------|------|------------|-----------------|------------|------------|------------|-------|--------------|------|--------|------|
|           | in.          | mm.  |            | (Min.) in.      | (Max.) in. | (Min.) mm. | (Max.) mm. |       | ft.          | m.   | lbs.   | kg.  |
| 170-03098 | 1/8          | 3.1  | BSHLR180   | 0.094           | 0.25       | 2.4        | 6.4        | Black | 225          | 68.6 | 0.6    | 0.27 |
| 170-03100 | 1/4          | 6.4  | BSHLR140   | 0.125           | 0.437      | 3.1        | 11.1       | Black | 200          | 61.0 | 0.8    | 0.36 |
| 170-03102 | 3/8          | 9.5  | BSHLR380   | 0.187           | 0.625      | 4.7        | 15.9       | Black | 125          | 38.1 | 1.1    | 0.5  |
| 170-03104 | 1/2          | 12.7 | BSHLR120   | 0.25            | 0.75       | 6.4        | 19.1       | Black | 100          | 30.5 | 1.1    | 0.5  |
| 170-03106 | 3/4          | 19.1 | BSHLR340   | 0.5             | 1.25       | 12.7       | 31.8       | Black | 75           | 22.8 | 1.3    | 0.6  |
| 170-03108 | 1            | 25.4 | BSHLR100   | 0.625           | 1.625      | 16         | 41.4       | Black | 65           | 19.8 | 1.4    | 0.64 |
| 170-03110 | 1-1/4        | 31.8 | BSHLR1140  | 0.75            | 1.75       | 19.1       | 44.5       | Black | 50           | 15.2 | 1.3    | 0.6  |
| 170-03112 | 1-3/4        | 44.4 | BSHLR1340  | 1.25            | 2.75       | 31.8       | 69.9       | Black | 30           | 9.1  | 1.3    | 0.6  |
| 170-03114 | 2            | 50.8 | BSHLR200   | 1.5             | 3.5        | 38.1       | 88.9       | Black | 50           | 15.2 | 2.3    | 1.04 |
| 170-03099 | 1/8          | 3.1  | BSHLR1810  | 0.094           | 0.25       | 2.4        | 6.4        | White | 225          | 68.6 | 0.6    | 0.27 |
| 170-03101 | 1/4          | 6.4  | BSHLR1410  | 0.125           | 0.437      | 3.1        | 11.1       | White | 200          | 61.0 | 0.8    | 0.36 |
| 170-03103 | 3/8          | 9.5  | BSHLR3810  | 0.187           | 0.625      | 4.7        | 15.9       | White | 125          | 38.1 | 1.1    | 0.5  |
| 170-03105 | 1/2          | 12.7 | BSHLR1210  | 0.25            | 0.75       | 6.4        | 19.1       | White | 100          | 30.5 | 1.1    | 0.5  |
| 170-03107 | 3/4          | 19.1 | BSHLR3410  | 0.5             | 1.25       | 12.7       | 31.8       | White | 75           | 22.9 | 1.3    | 0.6  |
| 170-03109 | 1            | 25.4 | BSHLR1010  | 0.625           | 1.625      | 15.9       | 41.4       | White | 65           | 19.8 | 1.4    | 0.64 |
| 170-03111 | 1-1/4        | 31.8 | BSHLR11410 | 0.75            | 1.75       | 19.1       | 44.5       | White | 50           | 15.2 | 1.3    | 0.6  |
| 170-03113 | 1-3/4        | 44.4 | BSHLR13410 | 1.25            | 2.75       | 31.8       | 69.9       | White | 30           | 9.1  | 1.3    | 0.6  |
| 170-03115 | 2            | 50.8 | BSHLR2010  | 1.5             | 3.5        | 38.1       | 88.9       | White | 50           | 15.2 | 2.3    | 1.04 |

Use Part No. for ordering and Type for specification. \* Pre-cut lengths available upon request.  
Halar® is a registered trademark of the Solvay Solexis Corporation.  
Halar product is produced on 8" diameter mini spools, which will not fit in merchandising display.



## Split Wrap Braided Sleeving

A bundling and protection option with a lateral split and a semi-rigid braid configuration that is the ideal solution for circumstances where ease of installation is the primary concern. The lateral split allows the sleeving to open up to adjust to the bundling requirement while the 25% edge overlap folds back over to protect the connector or splices.

### Application

More flexible than spiral wraps or convoluted tubing, this product is a fast and easy option for adding protection in post-assembly or post-installation situations.

### Benefits

- Needs no fasteners (i.e., tape, hook and loop, etc.).
- Bends to a tight radius without distortion or splitting open.
- Allows future access without disassembly.
- Withstands cuts, abrasions and tension.

See installation tool on back cover.



#### Material Data

|                       |                                |
|-----------------------|--------------------------------|
| Material              | PET (Polyester)                |
| Flammability          | UL 94-V0                       |
| Operating Temperature | -94°F to 257°F, -70°C to 125°C |
| Melt Point            | 482°F / 250°C                  |
| Abrasion Protection   | Medium                         |
| Recommended Cutting   | Hot Knife                      |



#### Product Selection

| Part No.                      | Nominal Size |      | Type        | Wall Thickness |      | Color | Reel Length* |         | Weight |      |
|-------------------------------|--------------|------|-------------|----------------|------|-------|--------------|---------|--------|------|
|                               | in.          | mm.  |             | in.            | mm.  |       | ft.          | m.      | lbs.   | kg.  |
| 170-03037                     | 1/4          | 6.4  | BSPSW140    | 0.025          | 0.64 | Black | 100          | 30.5    | 0.6    | 0.28 |
| 170-03024                     | 1/2          | 12.7 | BSPSW120    | 0.025          | 0.64 | Black | 75           | 22.9    | 1.05   | 0.48 |
| 170-03038                     | 3/4          | 19.1 | BSPSW340    | 0.025          | 0.64 | Black | 50           | 15.2    | 0.8    | 0.36 |
| 170-03025                     | 1            | 25.4 | BSPSW100    | 0.038          | 0.97 | Black | 50           | 15.2    | 1.0    | 0.45 |
| 170-03026                     | 1-1/4        | 31.8 | BSPSW1140   | 0.038          | 0.97 | Black | 25           | 7.1     | 0.6    | 0.27 |
| <b>Bulk Box</b>               |              |      |             |                |      |       |              |         |        |      |
| 170-03124                     | 1/8          | 3.2  | BSPSW180B   | 0.024          | 0.61 | Black | 400          | 121.9   | 0.8    | 0.36 |
| 170-03125                     | 1/4          | 6.4  | BSPSW140B   | 0.025          | 0.64 | Black | 200          | 61.0    | 1.2    | 0.54 |
| 170-03126                     | 1/2          | 12.7 | BSPSW120B   | 0.025          | 0.64 | Black | 150          | 45.7    | 2.1    | 0.95 |
| 170-03127                     | 3/4          | 19.1 | BSPSW340B   | 0.025          | 0.64 | Black | 100          | 30.5    | 1.6    | 0.73 |
| 170-03128                     | 1            | 25.4 | BSPSW100B   | 0.038          | 0.97 | Black | 100          | 30.5    | 2.0    | 0.91 |
| 170-03129                     | 1-1/4        | 31.8 | BSPSW1140B  | 0.038          | 0.97 | Black | 75           | 22.9    | 1.8    | 0.82 |
| 170-03130                     | 1 1/2        | 38.1 | BSPSW1120B  | 0.038          | 0.97 | Black | 75           | 22.9    | 2.1    | 0.95 |
| 170-03131                     | 2            | 50.8 | BSPSW200B   | 0.038          | 0.97 | Black | 50           | 15.2    | 1.8    | 0.82 |
| <b>Large Bulk Sized Reels</b> |              |      |             |                |      |       |              |         |        |      |
| 170-03132                     | 1/8          | 3.2  | BSPSW180LB  | 0.024          | 0.61 | Black | 10,000       | 3,048.8 | 20.0   | 9.0  |
| 170-03133                     | 1/4          | 6.4  | BSPSW140LB  | 0.025          | 0.64 | Black | 3,000        | 914.4   | 18.0   | 8.2  |
| 170-03134                     | 1/2          | 12.7 | BSPSW120LB  | 0.025          | 0.64 | Black | 1,200        | 365.8   | 12.0   | 5.4  |
| 170-03135                     | 3/4          | 19.1 | BSPSW340LB  | 0.025          | 0.64 | Black | 500          | 152.4   | 16.8   | 7.6  |
| 170-03136                     | 1            | 25.4 | BSPSW100LB  | 0.038          | 0.97 | Black | 400          | 121.9   | 8.0    | 3.6  |
| 170-03137                     | 1-1/4        | 31.8 | BSPSW1140LB | 0.038          | 0.97 | Black | 250          | 76.2    | 6.0    | 2.7  |
| 170-03138                     | 1-1/2        | 38.1 | BSPSW1120LB | 0.038          | 0.97 | Black | 200          | 61.0    | 7.2    | 3.3  |
| 170-03139                     | 2            | 50.8 | BSPSW200LB  | 0.038          | 0.97 | Black | 150          | 45.7    | 5.4    | 2.4  |

Use Part No. for ordering and Type for specification purposes. \* Pre-cut lengths available upon request.

## Braided Sleeving

## Split Wrap Braided Sleeving - Orange

Used for safety identification, this non-expandable bundling and protection option offers a lateral split and a semi-rigid braid configuration that wraps around the bundle assembly without requiring any fasteners, such as hook & loop, cables ties or tape.


## Application

Provides abrasion protection and identification in electrical-powered vehicles, aircraft and automotive applications.

## Benefits

- Needs no fasteners (i.e., tape, hook and loop, etc.).
- Bends to a tight radius without distortion or splitting open.
- Adapts easily and will not impair the flexibility of the harness assembly, nor will it fracture under stress.

See installation tool on back cover.



## Material Data

|                       |                                |
|-----------------------|--------------------------------|
| Material              | PET (Polyester)                |
| Flammability          | UL 94-V0                       |
| Operating Temperature | -94°F to 257°F, -70°C to 125°C |
| Melt Point            | 482°F / 250°C                  |
| Abrasion Protection   | Medium                         |
| Recommended Cutting   | Hot Knife                      |



## Product Selection

| Part No.  | Nominal Size |      | Type       | Wall Thickness |               | Color  | Reel Length* |      | Weight |      |
|-----------|--------------|------|------------|----------------|---------------|--------|--------------|------|--------|------|
|           | in.          | mm.  |            | (Min.)<br>in.  | (Max.)<br>in. |        | ft.          | m.   | lbs.   | kg.  |
| 170-03082 | 1/4          | 6.4  | BSPSW143B  | 0.025          | 0.64          | Orange | 200          | 61.0 | 1.2    | 0.54 |
| 170-03083 | 1/2          | 12.7 | BSPSW123B  | 0.025          | 0.64          | Orange | 150          | 45.7 | 2.1    | 0.95 |
| 170-03084 | 3/4          | 19.1 | BSPSW343B  | 0.025          | 0.64          | Orange | 100          | 30.5 | 1.6    | 0.73 |
| 170-03085 | 1            | 25.4 | BSPSW103B  | 0.038          | 0.97          | Orange | 100          | 30.5 | 2.0    | 0.91 |
| 170-03086 | 1-1/4        | 31.8 | BSPSW1143B | 0.038          | 0.97          | Orange | 75           | 22.9 | 1.8    | 0.82 |
| 170-03087 | 1-1/2        | 38.1 | BSPSW1123B | 0.038          | 0.97          | Orange | 75           | 22.9 | 2.1    | 0.95 |
| 170-03088 | 2            | 50.8 | BSPSW203B  | 0.038          | 0.97          | Orange | 50           | 15.2 | 1.8    | 0.82 |

Use Part No. for ordering and Type for specification purposes. \* Pre-cut lengths available upon request.



## Hook & Loop Expandable Braided Sleeving

Designed for the quick and easy management of wire and cable bundles, this expandable sleeving has a hook and loop closure for easy installation and maintenance, as well as instant and convenient access for harness break-outs.

### Application

When component disassembly is not an option or when frequent access to wires and cables is essential. The primary application for this sleeving is the wrapping and bunching of cables in a deployed situation (i.e., location recordings).

### Benefits

- Conforms to irregular shapes and contours.
- Wraps effortlessly over a cable bundle and closes; readily reopens.
- Saves time, allows those working on cables to easily splice or combine wires.
- Made of PET yarn for excellent protection against cuts and abrasions.



#### Material Data

|                       |                                |
|-----------------------|--------------------------------|
| Material              | PET (Polyester)                |
| Flammability          | UL 94-V0                       |
| Operating Temperature | -94°F to 257°F, -70°C to 125°C |
| Melt Point            | 482°F / 250°C                  |
| Abrasion Protection   | Medium                         |
| Recommended Cutting   | Hot Knife                      |



#### Product Selection

| Part No.  | Nominal Size |      | Type        | Wall Thickness |     | Color | Reel Length* |      | Weight |      |
|-----------|--------------|------|-------------|----------------|-----|-------|--------------|------|--------|------|
|           | in.          | mm.  |             | in.            | mm. |       | ft.          | m.   | lbs.   | kg.  |
| 170-03148 | 1/2          | 12.7 | BSHKLP120B  | 0.063          | 1.6 | Black | 100          | 30.5 | 1.3    | 0.6  |
| 170-03149 | 3/4          | 19.1 | BSHKLP340B  | 0.063          | 1.6 | Black | 100          | 30.5 | 1.8    | 0.8  |
| 170-03150 | 1-1/4        | 31.8 | BSHKLP1140B | 0.063          | 1.6 | Black | 100          | 30.5 | 2.3    | 1.04 |
| 170-03151 | 2            | 50.8 | BSHKLP200B  | 0.063          | 1.6 | Black | 100          | 30.5 | 3.2    | 1.45 |
| 170-03152 | 2-1/2        | 63.5 | BSHKLP212B  | 0.063          | 1.6 | Black | 100          | 30.5 | 3.75   | 1.7  |

Use Part No. for ordering and Type for specification purposes. \* Pre-cut lengths available upon request.



## Braided Sleeving

### Split Wrap Woven Braided Sleeving

Split wrap woven braided sleeving is a self-closing protective sleeving manufactured from a unique blend of monofilament and multifilament polyester fibers to create a durable fabric-like material. The overlapping wraparound design provides ease of access to wires and cables, and offers excellent flexibility, coverage and abrasion resistance.

#### Application

The tightly-woven material protects sensitive electronics and communication systems from dust and debris, while also reducing noise in applications that involve movement or vibration.

#### Benefits

- Center slit allows for quick and easy access to wires and cables for future maintenance or inspection, without the need for disassembly.
- Flexible material wraps around a variety of component shapes and sizes, making it easier to use and more versatile than slit loom convoluted tubing or spiral wrap products.
- A unique weave pattern provides increased coverage and greater resistance to abrasion, dust and debris.
- Overlapping slit design enhances flexibility, allowing it to shift and bend without exposing wires and cables.



#### Material Data

|                       |                                              |
|-----------------------|----------------------------------------------|
| Material              | Polyester Monofilament (PET) + Multifilament |
| Operating Temperature | -94°F to 257°F, -70°C to 125°C               |
| Melt Point            | 482°F / 250°C                                |
| Abrasion Protection   | Medium                                       |
| Recommended Cutting   | Hot Knife                                    |



#### Product Selection

| Part No.  | Nominal Size |      | Type       | Wall Thickness |      | Color | Overlap | Reel Length* |       | Weight |      |
|-----------|--------------|------|------------|----------------|------|-------|---------|--------------|-------|--------|------|
|           | in.          | mm.  |            | in.            | mm.  |       |         | ft.          | m.    | lbs.   | kg.  |
| 170-03181 | 3/8          | 9.5  | BSSWV380B  | 0.027          | 0.68 | Black | 41%     | 450          | 137.1 | 6.75   | 3.06 |
| 170-03182 | 1/2          | 12.7 | BSSWV120B  | 0.027          | 0.68 | Black | 35%     | 300          | 91.4  | 5.40   | 2.45 |
| 170-03183 | 5/8          | 15.8 | BSSWV580B  | 0.027          | 0.68 | Black | 30%     | 250          | 76.2  | 5.25   | 2.38 |
| 170-03184 | 3/4          | 19.1 | BSSWV340B  | 0.027          | 0.68 | Black | 28%     | 150          | 45.7  | 3.60   | 1.63 |
| 170-03185 | 1            | 25.4 | BSSWV100B  | 0.027          | 0.68 | Black | 26%     | 100          | 30.4  | 3.20   | 1.45 |
| 170-03186 | 1 1/2        | 38.1 | BSSWV1120B | 0.027          | 0.68 | Black | 23%     | 50           | 15.2  | 2.25   | 1.02 |

Use Part No. for ordering and Type for specification. \* Pre-cut lengths available upon request.



## Braided Sleeving

## Extreme High Temperature Resin Saturated Fiberglass Expandable Braided Sleeving

Designed as protection for wires and cables subjected to continuous temperature variations, vibration, abrasion, and mechanical stress, this sleeving is resistant to extremely high temperatures.

### Application

Perfect for engine manifolds and exhaust systems or any application where fire and extremely high temperatures create a hazard to workforce and equipment.

### Benefits

- Provides thermal protection up to 1,200°F.
- Maintains its tight structure under extreme shaking, scraping, pressure and varying temperature conditions.
- Cuts cleanly with scissors and installs easily.
- Comes in a wide range of diameters.



#### Material Data

|                       |                                  |
|-----------------------|----------------------------------|
| Material              | Resin Saturated Fiberglass       |
| Flammability          | UL VW-1                          |
| Operating Temperature | -94°F to 1,202°F, -70°C to 650°C |
| Melt Point            | 2,048°F / 1,120°C                |
| Abrasion Protection   | Very High                        |
| Recommended Cutting   | Scissors                         |



#### Product Selection

| Part No.                | Nominal Size |      | Type       | Wall Thickness |      | Maximum Diameter |      | Color | Reel Length* |      | Weight |      |
|-------------------------|--------------|------|------------|----------------|------|------------------|------|-------|--------------|------|--------|------|
|                         | in.          | mm.  |            | in.            | mm.  | in.              | mm.  |       | ft.          | m.   | lbs.   | kg.  |
| 170-03058               | 1/4          | 6.4  | BSHTFG140  | 0.031          | 0.79 | 0.375            | 9.5  | Black | 50           | 15.2 | 1.0    | 0.45 |
| 170-03059               | 1/2          | 12.7 | BSHTFG120  | 0.046          | 1.67 | 0.75             | 19.1 | Black | 50           | 15.2 | 2.4    | 1.09 |
| 170-03060               | 3/4          | 19.1 | BSHTFG340  | 0.046          | 1.67 | 1.125            | 28.6 | Black | 50           | 15.2 | 3.2    | 1.46 |
| 170-03061               | 1            | 25.4 | BSHTFG100  | 0.057          | 1.45 | 1.625            | 41.3 | Black | 25           | 7.6  | 2.63   | 1.2  |
| <b>Bulk Sized Reels</b> |              |      |            |                |      |                  |      |       |              |      |        |      |
| 170-03050               | 1/4          | 6.4  | BSHTFG140B | 0.031          | 0.79 | 0.375            | 9.5  | Black | 200          | 61.0 | 4.0    | 1.81 |
| 170-03051               | 1/2          | 12.7 | BSHTFG120B | 0.046          | 1.17 | 0.75             | 19.1 | Black | 200          | 61.0 | 9.6    | 4.35 |
| 170-03052               | 3/4          | 19.1 | BSHTFG340B | 0.046          | 1.17 | 1.125            | 28.6 | Black | 200          | 61.0 | 12.8   | 5.81 |
| 170-03053               | 1            | 25.4 | BSHTFG100B | 0.057          | 1.45 | 1.625            | 41.3 | Black | 100          | 30.5 | 10.5   | 4.76 |

Use Part No. for ordering and Type for specification purposes. \* Pre-cut lengths available upon request.



## Braided Sleeving

### High Temperature Nomex® Expandable Braided Sleeving


Manufactured with densely woven aramid fibers, this soft and flexible sleeving is self-extinguishing and is able to withstand temperatures reaching up to 662°F.

#### Application

Excellent for use in extremely harsh environments including those with exposure to direct flame, high temperatures, as well as Beta, Gamma and X-ray radiation – in particular, military and aerospace wiring and harnessing applications.

#### Benefits

- Does not melt and is unaffected by most acids.
- Provides excellent thermal stability against flames.
- Meets FMVSS 302 approval for use in automotive engineering.
- Cuts with ordinary scissors which reduces assembly time.



#### Material Data

|                       |                                             |
|-----------------------|---------------------------------------------|
| Material              | Polyaramid Polymetaphenylene Isophthalamide |
| Flammability          | Non-Flammable                               |
| Operating Temperature | -320°F to 662°F, -196°C to 350°C            |
| Melt Point            | N/A                                         |
| Abrasion Protection   | Low                                         |
| Recommended Cutting   | Scissors                                    |



#### Product Selection

| Part No.  | Nominal Size |      | Type       | Expansion Range |            |            |            | Color | Reel Length |      | Weight |      |
|-----------|--------------|------|------------|-----------------|------------|------------|------------|-------|-------------|------|--------|------|
|           | in.          | mm.  |            | (Min.) in.      | (Max.) in. | (Min.) mm. | (Max.) mm. |       | ft.         | m.   | lbs.   | kg.  |
| 170-03158 | 1/8          | 3.2  | BSNMX185B  | 0.062           | 0.25       | 1.6        | 6.4        | Green | 100         | 30.5 | 0.12   | 0.05 |
| 170-03159 | 1/4          | 6.4  | BSNMX145B  | 0.125           | 0.312      | 3.2        | 7.9        | Green | 100         | 30.5 | 0.5    | 0.23 |
| 170-03160 | 3/8          | 9.5  | BSNMX385B  | 0.25            | 0.5        | 6.4        | 12.7       | Green | 100         | 30.5 | 0.67   | 0.3  |
| 170-03161 | 1/2          | 12.7 | BSNMX125B  | 0.312           | 0.625      | 7.9        | 15.9       | Green | 100         | 30.5 | 0.91   | 0.41 |
| 170-03162 | 3/4          | 19.1 | BSNMX345B  | 0.562           | 1          | 14.3       | 25.4       | Green | 100         | 30.5 | 1.34   | 0.61 |
| 170-03163 | 1            | 25.4 | BSNMX105B  | 0.75            | 1.12       | 19.1       | 28.6       | Green | 100         | 30.5 | 2.42   | 1.1  |
| 170-03164 | 1-1/4        | 31.8 | BSNMX1145B | 1.0             | 1.5        | 25.4       | 38.1       | Green | 100         | 30.5 | 3.49   | 1.58 |
| 170-03165 | 1-1/2        | 38.1 | BSNMX1125B | 1.25            | 1.75       | 31.8       | 44.4       | Green | 100         | 30.5 | 4.03   | 1.83 |
| 170-03166 | 1-3/4        | 44.4 | BSNMX1345B | 1.5             | 2.0        | 38.1       | 50.8       | Green | 100         | 30.5 | 4.76   | 2.16 |

Use Part No. for ordering and Type for specification purposes. Nomex® is a registered trademark of th DuPont Corporation.

## Braided Sleeving

## High Temperature Aluminum Laminated Fiberglass Sleeving

A tubular shaped product that combines the protection of bonded aluminum and fiberglass into a single solution that is able to reflect radiant heat away from the sensitive contents inside the tube.

### Application

Terrific for applications when appearance and insulation are important for protecting delicate wire bundles, cables and hoses from damage caused by nearby exhaust pipes, headers or heat-generating components.

### Benefits

- Adds a layer of protection that prevents scraping; cut and abrasion resistant.
- Resists gasoline and engine chemicals.
- Creates an insulation barrier for vulnerable cable and wire materials within high-temperature environments.
- Cuts cleanly with scissors.



#### Material Data

|                       |                                |
|-----------------------|--------------------------------|
| Material              | Bonded Aluminum + Fiberglass   |
| Flammability          | Non-Flammable                  |
| Operating Temperature | -76°F to 491°F, -60°C to 255°C |
| Melt Point            | 2,048°F / 1,120°C              |
| Abrasion Protection   | N/A                            |
| Recommended Cutting   | Scissors                       |



#### Product Selection

| Part No.                | Nominal Size |      | Type          | Wall Thickness*<br>±.006 in. |      | Maximum Diameter |      | Color  | Reel Length |      | Weight |      |
|-------------------------|--------------|------|---------------|------------------------------|------|------------------|------|--------|-------------|------|--------|------|
|                         | in.          | mm.  |               | in.                          | mm.  | in.              | mm.  |        | ft.         | m.   | lbs.   | kg.  |
| 170-03175               | 3/8          | 9.7  | BSHTTST38SR   | 0.025                        | 0.64 | 0.317            | 8.1  | Silver | 100         | 30.5 | 2.3    | 1.1  |
| 170-03062               | 1/2          | 12.7 | BSHTTST12SR   | 0.025                        | 0.64 | 0.437            | 11.1 | Silver | 100         | 30.5 | 2.55   | 1.16 |
| 170-03063               | 3/4          | 19.1 | BSHTTST34SR   | 0.025                        | 0.64 | 0.687            | 17.5 | Silver | 100         | 30.5 | 3.45   | 1.57 |
| 170-03064               | 1            | 25.4 | BSHTTST10SR   | 0.025                        | 0.64 | 0.937            | 23.8 | Silver | 100         | 30.5 | 4.5    | 2.0  |
| 170-03065               | 1-3/4        | 44.5 | BSHTTST134SR  | 0.025                        | 0.64 | 1.687            | 42.8 | Silver | 50          | 15.2 | 3.7    | 1.68 |
| 170-03097               | 2-1/2        | 63.5 | BSHTTST212SR  | 0.025                        | 0.64 | 2.375            | 60.3 | Silver | 50          | 15.2 | 5.05   | 2.3  |
| <b>Bulk Sized Reels</b> |              |      |               |                              |      |                  |      |        |             |      |        |      |
| 170-03054               | 1/2          | 12.7 | BSHTTST12SRB  | 0.025                        | 0.64 | 0.437            | 11.1 | Silver | 250         | 76.2 | 6.375  | 2.9  |
| 170-03055               | 3/4          | 19.1 | BSHTTST34SRB  | 0.025                        | 0.64 | 0.687            | 17.4 | Silver | 250         | 76.2 | 8.625  | 3.91 |
| 170-03056               | 1            | 25.4 | BSHTTST10SRB  | 0.025                        | 0.64 | 0.937            | 23.8 | Silver | 250         | 76.2 | 11.25  | 5.08 |
| 170-03057               | 1-3/4        | 44.5 | BSHTTST134SRB | 0.025                        | 0.64 | 1.687            | 42.8 | Silver | 100         | 30.5 | 7.4    | 3.36 |

Use Part No. for ordering and Type for specification. \*Nominal size measures external diameter of sleeving.

## Merchandising Display Rack

Designed to save space and provide easy access when dispensing braided sleeving, this unit allows for the efficient handling and management of sleeving.

- Simplifies cut-to-length counter sales.
- Dispenses easily from preformed slot.
- Includes mounting hardware.
- Constructed of durable ABS plastic.
- Holds six standard-sized spools; drop-in reels sold separately.
- Dimensions: 23.5" (W) x 10" (D) x 6" (H)



| Product Selection |           |       |
|-------------------|-----------|-------|
| Part No.          | Type      | Color |
| 170-03031         | BSDISPLAY | Black |

Use Part No. for ordering and Type for specification purposes.

## Split Wrap Installation Tool

Use this tool to guide a cable or insert a cable harness inside the split wrap loom tube. This tool protects installer's hands from cuts. Can also be used to apply convoluted tubing.

| Product Selection |        |            |                                     |
|-------------------|--------|------------|-------------------------------------|
| Part No.          | Size   | Type       | Description                         |
| 170-03067         | 1/4"   | BSWTOOL14  | 1/4" Split Wrap Installation Tool   |
| 170-03032         | 1/2"   | BSWTOOL12  | 1/2" Split Wrap Installation Tool   |
| 170-03068         | 3/4"   | BSWTOOL34  | 3/4" Split Wrap Installation Tool   |
| 170-03033         | 1"     | BSWTOOL1   | 1" Split Wrap Installation Tool     |
| 170-03034         | 1-1/4" | BSWTOOL114 | 1-1/4" Split Wrap Installation Tool |

Use Part No. for ordering and Type for specification purposes.



## Bench and Handheld Hot Knife Tools

Hot knife cuts through braided sleeving easily to minimize fraying and deliver optimum results.

| Product Selection |       |       |                                      |
|-------------------|-------|-------|--------------------------------------|
| Part No.          | Type  | Color | Description                          |
| 170-03039         | BSBHK | White | Bench Mount Braided Sleeve Hot Knife |
| 170-03040         | BSPHK | Black | Handheld Braided Sleeve Hot Knife    |

Use Part No. for ordering and Type for specification purposes.



Bench mount hot knife

- Designed for production environments
- Uses 2.5" blade
- Lighted power switch
- Heats to 1,112°F in 30 sec.
- 110 volt operation
- Replaceable blades



Handheld hot knife

- Trigger switch
- Heats quickly
- 110 volt operation
- Replaceable blades

# HellermannTyton

### HellermannTyton North American Corporate Headquarters

7930 N. Faulkner Rd, PO Box 245017  
Milwaukee, WI 53224-9517  
Phone: (414) 355-1130, (800) 537-1512  
Fax: (414) 355-7341, (800) 848-9866  
email: corp@htamericas.com  
www.hellermann.tyton.com

**TS16949, ISO 9001, and ISO 14001 certified**

### HellermannTyton Canada

Unit #4, 205 Industrial Parkway North  
Aurora, Ontario L4G 4C4 Canada  
Phone: (800) 661-2461  
Fax: (800) 390-3904  
email: sales@hellermannntyton.ca

### HellermannTyton Mexico

Anillo Periferico Sur 7980 Edificio 6A  
Parque Industrial Tecnológico II  
Santa María Tequepexpan  
Tlaquepaque, Jalisco, Mexico 45601  
Phone: 011-52-33-3-133-9880  
Fax: 011-52-33-3-133-9861  
email: info@htamericas.com.mx  
**ISO 9001 certified**