



E-Mail Address:

Password: [Forgot Me?](#)☐ Remember me[Register](#)[Home](#)[Promotions](#)[Products](#)[Technical](#)[Services](#)[Sales Reps &
Distributors](#)[ESD
Information](#)**On-Line Catalog**[SEARCH](#) | [CATALOG HOME](#)**Banana Plug Adapters****Features and Benefits:**

- All adapters designed to accept standard banana plug
- Made in America

P/N	Description
09700	Alligator Clip
09750	Large Clip with Banana Jack 10-32 x 1/2" threaded hole accepts standard banana plug or 10-32 thread
09780	Ring Terminal Banana Jack
09782	Stacking Snap Banana Jack, 10mm Snap and 10mm Socket

NOTE:

Per ESD 6.1 "Provisions may be made to include a resistor where it may be required for a purpose other than ESD."

ESD Handbook TR 20.20 paragraph 5.1.3 Basic Grounding Requirements

"The first step in ensuring that everything in an EPA is at the same electrical potential is to ground all conductive components of the work area (worksurfaces, people, equipment, etc.) to the same electrical ground point. This point is called the common point ground. The next step in completing the ground circuit is to connect the common point ground to the equipment ground (third wire, green)"

One Megohm resistor is required in wrist straps, however, the recommended practice is hard ground per ANSI/EOS/ESD S6.1 that is no resistor between the common point ground terminal and a worksurface, floor mat, or shelving. Per ANSI/ESD S20.20 Table 1 Grounding System Technical Requirement, the Recommended Range is less than 1 ohm AC impedance.

West Coast: 3651 Walnut Ave., Chino, CA 91710
Phone: (909) 627-8178 Fax: (909) 627-7449

East Coast: 90 Hudson Road, Canton, MA 02
Phone: (781) 821-8370 Fax: (781) 575-017

[Home](#) [Promotions](#) [Products](#) [Technical](#) [Services](#) [Contact](#) [ESD Information](#)

Copyright © 2006 Desco Industries, Inc. All Rights Reserved