



LOC		DIST		REVISIONS						
HM		00		P	LTR	DESCRIPTION	DATE	DWN	APVD	
					E	REV PER ECO-12-020239	03DEC2012	JM	MS	

1. DIMENSIONS SHOWN ARE NOMINAL UNLESS OTHERWISE SPECIFIED.
2. CABLE ASSEMBLY IS WIRED PER WIRING DIAGRAM.
3. MATERIAL:
- CONNECTOR HOUSINGS- POLYCARBONATE, UL 94V-0 RATED, NEMA GRAY.
- STRAIN RELIEFS- CARBON STEEL WITH NICKEL PLATING 5.08µm [0.000200] MINIMUM THICK.
- CONTACTS- COPPER ALLOY WITH SILVER PLATED STRIP 3.81µm [0.000150] MINIMUM THICK.
4. DIMENSION A SHALL BE MEASURED WITH CONDUIT IN THE RELAXED POSITION.
5. DESIGNATIONS IN PARENTHESES () ARE FOR REFERENCE ONLY.
6. MANUFACTURING LOCATION, DATE CODE, PART NUMBER AND LENGTH SHALL BE INK STAMPED APPROXIMATELY WHERE INDICATED.
7. APPLICATION: AMPINERGY (TM) - MODULAR POWER DISTRIBUTION SYSTEM, A MANUFACTURED WIRING SYSTEM.
8. CABLE CONNECTOR MATES WITH DEDICATED NEUTRAL (3-3-2) POWER CONNECTOR CABLE ASSEMBLIES. KEYING FEATURE MAINTAINS CORRECT POLARITY OF MATING POWER CONNECTORS.
9. TABS FOR POSITIVE LATCHING TO MATING COMPONENTS.
10. USE GROUND WIRE INSPECTION WINDOW TO VERIFY BONDING AND GROUNDING CONDUCTOR.

304.8 [12]	15240.0-15316.2 [600.00-603.00]	5-1933403-0	15.24 [50.00]
304.8 [12]	12192.0-12268.2 [480.00-483.00]	4-1933403-0	12.19 [40.00]
304.8 [12]	9144.0-9220.2 [360.00-363.00]	3-1933403-0	9.14 [30.00]
304.8 [12]	7620.0-7696.2 [300.00-303.00]	2-1933403-5	7.62 [25.00]
304.8 [12]	6096.0-6146.8 [240.00-242.00]	2-1933403-0	6.10 [20.00]
304.8 [12]	4572.0-4622.8 [180.00-182.00]	1-1933403-5	4.57 [15.00]
304.8 [12]	3048.0-3073.4 [120.00-121.00]	1-1933403-0	3.05 [10.00]
304.8 [12]	1524.0-1543.0 [60.00-60.75]	1933403-5	1.52 [5.00]
304.8 [12]	1219.2-1231.9 [48.00-48.50]	1933403-4	1.22 [4.00]
304.8 [12]	914.4-927.1 [36.00-36.50]	1933403-3	0.91 [3.00]
304.8 [12]	609.6-622.3 [24.00-24.50]	1933403-2	0.61 [2.00]
304.8 [12]	304.8-317.5 [12.00-12.50]	1933403-1	0.30 [1.00]
B DIM	A DIM 4	PART NUMBER	REF DIM

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN J MCNEAL 08JAN2008	TE Connectivity	
DIMENSIONS: mm [INCHES]		CHK S JONES 08JAN2008		
TOLERANCES UNLESS OTHERWISE SPECIFIED:		APVD S JONES 08JAN2008	NAME	
0 PLC ±		PRODUCT SPEC	CABLE ASSEMBLY, LINE ENTRY 3-3-2	
1 PLC ±		108-1234		
2 PLC ±		APPLICATION SPEC	SIZE	
3 PLC ±		114-6039	CAGE CODE	
4 PLC ±		WEIGHT	DRAWING NO	
ANGLES			A100779C=1933403	
FINISH		CUSTOMER DRAWING	RESTRICTED TO	
SCALE 1:1		SHEET 1 OF 1	REV E	

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity Divested:](#)

[3-1906043-0](#)