



# +3 Volt, Serial Input Complete 12-Bit DAC

## AD8300


### FEATURES

- Complete 12-Bit DAC
- No External Components
- Single +3 Volt Operation
- 0.5 mV/Bit with 2.0475 V Full Scale
- 6  $\mu$ s Output Voltage Settling Time
- Low Power: 3.6 mW
- Compact SO-8 1.5 mm Height Package

### APPLICATIONS

- Portable Communications
- Digitally Controlled Calibration
- Servo Controls
- PC Peripherals

### FUNCTIONAL BLOCK DIAGRAM



### GENERAL DESCRIPTION

The AD8300 is a complete 12-bit, voltage-output digital-to-analog converter designed to operate from a single +3 volt supply. Built using a CBCMOS process, this monolithic DAC offers the user low cost, and ease-of-use in single-supply +3 volt systems. Operation is guaranteed over the supply voltage range of +2.7 V to +5.5 V making this device ideal for battery operated applications.

The 2.0475 V full-scale voltage output is laser trimmed to maintain accuracy over the operating temperature range of the device. The binary input data format provides an easy-to-use one-half-millivolt-per-bit software programmability. The voltage outputs are capable of sourcing 5 mA.

A double buffered serial data interface offers high speed, three-wire, DSP and microcontroller compatible inputs using data in (SDI), clock (CLK) and load strobe ( $\overline{\text{LD}}$ ) pins. A chip select ( $\overline{\text{CS}}$ ) pin simplifies connection of multiple DAC packages by enabling the clock input when active low. Additionally, a  $\overline{\text{CLR}}$  input sets the output to zero scale at power on or upon user demand.

The AD8300 is specified over the extended industrial ( $-40^{\circ}\text{C}$  to  $+85^{\circ}\text{C}$ ) temperature range. AD8300's are available in plastic DIP, and low profile 1.5 mm height SO-8 surface mount packages.




Figure 1. Minimum Supply Voltage vs. Load




Figure 2. Linearity Error vs. Digital Code and Temperature

### REV. 0

Information furnished by Analog Devices is believed to be accurate and reliable. However, no responsibility is assumed by Analog Devices for its use, nor for any infringements of patents or other rights of third parties which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of Analog Devices.

One Technology Way, P.O. Box 9106, Norwood, MA 02062-9106, U.S.A.  
Tel: 617/329-4700 Fax: 617/326-8703

# AD8300—SPECIFICATIONS

## +3 V OPERATION (@ $V_{DD} = +2.7\text{ V}$ to $+3.6\text{ V}$ , $-40^{\circ}\text{C} \leq T_A \leq +85^{\circ}\text{C}$ , unless otherwise noted)

| Parameter                                       | Symbol                | Condition                                                                   | Min   | Typ       | Max   | Units                   |
|-------------------------------------------------|-----------------------|-----------------------------------------------------------------------------|-------|-----------|-------|-------------------------|
| STATIC PERFORMANCE                              |                       |                                                                             |       |           |       |                         |
| Resolution                                      | N                     | [Note 1]                                                                    | 12    |           |       | Bits                    |
| Relative Accuracy                               | INL                   |                                                                             | -2    | $\pm 1/2$ | +2    | LSB                     |
| Differential Nonlinearity <sup>2</sup>          | DNL                   | Monotonic                                                                   | -1    | $\pm 1/2$ | +1    | LSB                     |
| Zero-Scale Error                                | $V_{ZSE}$             | Data = 000 <sub>H</sub>                                                     |       | +1/2      | +3    | mV                      |
| Full-Scale Voltage <sup>3</sup>                 | $V_{FS}$              | Data = FFF <sub>H</sub>                                                     | 2.039 | 2.0475    | 2.056 | Volts                   |
| Full-Scale Tempco                               | $TCV_{FS}$            | [Notes 3, 4]                                                                |       | 16        |       | ppm/ $^{\circ}\text{C}$ |
| ANALOG OUTPUT                                   |                       |                                                                             |       |           |       |                         |
| Output Current (Source)                         | $I_{OUT}$             | Data = 800 <sub>H</sub> , $\Delta V_{OUT} = 5\text{ LSB}$                   |       |           | 5     | mA                      |
| Output Current (Sink)                           | $I_{OUT}$             | Data = 800 <sub>H</sub> , $\Delta V_{OUT} = 5\text{ LSB}$                   |       |           | 2     | mA                      |
| Load Regulation                                 | $L_{REG}$             | $R_L = 200\ \Omega$ to $\infty$ , Data = 800 <sub>H</sub>                   |       | 1.5       | 5     | LSB                     |
| Output Resistance to GND                        | $R_{OUT}$             | Data = 000 <sub>H</sub>                                                     |       | 30        |       | $\Omega$                |
| Capacitive Load                                 | $C_L$                 | No Oscillation <sup>4</sup>                                                 |       | 500       |       | pF                      |
| LOGIC INPUTS                                    |                       |                                                                             |       |           |       |                         |
| Logic Input Low Voltage                         | $V_{IL}$              |                                                                             |       |           | 0.6   | V                       |
| Logic Input High Voltage                        | $V_{IH}$              |                                                                             | 2.1   |           |       | V                       |
| Input Leakage Current                           | $I_{IL}$              |                                                                             |       |           | 10    | $\mu\text{A}$           |
| Input Capacitance                               | $C_{IL}$              |                                                                             |       |           | 10    | pF                      |
| INTERFACE TIMING SPECIFICATIONS <sup>4, 5</sup> |                       |                                                                             |       |           |       |                         |
| Clock Width High                                | $t_{CH}$              |                                                                             | 40    |           |       | ns                      |
| Clock Width Low                                 | $t_{CL}$              |                                                                             | 40    |           |       | ns                      |
| Load Pulse Width                                | $t_{LDW}$             |                                                                             | 50    |           |       | ns                      |
| Data Setup                                      | $t_{DS}$              |                                                                             | 15    |           |       | ns                      |
| Data Hold                                       | $t_{DH}$              |                                                                             | 15    |           |       | ns                      |
| Clear Pulse Width                               | $t_{CLR\ W}$          |                                                                             | 40    |           |       | ns                      |
| Load Setup                                      | $t_{LD1}$             |                                                                             | 15    |           |       | ns                      |
| Load Hold                                       | $t_{LD2}$             |                                                                             | 40    |           |       | ns                      |
| Select                                          | $t_{CSS}$             |                                                                             | 40    |           |       | ns                      |
| Deselect                                        | $t_{CSH}$             |                                                                             | 40    |           |       | ns                      |
| AC CHARACTERISTICS <sup>4</sup>                 |                       |                                                                             |       |           |       |                         |
| Voltage Output Settling Time                    | $t_s$                 | To $\pm 0.2\%$ of Full Scale                                                |       | 7         |       | $\mu\text{s}$           |
|                                                 |                       | To $\pm 1\text{ LSB}$ of Final Value <sup>6</sup>                           |       | 14        |       | $\mu\text{s}$           |
| Output Slew Rate                                | SR                    | Data = 000 <sub>H</sub> to FFF <sub>H</sub> to 000 <sub>H</sub>             |       | 2.0       |       | V/ $\mu\text{s}$        |
| DAC Glitch                                      |                       |                                                                             |       | 15        |       | nV/s                    |
| Digital Feedthrough                             |                       |                                                                             |       | 15        |       | nV/s                    |
| SUPPLY CHARACTERISTICS                          |                       |                                                                             |       |           |       |                         |
| Power Supply Range                              | $V_{DD\text{ RANGE}}$ | DNL $< \pm 1\text{ LSB}$                                                    | 2.7   |           | 5.5   | V                       |
| Positive Supply Current                         | $I_{DD}$              | $V_{DD} = 3\text{ V}$ , $V_{IL} = 0\text{ V}$ , Data = 000 <sub>H</sub>     |       | 1.2       | 1.7   | mA                      |
| Positive Supply Current                         | $I_{DD}$              | $V_{DD} = 3.6\text{ V}$ , $V_{IH} = 2.3\text{ V}$ , Data = FFF <sub>H</sub> |       | 1.9       | 3.0   | mA                      |
| Power Dissipation                               | $P_{DISS}$            | $V_{DD} = 3\text{ V}$ , $V_{IL} = 0\text{ V}$ , Data = 000 <sub>H</sub>     |       | 3.6       | 5.1   | mW                      |
| Power Supply Sensitivity                        | PSS                   | $\Delta V_{DD} = \pm 5\%$                                                   |       | 0.001     | 0.005 | %/%                     |

### NOTES

<sup>1</sup> 1 LSB = 0.5 mV for 0 V to +2.0475 V output range.

<sup>2</sup> The first two codes (000<sub>H</sub>, 001<sub>H</sub>) are excluded from the linearity error measurement.

<sup>3</sup> Includes internal voltage reference error.

<sup>4</sup> These parameters are guaranteed by design and not subject to production testing.

<sup>5</sup> All input control signals are specified with  $t_R = t_F = 2\text{ ns}$  (10% to 90% of +3 V) and timed from a voltage level of 1.6 V.

<sup>6</sup> The settling time specification does not apply for negative going transitions within the last 6 LSBs of ground. Some devices exhibit double the typical settling time in this 6 LSB region.

Specifications subject to change without notice.

**+5 V OPERATION** (@  $V_{DD} = +5\text{ V} \pm 10\%$ ,  $-40^{\circ}\text{C} \leq T_A \leq +85^{\circ}\text{C}$ , unless otherwise noted)

| Parameter                                             | Symbol                | Condition                                                                   | Min   | Typ       | Max   | Units                   |
|-------------------------------------------------------|-----------------------|-----------------------------------------------------------------------------|-------|-----------|-------|-------------------------|
| <b>STATIC PERFORMANCE</b>                             |                       |                                                                             |       |           |       |                         |
| Resolution                                            | N                     | [Note 1]                                                                    | 12    |           |       | Bits                    |
| Relative Accuracy                                     | INL                   |                                                                             | -2    | $\pm 1/2$ | +2    | LSB                     |
| Differential Nonlinearity <sup>2</sup>                | DNL                   | Monotonic                                                                   | -1    | $\pm 1/2$ | +1    | LSB                     |
| Zero-Scale Error                                      | $V_{ZSE}$             | Data = 000 <sub>H</sub>                                                     |       | $\pm 1/2$ | +3    | mV                      |
| Full-Scale Voltage <sup>3</sup>                       | $V_{FS}$              | Data = FFF <sub>H</sub>                                                     | 2.039 | 2.0475    | 2.056 | Volts                   |
| Full-Scale Tempco                                     | $TCV_{FS}$            | [Notes 3, 4]                                                                |       | 16        |       | ppm/ $^{\circ}\text{C}$ |
| <b>ANALOG OUTPUT</b>                                  |                       |                                                                             |       |           |       |                         |
| Output Current (Source)                               | $I_{OUT}$             | Data = 800 <sub>H</sub> , $\Delta V_{OUT} = 5\text{ LSB}$                   |       |           | 5     | mA                      |
| Output Current (Sink)                                 | $I_{OUT}$             | Data = 800 <sub>H</sub> , $\Delta V_{OUT} = 5\text{ LSB}$                   |       |           | 2     | mA                      |
| Load Regulation                                       | $L_{REG}$             | $R_L = 200\ \Omega$ to $\infty$ , Data = 800 <sub>H</sub>                   |       | 1.5       | 5     | LSB                     |
| Output Resistance to GND                              | $R_{OUT}$             | Data = 000 <sub>H</sub>                                                     |       | 30        |       | $\Omega$                |
| Capacitive Load                                       | $C_L$                 | No Oscillation <sup>4</sup>                                                 |       | 500       |       | pF                      |
| <b>LOGIC INPUTS</b>                                   |                       |                                                                             |       |           |       |                         |
| Logic Input Low Voltage                               | $V_{IL}$              |                                                                             |       |           | 0.8   | V                       |
| Logic Input High Voltage                              | $V_{IH}$              |                                                                             | 2.4   |           |       | V                       |
| Input Leakage Current                                 | $I_{IL}$              |                                                                             |       |           | 10    | $\mu\text{A}$           |
| Input Capacitance                                     | $C_{IL}$              |                                                                             |       |           | 10    | pF                      |
| <b>INTERFACE TIMING SPECIFICATIONS<sup>4, 5</sup></b> |                       |                                                                             |       |           |       |                         |
| Clock Width High                                      | $t_{CH}$              |                                                                             | 30    |           |       | ns                      |
| Clock Width Low                                       | $t_{CL}$              |                                                                             | 30    |           |       | ns                      |
| Load Pulse Width                                      | $t_{LDW}$             |                                                                             | 30    |           |       | ns                      |
| Data Setup                                            | $t_{DS}$              |                                                                             | 15    |           |       | ns                      |
| Data Hold                                             | $t_{DH}$              |                                                                             | 15    |           |       | ns                      |
| Clear Pulse Width                                     | $t_{CLWR}$            |                                                                             | 30    |           |       | ns                      |
| Load Setup                                            | $t_{LD1}$             |                                                                             | 15    |           |       | ns                      |
| Load Hold                                             | $t_{LD2}$             |                                                                             | 30    |           |       | ns                      |
| Select                                                | $t_{CSS}$             |                                                                             | 30    |           |       | ns                      |
| Deselect                                              | $t_{CSH}$             |                                                                             | 30    |           |       | ns                      |
| <b>AC CHARACTERISTICS<sup>4</sup></b>                 |                       |                                                                             |       |           |       |                         |
| Voltage Output Settling Time                          | $t_s$                 | To $\pm 0.2\%$ of Full Scale                                                |       | 6         |       | $\mu\text{s}$           |
| Voltage Output Settling Time                          | $t_s$                 | To $\pm 1\text{ LSB}$ of Final Value <sup>5</sup>                           |       | 13        |       | $\mu\text{s}$           |
| Output Slew Rate                                      | SR                    | Data = 000 <sub>H</sub> to FFF <sub>H</sub> to 000 <sub>H</sub>             |       | 2.2       |       | V/ $\mu\text{s}$        |
| DAC Glitch                                            |                       |                                                                             |       | 15        |       | nV/s                    |
| Digital Feedthrough                                   |                       |                                                                             |       | 15        |       | nV/s                    |
| <b>SUPPLY CHARACTERISTICS</b>                         |                       |                                                                             |       |           |       |                         |
| Power Supply Range                                    | $V_{DD\text{ RANGE}}$ | $DNL < \pm 1\text{ LSB}$                                                    | 2.7   |           | 5.5   | V                       |
| Positive Supply Current                               | $I_{DD}$              | $V_{DD} = 5\text{ V}$ , $V_{IL} = 0\text{ V}$ , Data = 000 <sub>H</sub>     |       | 1.2       | 1.7   | mA                      |
| Positive Supply Current                               | $I_{DD}$              | $V_{DD} = 5.5\text{ V}$ , $V_{IH} = 2.3\text{ V}$ , Data = FFF <sub>H</sub> |       | 2.8       | 4.0   | mA                      |
| Power Dissipation                                     | $P_{DISS}$            | $V_{DD} = 5\text{ V}$ , $V_{IL} = 0\text{ V}$ , Data = 000 <sub>H</sub>     |       | 6         | 5.1   | mW                      |
| Power Supply Sensitivity                              | PSS                   | $\Delta V_{DD} = \pm 10\%$                                                  |       | 0.001     | 0.006 | %/%                     |

## NOTES

<sup>1</sup> 1 LSB = 0.5 mV for 0 V to +2.0475 V output range.<sup>2</sup> The first two codes (000<sub>H</sub>, 001<sub>H</sub>) are excluded from the linearity error measurement.<sup>3</sup> Includes internal voltage reference error.<sup>4</sup> These parameters are guaranteed by design and not subject to production testing.<sup>5</sup> All input control signals are specified with  $t_R = t_F = 2\text{ ns}$  (10% to 90% of +5 V) and timed from a voltage level of 1.6 V.<sup>6</sup> The settling time specification does not apply for negative going transitions within the last 6 LSBs of ground. Some devices exhibit double the typical settling time in this 6 LSB region.

Specifications subject to change without notice.

# AD8300

## ABSOLUTE MAXIMUM RATINGS\*

|                                                    |                                       |
|----------------------------------------------------|---------------------------------------|
| $V_{DD}$ to GND                                    | −0.3 V, +7 V                          |
| Logic Inputs to GND                                | −0.3 V, +7 V                          |
| $V_{OUT}$ to GND                                   | −0.3 V, $V_{DD} + 0.3$ V              |
| $I_{OUT}$ Short Circuit to GND                     | 50 mA                                 |
| Package Power Dissipation                          | $(T_J \text{ Max} - T_A)/\theta_{JA}$ |
| Thermal Resistance $\theta_{JA}$                   |                                       |
| 8-Pin Plastic DIP Package (N-8)                    | 103°C/W                               |
| 8-Lead SOIC Package (SO-8)                         | 158°C/W                               |
| Maximum Junction Temperature ( $T_J \text{ Max}$ ) | 150°C                                 |
| Operating Temperature Range                        | −40°C to +85°C                        |
| Storage Temperature Range                          | −65°C to +150°C                       |
| Lead Temperature (Soldering, 10 secs)              | +300°C                                |

\*Stresses above those listed under “Absolute Maximum Ratings” may cause permanent damage to the device. This is a stress rating only and functional operation of the device at these or any other conditions above those indicated in the operational sections of this specification is not implied. Exposure to absolute maximum rating conditions for extended periods may affect device reliability.

## ORDERING GUIDE

| Model    | INL | Temp | Package Description | Package Option |
|----------|-----|------|---------------------|----------------|
| AD8300AN | ±2  | XIND | 8-Pin P-DIP         | N-8            |
| AD8300AR | ±2  | XIND | 8-Lead SOIC         | SO-8           |


## NOTES

XIND = −40°C to +85°C.


The AD8300 contains 630 transistors. The die size measures 72 mil × 65 mil.

## PIN CONFIGURATIONS

### SO-8



### Plastic DIP



## PIN DESCRIPTIONS

| Pin # | Name             | Function                                                                                                                                                                                                     |
|-------|------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 1     | $V_{DD}$         | Positive power supply input. Specified range of operation +2.7 V to +5.5 V.                                                                                                                                  |
| 2     | $\overline{CS}$  | Chip Select, active low input. Disables shift register loading when high. Does not affect $\overline{LD}$ operation.                                                                                         |
| 3     | CLK              | Clock input, positive edge clocks data into shift register.                                                                                                                                                  |
| 4     | SDI              | Serial Data Input, input data loads directly into the shift register.                                                                                                                                        |
| 5     | $\overline{LD}$  | Load DAC register strobes, active low. Transfers shift register data to DAC register. See Truth Table I for operation. Asynchronous active low input.                                                        |
| 6     | $\overline{CLR}$ | Resets DAC register to zero condition. Asynchronous active low input.                                                                                                                                        |
| 7     | GND              | Analog & Digital Ground.                                                                                                                                                                                     |
| 8     | $V_{OUT}$        | DAC voltage output, 2.0475 V full scale with 0.5 mV per bit. An internal temperature stabilized reference maintains a fixed full-scale voltage independent of time, temperature and power supply variations. |




Figure 3. Timing Diagram

## CAUTION

ESD (electrostatic discharge) sensitive device. Electrostatic charges as high as 4000 V readily accumulate on the human body and test equipment and can discharge without detection. Although the AD8300 features proprietary ESD protection circuitry, permanent damage may occur on devices subjected to high energy electrostatic discharges. Therefore, proper ESD precautions are recommended to avoid performance degradation or loss of functionality.



## Typical Performance Characteristics




Figure 4.  $I_{OUT}$  vs.  $V_{OUT}$




Figure 7. Logic Input Threshold Voltage vs.  $V_{DD}$




Figure 10. Detail Settling Time




Figure 5. Broadband Noise




Figure 8. Power Supply Rejection vs. Frequency




Figure 11. Large Signal Settling Time




Figure 6. Supply Current vs. Logic Input Voltage




Figure 9. Midscale Transition Performance




Figure 12. Digital Feedthrough vs. Time

# AD8300

## Typical Performance Characteristics




Figure 13. Total Unadjusted Error Histogram




Figure 15. Zero-Scale Voltage Drift vs. Temperature




Figure 18. Supply Current vs. Temperature




Figure 14. Full-Scale Voltage Drift vs. Temperature




Figure 16. Output Voltage Noise Density vs. Frequency




Figure 19. Full-Scale Output Tempco Histogram




Figure 17. Long Term Drift Accelerated by Burn-In

Table I. Control Logic Truth Table

| CS | CLK | CLR | LD | Serial Shift Register Function       | DAC Register Function                        |
|----|-----|-----|----|--------------------------------------|----------------------------------------------|
| H  | X   | H   | H  | No Effect                            | Latched                                      |
| L  | L   | H   | H  | No Effect                            | Latched                                      |
| L  | H   | H   | H  | No Effect                            | Latched                                      |
| L  | ↑   | H   | H  | Shift-Register-Data Advanced One Bit | Latched                                      |
| ↑  | L   | H   | H  | No Effect                            | Latched                                      |
| H  | X   | H   | ↓  | No Effect                            | Updated with Current Shift Register Contents |
| H  | X   | H   | L  | No Effect                            | Transparent                                  |
| H  | X   | L   | X  | No Effect                            | Loaded with All Zeros                        |
| H  | X   | ↑   | H  | No Effect                            | Latched All Zeros                            |

## NOTES

<sup>1</sup>↑ = Positive Logic Transition; ↓ = Negative Logic Transition; X = Don't Care.

<sup>2</sup>Do not clock in serial data while LD is LOW.

## OPERATION

The AD8300 is a complete ready to use 12-bit digital-to-analog converter. Only one +3 V power supply is necessary for operation. It contains a 12-bit laser-trimmed digital-to-analog converter, a curvature-corrected bandgap reference, rail-to-rail output op amp, serial-input register, and DAC register. The serial data interface consists of a serial-data-input (SDI) clock (CLK), and load strobe pins (LD) with an active low CS strobe. In addition an asynchronous CLR pin will set all DAC register bits to zero causing the V<sub>OUT</sub> to become zero volts. This function is useful for power on reset or system failure recovery to a known state.

## D/A CONVERTER SECTION

The internal DAC is a 12-bit device with an output that swings from GND potential to 0.4 volt generated from the internal bandgap voltage, see Figure 20. It uses a laser-trimmed segmented R-2R ladder which is switched by N-channel MOSFETs. The output voltage of the DAC has a constant resistance independent of digital input code. The DAC output is internally connected to the rail-to-rail output op amp.

## AMPLIFIER SECTION

The internal DAC's output is buffered by a low power consumption precision amplifier. This low power amplifier contains a differential PNP pair input stage that provides low offset voltage and low noise, as well as the ability to amplify the zero-scale DAC output voltages. The rail-to-rail amplifier is configured with a gain of approximately five in order to set the 2.0475 volt full-scale output (0.5 mV/LSB). See Figure 20 for an equivalent circuit schematic of the analog section.




Figure 20. Equivalent AD8300 Schematic of Analog Portion

The op amp has a 2 μs typical settling time to 0.4% of full scale. There are slight differences in settling time for negative slewing signals versus positive. Also negative transition settling time to within the last 6 LSB of zero volts has an extended settling time. See the oscilloscope photos in the typical performances section of this data sheet.

## OUTPUT SECTION

The rail-to-rail output stage of this amplifier has been designed to provide precision performance while operating near either power supply. Figure 21 shows an equivalent output schematic of the rail-to-rail amplifier with its N-channel pull-down FETs that will pull an output load directly to GND. The output sourcing current is provided by a P-channel pull-up device that can source current to GND terminated loads.




Figure 21. Equivalent Analog Output Circuit

The rail-to-rail output stage achieves the minimum operating supply voltage capability shown in Figure 2. The N-channel output pull-down MOSFET shown in Figure 21 has a 35 Ω on resistance which sets the sink current capability near ground. In addition to resistive load driving capability, the amplifier has also been carefully designed and characterized for up to 500 pF capacitive load driving capability.

## REFERENCE SECTION

The internal curvature-corrected bandgap voltage reference is laser trimmed for both initial accuracy and low temperature coefficient. Figure 19 provides a histogram of total output performance of full-scale vs. temperature which is dominated by the reference performance.

## POWER SUPPLY

The very low power consumption of the AD8300 is a direct result of a circuit design optimizing use of a CBCMOS process. By using the low power characteristics of the CMOS for the logic, and the low noise, tight matching of the complementary bipolar transistors, good analog accuracy is achieved.

For power-consumption sensitive applications it is important to note that the internal power consumption of the AD8300 is strongly dependent on the actual logic input voltage levels present on the SDI, CLK, CS, LD, and CLR pins. Since these inputs are standard CMOS logic structures, they contribute static power dissipation dependent on the actual driving logic



# AD8300

$V_{OH}$  and  $V_{OL}$  voltage levels. Consequently, for optimum dissipation use of CMOS logic versus TTL provides minimal dissipation in the static state. A  $V_{INL} = 0$  V on the logic input pins provides the lowest standby dissipation of 1.2 mA with a +3.3 V power supply.

As with any analog system, it is recommended that the AD8300 power supply be bypassed on the same PC card that contains the chip. Figure 12 shows the power supply rejection versus frequency performance. This should be taken into account when using higher frequency switched-mode power supplies with ripple frequencies of 100 kHz and higher.

One advantage of the rail-to-rail output amplifiers used in the AD8300 is the wide range of usable supply voltage. The part is fully specified and tested over temperature for operation from +2.7 V to +5.5 V. If reduced linearity and source current capability near full scale can be tolerated, operation of the AD8300 is possible down to +2.1 volts. The minimum operating supply voltage versus load current plot in Figure 2 provides information for operation below  $V_{DD} = +2.7$  V.

## TIMING AND CONTROL

The AD8300 has a separate serial-input register from the 12-bit DAC register that allows preloading of a new data value into the serial register without disturbing the present DAC output voltage value. Data can only be loaded when the CS pin is active low. After the new value is fully loaded in the serial-input register, it can be asynchronously transferred to the DAC register by strobing the LD pin. The DAC register uses a level sensitive LD strobe that should be returned high before any new data is loaded into the serial-input register. At any time the contents of the DAC register can be reset to zero by strobing the CLR pin which causes the DAC output voltage to go to zero volts. All of the timing requirements are detailed in Figure 3 along with Table I, Control Logic Truth Table.

All digital inputs are protected with a Zener type ESD protection structure (Figure 22) that allows logic input voltages to exceed the  $V_{DD}$  supply voltage. This feature can be useful if the user is loading one or more of the digital inputs with a 5 V CMOS logic input voltage level while operating the AD8300 on a +3.3 V power supply. If this mode of interface is used, make sure that the  $V_{OL}$  of the +5 V CMOS meets the  $V_{IL}$  input requirement of the AD8300 operating at 3 V. See Figure 7 for the effect on digital logic input threshold versus operating  $V_{DD}$  supply voltage.




Figure 22. Equivalent Digital Input ESD Protection

### Unipolar Output Operation

This is the basic mode of operation for the AD8300. The AD8300 has been designed to drive loads as low as 400  $\Omega$  in parallel with 500 pF. The code table for this operation is shown in Table II.

## APPLICATIONS INFORMATION

See DAC8512 data sheet for additional application circuit ideas.


### Table II. Unipolar Code Table

| Hexadecimal Number in DAC Register | Decimal Number in DAC Register | Analog Output Voltage (V) |
|------------------------------------|--------------------------------|---------------------------|
| FFF                                | 4095                           | +2.0475                   |
| 801                                | 2049                           | +1.0245                   |
| 800                                | 2048                           | +1.0240                   |
| 7FF                                | 2047                           | +1.0235                   |
| 000                                | 0                              | +0.0000                   |

## OUTLINE DIMENSIONS

Dimensions shown in inches and (mm).

### 8-Lead SOIC (SO-8)



### 8-Pin Plastic DIP (N-8)

