




ORDERING INFORMATION

SERIES	D B V 25 P 3 64 G T X XXX LF	LEAD FREE
SHELL SIZE	E, A, B, C, D	SPECIAL CODES
PANEL MOUNTING OPTIONS	BLANK-STANDARD V-FEM. SCREW LOCK (UNC) N-FEM. SCREW LOCK M3 S-SPACER RIVETTED TO SHELL L-CLINCH NUT (M3) O-CLINCH NUT (UNC)	DIMPLES X-ON MALE CONNECTORS ONLY
NO. OF CONTACTS	09, 15, 25, 37, 50	SHELL PLATING BLANK-ZINC (Cr+3) T-STD. TIN Over Cu
CONTACTS	P - PIN S - SOCKET	PCB MOUNTING OPTIONS BLANK-STANDARD G-HARPOON
TERMINATION TYPE	3-STRAIGHT SPILL 4-WIRE WRAP	CONTACT PLATING 64 - 200 MATING CYCLES 65 - 500 MATING CYCLES



"This LF product meets European Union Directives and other country regulations as described in GS-22-008"

The housing will withstand exposure to 260°C peak temperature for 3.5 seconds in a wave solder application with a 1.6mm minimum thick circuit board.

Packaging as per GS-14-920




LAY OUT OF 50P CONNECTOR




WIRE WRAP CODE 4

EXTENDED FEMALE SCREW LOCK WITH SPACER




ORD CODE -8630-01-062

SPACERS RIVETTED TO SHELL



PREFIX:- S

MALE SCREW LOCK




ORD CODE:-

8630-05(E.A.B.C.)
8630-03 D SHELL FEMALE
8630-15 D SHELL MALE
8630-04 E,A,B,C SHELL
WITH METAL HOOD

FOR 440 UNC 2A THREADED ADD UNC
TO THE CORRESPONDING ORD. CODE.

HARPOON PRESS FITTED TO SHELL



mat'l. code

SEE NOTE 4

ltr	ecn no	dr	date	surface	tolerance	projection
D	106-0074	GVJ	2006/06/08	ISO 1302	ISO 406 ISO 1101	MM
E	109-0179	AMR	2009/09/04	angles	linear	scale -
F	109-0195	AMR	2009/09/04			
G	111-0003	AMR	2011/01/06	dr	Mini K Vandanath	1999/03/20
H	111-0047	AMR	2011/03/05	enr	George V Joseph	1999/03/20
				chr	Abhilash M R	2009/09/04
				appd	Sudhir Varma	2009/09/04
sheet	revision	H				
index	sheet	1				

50	P	66.65	52.68	61.11	11.08	14.99	11.09	5.85	55.07	13.31	1.50	1.0
	S	66.65	52.30	61.11	10.62	14.99	11.21	6.05	55.07	13.31	1.10	0.8
37	P	68.94	55.30	63.50	8.23	12.17	11.09	5.85	57.45	10.46	1.50	1.0
	S	68.94	54.71	63.50	7.77	12.17	11.21	6.05	57.45	10.46	1.10	0.8
25	P	52.65	38.84	47.04	8.23	12.17	11.07	5.85	41.02	10.46	1.10	0.8
	S	52.65	38.25	47.04	7.77	12.17	11.21	6.05	41.02	10.46	1.10	0.8
15	P	38.76	25.12	33.32	8.23	12.17	10.99	5.85	27.25	10.46	1.10	0.8
	S	38.76	24.54	33.32	7.77	12.17	11.21	6.05	27.25	10.46	1.10	0.8
09	P	30.43	16.79	24.99	8.23	12.17	10.99	5.85	19.02	10.46	1.10	0.8
	S	30.43	16.21	24.99	7.77	12.17	11.21	6.05	19.02	10.46	1.10	0.8
SHELL SIZE		A ^{+0.76}	B ^{+0.25}	C ^{+0.12}	D ^{+0.25}	E ^{+0.76}	F ^{MAX}	G ^{+0.15}	H ^{+0.51}	J ^{+0.51}	K ^{±0.2}	L ^{+0.22}


DIMENSIONS

NOTE: INSIDE DIMENSION OF MALE AND OUTSIDE DIMENSION OF THE FEMALE CONNETOR


TECHNICAL SPECIFICATIONS

SHELLS	: TIN/ZINC PLATED STEEL
CONTACTS DIA ON ACTIVE AREA	: Ø1 MM.
CONTACTS MATERIAL	: COPPER ALLOY
CONTACT PLATING	: GXT / GOLD OVER NICKEL (ACTIVE ZONE) TIN OVER NICKEL (TERMINATION ZONE)
FOR LEAD FREE PLATING	: 2µ MIN. TIN TOP OVER 1.27µ MIN. NICKEL UNDER PLATE (ON TERMINATION ZONE)
INSULATOR MATERIAL	: SELF EXTINGUISHING THERMOPLASTIC- TO UL CLASS 94 V0 THE HOUSING WILL WITHSTAND EXPOSURE TO 260-265°C IF WE USE PROTECTIVE ADHESIVE (type Kapton or Teflon) OR PROTECTIVE METALLIC DEVICE
OPERATING TEMPERATURE	: -55°C +125°C
OPERATING CURRENT	: 5 A PER CONTACT
CONTACT RESISTANCE	: ≤10m Ω
INSULATION RESISTANCE	: ≥5000 M Ω
MAXIMUM VOLTAGE	: 1000 V.r.m.s
MECHANICAL ENDURANCE	: 500 MATINGS FOR CODE 64 200 MATINGS FOR CODE 65
DAMP HEAT	: 56 DAYS FOR ≥0.75µ GOLD PLATING 21 DAYS FOR ≤0.40µ GOLD PLATING


CLINCH NUT



HEXAGONAL FEMALE SCREW



HARPOON RIVETTED TO SHELL



product family

title

D- SUB S/S W/W CONNECTOR
(WITH ASSEMBLY OPTIONS)

dwg no

sheet 1 of 1

size

C-DSUB-0065

A3

type

Product

Customer

Drawing