

REVISIONS			DOC. NO. SPC-F005 * Effective: 12/21/98 * DCP No: 680					
DCP #	REV	DESCRIPTION	DRAWN	DATE	CHECKD	DATE	APPRVD	DATE
796	A	RELEASED	HYO	10/9/01	JWM	3/27/02	DJC	3/27/02



Static dissipative dispensers come with a Purity pump that protects against cross contamination by keeping fluid from returning to dispenser. Features an average surface resistivity of $10^9 \sim 10^{10}$ ohm, and can dissipate a $\pm 5000V$ charge in less than 2 seconds at 40% relative humidity.

DISCLAIMER:
ALL STATEMENTS AND TECHNICAL INFORMATION CONTAINED HEREIN ARE BASED UPON INFORMATION AND/OR TESTS WE BELIEVE TO BE ACCURATE AND RELIABLE. SINCE CONDITIONS OF USE ARE UNPREDICTABLE, OUR COMPANY DOES NOT WARRANT THE QUALITY OF THE PRODUCT OR THE RESULTS OF THE INTENDED USE AND ASSUME ALL RISK AND LIABILITY WHATSOEVER IN CONNECTION THEREWITH.



SPC TECHNOLOGY

UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE FOR REFERENCE PURPOSES ONLY.				DRAWING TITLE: 6 OUNCE ESD SOLVENT DISPENSER, PURITY PUMP			
DRAWN BY:	DATE:	HISHAM ODISH	10/9/01	SIZE	DWG. NO.	ELECTRONIC FILE	REV
CHECKED BY:	DATE:	JEFF MCVICKER	3/27/02	A	1466	10N689.DWG	A
APPROVED BY:	DATE:	DANIEL CAREY	3/27/02	SCALE:	NTS	U.O.M.: INCHES [mm]	SHEET: 1 OF 1