

# Low-Frequency, Spread-Spectrum EconOscillator


## General Description

The DS1090 is a low-cost, dithered oscillator intended to be used as an external clock for switched-mode power supplies and other low-frequency applications. The dithering or sweeping function reduces peak-radiated emissions from the power supply at its fundamental frequency, as well as harmonic frequencies. The device consists of a resistor-programmed master oscillator, factory-programmed clock prescaler, and a pin-programmed dither circuit. These features allow the DS1090 to be used in applications where a spread-spectrum clock is desired to reduce radiated emissions. A combination of factory-set prescalers and external resistor allows for output frequencies ranging from 125kHz to 8MHz. Both dither frequency and dither percentage are set using control pins.

## Applications

Switched-Mode Power Supplies  
Servers  
Printers  
Embedded Microcontrollers  
Industrial Controls  
Automotive Applications

## Typical Operating Circuit



EconOscillator is a trademark of Dallas Semiconductor.

## Features


- ◆ Low-Cost, Spread-Spectrum EconOscillator™
- ◆ Simple User Programming
- ◆ Output Frequency Programmable from 125kHz to 8MHz
- ◆ Dither Percentage Programmable from 0% to 8%
- ◆ Dither Rate Programmable ( $f_{MOSC}$  / 512, 1024, 2048, or 4096)
- ◆ 3.0V to 5.5V Single-Supply Operation
- ◆ CMOS/TTL-Compatible Output
- ◆ Operating Temperature Range: -40°C to +85°C

## Ordering Information

| PART        | OUTPUT FREQUENCY RANGE | PRESCALER | PIN-PACKAGE |
|-------------|------------------------|-----------|-------------|
| DS1090U-1+  | 4MHz to 8MHz           | 1         | 8 $\mu$ SOP |
| DS1090U-2+  | 2MHz to 4MHz           | 2         | 8 $\mu$ SOP |
| DS1090U-4+  | 1MHz to 2MHz           | 4         | 8 $\mu$ SOP |
| DS1090U-8+  | 500kHz to 1MHz         | 8         | 8 $\mu$ SOP |
| DS1090U-16+ | 250kHz to 500kHz       | 16        | 8 $\mu$ SOP |
| DS1090U-32+ | 125kHz to 250kHz       | 32        | 8 $\mu$ SOP |

Add "T" for Tape & Reel orders.

## Pin Configuration



# Low-Frequency, Spread-Spectrum EconOscillator

## ABSOLUTE MAXIMUM RATINGS

Voltage Range on  $V_{CC}$  Relative to Ground .....-0.5V to +6.0V  
 Voltage Range on Input Pins  
 Relative to Ground.....-0.5V to ( $V_{CC} + 0.5V$ ),  
 not to exceed 6.0V

Operating Temperature Range .....-40°C to +85°C  
 Storage Temperature Range .....-55°C to +125°C  
 Soldering Temperature .....See IPC/JEDEC  
 J-STD-020A Specification

Stresses beyond those listed under "Absolute Maximum Ratings" may cause permanent damage to the device. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those indicated in the operational sections of the specifications is not implied. Exposure to absolute maximum rating conditions for extended periods may affect device reliability.

## RECOMMENDED DC OPERATING CONDITIONS

( $T_A = -40^{\circ}\text{C}$  to  $+85^{\circ}\text{C}$ )

| PARAMETER                        | SYMBOL   | CONDITIONS | MIN            | TYP | MAX             | UNITS |
|----------------------------------|----------|------------|----------------|-----|-----------------|-------|
| Supply Voltage                   | $V_{CC}$ | (Note 1)   | 3.0            |     | 5.5             | V     |
| Input Logic 1 (J0, J1, JC0, JC1) | $V_{IH}$ |            | 0.7 x $V_{CC}$ |     | $V_{CC} + 0.3$  | V     |
| Input Logic 0 (J0, J1, JC0, JC1) | $V_{IL}$ |            | -0.3           |     | +0.3 x $V_{CC}$ | V     |

## DC ELECTRICAL CHARACTERISTICS

( $V_{CC} = +3.0V$  to  $+5.5V$ ,  $T_A = -40^{\circ}\text{C}$  to  $+85^{\circ}\text{C}$ , unless otherwise noted.)

| PARAMETER                                   | SYMBOL    | CONDITIONS                                                    | MIN  | TYP | MAX  | UNITS         |
|---------------------------------------------|-----------|---------------------------------------------------------------|------|-----|------|---------------|
| Supply Current                              | $I_{CC}$  | $C_L = 15\text{pF}$ , $V_{CC} = 3.3V$ , $R_{SET} = 40k\Omega$ |      | 1.4 |      | mA            |
|                                             |           | $C_L = 15\text{pF}$ , $V_{CC} = 5.5V$ , $R_{SET} = 40k\Omega$ |      | 1.7 | 3    |               |
| High-Level Output Voltage (OUT)             | $V_{OH}$  | $I_{OH} = -4\text{mA}$<br>$V_{CC} = \text{min}$               | 2.4  |     |      | V             |
| Low-Level Output Voltage (OUT)              | $V_{OL}$  | $I_{OL} = 4\text{mA}$                                         |      |     | 0.4  | V             |
| High-Level Input Current (J0, J1, JC0, JC1) | $I_{IH}$  | $V_{IH} = V_{CC}$                                             |      |     | +1.0 | $\mu\text{A}$ |
| Low-Level Input Current (J0, J1, JC0, JC1)  | $I_{IL}$  | $V_{IL} = 0V$                                                 | -1.0 |     |      | $\mu\text{A}$ |
| Resistor Current                            | $I_{RES}$ | $V_{CC} = \text{max}$                                         |      |     | 150  | $\mu\text{A}$ |

# Low-Frequency, Spread-Spectrum EconOscillator

DS1090

## AC ELECTRICAL CHARACTERISTICS

( $V_{CC}$  = +3.0V to +5.5V,  $T_A$  = -40°C to +85°C, unless otherwise noted.)

| PARAMETER                                     | SYMBOL               | CONDITIONS                                                                              | MIN   | TYP | MAX   | UNITS |
|-----------------------------------------------|----------------------|-----------------------------------------------------------------------------------------|-------|-----|-------|-------|
| Internal Master Oscillator Frequency          | $f_{MOSC}$           |                                                                                         | 4.0   |     | 8.0   | MHz   |
| Output Frequency Tolerance                    | $\Delta f_{OUT}$     | $V_{CC} = 3.3V$ ,<br>$T_A = +25^\circ C$                                                | -3.0  |     | +3.0  | %     |
| Voltage Frequency Variation                   | $\Delta f_{OUT}$     | $T_A = +25^\circ C$ , $R_{SET} = 60k\Omega$ ,<br>$V_{CC} = 3.0V$ to $3.6V$ (Notes 2, 3) | -0.5  |     | +0.5  | %     |
|                                               |                      | $T_A = +25^\circ C$ , $R_{SET} = 60k\Omega$ ,<br>$V_{CC} = 4.5V$ to $5.5V$ (Notes 2, 3) | -1.25 |     | +1.25 |       |
| Temperature Frequency Variation               | $\Delta f_{OUT}$     | $V_{CC} = 3.3V$<br>(Notes 2, 3, 4)                                                      | -2.0  |     | +2.0  | %     |
| Peak-to-Peak Dither ( $3\sigma$ )<br>(Note 5) |                      | $J0 = GND$ , $J1 = GND$                                                                 |       | 0   |       | %     |
|                                               |                      | $J0 = V_{CC}$ , $J1 = GND$                                                              |       | 2   |       |       |
|                                               |                      | $J0 = GND$ , $J1 = V_{CC}$                                                              |       | 4   |       |       |
|                                               |                      | $J0 = V_{CC}$ , $J1 = V_{CC}$                                                           |       | 8   |       |       |
| Power-Up Time                                 | $t_{POR} + t_{STAB}$ | (Note 6)                                                                                |       | 0.1 | 0.5   | ms    |
| Load Capacitance                              | $C_L$                | (Note 7)                                                                                |       |     | 30    | pF    |
| Output Duty Cycle                             |                      | 4MHz to 8MHz, $T_A = +25^\circ C$ (Note 3)                                              | 45    |     | 55    | %     |
|                                               |                      | <4MHz (Note 4)                                                                          |       | 50  |       |       |
| Output Rise/Fall Time                         | $t_R, t_F$           | $C_L = 15pF$                                                                            |       |     | 20    | ns    |

**Note 1:** All voltages referenced to ground.

**Note 2:** This is the change observed in output frequency due to changes in temperature or voltage.

**Note 3:** See the Typical Operating Characteristics section.

**Note 4:** Parameter is guaranteed by design and is not production tested.

**Note 5:** This is a percentage of the output period. Parameter is characterized but not production tested. This can be varied from 0% to 8%.







**Note 6:** This indicates the time between power-up and the outputs becoming active. An on-chip delay is intentionally introduced to allow the oscillator to stabilize.  $t_{STAB}$  is equivalent to ~500 clock cycles and is dependent upon the programmed output frequency.

**Note 7:** Output voltage swings can be impaired at high frequencies combined with high output loading.

# Low-Frequency, Spread-Spectrum EconOscillator

## Typical Operating Characteristics

( $V_{CC} = +3.3V$ ,  $T_A = +25^\circ C$ , unless otherwise noted.)









# Low-Frequency, Spread-Spectrum EconOscillator

DS1090

## Typical Operating Characteristics (continued)

( $V_{CC} = +3.3V$ ,  $T_A = +25^\circ C$ , unless otherwise noted.)




# Low-Frequency, Spread-Spectrum EconOscillator

## Pin Description

| PIN | NAME | FUNCTION                                              |
|-----|------|-------------------------------------------------------|
| 1   | OUT  | Oscillator Output                                     |
| 2   | RSET | Frequency Control Resistor Input                      |
| 3   | VCC  | Positive-Supply Terminal                              |
| 4   | GND  | Ground                                                |
| 5   | J0   | Dither Amplitude (Percentage) Inputs<br>(see Table 2) |
| 6   | J1   |                                                       |
| 7   | JC0  | Dither Rate Divisor Inputs (see Table 1)              |
| 8   | JC1  |                                                       |

## Block Diagram



# Low-Frequency, Spread-Spectrum EconOscillator




Figure 1. Master Oscillator Frequency

## Detailed Description

The DS1090 is a center-dithered, spread-spectrum silicon oscillator for use as an external clock in reduced-EMI applications. With a combination of factory-programmed prescalers and a user-selected external resistor, output frequencies from 125kHz to 8MHz can be achieved. The output center frequency can be dithered by selecting the desired dither rate and amplitude with discrete inputs J0, J1, JC0, and JC1.

The DS1090 contains four basic circuit blocks: master oscillator, factory-programmed prescaler, dither generator, and the voltage-bias circuit that provides the feedback path to the master oscillator for frequency control and dithering functions.

### Master Oscillator

The master oscillator is programmable in the application by the use of an external resistor (R<sub>SET</sub>) tied to ground (GND). Resistor values of 45kΩ to 91kΩ vary the square-wave output frequency of the voltage-controlled master oscillator (f<sub>MOSC</sub>) from 8MHz down to 4MHz (see Figure 1).

The master oscillator (Hz) frequency can be stated as

$$f_{MOSC} \cong \frac{3.6461E+11}{\text{Resistor}}$$




Figure 2. Center Frequency Dither Diagram

### Factory-Programmed Prescaler

The prescaler divides the frequency of the master oscillator by 1, 2, 4, 8, 16, or 32 to generate the square-wave output clock (f<sub>OSC</sub>). This divisor is factory-set and is an ordering option.

### Dither Generator

Spread-spectrum functionality is achieved by a user-configurable divider (determines dither rate), a triangle generator, and a user-configurable dither amplitude circuit (see *Block Diagram*).

The input to the triangle-wave generator is derived from the internal master oscillator and is fed through a user-configurable divider. The settings of control pins JC0 and JC1 determine this dither rate divisor setting (see Table 1), dividing the master clock by 4, 8, 16, or 32. The clock signal is further divided by 128 in the triangle-wave generator, which results in a triangle-wave signal of either 1/512th, 1/1024th, 1/2048th, or 1/4096th of the master oscillator (f<sub>MOD</sub>), depending upon the user's divisor setting.

The dithering frequency can be also expressed as the result of

$$f_{MOD} = \frac{f_{MOSC}}{\text{Divisor} \times 128}$$

where Divisor is 4, 8, 16, or 32.

Table 1. Dither Rate Divisor Settings

| JC1 | JC0 | DITHERING PERCENTAGE (f <sub>MOSC</sub> /n) | DIVISOR SETTING |
|-----|-----|---------------------------------------------|-----------------|
| 0   | 0   | f <sub>MOSC</sub> / 512                     | 4               |
| 0   | 1   | f <sub>MOSC</sub> / 1024                    | 8               |
| 1   | 0   | f <sub>MOSC</sub> / 2048                    | 16              |
| 1   | 1   | f <sub>MOSC</sub> / 4096                    | 32              |

# Low-Frequency, Spread-Spectrum EconOscillator

**Table 2. Dither Percentage Setting**

| J1 | J0 | DITHER PERCENT (%) |
|----|----|--------------------|
| 0  | 0  | 0                  |
| 0  | 1  | 2                  |
| 1  | 0  | 4                  |
| 1  | 1  | 8                  |

## Dither Percentage Settings

Dither amplitude (measured in percent  $\pm$  from the master oscillator center frequency) is set using input pins J0 and J1. This circuit uses a sense current from the master oscillator bias circuit to adjust the amplitude of the triangle-wave signal to a voltage level that modulates the master oscillator to a percentage of its resistor-set center frequency. This percentage is set in the end application to be 0%, 2%, 4%, or 8% (see Table 2).

## Application Information

### Pin Connection

The DS1090 is intended to provide a fixed-frequency, dithered clock to be used as a clock driver for DC-DC converters and other applications requiring a low-frequency EMI-reduced clock oscillator. All control pins must be biased per Tables 1 and 2 for proper operation for the individual application's requirements. RSET must be tied to ground (GND) by a customer-supplied resistor.

### RSET Resistor Selection

The value of the resistor used to select the desired frequency is calculated using the formula in the *Master Oscillator* section (see also Figure 1). It is recommended to use, at minimum, a 1%-tolerance, 1/16th-watt component with a temperature coefficient that satisfies the overall stability requirements desired of the end-equipment. Place the external RSET resistor as close as possible to minimize lead inductance.

### Power-Supply Decoupling

To achieve best results, it is highly recommended that a decoupling capacitor is used on the IC power-supply pins. Typical values of decoupling capacitors are 0.01 $\mu$ F and 0.1 $\mu$ F. Use a high-quality, ceramic, surface-mount capacitor, and mount it as close as possible to the VCC and GND pins of the IC to minimize lead inductance.

## Chip Information

TRANSISTOR COUNT: 1883

SUBSTRATE CONNECTED TO GROUND

## Package Information

For the latest package outline information, go to [www.maxim-ic.com/DallasPackInfo](http://www.maxim-ic.com/DallasPackInfo).

Maxim cannot assume responsibility for use of any circuitry other than circuitry entirely embodied in a Maxim product. No circuit patent licenses are implied. Maxim reserves the right to change the circuitry and specifications without notice at any time.

8 **Maxim Integrated Products, 120 San Gabriel Drive, Sunnyvale, CA 94086 408-737-7600**

© 2007 Maxim Integrated Products

**MAXIM** is a registered trademark of Maxim Integrated Products.



**DALLAS** is a registered trademark of Dallas Semiconductor Corporation.