

Dissipative Two layer Rubber



RoHS
Compliant



Description

Matting materials have a tendency to shrink slightly when first unrolled. In applications where length is critical, allow the material to relax for at least 4 hours before cutting to size. Always trim with a sharp knife or razor blade.

Specifications:

Resistance Top to Top (RTT)	: 10E7 - 10E8Ω, per S20.20 STM S4.1
Resistance Top to Ground Point (RTG)	: 10E6 - 10E8 ohms, per S20.20 STM S4.1
Static Decay	: 5kV to (50volts) >2 seconds In accordance with FTMS 101C Method 4046
Thickness	: 0.078" ±0.01"
Colour	: Light Grey

Part Number Table

Description	Part Number
Light Grey Rubber, 24" × 50'	MC23790

Important Notice : This data sheet and its contents (the "Information") belong to the members of the Premier Farnell group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. DURATOOL is the registered trademark of the Group. © Premier Farnell plc 2012.

