



# LP3985 Micropower, 150-mA Low-Noise Ultra-Low-Dropout CMOS Voltage Regulator

## 1 Features

- Input Voltage: 2.5 V to 6 V
- 100-mV Maximum Dropout with 150-mA Load
- 150-mA Verified Output
- 50-dB PSRR at 1 kHz at  $V_{IN} = V_{OUT} + 0.2$  V
- $\leq 1.5$ - $\mu$ A Quiescent Current when Shut Down
- Fast Turn-On time: 200  $\mu$ s (typ.)
- 30- $\mu$ V<sub>RMS</sub> Output Noise (typical) over 10 Hz to 100 kHz
- $-40^{\circ}\text{C}$  to  $125^{\circ}\text{C}$  Junction Temperature Range for Operation
- 2.5-V, 2.6-V, 2.7-V, 2.8-V, 2.85-V, 2.9-V, 3-V, 3.1-V, 3.2-V, 3.3-V, 4.7-V, 4.75-V, 4.8-V and 5-V Outputs Standard
- Logic Controlled Enable
- Stable with Ceramic and High-Quality Tantalum Capacitors
- Fast Turnon
- Thermal Shutdown and Short-Circuit Current Limit

## 2 Applications

- CDMA Cellular Handsets
- Wideband CDMA Cellular Handsets
- GSM Cellular Handsets
- Portable Information Appliances

## 3 Description

The LP3985 is designed for portable and wireless applications with demanding performance and space requirements. LP3985 performance is optimized for battery-powered systems to deliver ultra low noise, extremely low dropout voltage, and low quiescent current. Regulator ground current increases only slightly in dropout, further prolonging the battery life.

The LP3985 is stable with a small 1- $\mu$ F  $\pm 30\%$  ceramic or high-quality tantalum output capacitor. The DSBGA requires the smallest possible PC board area - the total application circuit area can be less than 2 mm x 2.5 mm, a fraction of a 1206 case size.


An optional external bypass capacitor reduces the output noise without slowing down the load transient response. Fast startup time is achieved by utilizing an internal power-on circuit that actively pre-charges the bypass capacitor.

Power supply rejection is better than 50 dB at low frequencies and starts to roll off at 1 kHz. High power supply rejection is maintained down to low input voltage levels common to battery operated circuits.

The device is ideal for mobile phone and similar battery-powered wireless applications. It provides up to 150 mA, from a 2.5-V to 6-V input. The LP3985 consumes less than 1.5  $\mu$ A in disable mode and has fast turn-on time less than 200  $\mu$ s.

The LP3985 is available with fixed output voltages from 2.5 V to 5 V. Contact Texas Instruments Sales for specific voltage option needs.

**Simplified Schematic**



Pin Numbers in parenthesis indicate DSBGA package.

\* Optional Noise Reduction Capacitor.

**Device Information<sup>(1)</sup>**

| PART NUMBER | PACKAGE    | BODY SIZE                 |
|-------------|------------|---------------------------|
| LP3985      | DSBGA (5)  | 1.502 mm x 1.045 mm (MAX) |
|             | SOT-23 (5) | 2.90 mm x 1.60 mm (NOM)   |

(1) For all available packages, see the Package Option Addendum at the end of the datasheet.



## Table of Contents

|                                                |           |                                                                  |           |
|------------------------------------------------|-----------|------------------------------------------------------------------|-----------|
| <b>1 Features</b> .....                        | <b>1</b>  | 7.4 Device Functional Modes.....                                 | <b>14</b> |
| <b>2 Applications</b> .....                    | <b>1</b>  | <b>8 Application and Implementation</b> .....                    | <b>15</b> |
| <b>3 Description</b> .....                     | <b>1</b>  | 8.1 Application Information.....                                 | <b>15</b> |
| <b>4 Revision History</b> .....                | <b>2</b>  | 8.2 Typical Application .....                                    | <b>15</b> |
| <b>5 Pin Configuration and Functions</b> ..... | <b>3</b>  | <b>9 Power Supply Recommendations</b> .....                      | <b>18</b> |
| <b>6 Specifications</b> .....                  | <b>4</b>  | <b>10 Layout</b> .....                                           | <b>19</b> |
| 6.1 Absolute Maximum Ratings .....             | 4         | 10.1 Layout Guidelines .....                                     | 19        |
| 6.2 ESD Ratings.....                           | 4         | 10.2 Layout Examples.....                                        | 19        |
| 6.3 Recommended Operating Conditions.....      | 4         | 10.3 DSBGA Mounting.....                                         | 19        |
| 6.4 Thermal Information .....                  | 4         | 10.4 DSBGA Light Sensitivity .....                               | 19        |
| 6.5 Electrical Characteristics.....            | 5         | <b>11 Device and Documentation Support</b> .....                 | <b>21</b> |
| 6.6 Typical Performance Characteristics .....  | 7         | 11.1 Documentation Support .....                                 | 21        |
| <b>7 Detailed Description</b> .....            | <b>13</b> | 11.2 Trademarks .....                                            | 21        |
| 7.1 Overview .....                             | 13        | 11.3 Electrostatic Discharge Caution.....                        | 21        |
| 7.2 Functional Block Diagram .....             | 13        | 11.4 Glossary .....                                              | 21        |
| 7.3 Feature Description.....                   | 13        | <b>12 Mechanical, Packaging, and Orderable Information</b> ..... | <b>21</b> |

## 4 Revision History

NOTE: Page numbers for previous revisions may differ from page numbers in the current version.


| Changes from Revision AD (October 2014) to Revision AE                                                       | Page      |
|--------------------------------------------------------------------------------------------------------------|-----------|
| • Changed update pin names to TI nomenclature; replace <i>Handling Ratings</i> with <i>ESD Ratings</i> ..... | <b>1</b>  |
| • Deleted <i>Voltage Options</i> table - information in POA .....                                            | <b>1</b>  |
| • Added GND as type for ground pins .....                                                                    | <b>3</b>  |
| • Added <i>Thermal Considerations</i> sub-section .....                                                      | <b>17</b> |

| Changes from Revision AC (May 2013) to Revision AD                                                                                                                                                                                                                                                                                                                                                                                                | Page     |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------|
| • Added <i>Device Information</i> and <i>Handling Rating</i> tables, <i>Feature Description</i> , <i>Device Functional Modes</i> , <i>Application and Implementation</i> , <i>Power Supply Recommendations</i> , <i>Layout</i> , <i>Device and Documentation Support</i> , and <i>Mechanical, Packaging, and Orderable Information</i> sections; moved some curves to <i>Application Curves</i> section; add new <i>Thermal Information</i> ..... | <b>1</b> |


| Changes from Revision AB (May 2013) to Revision AC         | Page      |
|------------------------------------------------------------|-----------|
| • Changed layout of National Data Sheet to TI format ..... | <b>20</b> |

## 5 Pin Configuration and Functions

**DBV Package  
5 Pin SOT-23  
Top View**



**YZR Package  
5 Pin DSBGA  
Top View**



### Pin Functions

| PIN    |                             |               | TYPE | DESCRIPTION                                   |
|--------|-----------------------------|---------------|------|-----------------------------------------------|
| NAME   | DSBGA NUMBER <sup>(1)</sup> | SOT-23 NUMBER |      |                                               |
| BYPASS | A3                          | 4             | I/O  | Optional bypass capacitor for noise reduction |
| EN     | A1                          | 3             | I    | Enable input logic, enable high               |
| GND    | B2                          | 2             | GND  | Common ground                                 |
| IN     | C3                          | 1             | I    | Input voltage of the LDO                      |
| OUT    | C1                          | 5             | O    | Output voltage of the LDO                     |

- (1) The pin numbering scheme for the DSBGA package was revised in April 2002 to conform to JEDEC standard. Only the pin numbers were revised. No changes to the physical location of the inputs/outputs were made. For reference purposes, the obsolete numbering scheme had VEN as pin 1, GND as pin 2, VOUT as pin 3, VIN as pin 4, and BYPASS as pin 5.

## 6 Specifications

### 6.1 Absolute Maximum Ratings

 over operating free-air temperature range (unless otherwise noted) <sup>(1)(2)(3)</sup>

|                                       |                       | MIN  | MAX                    | UNIT |
|---------------------------------------|-----------------------|------|------------------------|------|
| IN, EN                                |                       | −0.3 | 6.5                    | V    |
| OUT                                   |                       | −0.3 | $(V_{IN} + 0.3) < 6.5$ |      |
| Junction temperature                  |                       |      | 150                    | °C   |
| Lead temperature                      |                       |      | 235                    |      |
| Pad temperature <sup>(4)</sup>        |                       |      | 235                    |      |
| Maximum power dissipation             | SOT-23 <sup>(5)</sup> |      | 364                    | mW   |
|                                       | DSBGA <sup>(5)</sup>  |      | 314                    |      |
| Storage temperature, T <sub>stg</sub> |                       | −65  | 150                    | °C   |

- Stresses beyond those listed under *Absolute Maximum Ratings* may cause permanent damage to the device. These are stress ratings only, which do not imply functional operation of the device at these or any other conditions beyond those indicated under *Recommended Operating Conditions*. Exposure to absolute-maximum-rated conditions for extended periods may affect device reliability.
- All voltages are with respect to potential at the GND pin.
- If Military/Aerospace specified devices are required, please contact the Texas Instruments Sales Office/ Distributors for availability and specifications.
- Additional information on lead temperature and pad temperature can be found in Texas Instruments Application Note AN-1187 *Leadless Leadframe Package (LLP)* ([SNOA401](#)).
- The Absolute Maximum power dissipation depends on the ambient temperature and can be calculated using the formula:  $P_D = (T_J - T_A)/R_{\theta JA}$ , where  $T_J$  is the junction temperature,  $T_A$  is the ambient temperature, and  $R_{\theta JA}$  is the junction-to-ambient thermal resistance. The 364-mW rating for SOT23-5 appearing under *Absolute Maximum Ratings* results from substituting the Absolute Maximum junction temperature, 150°C for  $T_J$ , 70°C for  $T_A$ , and 220°C/W for  $R_{\theta JA}$ . More power can be dissipated safely at ambient temperatures below 70°C. Less power can be dissipated safely at ambient temperatures above 70°C. The Absolute Maximum power dissipation can be increased by 4.5 mW for each degree below 70°C, and it must be derated by 4.5 mW for each degree above 70°C.

### 6.2 ESD Ratings

|                    |                         |                                                                   | VALUE | UNIT |
|--------------------|-------------------------|-------------------------------------------------------------------|-------|------|
| V <sub>(ESD)</sub> | Electrostatic discharge | Human-body model (HBM), per ANSI/ESDA/JEDEC JS-001 <sup>(1)</sup> | ±2000 | V    |

- JEDEC document JEP155 states that 500-V HBM allows safe manufacturing with a standard ESD control process.

### 6.3 Recommended Operating Conditions

over operating free-air temperature range (unless otherwise noted)

|                  |                                | MIN                | MAX             | UNIT |
|------------------|--------------------------------|--------------------|-----------------|------|
| V <sub>IN</sub>  | Supply input voltage           | 2.5 <sup>(1)</sup> | 6               | V    |
| V <sub>EN</sub>  | ON/OFF input voltage           | 0                  | V <sub>IN</sub> | V    |
| I <sub>OUT</sub> | Output current                 |                    | 150             | mA   |
| T <sub>J</sub>   | Operating junction temperature | −40                | 125             | °C   |

- Recommended minimum V<sub>IN</sub> is the greater of 2.5-V or V<sub>OUT(MAX)</sub> + rated dropout voltage (max) for operating load current.

### 6.4 Thermal Information

| THERMAL METRIC <sup>(1)</sup> |                                              | LP3985       |             | UNIT |
|-------------------------------|----------------------------------------------|--------------|-------------|------|
|                               |                                              | SOT-23 (DBV) | DSBGA (YZR) |      |
|                               |                                              | 5 PINS       |             |      |
| R <sub>θJA</sub>              | Junction-to-ambient thermal resistance       | 220          | 255         | °C/W |
| R <sub>θJC(top)</sub>         | Junction-to-case (top) thermal resistance    | 79.8         | 0.8         |      |
| R <sub>θJB</sub>              | Junction-to-board thermal resistance         | 31.6         | 107.9       |      |
| ψ <sub>JT</sub>               | Junction-to-top characterization parameter   | 3.1          | 0.5         |      |
| ψ <sub>JB</sub>               | Junction-to-board characterization parameter | 31.1         | 107.9       |      |
| R <sub>θJC(bot)</sub>         | Junction-to-case (bottom) thermal resistance | N/A          | N/A         |      |

- For more information about traditional and new thermal metrics, see the *IC Package Thermal Metrics* application report, [SPRA953](#).

## 6.5 Electrical Characteristics

Unless otherwise specified:  $V_{IN} = V_{OUT(nom)} + 0.5\text{ V}$ ,  $C_{IN} = 1\text{ }\mu\text{F}$ ,  $I_{OUT} = 1\text{ mA}$ ,  $C_{OUT} = 1\text{ }\mu\text{F}$ ,  $C_{BYPASS} = 0.01\text{ }\mu\text{F}$ . Minimum (MIN) and Maximum (MAX) values apply over  $-40^{\circ}\text{C} \leq T_J \leq 125^{\circ}\text{C}$  and typical values are  $T_A = 25^{\circ}\text{C}$ , unless otherwise indicated.

(1)(2)

| PARAMETER                      |                                        | TEST CONDITIONS                                                                                                | MIN                     | TYP        | MAX                   | UNIT                       |
|--------------------------------|----------------------------------------|----------------------------------------------------------------------------------------------------------------|-------------------------|------------|-----------------------|----------------------------|
| ΔV <sub>OUT</sub>              | Output voltage tolerance               | I <sub>OUT</sub> = 1 mA                                                                                        | −2 <sup>(3)</sup><br>−3 |            | 2 <sup>(3)</sup><br>3 | % of V <sub>OUT(nom)</sub> |
|                                | Line regulation error                  | V <sub>IN</sub> = (V <sub>OUT(nom)</sub> + 0.5 V) to 6 V,<br>For 4.7-V to 5-V options<br>For all other options | −0.19<br>−0.1           |            | 0.19<br>0.1           | %/V                        |
|                                | Load regulation error <sup>(4)</sup>   | I <sub>OUT</sub> = 1 mA to 150 mA<br>LP3985IM5 (SOT23-5)                                                       |                         | 0.0025     | 0.005                 | %/mA                       |
|                                |                                        | LP3985 (DSBGA)                                                                                                 |                         | 0.0004     | 0.002                 | %/mA                       |
| Output AC line regulation      |                                        | V <sub>IN</sub> = V <sub>OUT(nom)</sub> + 1 V,<br>I <sub>OUT</sub> = 150 mA (Figure 1)                         |                         | 1.5        |                       | mV <sub>P-P</sub>          |
| PSRR                           | Power supply rejection ratio           | V <sub>IN</sub> = V <sub>OUT(nom)</sub> + 0.2 V,<br>f = 1 kHz,<br>I <sub>OUT</sub> = 50 mA (Figure 2)          |                         | 50         |                       | dB                         |
|                                |                                        | V <sub>IN</sub> = V <sub>OUT(nom)</sub> + 0.2 V,<br>f = 10 kHz,<br>I <sub>OUT</sub> = 50 mA (Figure 2)         |                         | 40         |                       | dB                         |
| I <sub>Q</sub>                 | Quiescent current                      | V <sub>EN</sub> = 1.4 V, I <sub>OUT</sub> = 0 mA<br>For 4.7-V to 5-V options<br>For all other options          |                         | 100<br>85  | 165<br>150            | μA                         |
|                                |                                        | V <sub>EN</sub> = 1.4 V, I <sub>OUT</sub> = 0 to 150 mA<br>For 4.7-V to 5-V options<br>For all other options   |                         | 155<br>140 | 250<br>200            |                            |
|                                |                                        | V <sub>EN</sub> = 0.4 V                                                                                        |                         | 0.003      | 1.5                   |                            |
| Dropout voltage <sup>(5)</sup> |                                        | I <sub>OUT</sub> = 1 mA                                                                                        |                         | 0.4        | 2                     | mV                         |
|                                |                                        | I <sub>OUT</sub> = 50 mA                                                                                       |                         | 20         | 35                    | mV                         |
|                                |                                        | I <sub>OUT</sub> = 100 mA                                                                                      |                         | 45         | 70                    | mV                         |
|                                |                                        | I <sub>OUT</sub> = 150 mA                                                                                      |                         | 60         | 100                   | mV                         |
| I <sub>SC</sub>                | Short circuit current limit            | Output Grounded<br>(Steady State)                                                                              |                         | 600        |                       | mA                         |
| I <sub>OUT(PK)</sub>           | Peak output current                    | V <sub>OUT</sub> ≥ V <sub>OUT(nom)</sub> − 5%                                                                  | 300                     | 550        |                       | mA                         |
| T <sub>ON</sub>                | Turnon time <sup>(6)</sup>             | C <sub>BYPASS</sub> = 0.01 μF                                                                                  |                         | 200        |                       | μs                         |
| e <sub>n</sub>                 | Output noise voltage <sup>(7)</sup>    | BW = 10 Hz to 100 kHz,<br>C <sub>OUT</sub> = 1 μF                                                              |                         | 30         |                       | μV <sub>RMS</sub>          |
|                                | Output noise density                   | C <sub>BP</sub> = 0                                                                                            |                         | 230        |                       | nV/√Hz                     |
| I <sub>EN</sub>                | Maximum input current at EN            | V <sub>EN</sub> = 0.4 V and V <sub>IN</sub> = 6 V                                                              |                         | ±1         |                       | nA                         |
| V <sub>IL</sub>                | Maximum low-level input voltage at EN  | V <sub>IN</sub> = 2.5 V to 6 V                                                                                 |                         |            | 0.4                   | V                          |
| V <sub>IH</sub>                | Minimum high-level input voltage at EN | V <sub>IN</sub> = 2.5 V to 6 V                                                                                 | 1.4                     |            |                       | V                          |
| TSD                            | Thermal shutdown temperature           |                                                                                                                |                         | 160        |                       | °C                         |
|                                | Thermal shutdown hysteresis            |                                                                                                                |                         | 20         |                       | °C                         |

(1) All limits are verified. All electrical characteristics having room-temperature limits are tested during production with  $T_A = 25^{\circ}\text{C}$  or correlated using Statistical Quality Control (SQC) methods. All hot and cold limits are specified by correlating the electrical characteristics to process and temperature variations and applying statistical process control.

(2) The target output voltage, which is labeled  $V_{OUT(NOM)}$ , is the desired voltage option.


(3)  $T_A = 25^{\circ}\text{C}$  only.

(4) An increase in the load current results in a slight decrease in the output voltage and vice versa.


(5) Dropout voltage is the input-to-output voltage difference at which the output voltage is 100mV below its nominal value. This specification does not apply for input voltages below 2.5V.

(6) Turnon time is time measured between the enable input just exceeding  $V_{IH}$  and the output voltage just reaching 95% of its nominal value.

(7) The output noise varies with output voltage option. The  $30\text{ }\mu\text{V}_{RMS}$  is measured with 2.5-V voltage option. To calculate an approximated output noise for other options, use the equation:  $(30\text{ }\mu\text{V}_{RMS})(X)/2.5$ , where X is the voltage option value.




**Figure 1. Line Transient Input Test Signal**




**Figure 2. PSRR Input Test Signal**

## 6.6 Typical Performance Characteristics


Unless otherwise specified,  $C_{IN} = C_{OUT} = 1\ \mu\text{F}$  ceramic,  $C_{BYPASS} = 0.01\ \mu\text{F}$ ,  $V_{IN} = V_{OUT} + 0.2\ \text{V}$ ,  $T_A = 25^\circ\text{C}$ , EN pin is tied to  $V_{IN}$ .




**Figure 3. Output Voltage Change vs Temperature**




**Figure 4. Dropout Voltage vs Load Current**




**Figure 5. Ground Current vs Load Current**



**Figure 6. Ground Current vs  $V_{IN}$  at  $25^\circ\text{C}$**




**Figure 7. Ground Current vs  $V_{IN}$  at  $-40^\circ\text{C}$**




**Figure 8. Ground Current vs  $V_{IN}$  at  $125^\circ\text{C}$**

## Typical Performance Characteristics (continued)


Unless otherwise specified,  $C_{IN} = C_{OUT} = 1\ \mu\text{F}$  ceramic,  $C_{BYPASS} = 0.01\ \mu\text{F}$ ,  $V_{IN} = V_{OUT} + 0.2\ \text{V}$ ,  $T_A = 25^\circ\text{C}$ , EN pin is tied to  $V_{IN}$ .




**Figure 9. Short Circuit Current (DSBGA)**




**Figure 10. Short Circuit Current (DSBGA)**




**Figure 11. Short Circuit Current (SOT)**



**Figure 12. Short Circuit Current (SOT)**




**Figure 13. Short Circuit Current (SOT)**




**Figure 14. Short Circuit Current (SOT)**

## Typical Performance Characteristics (continued)


Unless otherwise specified,  $C_{IN} = C_{OUT} = 1\ \mu\text{F}$  ceramic,  $C_{BYPASS} = 0.01\ \mu\text{F}$ ,  $V_{IN} = V_{OUT} + 0.2\ \text{V}$ ,  $T_A = 25^\circ\text{C}$ , EN pin is tied to  $V_{IN}$ .




**Figure 15. Short Circuit Current (DSBGA)**




**Figure 16. Short Circuit Current (DSBGA)**




**Figure 17. Output Noise Spectral Density**



**Figure 18. Ripple Rejection**



**Figure 19. Ripple Rejection**



**Figure 20. Ripple Rejection**

## Typical Performance Characteristics (continued)

Unless otherwise specified,  $C_{IN} = C_{OUT} = 1\ \mu\text{F}$  ceramic,  $C_{BYPASS} = 0.01\ \mu\text{F}$ ,  $V_{IN} = V_{OUT} + 0.2\ \text{V}$ ,  $T_A = 25^\circ\text{C}$ , EN pin is tied to  $V_{IN}$ .




Figure 21. Start-up Time




Figure 22. Start-up Time




Figure 23. Start-up Time




Figure 24. Start-up Time




Figure 25. Start-up Time






Figure 26. Line Transient Response

## Typical Performance Characteristics (continued)


Unless otherwise specified,  $C_{IN} = C_{OUT} = 1\ \mu\text{F}$  ceramic,  $C_{BYPASS} = 0.01\ \mu\text{F}$ ,  $V_{IN} = V_{OUT} + 0.2\ \text{V}$ ,  $T_A = 25^\circ\text{C}$ , EN pin is tied to  $V_{IN}$ .




**Figure 27. Line Transient Response**




**Figure 28. Load Transient Response**




**Figure 29. Load Transient Response**



**Figure 30. Load Transient Response**



**Figure 31. Load Transient Response**



**Figure 32. Enable Response**

## Typical Performance Characteristics (continued)

Unless otherwise specified,  $C_{IN} = C_{OUT} = 1 \mu\text{F}$  ceramic,  $C_{BYPASS} = 0.01 \mu\text{F}$ ,  $V_{IN} = V_{OUT} + 0.2 \text{ V}$ ,  $T_A = 25^\circ\text{C}$ , EN pin is tied to  $V_{IN}$ .




Figure 33. Enable Response




Figure 34. Enable Response




Figure 35. Output Impedance




Figure 36. Output Impedance

## 7 Detailed Description


### 7.1 Overview

The LP3985 family of fixed-output, ultra-low-dropout and low noise regulators offers exceptional, cost-effective performance for battery powered applications. Available in output voltages from 2.5 V to 5 V, the family is capable of delivering 150-mA continuous load current. Standard regulator features, such as overcurrent and overtemperature protection, are also included.

The LP3985 contains several features to facilitate battery powered designs:

- Multiple voltage options
- Low dropout voltage, typical dropout of 60 mV at 150-mA load current
- Low quiescent current and low ground current, typically 140  $\mu$ A at 150-mA load, and 85- $\mu$ A at 0-mA load
- A shutdown feature is available, allowing the regulator to consume only 0.003  $\mu$ A typically when the EN pin is pulled low
- Overtemperature protection and overcurrent protection circuitry is designed to safeguard the device during unexpected conditions
- Enhanced stability: The LP3985 is stable with output capacitor, which allows the use of ceramic capacitors on the output
- Power supply rejection is better than 50 dB at low frequencies and starts to roll off at 1 kHz.
- Low noise: A BYPASS pin allows for low-noise operation, with a typical output noise of 30  $\mu$ V<sub>RMS</sub>, with the use of a 10-nF bypass capacitor.

### 7.2 Functional Block Diagram



### 7.3 Feature Description

#### 7.3.1 No-Load Stability

The LP3985 will remain stable and in regulation with no external load. This is specially important in CMOS RAM keep-alive applications.

#### 7.3.2 On/Off Input Operation

The LP3985 is turned off by pulling the EN pin low, and turned on by pulling it high. If this feature is not used, the EN pin should be tied to  $V_{IN}$  to keep the regulator output on at all time. To assure proper operation, the signal source used to drive the EN input must be able to swing above and below the specified turnon/turnoff voltage thresholds listed in [Electrical Characteristics](#) under  $V_{IL}$  and  $V_{IH}$ .

## Feature Description (continued)

### 7.3.3 Fast On-Time

The LP3985 output is turned on after  $V_{REF}$  voltage reaches its final value (1.23 V, nominal). To speed up this process, the noise reduction capacitor at the BYPASS pin is charged with an internal 70- $\mu$ A current source. The current source is turned off when the bandgap voltage reaches approximately 95% of its final value. The turnon time is determined by the time constant of the bypass capacitor. The smaller the capacitor value, the shorter the turn on time, but less noise gets reduced. As a result, turn on time and noise reduction need to be taken into design consideration when choosing the value of the bypass capacitor.

## 7.4 Device Functional Modes

### 7.4.1 Operation with $V_{OUT(TARGET)} + 0.3\text{ V} \leq V_{IN} \leq 6\text{ V}$

The device operates if the input voltage is equal to, or exceeds,  $V_{OUT(TARGET)} + 0.3\text{ V}$ . At input voltages below the minimum  $V_{IN}$  requirement, the device does not operate correctly, and output voltage may not reach target value.

### 7.4.2 Operation Using the EN Pin

If the voltage on the EN pin is less than 0.4 V, the device is disabled, and in this state shutdown current does not exceed 1.5  $\mu$ A. Raising  $V_{EN}$  above 1.4 V initiates the start-up sequence of the device.

## 8 Application and Implementation


### NOTE

Information in the following applications sections is not part of the TI component specification, and TI does not warrant its accuracy or completeness. TI's customers are responsible for determining suitability of components for their purposes. Customers should validate and test their design implementation to confirm system functionality.

### 8.1 Application Information

The LP3985 can provide 150-mA output current with 2.5-V to 6-V input. It is stable with a small 1- $\mu$ F  $\pm$ 30% ceramic or high-quality tantalum output capacitor. The DSBGA requires the smallest possible PC board area – the total application circuit area can be less than 2 mm x 2.5 mm, a fraction of a 1206 case size. An optional external bypass capacitor reduces the output noise without slowing down the load transient response. Fast startup time is achieved by utilizing an internal power-on circuit that actively pre-charges the bypass capacitor. Typical output noise is 30  $\mu$ V<sub>RMS</sub> at frequencies from 10 Hz to 100 kHz. Typical power supply rejection is 50 dB at 1 kHz.

### 8.2 Typical Application



Pin Numbers in parenthesis indicate DSBGA package.  
\* Optional Noise Reduction Capacitor.

**Figure 37. LP3985 Typical Application**

#### 8.2.1 Design Requirements

| DESIGN PARAMETERS           | VALUE                                                               |
|-----------------------------|---------------------------------------------------------------------|
| Input voltage               | 4.2 V, $\pm$ 10% provided by the DC-DC converter switching at 1 MHz |
| Output voltage              | 3 V, $\pm$ 5%                                                       |
| Output current              | 150 mA (maximum)                                                    |
| RMS noise, 10 Hz to 100 kHz | 30 $\mu$ V <sub>RMS</sub>                                           |
| PSRR at 1 kHz               | 50 dB                                                               |

#### 8.2.2 Detailed Design Procedure

##### 8.2.2.1 External Capacitors

Like any low-dropout regulator, the LP3985 requires external capacitors for regulator stability. The LP3985 is specifically designed for portable applications requiring minimum board space and smallest components. These capacitors must be correctly selected for good performance.

##### 8.2.2.2 Input Capacitor

An input capacitance of approximately 1  $\mu$ F is required between the LP3985 input pin and ground (the amount of the capacitance may be increased without limit).

This capacitor must be located a distance of not more than 1 cm from the input pin and returned to a clean analog ground. A ceramic capacitor is recommended although a good quality tantalum or film capacitor may be used at the input.

#### NOTE

Tantalum capacitors can suffer catastrophic failures due to surge current when connected to a low-impedance source of power (like a battery or a very large capacitor). If a tantalum capacitor is used at the input, it must be verified by the manufacturer to have a surge current rating sufficient for the application.

There are no requirements for the ESR on the input capacitor, but tolerance and temperature coefficient must be considered when selecting the capacitor to ensure the capacitance will remain within the operational range over the full range of temperature and operating conditions.

#### 8.2.2.3 Output Capacitor

Correct selection of the output capacitor is important to ensure stable operation in the intended application.

The output capacitor must meet all the requirements specified in the recommended capacitor table over all conditions in the application. These conditions include DC-bias, frequency and temperature. Unstable operation will result if the capacitance drops below the minimum specified value. (See the next section Capacitor Characteristics).

The LP3985 is designed specifically to work with very small ceramic output capacitors. A 1- $\mu$ F ceramic capacitor (dielectric type X7R) with ESR between 5 m $\Omega$  to 500 m $\Omega$  is suitable in the LP3985 application circuit. X5R capacitors may be used but have a narrower temperature range. With these and other capacitor types (Y5V, Z6U) that may be used, selection is dependant on the range of operating conditions and temperature range for that application. (see [Capacitor Characteristics](#) ).

It may also be possible to use tantalum or film capacitors at the output, but these are not as attractive for reasons of size and cost (see [Capacitor Characteristics](#)).


It is also recommended that the output capacitor be placed within 1 cm from the output pin and returned to a clean ground line.

#### 8.2.2.4 Capacitor Characteristics

The LP3985 is designed to work with ceramic capacitors on the output to take advantage of the benefits they offer: for capacitance values in the range of 1  $\mu$ F to 4.7  $\mu$ F, ceramic capacitors are the smallest, least expensive, and have the lowest ESR values (which makes them best for eliminating high frequency noise). The ESR of a typical 1- $\mu$ F ceramic capacitor is in the range of 20 m $\Omega$  to 40 m $\Omega$ , which easily meets the ESR requirement for stability by the LP3985.

For both input and output capacitors careful interpretation of the capacitor specification is required to ensure correct device operation. The capacitor value can change greatly dependant on the conditions of operation and capacitor type.

In particular the output capacitor selection should take account of all the capacitor parameters to ensure that the specification is met within the application. Capacitance value can vary with DC bias conditions as well as temperature and frequency of operation. Capacitor values will also show some decrease over time due to aging. The capacitor parameters are also dependant on the particular case size with smaller sizes giving poorer performance figures in general. As an example [Figure 38](#) shows a typical graph showing a comparison of capacitor case sizes in a Capacitance vs. DC Bias plot. As shown in the graph, as a result of the DC Bias condition the capacitance value may drop below the minimum capacitance value given in the recommended capacitor table (0.7  $\mu$ F in this case). Note that the graph shows the capacitance out of spec for the 0402 case size capacitor at higher bias voltages. It is therefore recommended that the capacitor manufacturers' specifications for the nominal value capacitor are consulted for all conditions as some capacitor sizes (for example, 0402) may not be suitable in the actual application.



**Figure 38. Graph Showing A Typical Variation In Capacitance vs DC Bias**

The ceramic capacitor's capacitance can vary with temperature. The capacitor type X7R, which operates over a temperature range of  $-55^{\circ}\text{C}$  to  $125^{\circ}\text{C}$ , will only vary the capacitance to within  $\pm 15\%$ . The capacitor type X5R has a similar tolerance over a reduced temperature range of  $-55^{\circ}\text{C}$  to  $85^{\circ}\text{C}$ . Most large value ceramic capacitors (around  $2.2\ \mu\text{F}$ ) are manufactured with Z5U or Y5V temperature characteristics. Their capacitance can drop by more than 50% as the temperature goes from  $25^{\circ}\text{C}$  to  $85^{\circ}\text{C}$ . Therefore X7R is recommended over Z5U and Y5V in applications where the ambient temperature will change significantly above or below  $25^{\circ}\text{C}$ .

Tantalum capacitors are less desirable than ceramic for use as output capacitors because they are more expensive when comparing equivalent capacitance and voltage ratings in the  $1\text{-}\mu\text{F}$  to  $4.7\text{-}\mu\text{F}$  range.

Another important consideration is that tantalum capacitors have higher ESR values than equivalent size ceramics. This means that while it may be possible to find a tantalum capacitor with an ESR value within the stable range, it would have to be larger in capacitance (which means bigger and more costly) than a ceramic capacitor with the same ESR value. It should also be noted that the ESR of a typical tantalum will increase about 2:1 as the temperature goes from  $25^{\circ}\text{C}$  down to  $-40^{\circ}\text{C}$ , so some guard band must be allowed.

#### 8.2.2.5 Noise Bypass Capacitor

Connecting a  $0.01\text{-}\mu\text{F}$  capacitor between the CBYPASS pin and ground significantly reduces noise on the regulator output. This cap is connected directly to a high impedance node in the band gap reference circuit. Any significant loading on this node will cause a change on the regulated output voltage. For this reason, DC leakage current through this pin must be kept as low as possible for best output voltage accuracy.

The types of capacitors best suited for the noise bypass capacitor are ceramic and film. High-quality ceramic capacitors with either NPO or COG dielectric typically have very low leakage. Polypropylene and polycarbonate film capacitors are available in small surface-mount packages and typically have extremely low leakage current.

Unlike many other LDOs, addition of a noise reduction capacitor does not effect the load transient response of the device.

#### 8.2.2.6 Thermal Considerations

##### CAUTION

Due to the limited power dissipation characteristics of the available SOT-23 (DBV) and DSBGA (YZR) packages, all possible combinations of output current ( $I_{\text{OUT}}$ ), input voltage ( $V_{\text{IN}}$ ), output voltage ( $V_{\text{OUT}}$ ), and ambient temperatures ( $T_{\text{A}}$ ) cannot be ensured.

Power dissipation,  $P_{\text{D}}$  is calculated from the following formula:  $P_{\text{D}} = (V_{\text{IN}} - V_{\text{OUT}}) \times I_{\text{OUT}}$ .

The LP3985 regulator has internal thermal limiting designed to protect the device during overload conditions. For continuous normal conditions, the recommended maximum operating junction temperature is 125°C. It is important to give careful consideration to all sources of thermal resistance from junction to ambient. Additional heat sources mounted nearby must also be considered.

For surface-mount devices, heat sinking is accomplished by using the heat-spreading capabilities of the PC board and its copper traces. Copper board stiffeners and plated through-holes can also be used to spread the heat generated by power devices. Example: Given an output voltage of 3.3 V, an input voltage range of 4 V to 6 V, a maximum output current of 100 mA, and a maximum ambient temperature of 50°C, what is the maximum operating junction temperature? The power dissipated by the device is found using the formula:

$$P_{D(MAX)} = (V_{IN(MAX)} - V_{OUT}) \times I_{OUT(MAX)}$$

where

- $I_{OUT(MAX)} = 100 \text{ mA}$
- $V_{IN(MAX)} = 6 \text{ V}$
- $V_{OUT} = 3.3 \text{ V}$

(1)


For example,  $P_{D(MAX)} = ((6 \text{ V} - 3.3 \text{ V}) \times 100 \text{ mA}) = 0.27 \text{ W}$ .

Using the 5-pin SOT-23 (DBV) package, the LP3985 junction-to-ambient thermal resistance ( $R_{\theta JA}$ ) has a rating of 220°C/W using the standard JEDEC JESD51-7 PCB (High-K) circuit board. The junction temperature rise above ambient is found using the formula:


$$T_{RISE} = P_{D(MAX)} \times R_{\theta JA}$$

for example,  $T_{J(MAX)} = 50^\circ\text{C} + 59.4^\circ\text{C} = 109.4^\circ\text{C}$ .

### 8.2.3 Application Curves



**Figure 39. Start-up Time**



**Figure 40. Enable Response**

## 9 Power Supply Recommendations


The LP3985 is designed to operate from an input voltage supply range between 2.5 V and 6 V. The input-voltage range provides adequate headroom in order for the device to have a regulated output. This input supply must be well regulated. If the input supply is noisy, additional input capacitors with low ESR can help to improve the output noise performance.

## 10 Layout


### 10.1 Layout Guidelines

For best overall performance, place all circuit components on the same side of the circuit board and as near as practical to the respective LDO pin connections. Place ground return connections to the input and output capacitor, and to the LDO ground pin as close to each other as possible, connected by a wide, component-side, copper surface. The use of vias and long traces to create LDO circuit connections is strongly discouraged and negatively affects system performance. This grounding and layout scheme minimizes inductive parasitics, and thereby reduces load-current transients, minimizes noise, and increases circuit stability. A ground reference plane is also recommended and is either embedded in the PCB itself or located on the bottom side of the PCB opposite the components. This reference plane serves to assure accuracy of the output voltage, shield noise, and behaves similar to a thermal plane to spread (or sink) heat from the LDO device. In most applications, this ground plane is necessary to meet thermal requirements.

### 10.2 Layout Examples



**Figure 41. LP3985 SOT-23 Package Typical Layout**



**Figure 42. LP3985 DSBGA Package Typical Layout**

### 10.3 DSBGA Mounting

The DSBGA package requires specific mounting techniques which are detailed in Texas Instruments Application Note 1112 *DSBGA Wafer Level Chip Scale Package* ([SNVA009](#)). Referring to the section *Surface Mount Technology (SMT) Assembly Considerations*, it should be noted that the pad style which must be used with the 5-bump package is NSMD (non-solder mask defined) type.

For best results during assembly, alignment ordinals on the PC board may be used to facilitate placement of the DSBGA device.

### 10.4 DSBGA Light Sensitivity

Exposing the DSBGA device to direct sunlight will cause mis-operation of the device. Light sources such as halogen lamps can effect electrical performance if brought near to the device.

### DSBGA Light Sensitivity (continued)

The wavelengths which have most detrimental effect are reds and infra-reds, which means that the fluorescent lighting used inside most buildings has very little effect on performance. A DSBGA test board was brought to within 1 cm of a fluorescent desk lamp and the effect on the regulated output voltage was negligible, showing a deviation of less than 0.1% from nominal.

## 11 Device and Documentation Support

### 11.1 Documentation Support

#### 11.1.1 Related Documentation

For related documentation, see the following:

- Texas Instruments Application Note AN-1187 *Leadless Leadframe Package (LLP)* ([SNOA401](#)).
- Texas Instruments Application Note AN-1112 *DSBGA Wafer Level Chip Scale Package* ([SNVA009](#)).

### 11.2 Trademarks

All trademarks are the property of their respective owners.

### 11.3 Electrostatic Discharge Caution



This integrated circuit can be damaged by ESD. Texas Instruments recommends that all integrated circuits be handled with appropriate precautions. Failure to observe proper handling and installation procedures can cause damage.

ESD damage can range from subtle performance degradation to complete device failure. Precision integrated circuits may be more susceptible to damage because very small parametric changes could cause the device not to meet its published specifications.

### 11.4 Glossary

[SLYZ022](#) — *TI Glossary*.

This glossary lists and explains terms, acronyms, and definitions.

## 12 Mechanical, Packaging, and Orderable Information

The following pages include mechanical, packaging, and orderable information. This information is the most current data available for the designated devices. This data is subject to change without notice and revision of this document. For browser-based versions of this data sheet, refer to the left-hand navigation.

## PACKAGING INFORMATION

| Orderable part number               | Status<br>(1) | Material type<br>(2) | Package   Pins   | Package qty   Carrier | RoHS<br>(3) | Lead finish/<br>Ball material<br>(4) | MSL rating/<br>Peak reflow<br>(5) | Op temp (°C) | Part marking<br>(6) |
|-------------------------------------|---------------|----------------------|------------------|-----------------------|-------------|--------------------------------------|-----------------------------------|--------------|---------------------|
| <a href="#">LP3985IM5-2.5/NOPB</a>  | Active        | Production           | SOT-23 (DBV)   5 | 1000   SMALL T&R      | Yes         | SN                                   | Level-1-260C-UNLIM                | -40 to 125   | LCSB                |
| LP3985IM5-2.5/NOPB.A                | Active        | Production           | SOT-23 (DBV)   5 | 1000   SMALL T&R      | Yes         | SN                                   | Level-1-260C-UNLIM                | -40 to 125   | LCSB                |
| <a href="#">LP3985IM5-2.7/NOPB</a>  | Active        | Production           | SOT-23 (DBV)   5 | 1000   LARGE T&R      | Yes         | SN                                   | Level-1-260C-UNLIM                | -40 to 125   | LCUB                |
| LP3985IM5-2.7/NOPB.A                | Active        | Production           | SOT-23 (DBV)   5 | 1000   LARGE T&R      | Yes         | SN                                   | Level-1-260C-UNLIM                | -40 to 125   | LCUB                |
| <a href="#">LP3985IM5-2.8/NOPB</a>  | Active        | Production           | SOT-23 (DBV)   5 | 1000   SMALL T&R      | Yes         | SN                                   | Level-1-260C-UNLIM                | -40 to 125   | LCJB                |
| LP3985IM5-2.8/NOPB.A                | Active        | Production           | SOT-23 (DBV)   5 | 1000   SMALL T&R      | Yes         | SN                                   | Level-1-260C-UNLIM                | -40 to 125   | LCJB                |
| <a href="#">LP3985IM5-2.9/NOPB</a>  | Active        | Production           | SOT-23 (DBV)   5 | 1000   LARGE T&R      | Yes         | SN                                   | Level-1-260C-UNLIM                | -40 to 125   | LCYB                |
| LP3985IM5-2.9/NOPB.A                | Active        | Production           | SOT-23 (DBV)   5 | 1000   LARGE T&R      | Yes         | SN                                   | Level-1-260C-UNLIM                | -40 to 125   | LCYB                |
| <a href="#">LP3985IM5-3.0/NOPB</a>  | Active        | Production           | SOT-23 (DBV)   5 | 1000   SMALL T&R      | Yes         | NIPDAU   SN                          | Level-1-260C-UNLIM                | -40 to 125   | LCRB                |
| LP3985IM5-3.0/NOPB.A                | Active        | Production           | SOT-23 (DBV)   5 | 1000   SMALL T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | -40 to 125   | LCRB                |
| <a href="#">LP3985IM5-3.2/NOPB</a>  | Active        | Production           | SOT-23 (DBV)   5 | 1000   LARGE T&R      | Yes         | SN                                   | Level-1-260C-UNLIM                | -40 to 125   | LDPB                |
| LP3985IM5-3.2/NOPB.A                | Active        | Production           | SOT-23 (DBV)   5 | 1000   LARGE T&R      | Yes         | SN                                   | Level-1-260C-UNLIM                | -40 to 125   | LDPB                |
| <a href="#">LP3985IM5-3.3/NOPB</a>  | Active        | Production           | SOT-23 (DBV)   5 | 1000   SMALL T&R      | Yes         | NIPDAU   SN                          | Level-1-260C-UNLIM                | -40 to 125   | LDQB                |
| LP3985IM5-3.3/NOPB.A                | Active        | Production           | SOT-23 (DBV)   5 | 1000   SMALL T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | -40 to 125   | LDQB                |
| <a href="#">LP3985IM5-4.7/NOPB</a>  | Active        | Production           | SOT-23 (DBV)   5 | 1000   SMALL T&R      | Yes         | SN                                   | Level-1-260C-UNLIM                | -40 to 125   | LDRB                |
| LP3985IM5-4.7/NOPB.A                | Active        | Production           | SOT-23 (DBV)   5 | 1000   SMALL T&R      | Yes         | SN                                   | Level-1-260C-UNLIM                | -40 to 125   | LDRB                |
| <a href="#">LP3985IM5-5.0/NOPB</a>  | Active        | Production           | SOT-23 (DBV)   5 | 1000   SMALL T&R      | Yes         | NIPDAU   SN                          | Level-1-260C-UNLIM                | -40 to 125   | LDSB                |
| LP3985IM5-5.0/NOPB.A                | Active        | Production           | SOT-23 (DBV)   5 | 1000   SMALL T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | -40 to 125   | LDSB                |
| LP3985IM5X-2.5/NO.A                 | Active        | Production           | SOT-23 (DBV)   5 | 3000   LARGE T&R      | Yes         | SN                                   | Level-1-260C-UNLIM                | -40 to 125   | LCSB                |
| <a href="#">LP3985IM5X-2.5/NOPB</a> | Active        | Production           | SOT-23 (DBV)   5 | 3000   LARGE T&R      | Yes         | SN                                   | Level-1-260C-UNLIM                | -40 to 125   | LCSB                |
| LP3985IM5X-2.8/NO.A                 | Active        | Production           | SOT-23 (DBV)   5 | 3000   LARGE T&R      | Yes         | SN                                   | Level-1-260C-UNLIM                | -40 to 125   | LCJB                |
| <a href="#">LP3985IM5X-2.8/NOPB</a> | Active        | Production           | SOT-23 (DBV)   5 | 3000   LARGE T&R      | Yes         | SN                                   | Level-1-260C-UNLIM                | -40 to 125   | LCJB                |
| LP3985IM5X-285/NO.A                 | Active        | Production           | SOT-23 (DBV)   5 | 3000   LARGE T&R      | Yes         | SN                                   | Level-1-260C-UNLIM                | -40 to 125   | LCXB                |
| <a href="#">LP3985IM5X-285/NOPB</a> | Active        | Production           | SOT-23 (DBV)   5 | 3000   LARGE T&R      | Yes         | SN                                   | Level-1-260C-UNLIM                | -40 to 125   | LCXB                |
| LP3985IM5X-3.0/NO.A                 | Active        | Production           | SOT-23 (DBV)   5 | 3000   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | -40 to 125   | LCRB                |
| <a href="#">LP3985IM5X-3.0/NOPB</a> | Active        | Production           | SOT-23 (DBV)   5 | 3000   LARGE T&R      | Yes         | NIPDAU   SN                          | Level-1-260C-UNLIM                | -40 to 125   | LCRB                |
| LP3985IM5X-3.3/NO.A                 | Active        | Production           | SOT-23 (DBV)   5 | 3000   LARGE T&R      | Yes         | SN                                   | Level-1-260C-UNLIM                | -40 to 125   | LDQB                |
| <a href="#">LP3985IM5X-3.3/NOPB</a> | Active        | Production           | SOT-23 (DBV)   5 | 3000   LARGE T&R      | Yes         | SN                                   | Level-1-260C-UNLIM                | -40 to 125   | LDQB                |
| LP3985IM5X-4.7/NO.A                 | Active        | Production           | SOT-23 (DBV)   5 | 3000   LARGE T&R      | Yes         | SN                                   | Level-1-260C-UNLIM                | -40 to 125   | LDRB                |

| Orderable part number                | Status<br>(1) | Material type<br>(2) | Package   Pins   | Package qty   Carrier | RoHS<br>(3) | Lead finish/<br>Ball material<br>(4) | MSL rating/<br>Peak reflow<br>(5) | Op temp (°C) | Part marking<br>(6) |
|--------------------------------------|---------------|----------------------|------------------|-----------------------|-------------|--------------------------------------|-----------------------------------|--------------|---------------------|
| <a href="#">LP3985IM5X-4.7/NOPB</a>  | Active        | Production           | SOT-23 (DBV)   5 | 3000   LARGE T&R      | Yes         | SN                                   | Level-1-260C-UNLIM                | -40 to 125   | LDRB                |
| <a href="#">LP3985IM5X-5.0/NO.A</a>  | Active        | Production           | SOT-23 (DBV)   5 | 3000   LARGE T&R      | Yes         | SN                                   | Level-1-260C-UNLIM                | -40 to 125   | LDSB                |
| <a href="#">LP3985IM5X-5.0/NOPB</a>  | Active        | Production           | SOT-23 (DBV)   5 | 3000   LARGE T&R      | Yes         | SN                                   | Level-1-260C-UNLIM                | -40 to 125   | LDSB                |
| <a href="#">LP3985ITL-2.5/NOPB</a>   | Active        | Production           | DSBGA (YZR)   5  | 250   SMALL T&R       | Yes         | SNAGCU                               | Level-1-260C-UNLIM                | -40 to 125   | 5                   |
| <a href="#">LP3985ITL-2.5/NOPB.A</a> | Active        | Production           | DSBGA (YZR)   5  | 250   SMALL T&R       | Yes         | SNAGCU                               | Level-1-260C-UNLIM                | -40 to 125   | 5                   |
| <a href="#">LP3985ITL-2.6/NOPB</a>   | Active        | Production           | DSBGA (YZR)   5  | 250   SMALL T&R       | Yes         | SNAGCU                               | Level-1-260C-UNLIM                | -40 to 125   | 5                   |
| <a href="#">LP3985ITL-2.6/NOPB.A</a> | Active        | Production           | DSBGA (YZR)   5  | 250   SMALL T&R       | Yes         | SNAGCU                               | Level-1-260C-UNLIM                | -40 to 125   | 5                   |
| <a href="#">LP3985ITL-2.7/NOPB</a>   | Active        | Production           | DSBGA (YZR)   5  | 250   SMALL T&R       | Yes         | SNAGCU                               | Level-1-260C-UNLIM                | -40 to 125   | 5                   |
| <a href="#">LP3985ITL-2.7/NOPB.A</a> | Active        | Production           | DSBGA (YZR)   5  | 250   SMALL T&R       | Yes         | SNAGCU                               | Level-1-260C-UNLIM                | -40 to 125   | 5                   |
| <a href="#">LP3985ITL-2.8/NOPB</a>   | Active        | Production           | DSBGA (YZR)   5  | 250   SMALL T&R       | Yes         | SNAGCU                               | Level-1-260C-UNLIM                | -40 to 125   | 5                   |
| <a href="#">LP3985ITL-2.8/NOPB.A</a> | Active        | Production           | DSBGA (YZR)   5  | 250   SMALL T&R       | Yes         | SNAGCU                               | Level-1-260C-UNLIM                | -40 to 125   | 5                   |
| <a href="#">LP3985ITL-2.9/NOPB</a>   | Active        | Production           | DSBGA (YZR)   5  | 250   SMALL T&R       | Yes         | SNAGCU                               | Level-1-260C-UNLIM                | -40 to 125   | 5                   |
| <a href="#">LP3985ITL-2.9/NOPB.A</a> | Active        | Production           | DSBGA (YZR)   5  | 250   SMALL T&R       | Yes         | SNAGCU                               | Level-1-260C-UNLIM                | -40 to 125   | 5                   |
| <a href="#">LP3985ITL-285/NOPB</a>   | Active        | Production           | DSBGA (YZR)   5  | 250   SMALL T&R       | Yes         | SNAGCU                               | Level-1-260C-UNLIM                | -40 to 125   | 5                   |
| <a href="#">LP3985ITL-285/NOPB.A</a> | Active        | Production           | DSBGA (YZR)   5  | 250   SMALL T&R       | Yes         | SNAGCU                               | Level-1-260C-UNLIM                | -40 to 125   | 5                   |
| <a href="#">LP3985ITL-3.0/NOPB</a>   | Active        | Production           | DSBGA (YZR)   5  | 250   SMALL T&R       | Yes         | SNAGCU                               | Level-1-260C-UNLIM                | -40 to 125   | 5                   |
| <a href="#">LP3985ITL-3.0/NOPB.A</a> | Active        | Production           | DSBGA (YZR)   5  | 250   SMALL T&R       | Yes         | SNAGCU                               | Level-1-260C-UNLIM                | -40 to 125   | 5                   |
| <a href="#">LP3985ITL-3.1/NOPB</a>   | Active        | Production           | DSBGA (YZR)   5  | 250   SMALL T&R       | Yes         | SNAGCU                               | Level-1-260C-UNLIM                | -40 to 125   | 5                   |
| <a href="#">LP3985ITL-3.1/NOPB.A</a> | Active        | Production           | DSBGA (YZR)   5  | 250   SMALL T&R       | Yes         | SNAGCU                               | Level-1-260C-UNLIM                | -40 to 125   | 5                   |
| <a href="#">LP3985ITL-3.3/NOPB</a>   | Active        | Production           | DSBGA (YZR)   5  | 250   SMALL T&R       | Yes         | SNAGCU                               | Level-1-260C-UNLIM                | -40 to 125   | 5                   |
| <a href="#">LP3985ITL-3.3/NOPB.A</a> | Active        | Production           | DSBGA (YZR)   5  | 250   SMALL T&R       | Yes         | SNAGCU                               | Level-1-260C-UNLIM                | -40 to 125   | 5                   |
| <a href="#">LP3985ITL-4.8/NOPB</a>   | Active        | Production           | DSBGA (YZR)   5  | 250   SMALL T&R       | Yes         | SNAGCU                               | Level-1-260C-UNLIM                | -            | 5                   |
| <a href="#">LP3985ITL-4.8/NOPB.A</a> | Active        | Production           | DSBGA (YZR)   5  | 250   SMALL T&R       | Yes         | SNAGCU                               | Level-1-260C-UNLIM                | -40 to 125   | 5                   |
| <a href="#">LP3985ITL-5.0/NOPB</a>   | Active        | Production           | DSBGA (YZR)   5  | 250   SMALL T&R       | Yes         | SNAGCU                               | Level-1-260C-UNLIM                | -40 to 125   | 5                   |
| <a href="#">LP3985ITL-5.0/NOPB.A</a> | Active        | Production           | DSBGA (YZR)   5  | 250   SMALL T&R       | Yes         | SNAGCU                               | Level-1-260C-UNLIM                | -40 to 125   | 5                   |
| <a href="#">LP3985ITLX-2.5/NO.A</a>  | Active        | Production           | DSBGA (YZR)   5  | 3000   LARGE T&R      | Yes         | SNAGCU                               | Level-1-260C-UNLIM                | -40 to 125   | 5                   |
| <a href="#">LP3985ITLX-2.5/NOPB</a>  | Active        | Production           | DSBGA (YZR)   5  | 3000   LARGE T&R      | Yes         | SNAGCU                               | Level-1-260C-UNLIM                | -40 to 125   | 5                   |
| <a href="#">LP3985ITLX-2.7/NO.A</a>  | Active        | Production           | DSBGA (YZR)   5  | 3000   LARGE T&R      | Yes         | SNAGCU                               | Level-1-260C-UNLIM                | -40 to 125   | 5                   |
| <a href="#">LP3985ITLX-2.7/NOPB</a>  | Active        | Production           | DSBGA (YZR)   5  | 3000   LARGE T&R      | Yes         | SNAGCU                               | Level-1-260C-UNLIM                | -40 to 125   | 5                   |
| <a href="#">LP3985ITLX-2.8/NO.A</a>  | Active        | Production           | DSBGA (YZR)   5  | 3000   LARGE T&R      | Yes         | SNAGCU                               | Level-1-260C-UNLIM                | -40 to 125   | 5                   |
| <a href="#">LP3985ITLX-2.8/NOPB</a>  | Active        | Production           | DSBGA (YZR)   5  | 3000   LARGE T&R      | Yes         | SNAGCU                               | Level-1-260C-UNLIM                | -40 to 125   | 5                   |

| Orderable part number               | Status<br>(1) | Material type<br>(2) | Package   Pins  | Package qty   Carrier | RoHS<br>(3) | Lead finish/<br>Ball material<br>(4) | MSL rating/<br>Peak reflow<br>(5) | Op temp (°C) | Part marking<br>(6) |
|-------------------------------------|---------------|----------------------|-----------------|-----------------------|-------------|--------------------------------------|-----------------------------------|--------------|---------------------|
| LP3985ITLX-285/NO.A                 | Active        | Production           | DSBGA (YZR)   5 | 3000   LARGE T&R      | Yes         | SNAGCU                               | Level-1-260C-UNLIM                | -40 to 125   | 5                   |
| <a href="#">LP3985ITLX-285/NOPB</a> | Active        | Production           | DSBGA (YZR)   5 | 3000   LARGE T&R      | Yes         | SNAGCU                               | Level-1-260C-UNLIM                | -40 to 125   | 5                   |
| LP3985ITLX-3.0/NO.A                 | Active        | Production           | DSBGA (YZR)   5 | 3000   LARGE T&R      | Yes         | SNAGCU                               | Level-1-260C-UNLIM                | -40 to 125   | 5                   |
| <a href="#">LP3985ITLX-3.0/NOPB</a> | Active        | Production           | DSBGA (YZR)   5 | 3000   LARGE T&R      | Yes         | SNAGCU                               | Level-1-260C-UNLIM                | -40 to 125   | 5                   |
| LP3985ITLX-3.1/NO.A                 | Active        | Production           | DSBGA (YZR)   5 | 3000   LARGE T&R      | Yes         | SNAGCU                               | Level-1-260C-UNLIM                | -40 to 125   | 5                   |
| <a href="#">LP3985ITLX-3.1/NOPB</a> | Active        | Production           | DSBGA (YZR)   5 | 3000   LARGE T&R      | Yes         | SNAGCU                               | Level-1-260C-UNLIM                | -40 to 125   | 5                   |
| LP3985ITLX-3.3/NO.A                 | Active        | Production           | DSBGA (YZR)   5 | 3000   LARGE T&R      | Yes         | SNAGCU                               | Level-1-260C-UNLIM                | -40 to 125   | 5                   |
| <a href="#">LP3985ITLX-3.3/NOPB</a> | Active        | Production           | DSBGA (YZR)   5 | 3000   LARGE T&R      | Yes         | SNAGCU                               | Level-1-260C-UNLIM                | -40 to 125   | 5                   |
| LP3985ITLX-5.0/NO.A                 | Active        | Production           | DSBGA (YZR)   5 | 3000   LARGE T&R      | Yes         | SNAGCU                               | Level-1-260C-UNLIM                | -40 to 125   | 5                   |
| <a href="#">LP3985ITLX-5.0/NOPB</a> | Active        | Production           | DSBGA (YZR)   5 | 3000   LARGE T&R      | Yes         | SNAGCU                               | Level-1-260C-UNLIM                | -40 to 125   | 5                   |

<sup>(1)</sup> **Status:** For more details on status, see our [product life cycle](#).

<sup>(2)</sup> **Material type:** When designated, preproduction parts are prototypes/experimental devices, and are not yet approved or released for full production. Testing and final process, including without limitation quality assurance, reliability performance testing, and/or process qualification, may not yet be complete, and this item is subject to further changes or possible discontinuation. If available for ordering, purchases will be subject to an additional waiver at checkout, and are intended for early internal evaluation purposes only. These items are sold without warranties of any kind.

<sup>(3)</sup> **RoHS values:** Yes, No, RoHS Exempt. See the [TI RoHS Statement](#) for additional information and value definition.

<sup>(4)</sup> **Lead finish/Ball material:** Parts may have multiple material finish options. Finish options are separated by a vertical ruled line. Lead finish/Ball material values may wrap to two lines if the finish value exceeds the maximum column width.

<sup>(5)</sup> **MSL rating/Peak reflow:** The moisture sensitivity level ratings and peak solder (reflow) temperatures. In the event that a part has multiple moisture sensitivity ratings, only the lowest level per JEDEC standards is shown. Refer to the shipping label for the actual reflow temperature that will be used to mount the part to the printed circuit board.

<sup>(6)</sup> **Part marking:** There may be an additional marking, which relates to the logo, the lot trace code information, or the environmental category of the part.

Multiple part markings will be inside parentheses. Only one part marking contained in parentheses and separated by a "-" will appear on a part. If a line is indented then it is a continuation of the previous line and the two combined represent the entire part marking for that device.

**Important Information and Disclaimer:** The information provided on this page represents TI's knowledge and belief as of the date that it is provided. TI bases its knowledge and belief on information provided by third parties, and makes no representation or warranty as to the accuracy of such information. Efforts are underway to better integrate information from third parties. TI has taken and continues to take reasonable steps to provide representative and accurate information but may not have conducted destructive testing or chemical analysis on incoming materials and chemicals. TI and TI suppliers consider certain information to be proprietary, and thus CAS numbers and other limited information may not be available for release.

In no event shall TI's liability arising out of such information exceed the total purchase price of the TI part(s) at issue in this document sold by TI to Customer on an annual basis.

## TAPE AND REEL INFORMATION



\*All dimensions are nominal

| Device              | Package Type | Package Drawing | Pins | SPQ  | Reel Diameter (mm) | Reel Width W1 (mm) | A0 (mm) | B0 (mm) | K0 (mm) | P1 (mm) | W (mm) | Pin1 Quadrant |
|---------------------|--------------|-----------------|------|------|--------------------|--------------------|---------|---------|---------|---------|--------|---------------|
| LP3985IM5-2.5/NOPB  | SOT-23       | DBV             | 5    | 1000 | 178.0              | 8.4                | 3.2     | 3.2     | 1.4     | 4.0     | 8.0    | Q3            |
| LP3985IM5-2.7/NOPB  | SOT-23       | DBV             | 5    | 1000 | 178.0              | 8.4                | 3.2     | 3.2     | 1.4     | 4.0     | 8.0    | Q3            |
| LP3985IM5-2.8/NOPB  | SOT-23       | DBV             | 5    | 1000 | 178.0              | 8.4                | 3.2     | 3.2     | 1.4     | 4.0     | 8.0    | Q3            |
| LP3985IM5-2.9/NOPB  | SOT-23       | DBV             | 5    | 1000 | 178.0              | 8.4                | 3.2     | 3.2     | 1.4     | 4.0     | 8.0    | Q3            |
| LP3985IM5-3.0/NOPB  | SOT-23       | DBV             | 5    | 1000 | 180.0              | 8.4                | 3.2     | 3.2     | 1.4     | 4.0     | 8.0    | Q3            |
| LP3985IM5-3.0/NOPB  | SOT-23       | DBV             | 5    | 1000 | 178.0              | 8.4                | 3.2     | 3.2     | 1.4     | 4.0     | 8.0    | Q3            |
| LP3985IM5-3.2/NOPB  | SOT-23       | DBV             | 5    | 1000 | 178.0              | 8.4                | 3.2     | 3.2     | 1.4     | 4.0     | 8.0    | Q3            |
| LP3985IM5-3.3/NOPB  | SOT-23       | DBV             | 5    | 1000 | 180.0              | 8.4                | 3.2     | 3.2     | 1.4     | 4.0     | 8.0    | Q3            |
| LP3985IM5-3.3/NOPB  | SOT-23       | DBV             | 5    | 1000 | 178.0              | 8.4                | 3.2     | 3.2     | 1.4     | 4.0     | 8.0    | Q3            |
| LP3985IM5-4.7/NOPB  | SOT-23       | DBV             | 5    | 1000 | 178.0              | 8.4                | 3.2     | 3.2     | 1.4     | 4.0     | 8.0    | Q3            |
| LP3985IM5-5.0/NOPB  | SOT-23       | DBV             | 5    | 1000 | 178.0              | 8.4                | 3.2     | 3.2     | 1.4     | 4.0     | 8.0    | Q3            |
| LP3985IM5-5.0/NOPB  | SOT-23       | DBV             | 5    | 1000 | 180.0              | 8.4                | 3.2     | 3.2     | 1.4     | 4.0     | 8.0    | Q3            |
| LP3985IM5X-2.5/NOPB | SOT-23       | DBV             | 5    | 3000 | 178.0              | 8.4                | 3.2     | 3.2     | 1.4     | 4.0     | 8.0    | Q3            |
| LP3985IM5X-2.8/NOPB | SOT-23       | DBV             | 5    | 3000 | 178.0              | 8.4                | 3.2     | 3.2     | 1.4     | 4.0     | 8.0    | Q3            |
| LP3985IM5X-285/NOPB | SOT-23       | DBV             | 5    | 3000 | 178.0              | 8.4                | 3.2     | 3.2     | 1.4     | 4.0     | 8.0    | Q3            |
| LP3985IM5X-3.0/NOPB | SOT-23       | DBV             | 5    | 3000 | 178.0              | 8.4                | 3.2     | 3.2     | 1.4     | 4.0     | 8.0    | Q3            |

| Device              | Package Type | Package Drawing | Pins | SPQ  | Reel Diameter (mm) | Reel Width W1 (mm) | A0 (mm) | B0 (mm) | K0 (mm) | P1 (mm) | W (mm) | Pin1 Quadrant |
|---------------------|--------------|-----------------|------|------|--------------------|--------------------|---------|---------|---------|---------|--------|---------------|
| LP3985IM5X-3.0/NOPB | SOT-23       | DBV             | 5    | 3000 | 180.0              | 8.4                | 3.2     | 3.2     | 1.4     | 4.0     | 8.0    | Q3            |
| LP3985IM5X-3.3/NOPB | SOT-23       | DBV             | 5    | 3000 | 178.0              | 8.4                | 3.2     | 3.2     | 1.4     | 4.0     | 8.0    | Q3            |
| LP3985IM5X-4.7/NOPB | SOT-23       | DBV             | 5    | 3000 | 178.0              | 8.4                | 3.2     | 3.2     | 1.4     | 4.0     | 8.0    | Q3            |
| LP3985IM5X-5.0/NOPB | SOT-23       | DBV             | 5    | 3000 | 178.0              | 8.4                | 3.2     | 3.2     | 1.4     | 4.0     | 8.0    | Q3            |
| LP3985ITL-2.5/NOPB  | DSBGA        | YZR             | 5    | 250  | 178.0              | 8.4                | 1.09    | 1.55    | 0.76    | 4.0     | 8.0    | Q1            |
| LP3985ITL-2.6/NOPB  | DSBGA        | YZR             | 5    | 250  | 178.0              | 8.4                | 1.09    | 1.55    | 0.76    | 4.0     | 8.0    | Q1            |
| LP3985ITL-2.7/NOPB  | DSBGA        | YZR             | 5    | 250  | 178.0              | 8.4                | 1.09    | 1.55    | 0.76    | 4.0     | 8.0    | Q1            |
| LP3985ITL-2.8/NOPB  | DSBGA        | YZR             | 5    | 250  | 178.0              | 8.4                | 1.09    | 1.55    | 0.76    | 4.0     | 8.0    | Q1            |
| LP3985ITL-2.9/NOPB  | DSBGA        | YZR             | 5    | 250  | 178.0              | 8.4                | 1.09    | 1.55    | 0.76    | 4.0     | 8.0    | Q1            |
| LP3985ITL-285/NOPB  | DSBGA        | YZR             | 5    | 250  | 178.0              | 8.4                | 1.09    | 1.55    | 0.76    | 4.0     | 8.0    | Q1            |
| LP3985ITL-3.0/NOPB  | DSBGA        | YZR             | 5    | 250  | 178.0              | 8.4                | 1.09    | 1.55    | 0.76    | 4.0     | 8.0    | Q1            |
| LP3985ITL-3.1/NOPB  | DSBGA        | YZR             | 5    | 250  | 178.0              | 8.4                | 1.09    | 1.55    | 0.76    | 4.0     | 8.0    | Q1            |
| LP3985ITL-3.3/NOPB  | DSBGA        | YZR             | 5    | 250  | 178.0              | 8.4                | 1.09    | 1.55    | 0.76    | 4.0     | 8.0    | Q1            |
| LP3985ITL-4.8/NOPB  | DSBGA        | YZR             | 5    | 250  | 178.0              | 8.4                | 1.09    | 1.55    | 0.76    | 4.0     | 8.0    | Q1            |
| LP3985ITL-5.0/NOPB  | DSBGA        | YZR             | 5    | 250  | 178.0              | 8.4                | 1.09    | 1.55    | 0.76    | 4.0     | 8.0    | Q1            |
| LP3985ITLX-2.5/NOPB | DSBGA        | YZR             | 5    | 3000 | 178.0              | 8.4                | 1.09    | 1.55    | 0.76    | 4.0     | 8.0    | Q1            |
| LP3985ITLX-2.7/NOPB | DSBGA        | YZR             | 5    | 3000 | 178.0              | 8.4                | 1.09    | 1.55    | 0.76    | 4.0     | 8.0    | Q1            |
| LP3985ITLX-2.8/NOPB | DSBGA        | YZR             | 5    | 3000 | 178.0              | 8.4                | 1.09    | 1.55    | 0.76    | 4.0     | 8.0    | Q1            |
| LP3985ITLX-285/NOPB | DSBGA        | YZR             | 5    | 3000 | 178.0              | 8.4                | 1.09    | 1.55    | 0.76    | 4.0     | 8.0    | Q1            |
| LP3985ITLX-3.0/NOPB | DSBGA        | YZR             | 5    | 3000 | 178.0              | 8.4                | 1.09    | 1.55    | 0.76    | 4.0     | 8.0    | Q1            |
| LP3985ITLX-3.1/NOPB | DSBGA        | YZR             | 5    | 3000 | 178.0              | 8.4                | 1.09    | 1.55    | 0.76    | 4.0     | 8.0    | Q1            |
| LP3985ITLX-3.3/NOPB | DSBGA        | YZR             | 5    | 3000 | 178.0              | 8.4                | 1.09    | 1.55    | 0.76    | 4.0     | 8.0    | Q1            |
| LP3985ITLX-5.0/NOPB | DSBGA        | YZR             | 5    | 3000 | 178.0              | 8.4                | 1.09    | 1.55    | 0.76    | 4.0     | 8.0    | Q1            |

## TAPE AND REEL BOX DIMENSIONS



\*All dimensions are nominal

| Device              | Package Type | Package Drawing | Pins | SPQ  | Length (mm) | Width (mm) | Height (mm) |
|---------------------|--------------|-----------------|------|------|-------------|------------|-------------|
| LP3985IM5-2.5/NOPB  | SOT-23       | DBV             | 5    | 1000 | 208.0       | 191.0      | 35.0        |
| LP3985IM5-2.7/NOPB  | SOT-23       | DBV             | 5    | 1000 | 208.0       | 191.0      | 35.0        |
| LP3985IM5-2.8/NOPB  | SOT-23       | DBV             | 5    | 1000 | 208.0       | 191.0      | 35.0        |
| LP3985IM5-2.9/NOPB  | SOT-23       | DBV             | 5    | 1000 | 208.0       | 191.0      | 35.0        |
| LP3985IM5-3.0/NOPB  | SOT-23       | DBV             | 5    | 1000 | 210.0       | 185.0      | 35.0        |
| LP3985IM5-3.0/NOPB  | SOT-23       | DBV             | 5    | 1000 | 208.0       | 191.0      | 35.0        |
| LP3985IM5-3.2/NOPB  | SOT-23       | DBV             | 5    | 1000 | 208.0       | 191.0      | 35.0        |
| LP3985IM5-3.3/NOPB  | SOT-23       | DBV             | 5    | 1000 | 210.0       | 185.0      | 35.0        |
| LP3985IM5-3.3/NOPB  | SOT-23       | DBV             | 5    | 1000 | 208.0       | 191.0      | 35.0        |
| LP3985IM5-4.7/NOPB  | SOT-23       | DBV             | 5    | 1000 | 208.0       | 191.0      | 35.0        |
| LP3985IM5-5.0/NOPB  | SOT-23       | DBV             | 5    | 1000 | 208.0       | 191.0      | 35.0        |
| LP3985IM5-5.0/NOPB  | SOT-23       | DBV             | 5    | 1000 | 210.0       | 185.0      | 35.0        |
| LP3985IM5X-2.5/NOPB | SOT-23       | DBV             | 5    | 3000 | 208.0       | 191.0      | 35.0        |
| LP3985IM5X-2.8/NOPB | SOT-23       | DBV             | 5    | 3000 | 208.0       | 191.0      | 35.0        |
| LP3985IM5X-285/NOPB | SOT-23       | DBV             | 5    | 3000 | 208.0       | 191.0      | 35.0        |
| LP3985IM5X-3.0/NOPB | SOT-23       | DBV             | 5    | 3000 | 208.0       | 191.0      | 35.0        |
| LP3985IM5X-3.0/NOPB | SOT-23       | DBV             | 5    | 3000 | 210.0       | 185.0      | 35.0        |
| LP3985IM5X-3.3/NOPB | SOT-23       | DBV             | 5    | 3000 | 208.0       | 191.0      | 35.0        |

| Device              | Package Type | Package Drawing | Pins | SPQ  | Length (mm) | Width (mm) | Height (mm) |
|---------------------|--------------|-----------------|------|------|-------------|------------|-------------|
| LP3985IM5X-4.7/NOPB | SOT-23       | DBV             | 5    | 3000 | 208.0       | 191.0      | 35.0        |
| LP3985IM5X-5.0/NOPB | SOT-23       | DBV             | 5    | 3000 | 208.0       | 191.0      | 35.0        |
| LP3985ITL-2.5/NOPB  | DSBGA        | YZR             | 5    | 250  | 208.0       | 191.0      | 35.0        |
| LP3985ITL-2.6/NOPB  | DSBGA        | YZR             | 5    | 250  | 208.0       | 191.0      | 35.0        |
| LP3985ITL-2.7/NOPB  | DSBGA        | YZR             | 5    | 250  | 208.0       | 191.0      | 35.0        |
| LP3985ITL-2.8/NOPB  | DSBGA        | YZR             | 5    | 250  | 208.0       | 191.0      | 35.0        |
| LP3985ITL-2.9/NOPB  | DSBGA        | YZR             | 5    | 250  | 208.0       | 191.0      | 35.0        |
| LP3985ITL-285/NOPB  | DSBGA        | YZR             | 5    | 250  | 208.0       | 191.0      | 35.0        |
| LP3985ITL-3.0/NOPB  | DSBGA        | YZR             | 5    | 250  | 208.0       | 191.0      | 35.0        |
| LP3985ITL-3.1/NOPB  | DSBGA        | YZR             | 5    | 250  | 208.0       | 191.0      | 35.0        |
| LP3985ITL-3.3/NOPB  | DSBGA        | YZR             | 5    | 250  | 208.0       | 191.0      | 35.0        |
| LP3985ITL-4.8/NOPB  | DSBGA        | YZR             | 5    | 250  | 208.0       | 191.0      | 35.0        |
| LP3985ITL-5.0/NOPB  | DSBGA        | YZR             | 5    | 250  | 208.0       | 191.0      | 35.0        |
| LP3985ITLX-2.5/NOPB | DSBGA        | YZR             | 5    | 3000 | 208.0       | 191.0      | 35.0        |
| LP3985ITLX-2.7/NOPB | DSBGA        | YZR             | 5    | 3000 | 208.0       | 191.0      | 35.0        |
| LP3985ITLX-2.8/NOPB | DSBGA        | YZR             | 5    | 3000 | 208.0       | 191.0      | 35.0        |
| LP3985ITLX-285/NOPB | DSBGA        | YZR             | 5    | 3000 | 208.0       | 191.0      | 35.0        |
| LP3985ITLX-3.0/NOPB | DSBGA        | YZR             | 5    | 3000 | 208.0       | 191.0      | 35.0        |
| LP3985ITLX-3.1/NOPB | DSBGA        | YZR             | 5    | 3000 | 208.0       | 191.0      | 35.0        |
| LP3985ITLX-3.3/NOPB | DSBGA        | YZR             | 5    | 3000 | 208.0       | 191.0      | 35.0        |
| LP3985ITLX-5.0/NOPB | DSBGA        | YZR             | 5    | 3000 | 208.0       | 191.0      | 35.0        |



## SOT-23 - 1.45 mm max height

## SMALL OUTLINE TRANSISTOR




1. All linear dimensions are in millimeters. Any dimensions in parenthesis are for reference only. Dimensioning and tolerancing per ASME Y14.5M.
2. This drawing is subject to change without notice.
3. Reference JEDEC MO-178.
4. Body dimensions do not include mold flash, protrusions, or gate burrs. Mold flash, protrusions, or gate burrs shall not exceed 0.25 mm per side.
5. Support pin may differ or may not be present.

# EXAMPLE BOARD LAYOUT


DBV0005A

SOT-23 - 1.45 mm max height

SMALL OUTLINE TRANSISTOR



LAND PATTERN EXAMPLE  
EXPOSED METAL SHOWN  
SCALE:15X



SOLDER MASK DETAILS

4214839/K 08/2024

NOTES: (continued)


6. Publication IPC-7351 may have alternate designs.
7. Solder mask tolerances between and around signal pads can vary based on board fabrication site.

## EXAMPLE STENCIL DESIGN

DBV0005A

SOT-23 - 1.45 mm max height

SMALL OUTLINE TRANSISTOR




SOLDER PASTE EXAMPLE  
BASED ON 0.125 mm THICK STENCIL  
SCALE:15X

4214839/K 08/2024

NOTES: (continued)




8. Laser cutting apertures with trapezoidal walls and rounded corners may offer better paste release. IPC-7525 may have alternate design recommendations.
9. Board assembly site may have different recommendations for stencil design.

YZR0005



DIMENSIONS ARE IN MILLIMETERS  
DIMENSIONS IN ( ) FOR REFERENCE ONLY

LAND PATTERN RECOMMENDATION



TLA05XXX (Rev C)

D: Max = 1.502 mm, Min = 1.441 mm

E: Max = 1.045 mm, Min = 0.984 mm

4215043/A 12/12

NOTES: A. All linear dimensions are in millimeters. Dimensioning and tolerancing per ASME Y14.5M-1994.  
B. This drawing is subject to change without notice.

## IMPORTANT NOTICE AND DISCLAIMER

TI PROVIDES TECHNICAL AND RELIABILITY DATA (INCLUDING DATA SHEETS), DESIGN RESOURCES (INCLUDING REFERENCE DESIGNS), APPLICATION OR OTHER DESIGN ADVICE, WEB TOOLS, SAFETY INFORMATION, AND OTHER RESOURCES "AS IS" AND WITH ALL FAULTS, AND DISCLAIMS ALL WARRANTIES, EXPRESS AND IMPLIED, INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR NON-INFRINGEMENT OF THIRD PARTY INTELLECTUAL PROPERTY RIGHTS.

These resources are intended for skilled developers designing with TI products. You are solely responsible for (1) selecting the appropriate TI products for your application, (2) designing, validating and testing your application, and (3) ensuring your application meets applicable standards, and any other safety, security, regulatory or other requirements.

These resources are subject to change without notice. TI grants you permission to use these resources only for development of an application that uses the TI products described in the resource. Other reproduction and display of these resources is prohibited. No license is granted to any other TI intellectual property right or to any third party intellectual property right. TI disclaims responsibility for, and you will fully indemnify TI and its representatives against, any claims, damages, costs, losses, and liabilities arising out of your use of these resources.

TI's products are provided subject to [TI's Terms of Sale](#) or other applicable terms available either on [ti.com](https://www.ti.com) or provided in conjunction with such TI products. TI's provision of these resources does not expand or otherwise alter TI's applicable warranties or warranty disclaimers for TI products.

TI objects to and rejects any additional or different terms you may have proposed.

Mailing Address: Texas Instruments, Post Office Box 655303, Dallas, Texas 75265  
Copyright © 2025, Texas Instruments Incorporated