

y	0	0	0	0	0	0	0	0	0	0				0	0	0	0	0	0	0	0	0	0	0		
h	8	8	8	8	8	8	8	8	8	8	1	1	8	8	1	1	8	8	1	1	8	8	1	1		
g	8	8	8	8	8	8	8	8	8	1	1	8	8	1	1	8	8	1	1	8	8	1	1	8	8	
f	8	F	F	8	8	F	F	8	8	F	F	1	1	F	F	1	1	F	F	1	1	F	F	1	1	
e	8	8	8	8	8	8	8	8	8	1	1	8	8	1	1	8	8	1	1	8	8	1	1	8	8	
d	8	8	8	8	8	8	8	8	8	8	1	1	8	8	1	1	8	8	1	1	8	8	1	1	8	8
c	F	8	8	F	F	8	8	F	F	1	1	F	F	1	1	F	F	1	1	F	F	1	1	F	F	
b	8	8	8	8	8	8	8	8	8	8	1	1	8	8	1	1	8	8	1	1	8	8	1	1	8	8
a	8	8	8	8	8	8	8	8	8	1	1	8	8	1	1	8	8	1	1	8	8	1	1	8	8	
z	0	0	0	0	0	0	0	0	0	0				0	0	0	0	0	0	0	0	0	0	0	0	
pos	0 1					0 5					1 0					1 5					2 0					2 5

SEATING PLANE
FOR CONNECTOR

A diagram of a rectangular mesh. The horizontal dimension is labeled 480 and the vertical dimension is labeled 140. The mesh consists of a grid of small circles. A dashed line runs horizontally across the top of the grid, just below the 480 dimension line. A solid line runs horizontally across the bottom of the grid, just above the 140 dimension line. A vertical dashed line runs down the left side of the grid, just to the right of the 480 dimension line. A vertical solid line runs down the right side of the grid, just to the left of the 140 dimension line. The grid is composed of 12 columns and 11 rows of circles.

Technical drawing of a connector assembly, showing top, side, and detail views with dimensions and callouts.

Top View:

- Overall width: 48.0
- Pin pitch: $2.00 \pm 0.05 (24X)$
- Callouts: NOTA 5, NOTA 6

Side View:

- Overall height: 18.0
- Pin height: $2.00 \pm 0.05 (9X)$
- Overall length: 50.0 MAX.


Detail View (Note 3):

- Pin pitch: 1.70 ± 0.10
- Pin height: 13.45 ± 0.10
- Pin length: 3.00 ± 0.0
- Callout: note 7

HM2P95PNF110_

PLATING CODE (DIGIT 13 AND 14)
(REF DWG No. BS.C.201844.003)

1. THIS PRODUCT IS CSA APPROVED.
2. THIS PRODUCT IS UL RECOGNIZED.
3. MEASURED AT THE BOTTOM.
4. MATERIAL CONTACT: PHOSPHORBRONZE
HOUSING: CREAM WHITE GLASSFILLED
POLYESTER UL-94V0
5. CONNECTOR PRINTED WITH P/N AND DATE CODE.
6. FOR ACTUAL CONTACT LOADINGS, SEE LOADING PATTERN
MATING SIDE.
7. SHAPE OF CONNECTOR HOUSING CAN ALTER
DEPENDING ON PRODUCTION LOCATION.
8. THE PRODUCT (LF) MEETS EUROPEAN UNION DIRECTIVES AND OTHER COUNTRY
REGULATIONS AS DESCRIBED IN GS-22-008
9. FOR RECOMMENDED PTH DIMENSIONS REFER DRAWING : BS.A .201572.001

1DEC ± 0.2 2DEC ± 0.1 ANGLES $\pm 1^\circ$	APPR.	DATE	SIGN.	LOADING PATTERN OVERVIEW (8+2 ROW)		
	DRAFT	2000-05-09	M.Fret	CAT. No. HM2P95PNF110----		
	CHECKED				www.fciconnect.com	SCALE
	PROD. MGR.					
WE RESERVE THE RIGHT TO CHANGE DIMENSIONS OR REQUIREMENTS WITHOUT PRIOR NOTICE.	PR. ENG. MGR.					
ALL DIMENSIONS IN MM 	REFERENCES			BS, C , 202175, 169		C
				DRAWING No.		CUSTOMER DRAWING
						REVISION