





Features

- High efficiency and low standby power.
- 30% Miniaturization from previous models.
- 100% load at 50°C, suitable for industrial equipment.
- 5 Years warranty (conditions applied)

Applications



Model name identification method



Conformity to RoHS Directive

This means that, in conformity with EU Directive 2002/95/EC, lead, cadmium, mercury, hexavalent chromium, and specific bromine-based flame retardants, PBB and PBDE, have not been used, except for exempted applications.

Product line up

Model	VS50E 50W		VS75E 75W		VS100E 100W		VS150E 150W	
	Output Current	Efficiency(Typ)	Output Current	Efficiency(Typ)	Output Current	Efficiency(Typ)	Output Current	Efficiency(Typ)
3.3V	10A	80%	15A	80%	20A	80%	30A	80%
5V	10A	85%	15A	85%	20A	85%	30A	86%
12V	4.3A	85%	6.3A	85%	8.5A	85%	12.5A	87%
15V	3.5A	85%	5.0A	85%	7.0A	85%	10.0A	87%
24V	2.5A	85%	3.2A	86%	4.3A	86%	6.3A	87%
48V	1.3A	87%	1.6A	87%	2.2A	87%	3.2A	88%

Option line up

Model	VS50E 50W				VS75E 75W				VS100E 100W				VS150E 150W			
	/A	/L	/CO2	/FV	/A	/L	/CO2	/FV	/A	/L	/CO2	/FV	/A	/L	/CO2	/FV
3.3V	○	○	○	-	○	○	○	-	○	○	○	-	○	○	○	-
5V	○	○	○	-	○	○	○	-	○	○	○	-	○	○	○	-
12V	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○
15V	○	○	○	-	○	○	○	-	○	○	○	-	○	○	○	-
24V	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○
48V	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○

VS50E Specifications

ITEMS/UNITS			MODEL	VS50E-3	VS50E-5	VS50E-12	VS50E-15	VS50E-24	VS50E-48
Input	Voltage Range	(*2)	V	AC 85 - 132					
	Frequency	(*2)	Hz	47 - 63					
	Efficiency (Typ)	(*1)	%	80	85				87
	Current (Typ)	(*1)	A	0.9	1.1			1.3	
	Inrush Current (Typ)	(*1)(*11)	A	30 at Cold Start					
	Leakage Current	(*8)	mA	Less than 0.5					
Output	Nominal Voltage		VDC	3.3	5	12	15	24	48
	Maximum Current		A	10		4.3	3.5	2.5	1.3
	Maximum Power		W	33.0	50.0	51.6	52.5	60.0	62.4
	Maximum Line Regulation	(*3)(*4)	mV	20		48	60	96	192
	Maximum Load Regulation	(*3)(*5)	mV	40		96	120	150	240
	Temperature Coefficient	(*3)		Less than 0.02% / °C					
	Maximum Ripple & Noise(0≤Ta≤70°C)	(*3)	mVp-p	120		150			200
	Maximum Ripple & Noise(-10≤Ta<0°C)	(*3)	mVp-p	160		180			240
	Hold-up Time (Typ)	(*1)	ms	20					
	Voltage Adjustable Range	(*12)	VDC	2.97 - 3.63	4.5 - 5.5	10.8 - 13.2	13.5 - 16.5	21.6 - 26.4	43.2 - 52.8
Function	Over Current Protection	(*6)	A	10.5 -		4.51 -	3.67 -	2.62 -	1.36 -
	Over Voltage Protection	(*7)	VDC	3.80 - 4.46	5.75 - 6.75	13.8 - 16.2	17.3 - 20.3	27.6 - 32.4	55.2 - 64.8
	Parallel Operation			-					
	Series Operation			Possible					
Environment	Operating Temperature	(*9)	°C	Convection : -10 - +70 (-10 - +50:100%, +60:70%, +70:20%)					
	Storage Temperature		°C	-30 - +85					
	Operating Humidity		%RH	30 - 90 (No dewdrop)					
	Storage Humidity		%RH	10 - 95 (No dewdrop)					
	Vibration			At no operating, 10 - 55Hz (Sweep for 1min) 19.6m/s² Constant, X,Y,Z 1hour each.					
	Shock			Less than 196.1m/s²					
	Cooling			Convection Cooling					
Isolation	Withstand Voltage			Input - FG : 2kVAC (10mA), Input - Output : 2kVAC (10mA) Output - FG : 500VAC (20mA) for 1min					
	Isolation Resistance			More than 100MΩ at 25°C and 70%RH Output - FG : 500VDC					
Standards	Safety Standards			Designed to meet UL60950-1, CSA60950-1, EN60950-1, EN50178(OV II), DENAN (Section 2).					
	EMI			Designed to meet EN55011/EN55022-B, FCC-B, VCCI-B					
	Immunity			Designed to meet IEC61000-4-2(Level 2,3), -3(Level 3), -4(Level 3), -5(Level 2,3), -6(Level 3), -8(Level 4), -11					
Mechanical	Weight (Typ)		g	150					
	Size (W×H×D)	(*10)	mm	50 x 23 x 132 (Refer to Outline Drawing)					

*Read instruction manual carefully, before using the power supply unit.

(*1) At 100VAC, Ta=25°C, nominal output voltage and maximum output power.

(*2) For cases where conformance to various safety specs (UL, CSA, EN) are required, to be described as 100 - 120VAC(50/60Hz).

(*3) Please refer to Fig. A for measurement of line & load regulation and ripple voltage.

(*4) 85 - 132VAC, constant load.

(*5) No load-Full load, constant input voltage.

(*6) Fold back current limit with automatic recovery. Avoid to operate at over load or short circuit condition for more than 30seconds.

(*7) OVP circuit will shut the output down, manual reset (Re power on).

(*8) Measured by the each measuring method of UL, CSA, EN and DENAN(at 60Hz), Ta=25°C.

(*9) Ratings - Derating at standard mounting. Refer to output derating curve(A239-01-02_).

- Load (%) is percent of maximum output power or maximum output current, whichever is greater.


(*10) Not include lead length on solder side.

(*11) Inrush Current suppressors type. Limits vary according to ambient temperature and in case of re-entry.

(*12) /FV option is for fixed output voltage.

Outline Drawing

VS50E Standard Specification, /CO2, /FV



CONNECTOR USED

PART DESCRIPTION	PART NAME	MANUFACT	QTY
PIN HEADER (INPUT SIDE CN1)	B3P5-VH(LF)(SN)	J.S.T.	1
PIN HEADER (OUTPUT SIDE CN51)	B4P-VH(LF)(SN)	J.S.T.	1

* OUTPUT CURRENT OF EACH CONNECTOR PIN MUST BE LESS THAN 5A.


MATCHING HOUSINGS & PIN.(NOT INCLUDED WITH THE PRODUCT.)

PART DESCRIPTION	PART NAME	MANUFACT	QTY
SOCKET HOUSING (CN1)	VHR-5N	J.S.T.	1
SOCKET HOUSING (CN51)	VHR-4N	J.S.T.	1
Terminal pin	SVH-21T-P1.1 BVH-21T-P1.1	J.S.T.	7
HAND CRIMPING TOOL	YC-160R	J.S.T.	-


OPEN HARNESS

	PART NAME
INPUT	HA-2-IN
OUTPUT	HA-3-OU

VS50E/A




VS50E/L





Output Derating


VS50E Standard Specification, /CO2, /FV, /L
VS50E-3, -5, -12, -15, -24





VS50E-48



VS50E/A
VS50E-3/A, -5/A, -12/A, -15/A, -24/A



VS50E-48/A



VS75E Specifications

ITEMS/UNITS			MODEL	VS75E-3	VS75E-5	VS75E-12	VS75E-15	VS75E-24	VS75E-48
Input	Voltage Range	(*2)	V	AC 85 - 132					
	Frequency	(*2)	Hz	47 - 63					
	Efficiency (Typ)	(*1)	%	80	85			86	87
	Current (Typ)	(*1)	A	1.1	1.6				
	Inrush Current (Typ)	(*1)(*12)	A	30A at Cold Start					
	Leakage Current	(*9)	mA	Less than 0.5					
Output	Nominal Voltage		VDC	3.3	5	12	15	24	48
	Maximum Current		A	15		6.3	5.0	3.2	1.6
	Maximum Power		W	49.5	75.0	75.6	75.0	76.8	
	Maximum Line Regulation	(*3)(*5)	mV	20		48	60	96	192
	Maximum Load Regulation	(*3)(*6)	mV	40		96	120	150	240
	Temperature Coefficient	(*3)		Less than 0.02% / °C					
	Maximum Ripple & Noise(0≤Ta≤70°C)	(*3)(*4)	mVp-p	120		150			200
	Maximum Ripple & Noise(-10≤Ta<0°C)	(*3)(*4)	mVp-p	160		180			240
	Hold-up Time (Typ)	(*1)	ms	20					
	Voltage Adjustable Range	(*13)	VDC	2.97 - 3.63	4.5 - 5.5	10.8 - 13.2	13.5 - 16.5	21.6 - 26.4	43.2 - 52.8
Function	Over Current Protection	(*7)	A	15.7 -		6.61 -	5.25 -	3.36 -	1.68 -
	Over Voltage Protection	(*8)	VDC	3.80 - 4.46	5.75 - 6.75	13.8 - 16.2	17.3 - 20.3	27.6 - 32.4	55.2 - 64.8
	Parallel Operation			-					
	Series Operation			Possible					
Environment	Operating Temperature	(*10)	°C	Convection : -10 - +70 (-10 - +50:100%, +60:70%, +70:20%)					
	Storage Temperature		°C	-30 - +85					
	Operating Humidity		%RH	30 - 90 (No dewdrop)					
	Storage Humidity		%RH	10 - 95 (No dewdrop)					
	Vibration			At no operating, 10 - 55Hz (Sweep for 1min) 19.6m/s² Constant, X, Y, Z 1hour each.					
	Shock			Less than 196.1m/s²					
	Cooling			Convection Cooling					
Isolation	Withstand Voltage			Input - FG : 2kVAC (10mA), Input - Output : 2kVAC (10mA) Output - FG : 500VAC (20mA) for 1min					
	Isolation Resistance			More than 100MΩ at 25°C and 70%RH Output - FG : 500VDC					
Standards	Safety Standards			Designed to meet UL60950-1, CSA60950-1, EN60950-1, EN50178(OV II), DENAN (Section 2).					
	EMI			Designed to meet EN55011/EN55022-B, FCC-B, VCCI-B					
	Immunity			Designed to meet IEC61000-4-2(Level 2,3), -3(Level 3), -4(Level 3), -5(Level 2,3), -6(Level 3), -8(Level 4), -11					
Mechanical	Weight (Typ)		g	200					
	Size (W×H×D)	(*11)	mm	50 x 29 x 150 (Refer to Outline Drawing)					

*Read instruction manual carefully, before using the power supply unit.

(*1) At 100VAC, Ta=25°C, nominal output voltage and maximum output power.

(*2) For cases where conformance to various safety specs (UL, CSA, EN) are required, to be described as 100 - 120VAC(50/60Hz).

(*3) Please refer to Fig. A for measurement of line & load regulation and ripple voltage.

(*4) For start up at low ambient temperature and low input voltage, output ripple noise might not meet specification.

However, there is no overshoot at start up and output ripple noise specification can be met after one second.

(*5) 85 - 132VAC, constant load.

(*6) No load-Full load, constant input voltage.

(*7) 3.3, 5V model : Constant current limit and hiccup with automatic recovery.

12 - 48V model : Constant current limit with automatic recovery.

Avoid to operate at over load or short circuit condition for more than 30seconds.

(*8) OVP circuit will shut the output down, manual reset (Re power on).

(*9) Measured by the each measuring method of UL, CSA, EN and DENAN (at 60Hz), Ta=25°C.

(*10) Ratings

- Derating at standard mounting. Refer to output derating curve(A240-01-02_).

- Load (%) is percent of maximum output power or maximum output current, whichever is greater.


(*11) Not include lead length on solder side.

(*12) Inrush Current suppressors type. Limits vary according to ambient temperature and in case of re-entry.

(*13) /FV option is for fixed output voltage.

Outline Drawing

VS75E Standard Specification, /CO2, /FV



CONNECTOR USED

PART DESCRIPTION	PART NAME	MANUFACT	QTY
PIN HEADER (INPUT SIDE CN1)	B3P5-VH(LF)(SN)	J.S.T.	1
PIN HEADER(OUTPUT SIDE CN51)	B6P-VH(LF)(SN)	J.S.T.	1

* OUTPUT CURRENT OF EACH CONNECTOR PIN MUST BE LESS THAN 5A.


MATCHING HOUSINGS & PIN.(NOT INCLUDED WITH THE PRODUCT.)

PART DESCRIPTION	PART NAME	MANUFACT	QTY
SOCKET HOUSING (CN1)	VHR-5N	J.S.T.	1
SOCKET HOUSING (CN51)	VHR-6N	J.S.T.	1
Terminal pin	SVH-21T-P1.1 BVH-21T-P1.1	J.S.T.	9
HAND CRIMPING TOOL	YC-160R	J.S.T.	-


OPEN HARNESS

	PART NAME
INPUT	HA-2-IN
OUTPUT	HA-4-OU

VS75E/A




VS75E/L





Output Derating


VS75EStandard Specification, /CO2, /FV, /L




VS75E/A




MOUNTING A
(STANDARD MOUNTING)




MOUNTING B




MOUNTING C



MOUNTING D



MOUNTING E



DON'T USE

VS100E Specifications

ITEMS/UNITS			MODEL	VS100E-3	VS100E-5	VS100E-12	VS100E-15	VS100E-24	VS100E-48
Input	Voltage Range	(*2)	V	AC 85 - 132 or DC 110 - 175					
	Frequency	(*2)	Hz	47 - 63					
	Efficiency (Typ)	(*1)	%	80	85			86	87
	Current (Typ)	(*1)	A	1.6	2.1				
	Inrush Current (Typ)	(*1)(*12)	A	30A at Cold Start					
	Leakage Current	(*9)	mA	Less than 0.5					
Output	Nominal Voltage		VDC	3.3	5	12	15	24	48
	Maximum Current		A	20		8.5	7.0	4.3	2.2
	Maximum Power		W	66.0	100.0	102.0	105.0	103.2	105.6
	Maximum Line Regulation	(*3)(*5)	mV	20		48	60	96	192
	Maximum Load Regulation	(*3)(*6)	mV	40		96	120	150	240
	Temperature Coefficient	(*3)		Less than 0.02% / °C					
	Maximum Ripple & Noise(0≤Ta≤70°C)	(*3)(*4)	mVp-p	120		150			200
	Maximum Ripple & Noise(-10≤Ta<0°C)	(*3)(*4)	mVp-p	160		180			240
	Hold-up Time (Typ)	(*1)	ms	20					
	Voltage Adjustable Range	(*13)	VDC	2.97 - 3.63	4.5 - 5.5	10.8 - 13.2	13.5 - 16.5	21.6 - 26.4	43.2 - 52.8
Function	Over Current Protection	(*7)	A	21.0 -		8.92 -	7.35 -	4.51 -	2.31 -
	Over Voltage Protection	(*8)	VDC	3.80 - 4.46	5.75 - 6.75	13.8 - 16.2	17.3 - 20.3	27.6 - 32.4	55.2 - 64.8
	Parallel Operation			-					
	Series Operation			Possible					
Environment	Operating Temperature	(*10)	°C	Convection : -10 - +70 (-10 - +50:100%, +60:70%, +70:20%)					
	Storage Temperature		°C	-30 - +85					
	Operating Humidity		%RH	30 - 90 (No dewdrop)					
	Storage Humidity		%RH	10 - 95 (No dewdrop)					
	Vibration			At no operating, 10 - 55Hz (Sweep for 1min) 19.6m/s² Constant, X,Y,Z 1hour each.					
	Shock			Less than 196.1m/s²					
	Cooling			Convection Cooling					
Isolation	Withstand Voltage			Input - FG : 2kVAC (10mA), Input - Output : 2kVAC (10mA) Output - FG : 500VAC (20mA) for 1min					
	Isolation Resistance			More than 100MΩ at 25°C and 70%RH Output - FG : 500VDC					
Standards	Safety Standards			Designed to meet UL60950-1, CSA60950-1, EN60950-1, EN50178(OV II), DENAN (Section 2).					
	EMI			Designed to meet EN55011/EN55022-B, FCC-B, VCCI-B					
	Immunity			Designed to meet IEC61000-4-2(Level 2,3), -3(Level 3), -4(Level 3), -5(Level 2,3), -6(Level 3), -8(Level 4), -11					
Mechanical	Weight (Typ)		g	290					
	Size (W×H×D)	(*11)	mm	62 x 29 x 155 (Refer to Outline Drawing)					

*Read instruction manual carefully, before using the power supply unit.

(*1) At 100VAC, Ta=25°C, nominal output voltage and maximum output power.

(*2) For cases where conformance to various safety specs (UL, CSA, EN) are required, to be described as 100 - 120VAC(50/60Hz).

(*3) Please refer to Fig. A for measurement of line & load regulation and ripple voltage.

(*4) For start up at low ambient temperature and low input voltage, output ripple noise might not meet specification.

However, there is no overshoot at start up and output ripple noise specification can be met after one second.

(*5) 85 - 132VAC, constant load.

(*6) No load-Full load, constant input voltage.

(*7) 3.3, 5V model: Constant current limit and hiccup with automatic recovery.

12 - 48V model: Constant current limit with automatic recovery.

Avoid to operate at over load or short circuit condition for more than 30seconds.

(*8) OVP circuit will shut the output down, manual reset (Re power on).

(*9) Measured by the each measuring method of UL, CSA, EN and DENAN(at 60Hz), Ta=25°C.

(*10) Ratings

- Derating at standard mounting. Refer to output derating curve(A241-01-02_).


- Load (%) is percent of maximum output power or maximum output current, whichever is greater.

(*11) Not include lead length on solder side.

(*12) Inrush Current suppressors type. Limits vary according to ambient temperature and in case of re-entry.

(*13) /FV option is for fixed output voltage.

VS100E Standard Specification, /CO2, /FV




OPEN HARNESS

	PART NAME
INPUT	HA-2-IN
OUTPUT	HA-5-OU

The drawing shows the PCB layout for the ADXL055. The top view includes dimensions for the overall size (173±0.5 x 45±1 mm), mounting holes (2-φ4.5), and component locations (NAME PLATE, INPUT, OUTPUT, VRS1, CN51). The bottom view shows dimensions for the overall size (173±0.5 x 45±1 mm), mounting holes (2-φ4.5), and component locations (VRS1, CN51, R2.25, 4-M4).

Ta (°C)	Mounting A, B Load (%)	Mounting C, D Load (%)	Mounting E Load (%)
-10	100	100	100
30	100	100	100
35	100	70	100
40	100	70	100
45	70	70	70
50	40	0	70
55	0	0	40
60	0	0	20



DON'T USE

VS150E Specifications

ITEMS/UNITS			MODEL	VS150E-3	VS150E-5	VS150E-12	VS150E-15	VS150E-24	VS150E-48
Input	Voltage Range	(*2)	V	AC 85 - 132 or DC 110 - 175					
	Frequency	(*2)	Hz	47 - 63					
	Efficiency (Typ)	(*1)	%	80	86	87			88
	Current (Typ)	(*1)	A	2.4	3.2				
	Inrush Current (Typ)	(*1)(*12)	A	30A at Cold Start					
	Leakage Current	(*9)	mA	Less than 0.5					
Output	Nominal Voltage		VDC	3.3	5	12	15	24	48
	Maximum Current		A	30		12.5	10.0	6.3	3.2
	Maximum Power		W	99.0	150.0			151.2	153.6
	Maximum Line Regulation	(*3)(*5)	mV	20		48	60	96	192
	Maximum Load Regulation	(*3)(*6)	mV	40		96	120	150	240
	Temperature Coefficient	(*3)		Less than 0.02% / °C					
	Maximum Ripple & Noise(0≤Ta≤70°C)	(*3)(*4)	mVp-p	120		150			200
	Maximum Ripple & Noise(-10≤Ta<0°C)	(*3)(*4)	mVp-p	160		180			240
	Hold-up Time (Typ)	(*1)	ms	20					
	Voltage Adjustable Range	(*13)	VDC	2.97 - 3.63	4.5 - 5.5	10.8 - 13.2	13.5 - 16.5	21.6 - 26.4	43.2 - 52.8
Function	Over Current Protection	(*7)	A	31.5 -		13.12 -	10.5 -	6.61 -	3.36 -
	Over Voltage Protection	(*8)	VDC	3.80 - 4.46	5.75 - 6.75	13.8 - 16.2	17.3 - 20.3	27.6 - 32.4	55.2 - 64.8
	Parallel Operation			-					
	Series Operation			Possible					
Environment	Operating Temperature	(*10)	°C	Convection : -10 - +70 (-10 - +50:100%, +60:70%, +70:20%)					
	Storage Temperature		°C	-30 - +85					
	Operating Humidity		%RH	30 - 90 (No dewdrop)					
	Storage Humidity		%RH	10 - 95 (No dewdrop)					
	Vibration			At no operating, 10 - 55Hz (Sweep for 1min) 19.6m/s² Constant, X,Y,Z 1hour each.					
	Shock			Less than 196.1m/s²					
	Cooling			Convection Cooling					
Isolation	Withstand Voltage			Input - FG : 2kVAC (10mA), Input - Output : 2kVAC (10mA) Output - FG : 500VAC (20mA) for 1min					
	Isolation Resistance			More than 100MΩ at 25°C and 70%RH Output - FG : 500VDC					
Standards	Safety Standards			Designed to meet UL60950-1, CSA60950-1, EN60950-1, EN50178(OV II), DENAN (Section 2).					
	EMI			Designed to meet EN55011/EN55022-B, FCC-B, VCCI-B					
	Immunity			Designed to meet IEC61000-4-2(Level 2,3), -3(Level 3), -4(Level 3), -5(Level 2,3), -6(Level 3), -8(Level 4), -11					
Mechanical	Weight (Typ)		g	390					
	Size (W×H×D)	(*11)	mm	75 x 34 x 160 (Refer to Outline Drawing)					

*Read instruction manual carefully, before using the power supply unit.

(*1) At 100VAC, Ta=25°C, nominal output voltage and maximum output power.

(*2) For cases where conformance to various safety specs (UL, CSA, EN) are required, to be described as 100 - 120VAC(50/60Hz).

(*3) Please refer to Fig. A for measurement of line & load regulation and ripple voltage.

(*4) For start up at low ambient temperature and low input voltage, output ripple noise might not meet specification.

However, there is no overshoot at start up and output ripple noise specification can be met after one second.

(*5) 85 - 132VAC, constant load.

(*6) No load-Full load, constant input voltage.

(*7) 3.3, 5V model: Constant current limit and hiccup with automatic recovery.

12 - 48V model: Constant current limit with automatic recovery.

Avoid to operate at over load or short circuit condition for more than 30seconds.

(*8) OVP circuit will shut the output down, manual reset (Re power on).

(*9) Measured by the each measuring method of UL, CSA, EN and DENAN(at 60Hz), Ta=25°C.

(*10) Ratings

- Derating at standard mounting. Refer to output derating curve(A242-01-02_).

- Load (%) is percent of maximum output power or maximum output current, whichever is greater.


(*11) Not include lead length on solder side.

(*12) Inrush Current suppressors type. Limits vary according to ambient temperature and in case of re-entry.

(*13) /FV option is for fixed output voltage.

Outline Drawing

VS1150E Standard Specification, /CO2, /FV



CONNECTOR USED

PART DESCRIPTION	PART NAME	MANUFACT	QTY
PIN HEADER (INPUT SIDE CN1)	B3P5-VH(LF)(SN)	J.S.T.	1
PIN HEADER(OUTPUT SIDE CN51)	B6P-VH(LF)(SN)	J.S.T.	1
PIN HEADER(OUTPUT SIDE CN52)	B7P-VH(LF)(SN)	J.S.T.	1

* OUTPUT CURRENT OF EACH CONNECTOR PIN MUST BE LESS THAN 5A.


MATCHING HOUSINGS & PIN.(NOT INCLUDED WITH THE PRODUCT.)

PART DESCRIPTION	PART NAME	MANUFACT	QTY
SOCKET HOUSING (CN1)	VHR-5N	J.S.T.	1
SOCKET HOUSING (CN51)	VHR-6N	J.S.T.	1
SOCKET HOUSING (CN52)	VHR-7N	J.S.T.	1
Terminal pin	SVH-21T-P1.1 BVH-21T-P1.1	J.S.T.	11
HAND CRIMPING TOOL	YC-160R	J.S.T.	-


OPEN HARNESS

	PART NAME
INPUT	HA-2-IN
OUTPUT	+ : HA-6-OU - : HA-7-OU

VS150E/A




VS150E/L



Output Derating

VS150E Standard Specification, /CO2, /FV, /L



VS150E/A

