

FEED-THROUGH

35 or 32mm DIN Rail

Altech "U" Series Universal Rail Mounting Standard Screw Clamp Feed through terminals are the most versatile terminals for wire-to-wire connection in control, automation, instrumentation and power distribution applications. A special design feature on the flexible foot enables easy mounting and dismounting from the DIN Rail with the help of a screwdriver.

The terminals with AEx eII EEEx eII can be used in a potentially explosive atmosphere which may occur in chemical and petrochemical industry. These terminals can be used in Class 1, Zone 0, 1 & 2 hazardous locations. These terminal blocks comply to En 500019.




COLOR BLOCKS

(other than grey standard)

When ordering please add color suffix to Cat. No.


Example: CTS2.5U-N/R

Color	Ordering Suffix
Red	R
Blue	BU
Black	BL
Orange	O
Green	G
Yellow	Y
White	W
Beige	BG
Dark Brown	DB



Warning labels available. See page 67.

* 35A with one No. 10 AWG and 40A with two No. 12 AWG wires.



Terminal Width	5 mm
Height x Length	45 x 43 mm
Stripping Length	9 mm
Insulation Material	Polyamide 6.6
Type of Connection	2 screw clamps & 1 tapped hole for cross connection
Approvals	
Wire Range	22-12 AWG 0.5-2.5 sq.mm 22-14 AWG
Voltage Rating	600 V 750 V 600 V
Current Rating	25 A 24 A 20 A
Torque	7 lb-in 0.4 Nm 7 lb-in

Terminal Block	Cat. No. CTS2.5U-N	Std. Pk. 100
End Plate	EP2.5/4UN	50
Isolation Partition	PP2.5/4UN	50
Separator Plate	SP2.5/4UN	100

DIN Rail
for ordering information refer to page 62

End Stop	CA702	50
for ordering information refer to page 63	CA802	50

Internal Jumper	2 pole	CA721/2	100
	3 pole	CA721/3	50
	4 pole	CA721/4	50
	10 pole	CA721/10	10
	100 pole	CA721/100	10

Insulated Internal Jumper	2 pole	CA741/2	100
	3 pole	CA741/3	50
	4 pole	CA741/4	50
	10 pole	CA741/10	10
	100 pole	CA741/100	10

Current Bars	2 pole	CA703/01	100
	3 pole	CA704/01	100
	4 pole	CA705/01	100
	10 pole	CA731/10	100
	10 pole (breakable)	—	—
	100 pole	CA731/100	10


Shorting Sleeve & Screw	CA 707/S/Q/01	100
-------------------------	---------------	-----

External Jumper	2 pole	CA717/2	100
	3 pole	CA717/3	100
	4 pole	CA717/4	100
	10 pole	CA717/10	25

Marking Tags	MT5	100
--------------	-----	-----

Warning Label


CTS2.5U-N



AEx eII EEEx eII



CTS4U-N



AEx eII EEEx eII



Terminal Width	5 mm
Height x Length	45 x 43 mm
Stripping Length	9 mm
Insulation Material	Polyamide 6.6
Type of Connection	2 screw clamps & 1 tapped hole for cross connection
Approvals	
Wire Range	22-10 AWG 0.5-4 sq.mm 22-10 AWG
Voltage Rating	600 V 750 V 600 V
Current Rating	35/40 A* 32 A 35/40A*
Torque	7 lb-in 0.5 Nm 7 lb-in

Terminal Block	Cat. No. CTS4U-N	Std. Pk. 100
End Plate	EP2.5/4UN	50
Isolation Partition	PP2.5/4UN	50
Separator Plate	SP2.5/4UN	100

DIN Rail
for ordering information refer to page 62

End Stop	CA702	50
for ordering information refer to page 63	CA802	50

Internal Jumper	2 pole	CA722/2	100
	3 pole	CA722/3	50
	4 pole	CA722/4	50
	10 pole	CA722/10	10
	100 pole	CA722/100	10

Insulated Internal Jumper	2 pole	CA742/2	100
	3 pole	CA742/3	50
	4 pole	CA742/4	50
	10 pole	CA742/10	10
	100 pole	CA742/100	10

Current Bars	2 pole	CA703/1	100
	3 pole	CA704/1	100
	4 pole	CA705/1	100
	10 pole	CA732/10	100
	10 pole (breakable)	CA732/10-A	100
	100 pole	CA732/100	10

Shorting Sleeve & Screw	CA 707/S/Q/01	100
-------------------------	---------------	-----

External Jumper	2 pole	CA713/2	100
	3 pole	CA713/3	100
	4 pole	CA713/4	50
	10 pole	CA713/10	25

Marking Tags	MT6	100
--------------	-----	-----

Terminal Width	6 mm
Height x Length	45 x 43 mm
Stripping Length	9 mm
Insulation Material	Polyamide 6.6
Type of Connection	2 screw clamps & 1 tapped hole for cross connection
Approvals	
Wire Range	22-10 AWG 0.5-4 sq.mm 22-10 AWG
Voltage Rating	600 V 750 V 600 V
Current Rating	35/40 A* 32 A 35/40A*
Torque	7 lb-in 0.5 Nm 7 lb-in

Terminal Block	Cat. No. CTS4U-N	Std. Pk. 100
End Plate	EP2.5/4UN	50
Isolation Partition	PP2.5/4UN	50
Separator Plate	SP2.5/4UN	100

DIN Rail
for ordering information refer to page 62

End Stop	CA702	50
for ordering information refer to page 63	CA802	50

Internal Jumper	2 pole	CA722/2	100
	3 pole	CA722/3	50
	4 pole	CA722/4	50
	10 pole	CA722/10	10
	100 pole	CA722/100	10

Insulated Internal Jumper	2 pole	CA742/2	100
	3 pole	CA742/3	50
	4 pole	CA742/4	50
	10 pole	CA742/10	10
	100 pole	CA742/100	10




Current Bars	2 pole	CA703/1	100
	3 pole	CA704/1	100
	4 pole	CA705/1	100
	10 pole	CA732/10	100
	10 pole (breakable)	CA732/10-A	100
	100 pole	CA732/100	10

Shorting Sleeve & Screw	CA 707/S/Q/01	100
-------------------------	---------------	-----

External Jumper	2 pole	CA713/2	100
	3 pole	CA713/3	100
	4 pole	CA713/4	50
	10 pole	CA713/10	25

Marking Tags	MT6	100
--------------	-----	-----

CTS6U			CTS10U			CTS16U			CTS25U		
											
 AEx eII EEx eII 			 AEx eII EEx eII 			 AEx eII EEx eII 			 AEx eII EEx eII 		
8 mm			10 mm			12 mm			12 mm		
47 x 43 mm			47 x 43 mm			47 x 43 mm			56 x 49.5 mm		
12 mm			12 mm			16 mm			18 mm		
Polyamide 6.6			Polyamide 6.6			Polyamide 6.6			Polyamide 6.6		
2 screw clamps & 1 tapped hole for cross connection			2 screw clamps & 1 tapped hole for cross connection			2 screw clamps & 1 tapped hole for cross connection			2 screw clamps & 1 tapped hole for cross connection		
  			  			  			  		
22-8 AWG 1.5-6 sq.mm 22-8 AWG			22-6 AWG 1.5-10 sq.mm 16-6 AWG			22-6 AWG 2.5-16 sq.mm 20-4 AWG			12-2 AWG 6-25 sq.mm 14-2 AWG		
600 V 750 V 600 V			600 V 750 V 600 V			600 V 800 V 600 V			600 V 750 V 600 V		
50 A 41 A 50 A			65 A 57 A 65 A			70 A 76 A 85 A			115 A 101 A 115 A		
9 lb-in 0.8 Nm 14 lb-in			14 lb-in 1.2 Nm 14 lb-in			14 lb-in 1.2 Nm 14 lb-in			25 lb-in 2.0 Nm 25 lb-in		
Cat. No.		Std. Pk.	Cat. No.		Std. Pk.	Cat. No.		Std. Pk.	Cat. No.		Std. Pk.
CTS6U		100	CTS10U		100	CTS16U		50	CTS25U		50
EP6/10U		50	EP6/10U		50				EP25U		50
PP6/10U		50	PP6/10U		50				PP25U		50
SP6/10U		100	SP6/10U		100	SP6/10U		100			
											
CA702		50	CA702		50	CA702		50	CA702		50
CA802		50	CA802		50	CA802		50	CA802		50
CA723/2		100	CA724/2		100	CA751/2		50	CA725/2		50
CA723/3		50	CA724/3		50	CA751/3		50	CA725/3		25
CA723/4		50	CA724/4		50	CA751/4		50	CA725/4		25
CA723/10		10	CA724/10		10	CA751/10		10	CA725/10		10
CA743/2		100	CA744/2		100	CA761/2		50	CA745/2		50
CA743/3		50	CA744/3		50	CA761/3		50	CA745/3		25
CA743/4		50	CA744/4		50	CA761/4		50	CA745/4		25
CA743/10		10	CA744/10		10	CA761/10		10	CA745/10		10
CA703/2		100	CA703/3		100	CA703/8		100	CA703/4		100
CA704/2		100	CA704/3		100	CA704/8		100	CA704/4		100
CA705/2		100	CA705/3		100	CA705/8		100	CA705/4		100
CA733/10		100	CA734/10		100	CA739/10		100	CA735/10		100
CA707/S/Q/1		100	CA707/S/Q/1		100	CA707/S/Q/5		100	CA707/S/Q/2		100
CA710/2		100	CA718/2		100						
CA710/3		100	CA718/3		50						
CA710/4		100	CA718/4		50						
CA710/10		25	CA718/10		25						
MT8		100	MT10		100	MT12		100	MT12		100
SWL6		100									

	CTS35U			CTS50U			CTS95U		
									
	 AEx eII EEx eII 								
Terminal Width	15 mm			20.5 mm			25 mm		
Height x Length	58 x 52.5 mm			75.5 x 71 mm			90 x 83 mm		
Stripping Length	18 mm			22 mm			24 mm		
Insulation Material	Polyamide 6.6			Polyamide 6.6			Polyamide 6.6		
Type of Connection	2 screw clamps & 1 tapped hole for cross connection			2 screw clamp connections			2 Allen screw clamp connections		
Approvals	  			  			  		
Wire Range	8-2 AWG	10-35 sq.mm	8-2 AWG	6-2/0 AWG	16-50 sq.mm	6-2/0 AWG	2-4/0 AWG	16-95 sq.mm	2-4/0 AWG
Voltage Rating	600 V	750 V	600 V	600V	1000 V	600 V	600V	1000 V	600 V
Current Rating	145 A	125 A	145 A	150 A	150 A	150 A	230 A	232 A	230 A
Torque	25 lb-in	2.5 Nm	25 lb-in	60 lb-in	6.8 Nm	60 lb-in	160 lb-in	18.2 Nm	160 lb-in
Terminal Block	Cat. No. CTS35U	Std. Pk. 50		Cat. No. CTS50U	Std. Pk. 20		Cat. No. CTS95U	Std. Pk. 10	
End Plate	EP35U	50							
Isolation Partition	PP35U	50							
Separator Plate									
DIN Rail for ordering information refer to page 62									
End Stop for ordering information refer to page 63	 CA702 50 CA802 50			CA202 50 CA102 50			CA202 50 CA102 50		
Internal Jumper	 CA726/2 50 CA726/3 25 CA726/4 25 CA726/10 10								
Insulated Internal Jumper	 CA746/2 50 CA746/3 25 CA746/4 25 CA746/10 10								
Current Bars	 CA703/5 100 CA704/5 100 CA705/5 100 CA736/10 100								
Shorting Sleeve & Screw	 CA707/S/Q/2 100								
Marking Tags	 MT15 100			MT20 100			MT25 100		




FEED-THROUGH MULTI-CONNECTION

35 or 32mm DIN Rail

Connect multiple wires to a single terminal block and eliminate reliability problems encountered when connecting two wires into a single clamp. Two versions are available.

Type CMC1-2 features a single screw-cage clamp for 22-10 AWG wires on one side and two clamps on the other side for 22-10 AWG wires.

Type CMC2-2 has two identical clamps for 22-10 AWG wires on both sides.



Terminal Width

Height x Length

Stripping Length

Insulation Material

Type of Connection

Approvals

Wire Range

Voltage Rating

Current Rating

Torque



6 mm

47 x 46.5 mm

9 mm

Polyamide 6.6

3 screw clamps & 1 tapped hole for cross connection



22-10AWG

600 V

35 A

7 lb-in.

Cat. No.

CMC1-2

EPCMC1-2

Std. Pk.

100

50



6 mm

51.5 x 65 mm

9 mm

Polyamide 6.6

4 screw clamps & 2 tapped holes for cross connection



22-10AWG

600 V

35 A

7 lb-in.

Cat. No.

CMC2-2

EPCMC2-2



Terminal Block

End Plate



DIN Rail

for ordering information
refer to page 62

End Stop

for ordering information
refer to page 63



Internal
Jumper



2 pole
3 pole
4 pole
10 pole
100 pole

CA722/2
CA722/3
CA722/4
CA722/10
CA722/100

100
50
50
10
5

CA722/2
CA722/3
CA722/4
CA722/10
CA722/100

100
50
50
10
5

Insulated
Internal
Jumper



2 pole
3 pole
4 pole
10 pole
100 pole


CA742/2
CA742/3
CA742/4
CA742/10
CA742/100

100
50
50
10
5

CA742/2
CA742/3
CA742/4
CA742/10
CA742/100

100
50
50
10
5

Current
Bars



2 pole
3 pole
4 pole
10 pole
10 pole (breakable)
100 pole

CA703/1
CA704/1
CA705/1
CA732/10
CA732/10-A
CA732/100

100
100
100
100
100
10

CA703/1
CA704/1
CA705/1
CA732/10
CA732/10-A
CA732/100

100
100
100
100
100
10

Shorting Sleeve & Screw



CA707/S/Q/01

100

CA707/S/Q/01

100

External
Jumper



for use in upper level

2 pole
3 pole
4 pole
10 pole

CA713/2
CA713/3
CA713/4
CA713/10

100
100
50
25

CA713/2
CA713/3
CA713/4
CA713/10

100
100
50
25

Marking Tags (MT Type)



MT6

100

MT6

100



COLOR BLOCKS

(other than grey standard)

When ordering please add
color suffix to Cat. No.

Example: CTS2.5U-N/R


Color	Ordering Suffix
Red	R
Blue	BU
Black	BL
Orange	O
Green	G
Yellow	Y
White	W
Beige	BG
Dark Brown	DB

FEED-THROUGH DOUBLE LEVEL 35 or 32mm DIN Rail

Altech double level terminals are the answer to high wiring density problems posed by certain unavoidable wiring arrangements. Double level terminals have the following advantages:



- Double wiring density available without extension of mounting rails.
- Interconnection/shorting can be done at both levels.
- Marking/identification by marking tags possible at both levels.


CDL4U(I.S) internally shorted double level terminals are useful for distribution applications by using shorting links at lower levels.



CDL4U

CDL4U(I.S)



Terminal Width	6 mm			6 mm		
Height x Length	54 x 55.5 mm			54 x 55.5 mm		
Stripping Length	9 mm			9 mm		
Insulation Material	Polyamide 6.6			Polyamide 6.6		
Type of Connection	4 screw clamps & 2 tapped holes for cross connection			4 screw clamps & 1 tapped hole for cross connection		
Approvals	  			  		
Wire Range	22-10 AWG	0.5-4 sq.mm	22-10 AWG	22-10 AWG	0.5-4 sq.mm	22-10 AWG
Voltage Rating	300V	400 V	600 V	300 V	400 V	600 V
Current Rating	35 A	32 A	35 A	35 A	32 A	35 A
Torque	7 lb-in	0.5 Nm	7 lb-in	7 lb-in	0.5 Nm	7 lb-in
	Cat. No.	Std. Pk.		Cat. No.	Std. Pk.	
Terminal Block	CDL4U	100		CDL4U(I.S)	100	
End Plate 	EPCDL4U	50		EPCDL4U	50	
Separator Plate 	SPCDL4U	100		SPCDL4U	100	
DIN Rail for ordering information refer to page 62						
End Stop for ordering information refer to page 63 	CA702	50		CA702	50	
	CA802	50		CA802	50	
Internal Jumper 	2 pole	CA727/2	100	2 pole	CA727/2	100
	3 pole	CA727/3	50	3 pole	CA727/3	50
	4 pole	CA727/4	50	4 pole	CA727/4	50
	10 pole	CA727/10	10	10 pole	CA727/10	10
Insulated Internal Jumper 	2 pole	CA747/2	100	2 pole	CA747/2	100
	3 pole	CA747/3	50	3 pole	CA747/3	50
	4 pole	CA747/4	50	4 pole	CA747/4	50
	10 pole	CA747/10	10	10 pole	CA747/10	10
Current Bars 	2 pole	CA703/1	100	2 pole	CA703/1	100
	3 pole	CA704/1	100	3 pole	CA704/1	100
	4 pole	CA705/1	100	4 pole	CA705/1	100
	10 pole	CA732/10	100	10 pole	CA732/10	100
	10 pole (breakable)	CA732/10-A	100	10 pole (breakable)	CA732/10-A	100
	100 pole	CA732/100	10	100 pole	CA732/100	10
Shorting Sleeve & Screw 		CA607/S/Q	100		CA607/S/Q	100
External Jumper 	2 pole	CA714/2	100	2 pole	CA714/2	100
	3 pole	CA714/3	100	3 pole	CA714/3	100
	4 pole	CA714/4	50	4 pole	CA714/4	50
	10 pole	CA714/10	25	10 pole	CA714/10	25
Marking Tags (MT Type) 	MT2	100		MT2	100	



COLOR BLOCKS

(other than grey standard)

When ordering please add color suffix to Cat. No.


Example: CTS2.5U-N/R

Color	Ordering Suffix
Red	R
Blue	BU
Black	BL
Orange	O
Green	G
Yellow	Y
White	W
Beige	BG
Dark Brown	DB

FEED-THROUGH OFFSET DOUBLE LEVEL

Altech Offset Double Level Terminals, which provide a separate connection at two levels. In ODL, the top level is offset from the bottom level by half the thickness of the terminal. This offset provides better accessibility to the screws on the lower level.

*It is recommended to use end plates at both ends of assembled ODL terminal sets for flat alignment to enable effective use of end stops.



Terminal Width	6 mm		
Height x Length	63 x 68 mm		
Stripping Length	9 mm		
Insulation Material	Polyamide 6.6		
Type of Connection	4 screw clamps & 2 tapped holes for cross connection		
Approvals	  		
Wire Range	22-10 AWG	0.5-4 sq.mm	22-10 AWG
Voltage Rating	600 V	600 V	600 V
Current Rating	35 A	32 A	35 A
Torque	7 lb-in	0.5 Nm	7 lb-in

	Cat. No.	Std. Pk.
Terminal Block	ODL4U	50
End Plate* Front Back	EPODL4U	50
	EP1ODL4U	50

DIN Rail
for ordering information
refer to page 62



End Stop
for ordering information
refer to page 63



Internal Jumper	2 pole	CA727/2	10
	3 pole	CA727/3	10
	4 pole	CA727/4	10
	10 pole	CA727/10	10

Insulated Internal Jumper	2 pole	CA747/2	100
	3 pole	CA747/3	50
	4 pole	CA747/4	50
	10 pole	CA747/10	10

Current Bars	2 pole	CA703/1	100
	3 pole	CA704/1	100
	4 pole	CA705/1	100
	10 pole	CA732/10	100
	10 pole (breakable)	CA732/10-A	100
	100 pole	CA732/100	10

Shorting Sleeve & Screw		CA607/S/Q	100
-------------------------	--	-----------	-----

External Jumper	2 pole	CA714/2	100
	3 pole	CA714/3	100
	4 pole	CA714/4	50
	10 pole	CA714/10	25

Marking Tags (MT Type)		MT6	100
------------------------	--	-----	-----



COLOR BLOCKS

(other than grey standard)

When ordering please add color suffix to Cat. No.

Example: CTS2.5U-N/R

Color	Ordering Suffix
Red	R
Blue	BU
Black	BL
Orange	O
Green	G
Yellow	Y
White	W
Beige	BG
Dark Brown	DB

FEED-THROUGH TRIPLE LEVEL 35 or 32mm DIN Rail


For applications with extreme space constraints. Only 6mm (.236") wide, with three separate feed-through levels. Jumpers can be used to reduce field wiring.

They can also be used in control systems where sensors and actuator applications are involved.


The top level of CTL2.5UH terminal block provide connecting points for signal while middle and bottom level provide connecting points are used for positive and negative potential.

In applications where switching indication is required, choice of CTL2.5UHL and CTL2.5UL terminal blocks with built-in electronic components are available.

CTL2.5U-H



CTL2.5U



Terminal Width	6 mm			6 mm		
Height x Length	67 x 61 mm			67 x 84 mm		
Stripping Length	9 mm			9 mm		
Insulation Material	Polyamide 6.6			Polyamide 6.6		
Type of Connection	4 Screw clamps & 3 tapped holes for cross connection			6 Screw clamps & 3 tapped holes for cross connection		
Approvals						
Wire Range	22-12 AWG	0.5-2.5 sq.mm	22-12 AWG	22-12 AWG	0.5-2.5 sq.mm	22-12 AWG
Voltage Rating	300 V	500 V	300 V	300 V	500 V	300 V
Current Rating	25 A	24 A	25 A	25 A	24 A	25 A
Torque	4.5 lb-in	0.4 Nm	4.5 lb-in	4.5 lb-in	0.4 Nm	4.5 lb-in

	Cat. No.	Std. Pk.	Cat. No.	Std. Pk.
Terminal Block	CTL2.5U-H	50	CTL2.5U	50
End Plate	EPCTL2.5U-H	50	EPCTL2.5U	50

DIN Rail
for ordering information
refer to page 62



End Stop
for ordering information
refer to page 63



Internal Jumper	2 pole	CA722/2	100	CA722/2	100
	3 pole	CA722/3	50	CA722/3	50
	4 pole	CA722/4	50	CA722/4	50
	10 pole	CA722/10	10	CA722/10	10
	100 pole	CA722/100	5	CA722/100	5

Current Bars	2 pole	CA703/1	100	CA703/1	100
	3 pole	CA704/1	100	CA704/1	100
	4 pole	CA705/1	100	CA705/1	100
	10 pole	CA732/10	100	CA732/10	100
	10 pole (breakable)	CA732/10-A	100	CA732/10-A	100
	100 pole	CA732/100	10	CA732/100	10

Shorting Sleeve & Screw	CA707/S/Q/01	100	CA707/S/Q/01	100
-------------------------	--------------	-----	--------------	-----

External Jumper	2 pole	CA715/2	100	CA715/2	100
	3 pole	CA715/3	100	CA715/3	100
	4 pole	CA715/4	100	CA715/4	100
	10 pole	CA715/10	50	CA715/10	50

Marking Tags (MT Type)	MT2	100	MT2	100
------------------------	-----	-----	-----	-----



COLOR BLOCKS


(other than grey standard)

When ordering please add
color suffix to Cat. No.

Example: CTS2.5U-N/R

Color	Ordering Suffix
Red	R
Blue	BU
Black	BL
Orange	O
Green	G
Yellow	Y
White	W
Beige	BG
Dark Brown	DB

CTL2.5U-H(L)*



6 mm

67 x 61 mm

9 mm

Polyamide 6.6

4 Screw clamps & 2 tapped holes for cross connection



22-12 AWG 0.5-2.5 sq.mm 22-12 AWG

300 V

500 V

300 V

25 A

24 A


25 A

4.5 lb-in

0.4 Nm

4.5 lb-in

CTL2.5U(L)*



6 mm

67 x 84 mm

9 mm

Polyamide 6.6

6 Screw clamps & 2 tapped holes for cross connection



22-12 AWG 0.5-2.5 sq.mm 22-12 AWG

300 V

500 V

300 V

25 A

24 A

25 A

4.5 lb-in

0.4 Nm

4.5 lb-in

Cat. No.	Std. Pk.
CTL2.5U-H(L)*	50
EPCTL2.5U-H	50

Cat. No.	Std. Pk.
CTL2.5U(L)*	50
EPCTL2.5U	50



CA702

50

CA802

50

CA722/2

100

CA722/3

50

CA722/4

50

CA722/10

10

CA722/100

5

CA703/1

100

CA704/1

100

CA705/1

100

CA732/10

100

CA732/10-A

100

CA732/100

10

CA707/S/Q/01

100

CA715/2

100

CA715/3

100

CA715/4

100

CA715/10

50

MT2

100



CA702

50

CA802

50

CA722/2

100

CA722/3

50

CA722/4

50

CA722/10

10

CA722/100

5

CA703/1

100

CA704/1

100

CA705/1

100

CA732/10

100

CA732/10-A

100

CA732/100

10

CA707/S/Q/01

100

CA715/2

100

CA715/3

100

CA715/4


100

CA715/10

50

MT2

100



*Ideal for sensor applications.
See Altech's Inductive Proximity Sensor catalog for ordering information.*

* Add required voltage to part number as suffix;
i.e. CTL2.5U(L)/24 for 24V DC

DISTRIBUTION BLOCK

Altech CDB Compact Distribution Blocks are an ideal choice for a simplified distribution system. A lug/bolt secures the incoming cable and the screw clamp design of the block provides the outgoing connections. These provide easy connect points and ensure perfect continuity for distribution. A protective shield effectively shrouds the incoming connection.

Application Information:

Sum of outgoing currents on either side of center should not exceed half the maximum permissible incoming current.

Sum of total outgoing currents should not exceed maximum permissible incoming current.

Connection for higher outgoing currents should be done through the terminal nearest to the incoming connection.

CMDB blocks are the modified version of CDB terminal blocks without central incoming terminal connections.




COLOR BLOCKS

(other than grey standard)

When ordering please add color suffix to Cat. No.

Example: CTS2.5U-N/R

Color	Ordering Suffix
Red	R
Blue	BU
Black	BL
Orange	O
Green	G
Yellow	Y
White	W
Beige	BG
Dark Brown	DB



CDB4

CDB4(1)



Terminal Width	6 mm	6 mm
Height & Width	45 x 43 mm	45 x 43 mm
Stripping Length	9 mm	9 mm
Insulation Material	Polyamide 6.6	Polyamide 6.6
Type of Connection	Input Output	Input Output
Approvals		
Wire Range	Input Output	Input Output
Voltage Rating	600 V	600 V
Current Rating	Input Max. Individual Output	Input Max. Individual Output
Torque	Input Output	Input Output

	Cat. No.	H x W x L (mm)	Outputs	Std. Pk.	Cat. No.	H x W x L (mm)	Outputs	Std. Pk.
Terminal Block	CDB4/1	45 x 43 x 43.8	4	10	CDB4/2(1)	45 x 43 x 52	4	10
	CDB4/2	45 x 43 x 55.8	8	10	CDB4/3(1)	45 x 43 x 58	6	10
	CDB4/3	45 x 43 x 67.8	12	10	CDB4/4(1)	45 x 43 x 64	8	5
	CDB4/4	45 x 43 x 80	16	5	CDB4/5(1)	45 x 43 x 70	10	5
	CDB4/5	45 x 43 x 96	20	5	CDB4/6(1)	45 x 43 x 76	12	5
					CDB4/10(1)	45 x 43 x 100	20	5
					CDB4/11(1)	45 x 43 x 106	22	5


Cat. No.

Std. Pk.

Cat. No.

Std. Pk.

DIN Rail
for ordering information
refer to page 62



End Stop
for ordering information
refer to page 63



CA702
CA802

50
50

CA702
CA802

50
50

Marking Tags (MT Type)



MT6

100

MT6

100

Warning Label

CDB6



8 mm

43 x 47 mm

12 mm

Polyamide 6.6

1 Lug/ M6 bolt connection for ring lug

Screw clamp connection



10-6 AWG
22-8 AWG

6-25 sq.mm
1.5-6 sq.mm

10-2 AWG
22-8 AWG

600 V

750 V

600 V

100 A
50 A

41 A

100 A
50 A

25 lb-in
9 lb-in

3.0 Nm
0.8 Nm

35 lb-in
14 lb-in

CDB10



10 mm

43 x 47 mm

12 mm

Polyamide 6.6

1 Lug/ M8 bolt connection for ring lug

Screw clamp connection



7-2 AWG
15-7 AWG

10-35 sq.mm
1.5-10 sq.mm

8-1/0 AWG
22-6 AWG

600 V

750 V

600 V

125 A
65 A

57 A

130 A
65 A

53 lb-in
14 lb-in

6.0 Nm
1.2 Nm

53 lb-in
14 lb-in

CMDB4



6 mm

45 x 43 mm

9 mm

Polyamide 6.6

Screw clamp connection

22-10 AWG

0.5-4 sq.mm

22-10 AWG

600 V

800 V

600 V

35 A

32 A

35 A

7 lb-in

0.5 Nm

7 lb-in

Cat. No.	H x W x L (mm)	Outputs	Std.Pk
CDB6/2	43 x 47 x 64	8	10
CDB6/3	43 x 47 x 80	12	10
CDB6/4	43 x 47 x 96	16	5

Cat. No.	H x W x L (mm)	Outputs	Std.Pk
CDB10/2	43 x 47 x 72	8	10
CDB10/3	43 x 47 x 92	12	10
CDB10/4	43 x 47 x 112	16	5

Cat. No.	H x W x L (mm)	Outputs	Std.Pk
CMDB4/2	45 x 43 x 13.5	4	10
CMDB4/3	45 x 43 x 19.5	6	10
CMDB4/4	45 x 43 x 25.5	8	5
CMDB4/10	45 x 43 x 61.5	20	5

Cat. No. Std. Pk.



CA702
CA802

50
50

Cat. No. Std. Pk.



CA702
CA802

50
50

Cat. No. Std. Pk.



CA702
CA802

50
50



MT8 100

SWL6 100

MT10 100

MT6 100

		CMDB6			CMDB10		
							
							
		CE			CE		
Terminal Width		8 mm			10 mm		
Height & Width		43 x 47 mm			43 x 47 mm		
Stripping Length		12 mm			12 mm		
Insulation Material		Polyamide 6.6			Polyamide 6.6		
Type of Connection	Input Output	Screw clamp connection			Screw clamp connection		
Approvals							
Wire Range	Input Output	22-8 AWG	1.5-6 sq.mm	22-8 AWG	15-7 AWG	1.5-10 sq.mm	20-6 AWG
Voltage Rating		600 V	800 V	600 V	600 V	800 V	600 V
Current Rating	Input Max. Individual Output	50 A	41 A	50 A	65 A	57 A	65 A
Torque	Input Output	9 lb-in	0.8 Nm	14 lb-in	14 lb-in	1.2 Nm	14 lb-in

Terminal Block		Cat. No.	H x W x L (mm)	Outputs	Std. Pk			Cat. No.	H x W x L (mm)	Outputs	Std. Pk
		CMDB6/2	43 x 48 x 17.5	4	10			CMDB10/2	43 x 48 x 21.5	4	10
		CMDB6/3	43 x 48 x 25.5	6	10			CMDB10/3	43 x 48 x 31.5	6	10
		CMDB6/4	43 x 48 x 33.5	8	10			CMDB10/4	43 x 48 x 41.5	8	10
		CMDB6/10	43 x 48 x 81.5	20	5			CMDB10/10	43 x 48 x 101.5	20	5
DIN Rail		Cat. No.		Std. Pk.				Cat. No.		Std. Pk.	
for ordering information refer to page 62											
End Stop		Cat. No.		Std. Pk.				Cat. No.		Std. Pk.	
for ordering information refer to page 63											
		CA702		50				CA702		50	
		CA802		50				CA802		50	
Marking Tags		Cat. No.		Std. Pk.				Cat. No.		Std. Pk.	
(MT Type) 											
		MT8		100				MT10		100	
Warning Label		SWL6		100							

COLOR BLOCKS
 (other than grey standard)

When ordering please add
 color suffix to Cat. No.

 Example: CTS2.5U-N/R

Color	Ordering Suffix
Red	R
Blue	BU
Black	BL
Orange	O
Green	G
Yellow	Y
White	W
Beige	BG
Dark Brown	DB



ONE PHASE POWER DISTRIBUTION BLOCKS

- Speed of mounting and wiring
- IP20 Finger Safe
- DIN Rail or Panel Mount
- Blocks fit with other DIN Rail mountable modular devices (height 95mm, depth 44.5mm)
- Accessories increase the number of outputs with only one input.

38049

38041



CE



CE

Part Number:

White

38049 (UL File E98082)

38041 (UL File E98082)

Gray

DB16 (UL File E220514)

DB35 (UL File E220514)

Approvals



Current Rating

80A

80A

115A

125A

Voltage Rating

600V AC

690V AC

600V AC

690V AC

No. of Inputs

1

1

1

1

Wire Range

8-4 AWG

6-16mm²

8-2 AWG

10-35mm²

Torque

13.5lb.-in.

1.5Nm

31lb.-in.

3.5Nm

(40 for DB35)

Screw Type

Pozi Drive 2

Pozi Drive 2

No. of Outputs

6

6

6

6

Wire Range

(2x)8-4 AWG

(2x)6-16mm²

14-6 AWG

2.5-16mm²

Torque

13.5lb.-in.

1.5Nm

17.5lb.-in.

2Nm

Wire Range

(4x)14-10 AWG

(4x)2.5-6mm²

Torque

7.2lb.-in.

0.8Nm

Screw Type

Pozi Drive 2

Pozi Drive 2

Optional






Marking Tag

MT2

MT2


(for DB16 and DB35)

Dimensions:




Accessories Fork Type Busbar
Part Number: **38045** to jump 2 Blocks
38046 to jump 8 Blocks
can be cut to customer needs


38032



38020



38019



Part Number:

38032

38020

38019

Approvals



Current Rating

160A

160A

230A

250A

310A

400A

Voltage Rating

600V AC

690V AC

600V AC

690V AC

600V AC

690V AC

No. of Inputs

1

1

1

1

1

1

Wire Range

8-2/0AWG

10-70mm²

2-4/0AWG

35-120mm²

3/0-350kcmil

95-185mm²

Torque

35.5lb. in.

4Nm

170lb. in.

19Nm

230lb. in.

25Nm

No. of Outputs

6

6

11

11

11

11

Wire Range

14-6 AWG

2.5-16mm²

2x 14-2AWG

2.5-35mm²

2x 14-2AWG

2.5-35mm²

Torque

17.5lb. in.

2Nm

31lb. in.

3.5Nm

31lb. in.

3.5Nm

Wire Range

14-6 AWG

2.5-16mm²

5x 14-6AWG

2.5-16mm²

5x 14-6AWG

2.5-16mm²

Torque

17.5lb. in.

2Nm

17.5lb. in.

2Nm

17.5lb. in.

2Nm

Wire Range

14-8 AWG

2.5-10mm²

4x 14-8AWG

2.5-10mm²

4 x 14-8AWG

2.5-10mm²

Torque

17.5lb. in.

2Nm




17.5lb. in.

2Nm

17.5lb. in.



2Nm

Dimensions:




Accessories
Part Number:

Copper Jumper Bar
3803221 for 2 Blocks
3803231 for 3 Blocks
3803241 for 4 Blocks
can be cut to customer needs



THREE PHASE POWER DISTRIBUTION BLOCKS

- Speed of mounting and wiring
- IP20 Finger Safe
- DIN Rail or Panel Mount
- Blocks fit with other DIN Rail mountable modular devices
- Same compact size for both ratings



3 Pole



Part Number:

38075


38073

Approvals



Current Rating	115A	115A	175A	175A
Voltage Rating	600V AC	690V AC	600V AC	690V AC
No. of Inputs	3x1	3x1	3x1	3x1
Wire Range	8-2AWG	10-35mm ²	8-2/0AWG	10-70mm ²
Torque	31lb. in.	3.5Nm	35.5lb. in.	4Nm
No. of Outputs	3x6	3x6	3x6	3x6
Wire Range	14-4AWG	2.5-16mm ²	14-4AWG	2.5-16mm ²
Torque	17.5lb. in.	2Nm	17.5 lb. in.	2Nm

Dimensions:



GROUND

35 and 32mm DIN Rail

Use ground blocks instead of grounding studs and wire lugs to terminate ground wires, saving installation and wiring time.

Ground blocks clamp mechanically onto the DIN Rail by tightening the center mounting screw, making a reliable electrical connection between the cage clamp terminals and the DIN Rail. The rail serves as a busbar and automatically distributes ground potential to all other ground terminals on the same rail.

Ground blocks can also be used as end stops, preventing other terminal blocks and components from moving laterally on the DIN Rail.


They are supplied with a standard green/yellow housing for easy identification and accept standard marking tags.

CGT4U, CGT10U and CGT35U can be mounted on both DIN 32mm and DIN 35mm rails.

CGT4N & CGT6N can be mounted on 35mm DIN rail and have the same top outer profile as the feed through blocks (CTS4U-N, CTS2.5U-N, CTS6U, CTS10U).

CGMT4 can be mounted on 15mm DIN rails and has the same top outer profile as the CMT4 feed through blocks.

- High density
- Screw-cage clamp
- Special clamping foot
- Polyamide 6.6
- Color: green/yellow



Terminal Width

Height x Length

Stripping Length

Insulation Material

Type of Connection

Approvals

Wire Range

Torque

CGT4U



AEx eII EEx eII

CE

CGT4N



CE

6 mm

48 x 43 mm

9 mm

Polyamide 6.6

2 screw clamps



22-10 AWG 0.5-4 sq.mm 22-10 AWG

7 lb-in

0.5 Nm

7 lb-in

6 mm

45.4 x 54.2 mm

9 mm

Polyamide 6.6

2 screw clamps



22-10 AWG 0.5-4 sq.mm 22-10 AWG

7 lb-in

0.8 Nm

7 lb-in

Terminal Block

DIN Rail
for ordering information
refer to page 62

End Plate



Marking Tags
(MT Type)




Cat. No.

Std. Pk.

CGT4N

50



EPCGT4U

100

MT6


100

Cat. No.

Std. Pk.

CGT4N

50




EPCGT4U

100




MT6

100



Assembly for single phase
3 wire circuits.

CGT6N	CGT10U	CGT35U	CGMT4
			
CE	Ex AEx eII EEx eII	CE	CE
8 mm	10 mm	16 mm	6 mm
47 x 54.5 mm	49.5 x 45 mm	61.5 x 58 mm	28.5 x 27 mm
12 mm	12 mm	18 mm	9 mm
Polyamide 6.6	Polyamide 6.6	Polyamide 6.6	Polyamide 6.6
2 screw clamps	2 screw clamps	2 screw clamps	2 screw clamps
  	  	  	  
22-8 AWG 1.5-6 sq.mm 22-8 AWG	22-6 AWG 1.5-10 sq.mm 16-8 AWG	8-2 AWG 10-35 sq.mm 8-2 AWG	22-10 AWG 0.5-4 sq.mm 22-10 AWG
14 lb-in 0.8 Nm 14 lb-in	14 lb-in 1.2 Nm 14 lb-in	25 lb-in 2.5 Nm 25 lb-in	7 lb-in 0.5 Nm 7 lb-in

Cat. No.	Std. Pk.	Cat. No.	Std. Pk.	Cat. No.	Std. Pk.	Cat. No.	Std. Pk.
CGT6N	50	CGT10N	50	CGT35N	20	CGMT4	50
							
EPCGT4U	100	EPCGT4U	100	EPCGT4U	100	EPCGT4U	100
MT8	100	MT10	100	MT15	100	MT2	100

DISCONNECT

35 or 32mm DIN Rail



Disconnect and test terminals are an ideal choice for measuring control and regulatory circuits. The terminals provide a clear functional advantage for devices having utility instruments and associated transformers.

Five versions of disconnect and test terminals are available:

- CDTTU - disconnection is achieved by means of a slide link operated with a screw driver.
- CDTTU-SH - disconnect and test terminals are ideal for use in current transformer applications when it is mandatory to keep the secondary side shorted at any point while taking current measurements.
- CKT4U - disconnection is achieved by lifting the knife contact lever.
- CSDL4U - hinged disconnection and testing terminal, incorporates a connecting link in place of the fuse link.
- CSDL6U - hinged disconnect block for 8 AWG size wires.
- DDDL4U - double level disconnect terminal with hinged disconnect in upper level.

Specially designed socket head screws act as test/monitoring points in both CDTTU, CDTTU-SH and CKT4U.

Important: The disconnecting device is not suitable for interrupting load. The supply must be switched off before operating the slide link/lever.



Terminal Width	8 mm			16 mm		
Height x Length	57 x 63 mm			57 x 63 mm		
Stripping Length	12 mm			12 mm		
Insulation Material	Polyamide 6.6			Polyamide 6.6		
Type of Connection	2 screw clamps			4 screw clamps		
Approvals	  			 		
Wire Range	16-8 AWG	1.5-6 sq.mm	16-8 AWG	16-8 AWG	1.5-6 sq.mm	16-8 AWG
Voltage Rating	600 V	750 V	600 V	300 V	300 V	600 V
Current Rating	41 A	41 A	41 A	10 A	10 A	10 A
Torque	14 lb-in	1.2 Nm	14 lb-in	14 lb-in	1.6 Nm	14 lb-in

	Cat. No.	Std. Pk.	Cat. No.	Std. Pk.
Terminal Block	CDTTU	50	CDTTU-SH	50
End Plate 	EPCDTTU	50	EPCDTTU	50
Isolation Partition 				
DIN Rail for ordering information refer to page 62	 		 	
End Stop for ordering information refer to page 63	CA702	50	CA702	50
	CA802	50	CA802	50
External Jumper for internal jumpers refer to page 60	 2 pole 3 pole 4 pole 10 pole	CA710/2 100 CA710/3 100 CA710/4 100 CA710/10 25	CA710/2 100 CA710/3 100 CA710/4 100 CA710/10 25	
Marking Tags (MT Type)  (MT Type on Lever)	MT8	100	MT8	100

COLOR BLOCKS






(other than grey standard)

When ordering please add color suffix to Cat. No.

Example: CTS2.5U-N/R

Color	Ordering Suffix
Red	R
Blue	BU
Black	BL
Orange	O
Green	G
Yellow	Y
White	W
Beige	BG
Dark Brown	DB



CKT4U			CSDL4U			CSDL6U			DDDL4U		
											
CE			CE			CE			CE		
6 mm			8 mm			8 mm			8 mm		
46 x 46.3 mm			43 x 58 mm			60 x 43 mm			66 x 88 mm		
9 mm			9.5 mm			9.5 mm			9.5 mm		
Polyamide 6.6			Polyamide 6.6			Polyamide 6.6			Polyamide 6.6		
2 screw clamps			2 screw clamps			2 screw clamps			4 screw clamps		
  			 								
22-10 AWG	0.5-4 sq.mm	22-10 AWG	22-10 AWG	0.5-4 sq.mm	22-10 AWG	22-8 AWG	1.5-6 sq.mm	22-8 AWG	22-10 AWG	22-10 AWG	
600 V	750 V	600 V	600 V	750 V	600 V	300 V	500 V	300 V	600 V	300 V	
16 A	16 A	16 A	14 A	6.3 A	14 A	10 A	6.3 A	10 A	14 / 35 A	14 / 35 A	
7 lb-in	0.5 Nm	7 lb-in	7 lb-in	0.5 Nm	7 lb-in	14 lb-in	0.8 Nm	14 lb-in	7 lb-in	7 lb-in	
Cat. No.		Std. Pk.	Cat. No.		Std. Pk.	Cat. No.		Std. Pk.	Cat. No.		Std. Pk.
CKT4U		50	CSDL4U		100	CSDL6U		50	DDDL4U		20
EPCKT4U		50	EPCSFL4U		50	EPCSFL6U		50	EPDDL4U		25
			PPCSFL4U		50						
											
CA702	50		CA702	50		CA702	50		CA702	50	
CA802	50		CA802	50		CA802	50		CA802	50	
CA713/2	100		CA711/2	100		CA710/2	100		CA711/2	100	
CA713/3	100		CA711/3	100		CA710/3	50		CA711/3	100	
CA713/4	50		CA711/4	50		CA710/4	50		CA711/4	50	
CA713/10	25		CA711/10	25		CA710/10	25		CA711/10	25	
MT6	100		MT8	100		MT8	100		MT8	100	
			MT2	100					MT2	100	

FUSE BLOCKS

Certain electrical and control systems require protection by fuses. CSFL4U and CSFL6U have a specially designed space for cartridge type glass fuse and accept Ø5 x 20 or Ø5 x 25 mm fuses. CAFL4U accepts Ø1/4 x 1-1/4 in. fuses. The fuse can be engaged or disengaged by the movement of the carrier.


Altech fuse terminals are also available with light indication - CSFL4U(L). A specially designed built-in circuit gives light indication in the event of fuse blow out. Thus, fault in a circuit can be easily located.

However, an application of such terminals must take into consideration residual current flow.


CAFL4U(L) is equipped with a LED for blown fuse indication. CAFL4U(N) is equipped with a neon bulb for same application.

Important: The disconnecting device is not suitable for interrupting load. The supply must be switched off before operating the slide link/lever.

† Fuses are sold separately Altech, see page 34 for details.




CSFL4U



† Fuse not included.

CSFL4U(L)*



† Fuse not included.

Terminal Width	8 mm			8 mm		
Height x Length	43 x 58 mm			43 x 58 mm		
Stripping Length	9.5 mm			9.5 mm		
Insulation Material	Polyamide 6.6			Polyamide 6.6		
Type of Connection	2 screw clamps			2 screw clamps		
Fusion Voltage				24V AC/DC, 48V AC/DC, 110V AC/DC, 220V AC		
Type of Fuse Used	Ø5x20, Ø5x25 mm			Ø5x20, Ø5x25 mm		
Approvals						
Wire Range	22-10 AWG	0.5-4 sq.mm	22-10 AWG	22-10 AWG	0.5-4 sq.mm	22-10 AWG
Voltage Rating	600 V	750 V	600 V	600 V	750 V	600 V
Current Rating	16 A	6.3 A	8 A	6.3 A	6.3 A	8 A
Torque	7 lb-in	0.5 Nm	7 lb-in	7 lb-in	0.5 Nm	7 lb-in
	Cat. No.	Std. Pk.		Cat. No.	Std. Pk.	
Terminal Block	CSFL4U	100		CSFL4U(L)*	50	
End Plate 	EPCSFL4U	50		EPCSFL4U	50	
Isolation Partition 	PPCSFL4U	50		PPCSFL4U	50	
DIN Rail for ordering information refer to page 62						
End Stop for ordering information refer to page 63 	CA702	50		CA702	50	
	CA802	50		CA802	50	
External Jumper 2 pole 3 pole 4 pole 10 pole 	CA711/2	100		CA711/2	100	
	CA711/3	100		CA711/3	100	
	CA711/4	50		CA711/4	50	
	CA711/10	25		CA711/10	25	
Marking Tags (MT Type)  (MT Type on Lever)	MT8	100		MT8	100	
	MT2	100		MT2	100	

COLOR BLOCKS

(other than grey standard)









When ordering please add color suffix to Cat. No.

Example: CTS2.5U-N/R

Color	Ordering Suffix
Red	R
Blue	BU
Black	BL
Orange	O
Green	G
Yellow	Y
White	W
Beige	BG
Dark Brown	DB



* Add required voltage to part number as a suffix. i.e. CSFL4U(L)/24 for 24V AC/DC.

CAFL4U	CAFL4U(L)*	CAFL4U(N)	CSFL6U
			
† Fuse not included.	† Fuse not included.	† Fuse not included.	† Fuse not included.
9 mm	9 mm	9 mm	8 mm
50 x 72 mm	50 x 70 mm	50 x 70 mm	60 x 43 mm
12 mm	12 mm	12 mm	12 mm
Polyamide 6.6	Polyamide 6.6	Polyamide 6.6	Polyamide 6.6
2 screw clamps	2 screw clamps	2 screw clamps	2 screw clamps
Ø1/4x1 in., Ø1/4x1 1/4 in.	Ø1/4x1 in., Ø1/4x1 1/4 in.	Ø1/4x1 in., Ø1/4x1 1/4 in.	Ø5x20, Ø5x25 mm
 US C E220514	 US C E220514	 US C E220514	 US C E220514
22-10 AWG 0.5-4 sq.mm 22-10 AWG	22-10 AWG 0.5-4 sq.mm 22-10 AWG	22-10 AWG 0.5-4 sq.mm 22-10 AWG	22-8 AWG 1.5-6 sq.mm 22-8 AWG
600 V 600 V 600 V	600 V 600 V 600 V	600 V 600 V 600 V	300 V 500 V 300 V
16 A 6.3 A 12 A	16 A 6.3 A 12 A	16 A 6.3 A 12 A	10 A 6.3 A 10 A
7 lb-in 0.5 Nm 7 lb-in	7 lb-in 0.5 Nm 7 lb-in	7 lb-in 0.5 Nm 7 lb-in	14 lb-in 0.8 Nm 14 lb-in
Cat. No. Std. Pk.	Cat. No. Std. Pk.	Cat. No. Std. Pk.	Cat. No. Std. Pk.
CAFL4U 25	CAFL4U(L)* 25	CAFL4U(N) 25	CSFL6U 50
EPCAFL4U 50	EPCAFL4U 50	EPCAFL4U 50	EPSCFL6U 50
			
CA702 50 CA802 50	CA702 50 CA802 50	CA702 50 CA802 50	CA702 50 CA802 50
CA716/2 50 CA716/3 50 CA716/4 50 CA716/10 25	CA716/2 50 CA716/3 50 CA716/4 50 CA716/10 25	CA716/2 50 CA716/3 50 CA716/4 50 CA716/10 25	CA710/2 100 CA710/3 100 CA710/4 100 CA710/10 25
MT9 100	MT9 100	MT9 100	MT8 100 MT6 100

* Add required voltage to part number as a suffix. i.e. CSFL4U(L)/24 for 24V AC/DC.

FUSE BLOCKS

DDFL4U - Double Level Fuse Terminal with fuse link on the top level has a separate feed through terminal at the lower level. This eliminates use of an additional feed through terminal.

In DDFL4U(E), specially designed built in circuit gives light indication in the event of a fuse blow out at the top level. The terminal provides separate feed through connection possibility at the lower level.

DDFL4U(LR): This is a modified version of DDFL4U(E) terminal where in two equipotential connection points are available on both ends of the terminal.

Important: The disconnecting device is not suitable for interrupting load. The supply must be switched off before operating the slide link/lever.

† Fuses are sold separately
Altech, see page 34
for details.



COLOR BLOCKS


(other than grey standard)

When ordering please add color suffix to Cat. No.

Example: CTS2.5U-N/R


Color	Ordering Suffix
Red	R
Blue	BU
Black	BL
Orange	O
Green	G
Yellow	Y
White	W
Beige	BG
Dark Brown	DB

DDFL4U




† Fuse not included.



DDFL4U(E)*



† Fuse not included.

Terminal Width	8 mm			8 mm				
Height x Length	66 x 88 mm			66 x 88 mm				
Stripping Length	9.5 mm			9.5 mm				
Insulation Material	Polyamide 6.6			Polyamide 6.6				
Type of Connection	4 screw clamps			4 screw clamps				
Fusion Voltage				24V AC/DC, 48V AC/DC, 110V AC/DC, 220V AC				
Type of Fuse Used	Ø5x20, Ø5x25 mm			Ø5x20, Ø5x25 mm				
Approvals	 			 				
Wire Range	22-10 AWG	0.5-4 sq.mm	22-10 AWG	22-10 AWG	0.5-4 sq.mm	22-10 AWG		
Voltage Rating	600 V	600 V	600 V	600 V	600 V	600 V		
Current Rating	Top Level Bottom Level	6.3 A 35 A	6.3 A 32 A	8 A 35 A	6.3 A 32 A	8 A 35 A		
Torque	7 lb-in	0.5 Nm	7 lb-in	7 lb-in	0.5 Nm	7 lb-in		
	Cat. No.	Std. Pk.		Cat. No.	Std. Pk.			
Terminal Block	DDFL4U	20		DDFL4U(E)*	20			
End Plate 	EPDDFL4U	25		EPDDFL4U	25			
DIN Rail for ordering information refer to page 62	 			 				
End Stop for ordering information refer to page 63								
Internal Jumper	2 pole 3 pole 4 pole 10 pole			CA729/2 CA729/3 CA729/4 CA729/10	100 50 50 10			
Insulated Internal Jumper	2 pole 3 pole 4 pole 10 pole			CA749/2 CA749/3 CA749/4 CA749/10	100 50 50 10			
Current Bar	2 pole 3 pole 4 pole 10 pole			CA703/6 CA704/6 CA705/6 CA737/10	100 100 100 100			
Shorting Sleeve & Screw 	CA707/S/Q/3			100		CA707/S/Q/3	100	
External Jumper	2 pole 3 pole 4 pole 10 pole			CA711/2 CA711/3 CA711/4 CA711/10	100 100 50 25		CA711/2 CA711/3 CA711/4 CA711/10	100 100 50 25
Marking Tags (MTType) (MT Type on Lever) 	MT8 MT2			100 100		MT8 MT2	100 100	

*Add required voltage to part number as a suffix. i.e. DDFL4U(E)/24 for 24V AC/DC. ** 25A @ 500 V, 10A @ 690V, 16A @ 500V for fast blow.

	DDFL4ULR	DDFL4U(E)LR*
		
	† Fuse not included.	† Fuse not included.
Terminal Width	8 mm	8 mm
Height x Length	66 x 88 mm	66 x 88 mm
Stripping Length	9.5 mm	9.5 mm
Insulation Material	Polyamide 6.6	Polyamide 6.6
Type of Connection	4 screw clamps	4 screw clamps
Fusion Voltage		24V AC/DC, 48V AC/DC, 110V AC/DC, 220V AC
Type of Fuse Used	Ø5x20, Ø5x25 mm	Ø5x20, Ø5x25 mm
Approvals	 	 
Wire Range	22-10 AWG 0.5-4 sq.mm 22-10 AWG	22-10 AWG 0.5-4 sq.mm 22-10 AWG
Voltage Rating	600 V 600 V 600 V	600 V 600 V 600 V
Current Rating	6.3 A 6.3 A 6.3 A	6.3 A 6.3 A 6.3 A
	Top Level Bottom Level	
Torque	7 lb-in 0.5 Nm 7 lb-in	7 lb-in 0.5 Nm 7 lb-in
	Cat. No. Std. Pk.	Cat. No. Std. Pk.
Terminal Block	DDFL4ULR 20	DDFL4U(E)LR* 20
End Plate	EPDDL4U 20	EPDDL4U 20
DIN Rail for ordering information refer to page 62		
End Stop for ordering information refer to page 63	CA702 50 CA802 50	CA702 50 CA802 50
Internal Jumper	2 pole 100 3 pole 50 4 pole 50 10 pole 10	2 pole 100 3 pole 50 4 pole 50 10 pole 10
Insulated Internal Jumper	2 pole 100 3 pole 50 4 pole 50 10 pole 10	2 pole 100 3 pole 50 4 pole 50 10 pole 10
Current Bar	2 pole 100 3 pole 100 4 pole 100 10 pole 100	2 pole 100 3 pole 100 4 pole 100 10 pole 100
Shorting Sleeve & Screw	CA707/S/Q/3 100	CA707/S/Q/3 100
External Jumper	2 pole 100 3 pole 100 4 pole 50 10 pole 25	2 pole 100 3 pole 100 4 pole 50 10 pole 25
Marking Tags	MT8 100 MT2 100	MT8 100 MT2 100

*Add required voltage to part number as a suffix. i.e. DDFL4U(E)LR/24 for 24V AC/DC. ¹ Left or right side connection.

FUSE HOLDERS

The main characteristics of fuse disconnectors are:


- Compliance with IEC 60947-1, IEC 60947-3
- UL508 recognized
- Plastic parts are made of material resistant to high temperatures
- All contact surfaces are silver plated
- Mounting on standard DIN 35 mm rail (DIN EN60715).
- Available up to 4 pole
- For all sizes a version with electronic indicator is available. There are two technical types of indicator:

L (LED) with built in LED diode which blinks after the fuse-link operates. The internal circuit resistance is 2M, thus the total dissipation is minimal. The indicator is capable of operating in conditions of open circuit with minimum capacitance between connection cables. Operating voltage range spans from 50V to 690V AC and DC.

I (NEON) with neon lamp, which is constantly lit after the fuse-link operates. The internal circuit resistance is 570k, thus it is necessary that the circuit be closed in order for the indicator to function. The operational voltage range is 100 V to 750 V AC.

*** Fuses are sold separately Altech, see page 34 for details.**

	1 POLE			2 POLE			3 POLE		
									
Terminal Width (B)	17.5 mm			35 mm			52.5 mm		
Height x Length	77 x 63.5 mm			77 x 63.5 mm			77 x 63.5 mm		
Stripping Length	11 mm			11 mm			11 mm		
Insulation Material	Aculon ®			Aculon ®			Aculon ®		
Type of Connection	2 screw clamps			2 screw clamps			2 screw clamps		
Fusion Voltage									
Type of Fuse Used	Ø10 x 38 mm			Ø10 x 38 mm			Ø10 x 38 mm		
Approvals	 			 			 		
Wire Range	24-4 AWG	1.5-25sq.mm	24-4 AWG	24-4 AWG	1.5-25sq.mm	24-4 AWG	24-4 AWG	1.5-25sq.mm	24-4 AWG
Voltage Rating	690 V	400 V**	690 V	690 V	400 V**	690 V	690 V	400 V**	690 V
Current Rating	32A	32A**	32A	32A	32A**	32A	32A	32A**	32A
Torque	31 lb-in	2-2.5 Nm	31 lb-in	31 lb-in	2-2.5 Nm	31 lb-in	31 lb-in	2-2.5 Nm	31 lb-in
	Cat. No.	Std. Pk.		Cat. No.	Std. Pk.		Cat. No.	Std. Pk.	
Terminal Block Indicator:									
None	CB1038-1	1		CB1038-2	1		CB1038-3	1	
LED	CB1038-1/L	1		CB1038-2/L	1		CB1038-3/L	1	
Neon	CB1038-1/I	1		CB1038-2/I	1		CB1038-3/I	1	
End Plate									
DIN Rail									
for ordering information refer to page 62									
End Stop									
for ordering information refer to page 63	CA702	50		CA702	50		CA702	50	
	CA802	50		CA802	50		CA802	50	



Dimension for B:

1 Pole	17.5mm
1 Pole + Neutral	35mm
2 Pole	35mm
3 Pole	52.5mm
3 Pole + Neutral	70mm

FUSES

Cylinder Fuses are typically used in industrial applications to protect electrical devices such as motors, drives, etc.

They are available in four sizes with a current range from 1 to 125 Amps. Cylinder Fuses have metal caps at both ends, and a porcelain fuse body.

Please refer to pg 34 for ordering information for Cylinder Fuse Bases.

OPERATING CLASSES

gL/gG - Line Protection

Slow, typically used for distribution circuits or resistive loads.

Typical Markings: gL/gG

aM - Motor Protection

Fast acting short circuit protection, but slow acting overload protection.

Typical Marking: aM

aR - Semiconductor Protection

Partial range, short circuit protection for devices such as diodes, SCRs. etc.

Typical Markings: Ultra Rapid™, Sitor™, Silcu™, Protister™, Recticur™, Ultra Quick™, aR 

gR - Semiconductor Protection

Full range, short circuit protection for devices such as diodes, SCRs. etc.

Typical Markings: Ultra Rapid™, Sitor™, Silcu™, Protister™, Recticur™, Ultra Quick™, gR 

Note:

Other fuse sizes and fuse holders are available. Please refer to the Altech European Fuse catalog for more information.

gL/gG - Line Protection

Standard: IEC 20269-4-1
and IEC60269-1
Rated Voltage: 500V



10x38

Rated Current/ Rated Voltage	Cat. No.	Std. Pk.
0.5A	2620017	10
1A	2620000	10
2A	2620001	10
4A	2620003	10
6A	2620005	10
8A	2620006	10
10A	2620007	10
12A	2620008	10
16A	2620009	10
20A	2620011	10
25A	2620013	10
32A*	2620015	10

*400V

aM - Motor Protection

Standard: IEC 20269-4-1
and IEC60269-1
Rated Voltage: 500V



10x38

Rated Current/ Rated Voltage	Cat. No.	Std. Pk.
0.5A	2621017	10
1A	2621000	10
2A	2621001	10
4A	2621003	10
6A	2621005	10
8A	2621006	10
10A	2621007	10
12A	2621008	10
16A	2621009	10
20A	2621011	10
25A	2621013	10
32A*	2621015	10

*400V

aR - Semiconductor Protection

Standard: IEC 60269-4-1
Breaking Capacity: ~200 kA
Rated Voltage: ~600V**



10x38

In (A)	Cat. No.	Operating I ² -value (A's)	Power Dissipation (W)	Std. Pk.
6	2625005	30	1.5	10
8	2625006	50	2	10
10	2625007	70	2.5	10
12	2625008	120	3	10
16	2625009	150	3.5	10
20	2625011	260	4.8	10
25	2625013	290	6	10
32	2625015	600	7.5	10

** 6-25A (700V DC/ breaking capacity --- 50kA)
32A (400V DC/ breaking capacity --- 50kA)

gR - Semiconductor Protection

Standard: IEC 60269-4-1
Breaking Capacity: ~200 kA
Rated Voltage: ~690V




Certified for 700V



10x38

In (A)	Cat. No.	Operating I ² -value (A's)	Power Dissipation (W)	Std. Pk.
1	2645126	1.6	1	10
2	2645127	8	1.8	10
4	2645128	8	1.1	10
6	2645129	25	1.6	10
8	2645130	39	1.8	10
10	2645131	66	2.1	10
12	2645132	87	3.1	10
16	2645133	166	4.4	10
20	2645134	280	5.8	10
25	2645135	580	6.8	10
30	2645136	1.010	8.2	10



MINIATURE FUSES

Miniature Fuses are typically used to protect electronic devices, laboratory and measurement instruments, stereos, TV's, VCR's etc. They are available in four sizes with a current range of 20mA to 20 Amps.

Miniature Fuses are manufactured according to VDE 0820 part 1, VDE 0820 part 2, IEC publication 127, CEE publication 4 and actual DIN standards.

The 5x20, 5x25 fuses can be used in the CSFL4U series terminal blocks. The 6.3x32 fuse can be used in the CAFL4U series terminal blocks.


Operating Class:

Slow, Typical Marking: "T"


Medium, Typical Marking: "M"

Fast, Typical Marking: "F"


5 X 20



5 X 25



6.3 X 32 (1/4" X 1-1/4")



Voltage 250V AC/DC DIN 41662 IEC-127-2/III				Voltage 250V AC/DC DIN 41571-2		Voltage 250V AC/DC	
DIN 41571-2				DIN 41661 IEC-127-2/II			
Current	Cat. No.			Cat. No.		Cat. No.	
	Slow	Medium	Fast	Medium		Slow	Fast
20mA		0.02M5x20M				0.032M6.3x32Tv	
32mA		0.032M5x20M		0.032M5x25M		0.04M6.3x32Tv	
40mA				0.04M5x25M		0.05M6.3x32T ⁴	0.05M6.3x32F
50mA	0.05M5x20T ⁴	0.05M5x20M	0.05M5x20F ⁴	0.05M5x25M		0.063M6.3x32T ⁴	0.063M6.3x32F
63mA		0.063M5x20M		0.063M5x25M		0.08M6.3x32T ⁴	0.08M6.3x32F
80mA	0.08M5x20T ⁴	0.08M5x20M		0.08M5x25M		0.1M6.3x32T ⁴	0.1M6.3x32F
100mA	0.1M5x20T ⁴	0.1M5x20M	0.1M5x20F ⁴	0.1M5x25M		0.125M6.3x32T ⁴	0.125M6.3x32F
125mA	0.125M5x20T ⁴	0.125M5x20M	0.125M5x20F ⁴	0.125M5x25M		0.16M6.3x32T ⁴	0.16M6.3x32F
160mA	0.16M5x20T ⁴	0.16M5x20M	0.16M5x20F ⁴	0.16M5x25M		0.2M6.3x32T ⁴	0.2M6.3x32F
200mA	0.2M5x20T ⁴	0.2M5x20M	0.2M5x20F ⁴	0.2M5x25M		0.25M6.3x32T ⁴	0.25M6.3x32F
250mA	0.25M5x20T ⁴	0.25M5x20M	0.25M5x20F ⁴	0.25M5x25M		0.315M6.3x32T ⁴	0.315M6.3x32F
315mA	0.315M5x20T ⁴	0.315M5x20M	0.315M5x20F ⁴	0.315M5x25M			
400mA	0.4M5x20T ⁴	0.4M5x20M	0.4M5x20F ⁴	0.4M5x25M		0.4M6.3x32T ⁴	0.4M6.3x32F
500mA	0.5M5x20T ⁴	0.5M5x20M	0.5M5x20F ⁴	0.5M5x25M		0.5M6.3x32T ⁴	0.5M6.3x32F
630mA	0.63M5x20T ⁴	0.63M5x20M	0.63M5x20F ⁴	0.63M5x25M		0.63M6.3x32T ⁴	0.63M6.3x32F
700mA	0.7M5x20T ⁴	0.7M5x20M	0.7M5x20F ⁴	0.8M5x25M		0.7M6.3x32T ⁴	0.7M6.3x32F
800mA	0.8M5x20T ⁴	0.8M5x20M	0.8M5x20F ⁴			0.8M6.3x32T ⁴	0.8M6.3x32F
1.0A	1.0M5x20T ⁴	1.0M5x20M	1.0M5x20F ⁴	1.0M5x25M		1.0M6.3x32T ⁴	1.0M6.3x32F ⁴
1.25A	1.25M5x20T ⁴	1.25M5x20M	1.25M5x20F ⁴	1.25M5x25M		1.25M6.3x32T ⁴	1.25M6.3x32F ⁴
1.4A	1.4M5x20T ⁴	1.4M5x20M		1.6M5x25M			
1.6A	1.6M5x20T ⁴	1.6M5x20M	1.6M5x20F ⁴			1.6M6.3x32T ⁴	1.6M6.3x32F ⁴
2.0A	2.0M5x20T ⁴	2.0M5x20M	2.0M5x20F ⁴	2.0M5x25M		2.0M6.3x32T ⁴	2.0M6.3x32F ⁴
2.5A	2.5M5x20T ⁴	2.5M5x20M	2.5M5x20F ⁴	2.5M5x25M		2.5M6.3x32T ⁴	2.5M6.3x32F ^{2,4}
3.15A	3.15M5x20T ⁴	3.15M5x20M	3.15M5x20F ⁴	3.15M5x25M		3.15M6.3x32T ⁴	3.15M6.3x32F ^{2,4}
4.0A	4.0M5x20T ⁴	4.0M5x20M	4.0M5x20F ⁴	4.0M5x25M		4.0M6.3x32T ⁴	4.0M6.3x32F ^{2,4}
5.0A	5.0M5x20T ⁴	5.0M5x20M	5.0M5x20F ⁴	5.0M5x25M		5.0M6.3x32T ⁴	5.0M6.3x32F ^{3,4}
6.3A	6.3M5x20T ⁴	6.3M5x20M	6.3M5x20F ⁴	6.3M5x25M		6.3M6.3x32T ⁴	6.3M6.3x32F ^{3,4}
7.0A						7.0M6.3x32T ⁴	7.0M6.3x32F ³
8.0A	8.0M5x20T ¹	8.0M5x20M	8.0M5x20F ¹			8.0M6.3x32T ⁴	8.0M6.3x32F ³
10.0A	10.0M5x20T ¹	10.0M5x20M	10.0M5x20F ¹	8.0M5x25M ¹		10.0M6.3x32T ⁴	10.0M6.3x32F ³
12.5A	12.5M5x20T ¹	12.5M5x20M ¹	12.5M5x20F ¹	10.0M5x25M ¹		12.5M6.3x32T ⁴	12.5M6.3x32F ³
16.0A	16.0M5x20T ¹	16.0M5x20M ¹	16.0M5x20F ¹	16.0M5x25M ¹		16.0M6.3x32T ⁴	16.0M6.3x32F ³
20.0A	20.0M5x20T ¹	20.0M5x20M ¹	20.0M5x20F ¹			20.0M6.3x32T ⁴	20.0M6.3x32F ³
Std. Pk. 10				Std. Pk. 10		Std. Pk. 10	

- ¹ Not standard rating.
² Rated Voltage 150V.
³ Rated Voltage 60V.
⁴ UL recognized version available upon request.

THERMOCOUPLE TERMINAL BLOCK

Altech thermocouple terminal blocks are designed for use in temperature measuring circuits.

The current carrying part of the terminal blocks have the same material (according to DIN437134 and DIN43714) which is used for compensating cables in the temperature measurement circuit (up to 200°C). Thus fulfilling the norms stated in DIN EN60584.

The terminal block is marked for the respective type of thermocouple which enables easy identification for wiring.

- CTT2.5UK 'K' type - Chromel (NiCr) Alumel (NiAl)
- CTT2.5UJ 'J' type - Iron (Fe) Constantan (CuNi)
- CTT2.5UT 'T' type - Copper (Cu) Constantan (CuNi)
- CTT2.5UE 'E' type - Chromel (NiCr) Constantan (CuNi)



COLOR BLOCKS


(other than grey standard)

When ordering please add color suffix to Cat. No.

Example: CTS2.5U-N/R

Color	Ordering Suffix	
Red	R	
Blue	BU	
Black	BL	
Orange	O	
Green	G	
Yellow	Y	
White	W	
Beige	BG	
Dark Brown	DB	

CTT2.5UK/J/T/E



Terminal Width	10 mm
Height x Length	45 x 43 mm
Stripping Length	9 mm
Insulation Material	Polyamide 6.6
Current Carrying Material	Chromel/Alumel (NiCr/NiAl)
Type of Connection	4 screw clamps
Ratings:	
Wire Range	22-12 AWG
Voltage Rating	300 V
Current Rating	10 A
Torque	7 lb-in

	Cat. No.	Std. Pk.
Terminal Block	CTT2.5UK CTT2.5UJ CTT2.5UT CTT2.5UE	50 50 50 50
End Plate	EP2.5/4UN	50
Isolation Plate	PP2.5/4UN	50
DIN Rail for ordering information refer to page 63		
End Clamp	CA802 CA702	100 100

Stud Type


Terminal Blocks

Altech DIN rail mounting Stud Type Terminal Blocks are preferred for the connections that are subjected to very severe vibrations.

The wire is crimped to a ring / fork type lug and is screwed on to the flat current bar in terminal. The range includes terminal blocks for wires of size 22-4 AWG.


Jumpering can be achieved with the aid of external jumpers. The jumpers are insulated to make them shock proof. The terminal blocks have marker holding recess to accommodate MT type marking tags.

It is recommended to use protective covers in transparent plastic because assemblies of these terminals blocks are not fully covered.



CSTSN4U

CSTSN5U



Terminal Width	17 mm			17 mm		
Height x Length	44.5 x 50 mm			44.5 x 50 mm		
Stripping Length	12 mm			12 mm		
Insulation Material	Polyamide 6.6			Polyamide 6.6		
Type of Connection	2 screw connection for M4 ring/fork lugs			2 screw connection for M5 ring/fork lugs		
Approvals						
Wire Range	22-6 AWG	1.5-10 sq.mm	22-6 AWG	22-4 AWG	1.5-16 sq.mm	22-4 AWG
Voltage Rating	600 V	800 V	600 V	600 V	800 V	600 V
Current Rating	65 A	57 A	65 A	80 A	76 A	80 A
Torque	14 lb-in	1.2 Nm	14 lb-in	17.5 lb-in	2.0 Nm	17.5 lb-in

	Cat. No.	Std. Pk.	Cat. No.	Std. Pk.
Terminal Block	CSTSN4U	100	CSTSN5U	100
End Plate	EPCSTSN5U	50	EPCSTSN5U	50
DIN Rail for ordering information refer to page 62				
End Stop for ordering information refer to page 63	CA702 CA802	50 50	CA702 CA802	50 50
Protective Cover for covering	2 Terminal 3 Terminal	CSTSPC1 100 CSTSPC1-1 100	CSTSPC1 100 CSTSPC1-1 100	
Protective Cover in Length	100 mm 200 mm 300 mm	CSTSPC1-2 10 CSTSPC1-3 10 CSTSPC1-4 10	CSTSPC1-2 10 CSTSPC1-3 10 CSTSPC1-4 10	
Insulated Removable Jumpers	2 way 3 way 4 way	CA514/1-2 100 CA514/1-3 50 CA514/1-4 50	CA514/1-2 100 CA514/1-3 50 CA514/1-4 50	
Insulated Permanent Jumpers	2 way 3 way 4 way	CA514/3-2 100 CA514/3-3 50 CA514/3-4 50	CA514/3-2 100 CA514/3-3 50 CA514/3-4 50	
Marking Tags (MT Type)	MT2	100	MT2	100



COLOR BLOCKS


(other than grey standard)

When ordering please add color suffix to Cat. No.

Example: CTS2.5U-N/R

Color	Ordering Suffix
Red	R
Blue	BU
Black	BL
Orange	O
Green	G
Yellow	Y
White	W
Beige	BG
Dark Brown	DB

¹ Approval pending.

		CSTSB4U			CSTSB5U		
							
		CE			CE		
Terminal Width		17 mm			17 mm		
Height x Length		44.5 x 50 mm			44.5 x 50 mm		
Stripping Length		12 mm			12 mm		
Insulation Material		Polyamide 6.6			Polyamide 6.6		
Type of Connection		2 screw connection for M4 ring/fork lugs			2 screw connection for M5 ring/fork lugs		
Approvals		  			  		
Wire Range		22-6 AWG	1.5-10 sq.mm	22-6 AWG	22-4 AWG	1.5-16 sq.mm	22-4 AWG
Voltage Rating		600 V	800 V	600 V	600 V	800 V	600 V
Current Rating		65 A	57 A	65 A	80 A	76 A	80 A
Torque		14 lb-in	1.2 Nm	14 lb-in	17.5 lb-in	2.0 Nm	17.5 lb-in
		Cat. No.		Std. Pk.	Cat. No.		Std. Pk.
Terminal Block		CSTSB4U		100	CSTSB5U		100
End Plate		EPCSTN5U		50	EPCSTN5U		50
DIN Rail	for ordering information refer to page 62						
End Stop	for ordering information refer to page 63	CA702		50	CA702		50
		CA802		50	CA802		50
Protective Cover	for covering	2 Terminal	CSTSPC1	100	2 Terminal	CSTSPC1	100
		3 Terminal	CSTSPC1-1	100	3 Terminal	CSTSPC1-1	100
Protective Cover	in Length	100 mm	CSTSPC1-2	10	100 mm	CSTSPC1-2	10
		200 mm	CSTSPC1-3	10	200 mm	CSTSPC1-3	10
		300 mm	CSTSPC1-4	10	300 mm	CSTSPC1-4	10
Insulated Removable Jumpers		2 way	CA514/1-2	100	2 way	CA514/1-2	100
		3 way	CA514/1-3	50	3 way	CA514/1-3	50
		4 way	CA514/1-4	50	4 way	CA514/1-4	50
Insulated Permanent Jumpers		2 way	CA514/3-2	100	2 way	CA514/3-2	100
		3 way	CA514/3-3	50	3 way	CA514/3-3	50
		4 way	CA514/3-4	50	4 way	CA514/3-4	50
Marking Tags (MTType)		MT2		100	MT2		100

¹ Approval pending.

INDICATOR/ DIODE CIRCUITS


35 or 32mm DIN Rail

Altech offers different types of terminals incorporating electronic components for signal converting, circuit protection and status indication. Based on customer requirements, specially assembled terminals are offered.

CDL4U(O) - Double level terminal with open lower current bar to accommodate electronic components like diodes, resistors, LEDs, etc.

Diode Specifications

Diode	1N 4007
Diode Reverse Voltage	1000 V
Diode Current	1 A




CDL4U(E)D1/D2



With arc suppression circuit for contactors and solenoid valves - DC

CDL4U(E)D3



Diode circuit for reverse polarity protection

Terminal Width	6 mm			6 mm		
Height x Length	54 x 55.5 mm			54 x 55.5 mm		
Terminal Voltage	300 V~			300 V~		
Stripping Length	9 mm			9 mm		
Approvals						
Wire Range	22-10 AWG	0.5-4 sq.mm	22-10 AWG	22-10 AWG	0.5-4 sq.mm	22-10 AWG
Voltage Rating	600 V	400 V	600 V	600 V	400 V	600 V
Current Rating	25 A	32 A	35 A	25 A	32 A	35 A
Torque	7 lb-in	0.5 Nm	7 lb-in	7 lb-in	0.5 Nm	7 lb-in

	Cat. No.	Std. Pk.	Cat. No.	Std. Pk.
Terminal Block	CDL4U(E)D1 CDL4U(E)D2	100 100	CDL4U(E)D3	100
End Plate	EPCDL4U	50	EPCDL4U	50
DIN Rail for ordering information refer to page 62				
End Stop for ordering information refer to page 63				
Internal Jumper	2 pole 3 pole 4 pole 10 pole	CA727/2 10 CA727/3 10 CA727/4 10 CA727/10 10	CA727/2 10 CA727/3 10 CA727/4 10 CA727/10 10	
Current Bars	2 pole 3 pole 4 pole 10 pole 10 pole (breakable) 100 pole	CA703/1 100 CA704/1 100 CA705/1 100 CA732/10 100 CA732/10-A 100 CA732/100 10	CA703/1 100 CA704/1 100 CA705/1 100 CA732/10 100 CA732/10-A 100 CA732/100 10	
Shorting Sleeve & Screw		CA607/S/Q 100	CA607/S/Q 100	
Marking Tags (MT Type)		MT2 100	MT2 100	





COLOR BLOCKS




(other than grey standard)

When ordering please add color suffix to Cat. No.







Example: CTS2.5U-N/R


Color	Ordering Suffix
Red	R
Blue	BU
Black	BL
Orange	O
Green	G
Yellow	Y
White	W
Beige	BG
Dark Brown	DB




CDL4U(E)DD1/DD2	CDL4U(E)DD3/DD4	CDL4U(E)D4	CDL4U(E)DD5
			
Diode circuit for lamp testing	Diode circuit for lamp testing	Diode circuit for lamp testing with LED series resistance	Diode circuit for lamp testing with LED series resistance
6 mm	6 mm	6 mm	6 mm
54 x 55.5 mm	54 x 55.5 mm	54 x 55.5 mm	54 x 55.5 mm
300 V~	300 V~	24 V~	24 V~
9 mm	9 mm	9 mm	9 mm
  	  	  	  
22-10 AWG 0.5-4 sq.mm 22-10 AWG	22-10 AWG 0.5-4 sq.mm 22-10 AWG	22-10 AWG 0.5-4 sq.mm 22-10 AWG	22-10 AWG 0.5-4 sq.mm 22-10 AWG
600 V 400 V 600 V	600 V 400 V 600 V	600 V 400 V 600 V	600 V 400 V 600 V
25 A 32 A 35 A	25 A 32 A 35 A	25 A 32 A 35 A	25 A 32 A 35 A
7 lb-in 0.5 Nm 7 lb-in	7 lb-in 0.5 Nm 7 lb-in	7 lb-in 0.5 Nm 7 lb-in	7 lb-in 0.5 Nm 7 lb-in

Cat. No.	Std. Pk.	Cat. No.	Std. Pk.	Cat. No.	Std. Pk.	Cat. No.	Std. Pk.
CDL4U(E)DD1 100		CDL4U(E)DD3 100		CDL4U(E)D4 100		CDL4U(E)DD5 100	
CDL4U(E)DD2 100		CDL4U(E)DD4 100					
EPCDL4U 50		EPCDL4U 50		EPCDL4U 50		EPCDL4U 50	
							
CA702 50		CA702 50		CA702 50		CA702 50	
CA802 50		CA802 50		CA802 50		CA802 50	
CA727/2 10		CA727/2 10		CA727/2 10		CA727/2 10	
CA727/3 10		CA727/3 10		CA727/3 10		CA727/3 10	
CA727/4 10		CA727/4 10		CA727/4 10		CA727/4 10	
CA727/10 10		CA727/10 10		CA727/10 10		CA727/10 10	
CA703/1 100		CA703/1 100		CA703/1 100		CA703/1 100	
CA704/1 100		CA704/1 100		CA704/1 100		CA704/1 100	
CA705/1 100		CA705/1 100		CA705/1 100		CA705/1 100	
CA732/10 100		CA732/10 100		CA732/10 100		CA732/10 100	
CA732/10-A 100		CA732/10-A 100		CA732/10-A 100		CA732/10-A 100	
CA732/100 10		CA732/100 10		CA732/100 10		CA732/100 10	
CA607/S/Q 100		CA607/S/Q 100		CA607/S/Q 100		CA607/S/Q 100	
MT2 100		MT2 100		MT2 100		MT2 100	






CDL4U(E)N1




AC voltage indicator with neon lamp

CDL4U(E)LD5*



AC voltage indicator with LED

CDL4U(E)LD3*



AC/DC voltage indicator with LED

Terminal Width

6 mm

6 mm

6 mm

Height x Length

54 x 55.5 mm

54 x 55.5 mm

54 x 55.5 mm

Terminal Voltage

100 V~ to 220 V

24 V~, 48 V~, 120V~, 220V~

12 V~, 24 V~

Stripping Length

9 mm

9 mm

9 mm

Approvals



Wire Range

22-10 AWG 0.5-4 sq.mm 22-10 AWG

22-10 AWG 0.5-4 sq.mm 22-10 AWG

22-10 AWG 0.5-4 sq.mm 22-10 AWG

Voltage Rating

600 V 400 V 600 V

600 V 400 V 600 V

600 V 400 V 600 V

Current Rating

25 A 32 A 35 A

25 A 32 A 35 A


25 A 32 A 35 A


Torque

7 lb-in 0.5 Nm 7 lb-in


7 lb-in 0.5 Nm 7 lb-in

7 lb-in 0.5 Nm 7 lb-in


		Cat. No.	Std. Pk.		Cat. No.	Std. Pk.		Cat. No.	Std. Pk.	
Terminal Block		CDL4U(E)N1	50		CDL4U(E)LD5*	50		CDL4U(E)LD3*	50	
End Plate		EPCDL4U	50		EPCDL4U	50		EPCDL4U	50	
DIN Rail for ordering information refer to page 62										
End Stop for ordering information refer to page 63		CA702	50		CA702	50		CA702	50	
		CA802	50		CA802	50		CA802	50	
Internal Jumper		2 pole	CA727/2	10	2 pole	CA727/2	10	2 pole	CA727/2	10
		3 pole	CA727/3	10	3 pole	CA727/3	10	3 pole	CA727/3	10
		4 pole	CA727/4	10	4 pole	CA727/4	10	4 pole	CA727/4	10
		10 pole	CA727/10	10	10 pole	CA727/10	10	10 pole	CA727/10	10
Current Bars		2 pole	CA703/1	100	2 pole	CA703/1	100	2 pole	CA703/1	100
		3 pole	CA704/1	100	3 pole	CA704/1	100	3 pole	CA704/1	100
		4 pole	CA705/1	100	4 pole	CA705/1	100	4 pole	CA705/1	100
		10 pole	CA732/10	100	10 pole	CA732/10	100	10 pole	CA732/10	100
		10 pole (breakable)	CA732/10-A	100	10 pole (breakable)	CA732/10-A	100	10 pole (breakable)	CA732/10-A	100
		100 pole	CA732/100	10	100 pole	CA732/100	10	100 pole	CA732/100	10
Shorting Sleeve & Screw		CA607/S/Q	100		CA607/S/Q	100		CA607/S/Q	100	
Marking Tags (MTType)		MT2	100		MT2	100		MT2	100	



N1













LD5



LD3

* Add required voltage to part number as a suffix
i.e. CDL4U(E)LD5/110 is for 110V.

CDL4U(E)LD4*	CDL4U(E)LD1/LD2	CDL4U(E)L1/L2*	CDL4U(O)
			
AC/ DC voltage indicator with LED	DC voltage indicator with LED	DC voltage indicator with LED	Electronic Component Carrier
6 mm	6 mm	6 mm	6 mm
54 x 55.5 mm	54 x 55.5 mm	54 x 55.5 mm	54 x 55.5 mm
24 V~	24 V–	6 V–, 24 V–, 60 V–	–
9 mm	9 mm	9 mm	9 mm
  	  	  	  
22-10 AWG 0.5-4 sq.mm 22-10 AWG	22-10 AWG 0.5-4 sq.mm 22-10 AWG	22-10 AWG 0.5-4 sq.mm 22-10 AWG	22-10 AWG 0.5-4 sq.mm 22-10 AWG
600 V 400 V 600 V	600 V 400 V 600 V	600 V 400 V 600 V	600 V 400 V 600 V
25 A 32 A 35 A	25 A 32 A 35 A	25 A 32 A 35 A	25 A 32 A 35 A
7 lb-in 0.5 Nm 7 lb-in	7 lb-in 0.5 Nm 7 lb-in	7 lb-in 0.5 Nm 7 lb-in	7 lb-in 0.5 Nm 7 lb-in

Cat. No.	Std. Pk.	Cat. No.	Std. Pk.	Cat. No.	Std. Pk.	Cat. No.	Std. Pk.
CDL4U(E)LD4*	50	CDL4U(E)LD1 CDL4U(E)LD2	50 50	CDL4U(E)L1* CDL4U(E)L2*	50 50	CDL4U(O)	100
EPCDL4U	50	EPCDL4U	50	EPCDL4U	50	EPCDL4U	50
							
CA702 50 CA802 50		CA702 50 CA802 50		CA702 50 CA802 50		CA702 50 CA802 50	
CA727/2 10 CA727/3 10 CA727/4 10 CA727/10 10		CA727/2 10 CA727/3 10 CA727/4 10 CA727/10 10		CA727/2 10 CA727/3 10 CA727/4 10 CA727/10 10		CA727/2 10 CA727/3 10 CA727/4 10 CA727/10 10	
CA703/1 100 CA704/1 100 CA705/1 100 CA732/10 100 CA732/10-A 100 CA732/100 10		CA703/1 100 CA704/1 100 CA705/1 100 CA732/10 100 CA732/10-A 100 CA732/100 10		CA703/1 100 CA704/1 100 CA705/1 100 CA732/10 100 CA732/10-A 100 CA732/100 10		CA703/1 100 CA704/1 100 CA705/1 100 CA732/10 100 CA732/10-A 100 CA732/100 10	
CA607/S/Q 100		CA607/S/Q 100		CA607/S/Q 100		CA607/S/Q 100	
MT2 100		MT2 100		MT2 100		MT2 100	
		 		 			
LD4		LD1 LD2		L1 L2			


* Add required voltage to part number as a suffix
i.e. CDL4U(E)LD5/110 is for 110V

* Add required voltage to part number as a suffix
i.e. CDL4U(E)LD5/110 is for 110V.


SURGE SUPPRESSOR TERMINAL BLOCKS

In applications where circuit protection against transient overvoltage is required, Altech Surge Suppressor Terminal Blocks with built-in electronic components are recommended.


These terminals are designed to protect a single line against a longitudinal (line / earth) surge, thereby protecting distribution and inputs.



CDL4U(E)LA



CDL4U(E)3LA



Lightning Arrestor

3 Pole Lightning Arrestor

Terminal Width	12 mm	18 mm
Height x Length	54 x 55.5 mm	54 x 55.5 mm
Stripping Length	9 mm	9 mm
Insulation Material	Polyamide 6.6	Polyamide 6.6
Type of Connection	4 screw clamps	4 screw clamps
Ratings		
Wire Range	22-10 AWG	22-10 AWG
Voltage Rating	75, 90, 240, 600, 1000 V DC	90, 250, 350, 450 V DC
Nominal Discharge Current	20 KA (8/20 μ s)	10 KA (8/20 μ s)
Peak Current	–	–
Response Time	100 ns	100 ns
Nominal Current	10A	5A
Capacitance	<1.5 pf	<1.0 pf
Application	For coarse line protection of measuring, distributing or data communication interfaces.	For simultaneous protection of lines against transversal (line/line) and longitudinal (line/earth) surge.

	Cat. No.	Std. Pk.	Cat. No.	Std. Pk.
Terminal Block	CDL4U(E)LA*	20	CDL4U(E)3LA*	20
End Plate 	EPCDL4U	50	EPCDL4U	50
DIN Rail for ordering information refer to page 62				
End Stop for ordering information refer to page 63	CA702 CA802	50 50	CA702 CA802	50 50
Marking Tags (MT Type) 	MT2	100	MT2	100





COLOR BLOCKS

(other than grey standard)

When ordering please add color suffix to Cat. No.


Example: CTS2.5U-N/R

Color	Ordering Suffix
Red	R
Blue	BU
Black	BL
Orange	O
Green	G
Yellow	Y
White	W
Beige	BG
Dark Brown	DB



* Add required voltage to part number as a suffix
i.e. CDL4U(E)LA/75 is for 75V.

CDL4U(E)MOV¹



MOV

12 mm

54 x 55.5 mm

9 mm

Polyamide 6.6

4 screw clamps

22-10 AWG

130 V AC*

–

2kA-6.5kA (8/20 μ s)


<25ns

10A

100-20,000 pf

For protection from voltage surge, spikes

CDL4U(E)SD



Suppressor Diode

12 mm

54 x 55.5 mm

9 mm

Polyamide 6.6

4 screw clamps

22-10 AWG

12-48V DC / 12-160V AC**

1.5 KA (8/20 μ s)

–


1 ns DC / 5 ns AC

10A

–

For fine protection of data interfaeces, sensors, contacts, etc.

CDL4U(E)RC



RC Circuit

18 mm

54 x 55.5 mm

9 mm

Polyamide 6.6

4 screw clamps

22-10 AWG

250 V AC / 330 V DC

20A

–

–

10A

0.1 μ f or 0.22 μ f²

For protection of DC solenoid valves and contactors

Cat. No. Std. Pk.

CDL4U(E)MOV 20

EPCDL4U 50



CA702 50

CA802 50

MT2 100

Cat. No. Std. Pk.

CDL4U(E)SD 20

EPCDL4U 50



CA702 50


CA802 50

MT2 100

Cat. No. Std. Pk.

CDL4U(E)RC 10




EPCDL4U 50



CA702 50

CA802 50

MT2 100



¹ A fuse block is recommended to protect MOV terminals by disconnecting the faulted varistor. See pages 28-30 for fuse blocks.

* Other voltages available upon request. Call Altech for voltage selection.

** Phase to Phase / Phase to ground. Call Altech for voltage selection.

TAB, TERMI-POINT® TERMINAL BLOCKS

CTC4U Tab Connection terminals offer quick connection. Connection is achieved by pushing the lug onto the tab blade of the terminal block. The terminal housing is so designed that the wall protrudes beyond the tab blades.

The CTS4U-TM single level and the CDL4U-TM double level terminal blocks have a provision for clip connection according to DIN 41611-4. Three wires (0.5 sq. mm) can be connected with a clip onto the pin using a special tool (*contact Altech for information*). These terminal blocks provide high wiring density without extension of the mounting rail.

CTC4U is used primarily in railway systems. The CTS4U-TM and the CDL4U-TM is used mostly in the telecommunications industry.







COLOR BLOCKS (other than grey standard)

When ordering please add color suffix to Cat. No.

Example: CTS2.5U-N/R

Color	Ordering Suffix
Red	R
Blue	BU
Black	BL
Orange	O
Green	G
Yellow	Y
White	W
Beige	BG
Dark Brown	DB



CTC4U		CTS4U-TM		CDL4U-TM	
					
6 mm		6 mm		6 mm	
49.5 x 47 mm		67 x 43 mm		84 x 55.5 mm	
9 mm		9 mm		9 mm	
Polyamide 6.6		Polyamide 6.6		Polyamide 6.6	
5 tab connection points and 1 tapped hole for cross connection		1 screw connection and 1 blade for 3 (0.5 sq. mm) connections		2 screw connections and 2 blades for 6 (0.5 sq. mm) connections	
0.5-4 sq.mm	22-12 AWG	0.5-4 sq.mm	22-12 AWG	0.5-4 sq.mm	22-12 AWG
250 V	300 V	250 V	300 V	250 V	300 V
32 A	25 A	10 A	10 A	10 A	10 A
6.3 x 0.8	6.3 x 0.8	0.8 x 1.6	0.8 x 1.6	0.8 x 1.6	0.8 x 1.6
Cat No.	Std. Pk.	Cat No.	Std. Pk.	Cat No.	Std. Pk.
CTC4U	100	CTS4U-TM	100	CDL4U-TM	100
EPCTC4U	50	EP2.5/4UN	50	EPCDL4U	50
					
CA702	50	CA702	50	CA702	50
CA802	50	CA802	50	CA802	50
CA727/2	100	CA722/2	100	CA727/2	10
CA727/3	50	CA722/3	50	CA727/3	10
CA727/4	50	CA722/4	50	CA727/4	10
CA727/10	10	CA722/10	10	CA727/10	10
CA747/2	100	CA742/2	100	CA747/2	100
CA747/3	50	CA742/3	50	CA747/3	50
CA747/4	50	CA742/4	50	CA747/4	50
CA747/10	10	CA742/10	10	CA747/10	10
CA703/1	100	CA703/1	100	CA703/1	100
CA704/1	100	CA704/1	100	CA704/1	100
CA705/1	100	CA705/1	100	CA705/1	100
CA732/10	100	CA732/10	100	CA732/10	100
CA732/10-A	100	CA732/10-A	100	CA732/10-A	100
CA732/100	10	CA732/100	10	CA732/100	10
CA607/S/Q	100	CA707/S/Q/01	100	CA607/S/Q	100
		CA713/2	100	CA714/2	100
		CA713/3	100	CA714/3	100
		CA713/4	50	CA714/4	50
		CA713/10	25	CA714/10	25
MT6	100	MT6	100	MT2	100


HIGH TEMPERATURE CERAMIC EUROBLOCKS™

Suitable for use in high temperature applications up to 600°C (1112°F). Applications include hot melt glue guns, furnaces, heaters, process equipment and machinery. Terminal blocks are offered with mounting holes for panel mounting or free floating applications.

- Compact, space saving
 - Tubular screw clamp
 - Free float or panel mount
 - Temperature range: 600°C (1112°F)
 - Standard color: white
 - Material
- Housing: ceramic
Clamp: brass
Screws: zinc plated steel



Insulation Material	CB4		CB6		CB16	
Approvals	Ceramic C  US E220514		Ceramic C  US E220514		Ceramic C  US E220514	
Wire Range	24-12 AWG		22-10 AWG		20-6 AWG	
Voltage Rating	300V		300V		300V	
Current Rating	30 A		40 A		76 A	
	20 A		30 A		65 A	
No. of Poles	Cat. No.	Std. Pk.	Cat. No.	Std. Pk.	Cat. No.	Std. Pk.
1 (free floating)	CB4/1	50	CB6/1	50		
2 (free floating)	CB4/2	50				
2 (with mounting holes)	CB4/2H	50	CB6/2H	50	CB16/2H	50
3 (free floating)	CB4/3	50				
3 (with mounting holes)	CB4/3H	50	CB6/3H	50	CB16/3H	50



Dimensions mm

		W	T	H	C	D1	D2	Fixing Screw	Stripping Length
CB4/1	1 POLE	23	11	18.5	*				6
CB4/2	2 POLE	23	18	18.5	*				6
CB4/2H	2 POLE	23	24	18.5	14.6	6	3.5	M3X16	6
CB4/3	3 POLE	25	25	18.5	*				6
CB4/3H	3 POLE	25.4	36	18.5	13	6	3.5	M3X16	6
CB6/1	1 POLE	25	12	19.5	*				6
CB6/2H	2 POLE	25.5	26	19.5	12.6	6		M3X16	6
CB6/3H	3 POLE	25.5	41	19.5	15	6		M3X16	6
CB16/2H	2 POLE	28	31	23.2	16.5	6	3.5	M3X20	8.5
CB16/3H	3 POLE	27.5	48	23.2	17	6	3.5	M3X20	8.5


Note: All dimensions are shown in mm, to convert to inches please divide by 25.4.

MINI FEED-THROUGH

15mm DIN Rail

For wire-to-wire connecting in control, automation, instrumentation and power distribution applications.

Altech "miniature" terminal blocks offer tremendous space advantage as demanded by certain wiring configurations.



FUSE BLOCKS

Certain electrical and control systems require protection by fuses. The terminal has a hinged carrier that has a specially designed space for a cartridge type glass fuse of size Ø5 x 20 or Ø5 x 25 mm. The fuse can be engaged or disengaged by the movement of the carrier.

Altech fuse terminals are also available with light indication - CSFL 4U (L). A specially designed built-in circuit gives light indication in the event of fuse blow out.

† Fuses are sold separately
Altech, see page 34
for details.



COLOR BLOCKS

(other than grey standard)

When ordering please add color suffix to Cat. No.

Example: CTS2.5U-N/R

Color	Ordering Suffix
Red	R
Blue	BU
Black	BL
Orange	O
Green	G
Yellow	Y
White	W
Beige	BG
Dark Brown	DB


* Add required voltage to part number as a suffix, i.e. CSFL4U(L)/24 for 24V DC

CMT4



CE



CMT4S



CE

Terminal Width	6 mm	6 mm
Height x Length	29 x 27 mm	29 x 46 mm
Stripping Length	9 mm	9 mm
Insulation Material	Polyamide 6.6	Polyamide 6.6
Type of Connection	2 screw clamps & 1 tapped hole for cross connection	2 screw clamps, 2 solder points and 1 tapped hole for cross connection
Type of Fuse Used	—	—
Approvals		
Wire Range	22-10 AWG 0.5-4 sq.mm	22-10 AWG Upto 1.5 sq.mm
Voltage Rating	300 V 400 V 300 V	300 V 160 V 300 V
Current Rating	35 A 32 A 35 A	25 A 15 A 35 A
Torque	6 lb-in 0.5 Nm 7 lb-in	7 lb-in 0.5 Nm 7 lb-in

		Cat. No.	Std. Pk.	Cat. No.	Std. Pk.
Terminal Block		CMT4	100	CMT4S	50
End Plate		EPCMT4	50	EPCMT4	50
Isolation Partition		PPCMT4	50	PPCMT4	50
DIN Rail for ordering information refer to page 62		15 mm		15 mm	
End Stop for ordering information refer to page 63		CA602	100	CA602	50
Internal Jumper		2 pole 3 pole 4 pole 10 pole	CA727/2 100 CA727/3 50 CA727/4 50 CA727/10 10	2 pole 3 pole 4 pole 10 pole	CA727/2 100 CA727/3 50 CA727/4 50 CA727/10 10
Insulated Internal Jumper		2 pole 3 pole 4 pole 10 pole	CA747/2 100 CA747/3 50 CA747/4 50 CA747/10 10	2 pole 3 pole 4 pole 10 pole	CA747/2 100 CA747/3 50 CA747/4 50 CA747/10 10
Current Bars		2 pole 3 pole 4 pole 10 pole 10 pole (breakable) 100 pole	CA703/1 100 CA704/1 100 CA705/1 100 CA732/10 100 CA732/10-A 100 CA732/100 10	2 pole 3 pole 4 pole 10 pole 10 pole (breakable) 100 pole	CA703/1 100 CA704/1 100 CA705/1 100 CA732/10 100 CA732/10-A 100 CA732/100 10
Shorting Sleeve & Screw		CA607/S/Q	100	CA607/S/Q	100
External Jumper		2 pole 3 pole 4 pole 10 pole	CA714/2 100 CA714/3 100 CA714/4 50 CA714/10 25	2 pole 3 pole 4 pole 10 pole	CA714/2 100 CA714/3 100 CA714/4 50 CA714/10 25
Marking Tags (MT Type) (MT Type on Lever)		MT2	100	MT2	100

CMT4SU			CSFL4U			CSFL4U(L)*			CGMT4					
														
CE			† Fuse not included.			† Fuse not included.			CE					
6 mm			8 mm			8 mm			6 mm					
29 x 35.5 mm			43 x 58 mm			43 x 58 mm			28.5 x 27 mm					
9 mm			9.5 mm			9.5 mm			9 mm					
Polyamide 6.6			Polyamide 6.6			Polyamide 6.6			Polyamide 6.6					
2 uneven level solder points & 1 tapped hole for cross connection			2 screw clamps			2 screw clamps			2 screw clamps					
—			Ø5x20, Ø5x25mm			Ø5x20, Ø5x25mm			—					
														
22-14 AWG Upto 1.5 sq.mm 22-14 AWG			22-10 AWG 0.5-4 sq.mm 22-10 AWG			22-10 AWG 0.5-4 sq.mm 22-10 AWG			22-10 AWG 0.5-4 sq.mm 22-10 AWG					
300 V 160 V 300 V			600 V 600 V 600 V			600 V 600 V 600 V								
15 A 15 A 20 A			6.3 A 6.3 A 8 A			6.3 A 6.3 A 8 A								
— — —			7 lb-in 0.5 Nm 7 lb-in			7 lb-in 0.5 Nm 7 lb-in			7 lb-in 0.5 Nm 7 lb-in					
Cat. No.			Std. Pk.		Cat. No.			Std. Pk.		Cat. No.			Std. Pk.	
CMT4SU			100		CSFL4U			100		CSFL4U(L)*			100	
EPCMT4			50		EPCSFL4U			50		EPCSFL4U			50	
PPCMT4			50		PPCSFL4U			50		PPCSFL4U			50	
			15 mm											
CA602			50		CA602			100		CA602			100	
CA727/2			100											
CA727/3			50											
CA727/4			50											
CA727/10			10											
CA747/2			100											
CA747/3			50											
CA747/4			50											
CA747/10			10											
CA703/1			10											
CA704/1			10											
CA705/1			10											
CA732/10			10											
CA732/10-A			100											
CA732/100			10											
CA607/S/Q			10											
					CA711/2			100		CA711/2			100	
					CA711/3			100		CA711/3			100	
					CA711/4			50		CA711/4			50	
					CA711/10			25		CA711/10			25	
MT2			100		MT8			100		MT8			100	
					MT2			100		MT2			100	

MINI FEED-THROUGH

Panel Mount

For use when space constraints require extremely compact solutions and internal jumping is required.

Individual components can be used to build your own assemblies. Just snap the required number of terminal block components together and place a Mounting Section on each end.

The CMB 4 accepts internal jumpers and standard marking tags.

- Extremely compact and cost effective
- High density
- Screw-cage clamp
- Internal jumping provision
- Polyamide 6.6
- Standard color: gray




COLOR BLOCKS

(other than grey standard)

When ordering please add color suffix to Cat. No.

Example: CTS2.5U-N/R

Color	Ordering Suffix
Red	R
Blue	BU
Black	BL
Orange	O
Green	G
Yellow	Y
White	W
Beige	BG
Dark Brown	DB



CMB4



Terminal Width	6 mm
Height x Length	28 x 27 mm
Stripping Length	9 mm
Insulation Material	Polyamide 6.6
Type of Connection	2 screw clamps & 1 tapped hole for cross connection
Approvals	
Wire Range	22-10 AWG 0.5-4 sq.mm 22-10 AWG
Voltage Rating	300 V 400 V 300 V
Current Rating	35 A 32 A 35 A
Torque	7 lb-in 0.5 Nm 7 lb-in

Terminal Block	Cat. No.	Std. Pk.
Terminal Block	CMB4	100
Mounting Section	EPCMB4	50
Separator Plate	SPCMB4	100
Mounting Screw*		

Internal Jumper			
	2 pole	CA727/2	100
	3 pole	CA727/3	50
	4 pole	CA727/4	50
	10 pole	CA727/10	10


Insulated Internal Jumper			
	2 pole	CA747/2	100
	3 pole	CA747/3	50
	4 pole	CA747/4	50
	10 pole	CA747/10	10

Current Bars			
	2 pole	CA703/1	100
	3 pole	CA704/1	100
	4 pole	CA705/1	100
	10 pole	CA732/10	100
	10 pole (breakable)	CA732/10-A	100
	100 pole	CA732/100	10


Shorting Sleeve & Screw	CA607/S/Q	100
-------------------------	-----------	-----

External Jumper			
	2 pole	CA714/2	100
	3 pole	CA714/3	100
	4 pole	CA714/4	50
	10 pole	CA714/10	25

Marking Tags (MT Type)	MT2	100
------------------------	-----	-----




Preamsembled blocks are also available for quick and easy installations.
See Dimensions below.



Dimensions mm (in.)
CMB4

Cat No.	No. of Poles	Width (a)	Hole Spacing (b)
CMB4/2	2	26 (1.02)	19 (0.75)
CMB4/3	3	32 (1.26)	25 (0.98)
CMB4/4	4	38 (1.50)	31 (1.22)
CMB4/5	5	44 (1.73)	37 (1.46)
CMB4/6	6	50 (1.97)	43 (1.69)
CMB4/7	7	56 (2.20)	49 (1.93)
CMB4/8	8	62 (2.44)	55 (2.17)
CMB4/9	9	68 (2.68)	61 (2.40)
CMB4/10	10	74 (2.91)	67 (2.64)
CMB4/11	11	80 (3.15)	73 (2.87)
CMB4/12	12	86 (3.39)	79 (3.11)
CMB4/13	13	92 (3.62)	85 (3.35)
CMB4/14	14	98 (3.86)	91 (3.58)
CMB4/15	15	104 (4.09)	97 (3.82)
CMB4/16	16	110 (4.33)	103 (4.06)
CMB4/17	17	116 (4.57)	109 (4.29)
CMB4/18	18	122 (4.80)	115 (4.53)
CMB4/19	19	128 (5.04)	121 (4.76)
CMB4/20	20	134 (5.28)	127 (5.00)
CMB4/21	21	140 (5.51)	133 (5.24)
CMB4/22	22	146 (5.75)	139 (5.47)
CMB4/23	23	152 (5.98)	145 (5.71)
CMB4/24	24	158 (6.22)	151 (5.94)



Mounting Section
EPCMB4

* Any length M3 screw may be used.

BUSBAR SYSTEM

Panel Mount

A quick reliable solution for ground, neutral or low voltage distribution applications. The Busbar System consists of a busbar, busbar supports, and screw clamp terminals for terminating wires


NEB 10 (10 x 3 mm) and NEB 6 (6 x 6 mm), tin plated copper busbars are available in one meter lengths. Both have a 140A current carrying capacity.

NES plastic support with fixing screws for holding 10 x 3 & 6 x 6 busbar makes placing of busbar an easy task. Busbars up to 200 mm length should be supported at ends by two busbar supports. For busbars exceeding 200 mm length, it is recommended to provide intermediate busbar support. Easy to operate CENC clamp secures wire to the busbar.



	CENC4	CENC16	CENC35
			
			
			
Terminal Width	7.5 mm	9.8 mm	14.5 mm
Height x Length	30 x 23.3 mm	36 x 23.3 mm	45 x 27.3 mm
Stripping Length	12 mm	16 mm	16 mm
Insulation Material	Polyamide 6.6	Polyamide 6.6	Polyamide 6.6
Type of Connection	1 screw clamp connection	1 screw clamp connection	1 screw clamp connection
Approvals			
Wire Range	22-12 AWG 0.5-6 sq.mm 22-12 AWG	9-6 AWG 6-16 sq.mm 10-6 AWG	7-2 AWG 10-35 sq.mm 8-2 AWG
Current Rating*	25 A 41 A	76 A 76 A	125 A 125 A
Torque	14 lb-in 0.8 Nm 14 lb-in	14 lb-in 2.0 Nm 17.5 lb-in	25 lb-in 2.5 Nm 25 lb-in

	Cat. No.	Std. Pk.	Cat. No.	Std. Pk.	Cat. No.	Std. Pk.
Terminal Block Green Cap **	CENC4	50	CENC16	50	CENC35	50
Busbar (10 x 3 mm) 	NEB10	1 m	NEB10	1 m	NEB10	1 m
Busbar (6 x 6 mm) 	NEB6	1 m	NEB6	1 m	NEB6	1 m
Plastic Support with Fixing Screw 	NES	50	NES	50	NES	50
End Clamp/Bus bar support for rail mounting	CA202	50	CA202	50	CA202	50
Marking Tags (MT Type) 	MT5	100	MT6	100	MT6	100




* 140A current carrying capacity of busbar should be taken into account while connecting loads.

** Consult for other available colors.

FEED-THROUGH Spring Clamp Terminals


These terminal blocks offer a time saving alternative to the popular screw clamp connection. They can be mounted on 35 mm DIN rails. Insulated push-in type jumpers offer a quick and shock proof solution for most cross-connection applications.




CSC2.5T



CSC4T



CSC6T



Terminal Width	5 mm	6 mm	8 mm
Height x Length	36 x 58 mm	42 x 65 mm	45 x 72 mm
Stripping Length	9 mm	9 mm	12 mm
Insulation Material	Polyamide 6.6	Polyamide 6.6	Polyamide 6.6
Type of Connection	2 spring clamps & 2 slots for interconnection	2 spring clamps & 2 slots for interconnection	2 spring clamps & 2 slots for interconnection
Approvals	  	  	  
Wire Range	22-14 AWG 0.5-2.5 sq.mm 22-14 AWG	22-12AWG 0.5-4 sq.mm 22-12 AWG	22-8AWG 0.5-8sq.mm 22-8AWG
Voltage Rating	600 V 750 V 600 V	600 V 750 V 600 V	600 V 750 V 600 V
Current Rating	20 A 24 A 20 A	25 A 32 A 25 A	50 A 41 A 50 A

MULTI-CONNECTION Spring Clamp Terminals

Altech Multiple connection Spring Clamp terminals offer a reliable solution for problems posed by multiple voltage connections. The terminal eliminates conventional method of cross connection / looping, saving additional space.

The terminals provide of further multiplication connections through bridging. The Multiple Connection Terminal Blocks can even be bridged to Standard Feed Through Spring Clamp Terminal Block of respective wire size (CSC2.5T / CSC4T / CSC6T).

	Cat. No.	Std. Pk.	Cat. No.	Std. Pk.	Cat. No.	Std. Pk.
Terminal Block	CSC2.5T	100	CSC4T	100	CSC6T	50
End Plate 	EPCSC2.5T	50	EPCSC4T	50	EPCSC6T	50
Partition Plate 	PPCSC2.5T	50	PPCSC4T	50	PPCSC6T	50
DIN Rail for ordering information refer to page 62						
End Stop for ordering information refer to page 63 	CA702 50 CA802 50		CA702 50 CA802 50		CA702 50 CA802 50	
Jumpers Adjacent Alternate 	CA801/1 100 CA801/1-3 100		CA801/2 100 CA801/2-3 100		CA801/3 100 CA801/3-3 100	
Push in type wire jumper 	CA901/1 100		CA901/2 100		CA901/3 100	
Marking Tags (MT Type) 	MT5 100		MT6 100		MT8 100	

COLOR BLOCKS

(other than grey standard)

When ordering please add color suffix to Cat. No.

Example: CTS2.5U-N/R



Color

Red
Blue
Black
Orange
Green
Yellow
White
Beige
Dark Brown


Ordering Suffix

R
BU
BL
O
G
Y
W
BG
DB



CSC10T	CSC2.5T1-2	CSC2.5T2-2	CSC4T1-2
			
CE	CE	CE	CE
10 mm	5 mm	5 mm	6 mm
50 x 75 mm	36 x 74 mm	36 x 90 mm	42 x 85 mm
12 mm	9 mm	9 mm	9 mm
Polyamide 6.6	Polyamide 6.6	Polyamide 6.6	Polyamide 6.6
2 spring clamps & 2 slots for interconnection	3 spring clamps & 2 slots for interconnection	4 spring clamps & 2 slots for interconnection	3 spring clamps & 2 slots for interconnection
  	  	  	  
16-6 AWG 1.5-10 sq.mm. 16-6AWG	22-14 AWG 0.5-2.5 sq.mm. 22-14 AWG	22-14 AWG 0.5-2.5 sq.mm. 22-14 AWG	22-12 AWG 0.5-4 sq.mm. 22-12 AWG
600V 800V 600V	600V 750V 600V	600V 750V 600V	600V 750V 600V
65 A 57 A 65 A	20A 24 A 20 A	20A 24 A 20 A	25A 32 A 25 A

Cat. No.	Std. Pk.	Cat. No.	Std. Pk.	Cat. No.	Std. Pk.	Cat. No.	Std. Pk.
CSC10T	100	CSC2.5T1-2	100	CSC2.5T2-2	50	CSC4T1-2	50
EPCSC10T	50	EPCSC2.5T1-2	50	EPCSC2.5T2-2	50	EPCSC4T1-2	50

			
CA702 50	CA702 50	CA702 50	CA702 50
CA802 50	CA802 50	CA802 50	CA802 50

CA801/4 100	CA801/1 100 CA801/1-3 100	CA801/1 100 CA801/1-3 100	CA801/2 100 CA801/2-3 100
	CA901/1 100	CA901/1 100	CA901/2 100

MT10 100	MT5 100	MT5 100	MT6 100
----------	---------	---------	---------

*UL& CSA pending.

	CSC4T2-2			CSC6T1-2			ADL2.5		
									
	CE			CE			CE		
Terminal Width	6 mm			8 mm			5 mm		
Height x Length	42 x 105 mm			45 x 94 mm			50 x 79.5 mm		
Stripping Length	9 mm			12 mm			9 mm		
Insulation Material	Polyamide 6.6			Polyamide 6.6			Polyamide 6.6		
Type of Connection	4 spring clamps & 2 slots for interconnection			3 spring clamps & 2 slots for interconnection			4 spring clamps & 4 slots for interconnection		
Approvals	  			  			  		
Wire Range	22-12 AWG	0.5-4 sq.mm.	22-12 AWG	22-8 AWG	0.5-6 sq.mm.	22-8 AWG	22-14 AWG	2.5 sq.mm.	22-14 AWG
Voltage Rating	600 V	750 V	600 V	600 V	800 V	600 V	600 V	500 V	600 V
Current Rating	25 A	32 A	25 A	50 A	41 A	50 A	20 A	24 A	20 A
Terminal Block	Cat. No.	Std. Pk.		Cat. No.	Std. Pk.		Cat. No.	Std. Pk.	
	CSC4T2-2	50		CSC6T1-2	50		ADL2.5	50	
End Plate 	EPCSC4T2-2	50		EPCSC6T1-2	50		EPADL2.5	50	
DIN Rail for ordering information refer to page 62									
End Stop for ordering information refer to page 63 	CA702	50		CA702	50		CA702	50	
	CA802	50		CA802	50		CA802	50	
Jumpers Adjacent Alternate 	CA801/2	100		CA801/3	100		CA801/1	100	
	CA801/2-3	100		CA801/3-3	100		CA801/1-3	100	
Push in type wire jumper 	CA901/2	100		CA901/3	100		CA901/1	100	
Marking Tags (MT Type) 	MT6	100		MT8	100		MT5	100	

*UL & CSA pending.

Spring Clamp Fuse Terminal Blocks



Altech offers 'Screwless' Spring Clamp Fuse Terminal Blocks.

The terminal has a moving type hinged carrier that has specially designed space for cartridge type glass fuse of size Ø 5 x 20 or Ø 5 x 25 mm. The fuse can be engaged or disengaged by the movement of the carrier.

Cross connection is possible with specially designed push-in type jumpers.

ASF4

ASF4(L)*



Terminal Width	8 mm			8 mm		
Height x Length	60 x 80 mm			60 x 80 mm		
Stripping Length	9 mm			9 mm		
Insulation Material	Polyamide 6.6			Polyamide 6.6		
Type of Connection	2 spring clamps & 2 slots for interconnection			2 spring clamps & 2 slots for interconnection		
Type of fuse used	Ø5x20, Ø5x25mm			Ø5x20, Ø5x25mm		
Fusion Voltage				24V AC/DC, 48V AC/DC 110V AC/DC, 220V AC		
Approvals						
Wire Range	22-10 AWG 0.5-4 sq.mm 22-10 AWG			22-10 AWG 0.5-4 sq.mm 22-10 AWG		
Voltage Rating	600 V	500 V	600 V	600 V	500 V	600 V
Current Rating	8 A	6.3 A	8 A	8 A	6.3 A	8 A



COLOR BLOCKS

(other than grey standard)

When ordering please add color suffix to Cat. No.

Example: CTS2.5U-N/R

Color	Ordering Suffix
Red	R
Blue	BU
Black	BL
Orange	O
Green	G
Yellow	Y
White	W
Beige	BG
Dark Brown	DB

	Cat. No.	Std. Pk.	Cat. No.	Std. Pk.
Terminal Block	ASF4	100	ASF4(L)*	100
End Plate	EPASF4	50	EPASF4	50
DIN Rail for ordering information refer to page 62				
End Stop for ordering information refer to page 63	CA702	50	CA702	50
	CA802	50	CA802	50
Insulated Jumper (2 pole)	CA801/7	100	CA801/7	100
Marking Tags (MT Type)	MT8	100	MT8	100

¹ UL & CSA pending.

* Add required voltage to part number as a suffix. i.e. ASF4(L)/24 for 24V AC/DC.


Spring Clamp Ground (Earth) Terminal Blocks

Altech offers 'Screwless' Spring Clamp Ground Terminal Blocks. Specially designed alloy feet helps in achieving very low contact resistance and vibration proof grounding.


CSCG series terminals can be mounted on Din 35 rail along with other terminal blocks of CSC series. The terminal block profile matches with that of CSC terminal block of same wire size.

Special features of CSCG terminal blocks are:

- Vibration proof grounding
- Very low contact resistance because of special alloy feet
- Drop-on grounding connection
- Spring clamp to accept solid and stranded wire





CSCG2.5T



CSCG4T



Terminal Width	5 mm	6 mm
Height x Length	36 x 58 mm	42 x 65 mm
Stripping Length	9 mm	9 mm
Insulation Material	Polyamide 6.6	Polyamide 6.6
Type of Connection	2 spring clamp connection, grounding through alloy feet	2 spring clamp connection, grounding through alloy feet
Approvals	  	  
Wire Range	22-14 AWG 0.5-2.5 sq.mm 22-14 AWG	22-12 AWG 0.5-4 sq.mm 22-12 AWG
Voltage Rating	800 V	800 V
Current Rating	24 A	32 A

	Cat. No.	Std. Pk.	Cat. No.	Std. Pk.
Terminal Block	CSCG2.5T	100	CSCG4T	100
DIN Rail <i>for ordering information refer to page 62</i>				
Marking Tags (MT Type) 	MT5	100	MT6	100

*UL & CSA pending.

	CSCG6T	CSCG10T								
										
	CE	CE								
Terminal Width	8 mm	10 mm								
Height x Length	45 x 72 mm	50 x 75 mm								
Stripping Length	12 mm	12 mm								
Insulation Material	Polyamide 6.6	Polyamide 6.6								
Type of Connection	2 spring clamp connection, grounding through alloy feet	2 spring clamp connection, grounding through alloy feet								
Approvals	  	  								
Wire Range	22-8 AWG 0.5-6 sq.mm 22-8 AWG	16-6 AWG 0.5-10 sq.mm 16-6 AWG								
Voltage Rating	800 V	800 V								
Current Rating	41 A	57 A								
Terminal Block	<table><tr><th>Cat. No.</th><th>Std. Pk.</th></tr><tr><td>CSCG6T</td><td>50</td></tr></table>	Cat. No.	Std. Pk.	CSCG6T	50	<table><tr><th>Cat. No.</th><th>Std. Pk.</th></tr><tr><td>CSCG10T</td><td>50</td></tr></table>	Cat. No.	Std. Pk.	CSCG10T	50
Cat. No.	Std. Pk.									
CSCG6T	50									
Cat. No.	Std. Pk.									
CSCG10T	50									
DIN Rail for ordering information refer to page 62										
Marking Tags (MT Type)	MT8 100	MT10 100								

*UL & CSA pending.

Panel Mount Spring Clamp Terminals

Altech "screwless" spring clamp panel mount terminal blocks are an excellent solution for extremely compact wiring applications. These terminal blocks are "add-on" type and can be combined to form multi-pole assemblies. The stacked assembly is fitted with mounting end sections on both ends for easy installation on to the panel.

The terminal has marker holding recesses on three sides to accept marking tags. Cross connection can be achieved with the aid of insulated jumpers.

The CSCP2.5T2 panel mount terminal blocks have two connection points on each side all with the same potential. The terminals provide possibility of further multiplication through jumpering.



CE

CE

Terminal Width	5 mm			10 mm		
Height x Length	27 x 35 mm			27 x 35 mm		
Stripping Length	9 mm			9 mm		
Insulation Material	Polyamide 6.6			Polyamide 6.6		
Type of Connection	2 spring clamp connections			4 common spring clamp connections		
Approvals	 US   US			 US   US		
Wire Range	22-14 AWG 0.5-2.5 sq.mm 22-14 AWG			22-14 AWG 0.5-2.5 sq.mm 22-14 AWG		
Voltage Rating	600 V 750 V 600 V			600 V 750 V 600 V		
Current Rating	20 A 24 A 20 A			20 A 24 A 20 A		

	Cat. No.	Std. Pk.	Cat. No.	Std. Pk.
Terminal Block	CSCP2.5T	100	CSCP2.5T2	100
End Section (set of left and right) 	EPCSCP2.5T	50	EPCSCP2.5T	50
Insulated Jumper (2 pole) 	CA803/1	100	CA803/1	100
Operating Tool	SCA2-5	1	SCA2-5	1
Marking Tags (MT Type) 	MT4	100	MT3	100




COLOR BLOCKS



(other than grey standard)

When ordering please add color suffix to Cat. No.

Example: CTS2.5U-N/R

Color	Ordering Suffix
Red	R
Blue	BU
Black	BL
Orange	O
Green	G
Yellow	Y
White	W
Beige	BG
Dark Brown	DB





Custom Assemblies Available

- Most competitive in industry
- Made to your specifications
- Large inventory of parts
- Variety of colors available
- Custom marking tags
- Up to 6' custom assemblies



Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Altech:](#)

[EPCTC4U](#) [EP1ODL4U](#) [CTS4U-TM](#) [38049](#) [38073](#) [38075](#) [EPDR](#) [EP2.5/4UN/BG](#) [EPCMC1-2](#) [EP2.5/4UN/O](#)
[EP2.5/4UN/G](#) [EP2.5/4UN/Y](#) [EPDP1](#) [CTS6U/DB](#) [DB35](#) [CDL4U\(E\)L D3/12](#) [ODL4U/Y](#) [ODL4U/BU](#)