High Brightness Type ϕ 3.1 Circular Type LED Lamps (LEDs with Pressure Release Structure)

SLR343 Series



Shape	Emitting Surface Dimension (mm)		Blue		Green				
		InGaN on SiC							
			468nm		523nm 518nm				
Circular Type	φ3.1								
		SLR343BBT	SLR343BCT	SLR343BDT	SLR343EBT	SLR343ECT	SLR343EDT		

Note) "-" will be taken out for emitting color B/E series.

■ Absolute Maximum Ratings (Ta=25°C)


Part No.	Emitting color	Power dissipation Po (mW)	Forward current IF (mA)	Peak forward current * IFP (mA)	Reverse voltage V _R (V)	Operating temperature Topr	Stotage temperature T _{stg} (°C)
SLR343BBT	Blue	120	30	100	5	-20 to +80	
SLR343BCT							
SLR343BDT							-30 to +100
SLR343EBT							-30 10 +100
SLR343ECT	Green						
SLR343EDT							

^{*} IFP measured under duty $\leq 1/10,1$ kHz


■ Electrical Optical Characteristics (Ta=25°C)

Part No.	Resin Color	Forward voltage V _F		Reverse current In		Light wavelength Peak Half-wave λp Δλ			Brightness Iv		
		Typ.	lF (mA)	Max. (μA)	VR (V)	Typ. (nm)	Typ. (nm)	lF (mA)	Min. (mcd)	Typ. (mcd)	lF (mA)
SLR343BBT	Transparent Clear	0.5	00			468	26	20	90	350	20
SLR343BCT									200	600	
SLR343BDT		3.5		100	5				300	800	
SLR343EBT		20	20			523	36		420	1500	
SLR343ECT		0.0	3.8			518	35		610	2000	
SLR343EDT		3.8							900	3500	

■ External Dimensions (Unit: mm)









■ Recommemded Pad Layout


■ Packaging Spacifications (Unit:mm)






■ Electrical Characteristic Curves

Forward Current - Forward Voltage




SLR343BBT
SLR343BDT
SLR343EBT
SLR343EBT
SLR343EDT
SLR343EDT
SLR343EDT

Relative Luminous Intensity - Case Temperature




SLR343BBT
SLR343BCT
SLR343BDT
SLR343EBT
SLR343ECT
SLR343EDT

Relative Luminous Intensity - Forward Current




SLR343BBT
SLR343BCT
SLR343BDT
SLR343EBT
SLR343ECT
SLR343EDT

Ratio of Maximum Tolerable Peak Current - Pulse Duration



SLR343BBT
SLR343BCT
SLR343BDT
SLR343EBT
SLR343ECT
SLR343EDT

Derating



SLR343BBT
SLR343BCT
SLR343BDT
SLR343EBT
SLR343ECT
SLR343EDT

Notes

- No technical content pages of this document may be reproduced in any form or transmitted by any
 means without prior permission of ROHM CO.,LTD.
- The contents described herein are subject to change without notice. The specifications for the product described in this document are for reference only. Upon actual use, therefore, please request that specifications to be separately delivered.
- Application circuit diagrams and circuit constants contained herein are shown as examples of standard
 use and operation. Please pay careful attention to the peripheral conditions when designing circuits
 and deciding upon circuit constants in the set.
- Any data, including, but not limited to application circuit diagrams information, described herein are intended only as illustrations of such devices and not as the specifications for such devices. ROHM CO.,LTD. disclaims any warranty that any use of such devices shall be free from infringement of any third party's intellectual property rights or other proprietary rights, and further, assumes no liability of whatsoever nature in the event of any such infringement, or arising from or connected with or related to the use of such devices.
- Upon the sale of any such devices, other than for buyer's right to use such devices itself, resell or
 otherwise dispose of the same, no express or implied right or license to practice or commercially
 exploit any intellectual property rights or other proprietary rights owned or controlled by
- ROHM CO., LTD. is granted to any such buyer.
- Products listed in this document are no antiradiation design.

The products listed in this document are designed to be used with ordinary electronic equipment or devices (such as audio visual equipment, office-automation equipment, communications devices, electrical appliances and electronic toys).

Should you intend to use these products with equipment or devices which require an extremely high level of reliability and the malfunction of with would directly endanger human life (such as medical instruments, transportation equipment, aerospace machinery, nuclear-reactor controllers, fuel controllers and other safety devices), please be sure to consult with our sales representative in advance.

About Export Control Order in Japan

Products described herein are the objects of controlled goods in Annex 1 (Item 16) of Export Trade Control Order in Japan.

In case of export from Japan, please confirm if it applies to "objective" criteria or an "informed" (by MITI clause) on the basis of "catch all controls for Non-Proliferation of Weapons of Mass Destruction.

