

Zener Diode

1N5931B-1N5946B

Features:

- Lower profile package.
- Excellent clamping capability.
- Glass passivated junction.
- V_Z -tolerance $\pm 5\%$.



Applications:

Voltage stabilization.

Absolute Maximum Ratings $T_j = 25^\circ\text{C}$

Parameter	Test Conditions	Symbol	Value	Unit
Power dissipation	$T_{\text{amb}} \geq 50^\circ\text{C}$	P_V	3	W
Z-current		I_Z	P_V/V_Z	mA
Junction temperature		T_j	150	$^\circ\text{C}$
Storage temperature range		T_{stg}	-55 to +175	

Stresses exceeding maximum ratings may damage the device. Maximum ratings are stress ratings only. Functional above the recommended operating conditions is not implied. Extended exposure to stresses above the recommended operating conditions may affect device reliability.

Electrical Characteristics $T_j = 25^\circ\text{C}$

Parameter	Test Conditions	Symbol	Maximum	Unit
Forward voltage	$I_F = 200\text{mA}$	V_F	1.5	V

Specification Table

Description	V _{Znom} ¹⁾	I _{ZT} for r _{ZJT}		r _{Zjk} at I _{ZK}		I _R at V _R		Part Number
	V	mA	Ω	Ω	mA	μA	V	
Zener Diode	5.6	66.9	< 2	< 250	1	< 5	3	1N5919B
Zener Diode	6.2	60.5		< 200			4	1N5920B
Zener Diode	6.8	55.1	< 2.5				5.2	1N5921B
Zener Diode	10	37.5	< 4.5	< 500	0.25	<1	8	1N5925B
Zener Diode	12	31.2	< 6.5	< 550			9.1	1N5927B
Zener Diode	15	25	< 9	< 600			11.4	1N5929B
Zener Diode	18	20.8	< 12	< 650			13.7	1N5931B
Zener Diode	20	18.7	< 14				15.2	1N5932B
Zener Diode	24	15.6	< 19	< 700			18.2	1N5934B


¹⁾ Based on DC-measurement at thermal equilibrium while maintaining the lead temperature (T_L) at 30°C , 9.5mm (3/8 inches) from the diode body.

Zener Diode

1N5931B-1N5946B



Dimensions in mm



Dimensions	Dimensions			
	Inches		mm	
	Min	Max	Min	Max
A	1.000	-	25.4	-
B	0.230	0.300	5.8	7.6
C	0.026	0.034	0.7	0.9
D	0.104	0.140	2.6	3.6

Case : Moulded plastic DO-15.
Polarity : Cathode band.
Marking : Type number.

Marking



Important Notice : This data sheet and its contents (the "Information") belong to the members of the Premier Farnell group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp is the registered trademark of the Group. © Premier Farnell plc 2011.

