


TYCO ELECTRONICS RESERVES THE RIGHT TO AMEND THIS DRAWING AT ANY TIME.
USERS SHOULD EVALUATE THE SUITABILITY OF THE PRODUCT FOR THEIR APPLICATION.

REVISIONS			
LTR	DESCRIPTION	DATE	APPROVED
A	INITIAL RELEASE PER DCR# T-32027	OCT/3/03	M.HIGGY

If this document is printed it becomes uncontrolled.
Check for the latest revision.



SPECIFICATION CONTROL DRAWING

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES. METRIC DIMENSIONS ARE IN BRACKETS. DECIMALS .XXX ±.005 [.13mm] .XX ±.02 [.51mm] ANGLE ± X° WEIGHT lbs. [g] MAX.	DRAWN ZS. ORBAN	DATE September/9/03	tyco Electronics TYCO ELECTRONICS 300 Constitution Drive Menlo Park, CA. 94025 USA Raychem
	CHECKED	DATE	
	APPROVED	DATE	
	APPROVED M.HIGGY CAD NAME T32027a.DWG	DATE September/9/03	
THIRD ANGLE PROJECTION			TITLE 1 INCH SUB-ASSEMBLY RECEPTACLE SHELL, CADMIUM PLATED MTCR SERIES
SIZE C		CAGE CODE: 06090	DWG. NO. D-659-0034-01-003
DO NOT SCALE THIS DRAWING		SCALE NONE	REV A
		SHEET 1	OF 2

NOTES:

1 KEYING PIN CODE DOES NOT FORM A PART OF RAYCHEM PART NUMBERING SYSTEM AND SHOULD BE OMITTED WHEN ORDERING.
FOR MOUNTING / MATING AND KEYING INFORMATION, SEE RAYCHEM SPECIFICATION D-652-0004.

2. CONNECTOR SUB-ASSEMBLY SUPPLIED IN KIT FORM AND SHALL BE ASSEMBLED BY USER. THE COMPLETED ASSEMBLY DESIGNED TO MEET APPLICABLE REQUIREMENTS OF SPECIFICATION C-6115.

3. MATERIAL:

A) SHELL	ALUMINUM ALLOY PER QQ-A-591
B) ADAPTOR SCREW	STAINLESS STEEL, 300 SERIES PER QQ-S-763
C) ADAPTOR NUT	STAINLESS STEEL, 300 SERIES PER QQ-S-763
D) PANEL WASHER	300 SERIES PER ASTM A666 CONDITION 1/2 HARD
E) KEYING PIN	HIGH GRADE POLYARYLENE THERMOPLASTIC, MOLDED
F) KEY PINS INSERT	HIGH GRADE POLYARYLENE THERMOPLASTIC, MOLDED
G) CABLE CLAMP	STAINLESS STEEL, 300 SERIES PER QQ-S-763
H) CABLE CLAMP BUSHING	70 SHORE FLUROSILICONE WITH OIL RESISTANCE PER MIL-R-25988
I) CABLE CLAMP SCREW	STAINLESS STEEL, 300 SERIES PER QQ-S-763
J) DUST CAP	POLYETHYLENE LOW DENSITY PER L-P-390, COLOR RED

4. FINISH:

A) SHELL	CADMIUM PLATED PER SAE-AMS-QQ-P-416
B) ADAPTOR SCREW	CADMIUM PLATED PER SAE-AMS-QQ-P-416
C) ADAPTOR NUT	CADMIUM PLATED PER SAE-AMS-QQ-P-416
D) PANEL WASHER	CADMIUM PLATED PER SAE-AMS-QQ-P-416
E) CABLE CLAMP	CADMIUM PLATED PER SAE-AMS-QQ-P-416
F) CABLE CLAMP SCREW	CADMIUM PLATED PER SAE-AMS-QQ-P-416

5 DUST CAP SUPPLIED WITH EACH RECEPTACLE SHELL.

6 APPROPRIATE PART NUMBER AND DATE CODE ARE STAMPED APPROXIMATELY AS SHOWN.

7 THESE ITEMS ARE SUPPLIED UNASSEMBLED.

8 THIS RECEPTACLE IS REAR PANEL MOUNTED BY REMOVING AS MANY PANEL WASHERS AS REQUIRED TO ACCOMMODATE THE THICKNESS OF THE PANEL BEING USED. (SEE TABLE I)

9. CONNECTOR COMPONENTS AND ACCESSORIES ARE INDIVIDUALLY BAGGED AND LABELED.

TABLE I	
PANEL THICKNESS	NUMBER OF PANEL WASHERS FOR EACH FASTENER
0.031/0.036 [0.8]/[0.9]	2
0.062/0.067 [1.5]/[1.7]	1
0.093/0.097 [2.3]/[2.4]	0

If this document is printed it becomes uncontrolled.
Check for the latest revision.

DWG. NO.	REV
D-659-0034-01-003	A
CAD FILE No.: T32027b.DWG	SHEET 2 OF 2