

Three Phase Bridge (Power Modules), 60/70 A



MT-K

FEATURES

- Package fully compatible with the industry standard INT-A-PAK power modules series
- High thermal conductivity package, electrically insulated case
- Excellent power volume ratio, outline for easy connections to power transistor and IGBT modules
- 4000 V_{RMS} isolating voltage
- UL E78996 approved 
- Designed and qualified for industrial level
- Material categorization: For definitions of compliance please see www.vishay.com/doc?99912


RoHS
COMPLIANT

PRODUCT SUMMARY	
I _O	60 A to 70 A
V _{RRM}	800 V to 1600 V
Package	MT-K
Circuit	Three phase bridge

DESCRIPTION

A range of extremely compact, encapsulated three phase bridge rectifiers offering efficient and reliable operation. They are intended for use in general purpose and heavy duty applications.

MAJOR RATINGS AND CHARACTERISTICS				
SYMBOL	CHARACTERISTICS	VALUES 60MT.K	VALUES 70MT.K	UNITS
I _O		60 (75)	70 (90)	A
	T _C	85 (61)	85 (57)	°C
I _{FSM}	50 Hz	420	480	A
	60 Hz	440	500	
I ² t	50 Hz	870	1150	kA ² s
	60 Hz	790	1050	
I ² √t		8700	11 500	kA ² √s
V _{RRM}	Range	800 to 1600		V
T _{Stg}	Range	-40 to 150		°C
T _J		-40 to 150		

ELECTRICAL SPECIFICATIONS

VOLTAGE RATINGS				
TYPE NUMBER	VOLTAGE CODE	V _{RRM} , MAXIMUM REPETITIVE PEAK REVERSE VOLTAGE V	V _{RSM} , MAXIMUM NON-REPETITIVE PEAK REVERSE VOLTAGE V	I _{RRM} MAXIMUM AT T _J MAXIMUM mA
VS-60-70MT..K	80	800	900	10
	100	1000	1100	
	120	1200	1300	
	140	1400	1500	
	160	1600	1700	



FORWARD CONDUCTION							
PARAMETER	SYMBOL	TEST CONDITIONS			VALUES 60MT.K	VALUES 70MT.K	UNITS
Maximum DC output current at case temperature	I _O	120° rect. conduction angle			60 (75)	70 (90)	A
					85 (61)	85 (57)	°C
Maximum peak, one-cycle forward, non-repetitive surge current	I _{FSM}	t = 10 ms	No voltage reapplied	Initial T _J = T _J maximum	420	480	A
		t = 8.3 ms			440	500	
		t = 10 ms	100 % V _{RRM} reapplied		350	400	
		t = 8.3 ms			370	420	
Maximum I ² t for fusing	I ² t	t = 10 ms	No voltage reapplied		870	1150	kA ² s
		t = 8.3 ms			790	1050	
		t = 10 ms	100 % V _{RRM} reapplied		610	800	
		t = 8.3 ms			560	730	
Maximum I ² √t for fusing	I ² √t	t = 0.1 ms to 10 ms, no voltage reapplied			8700	11 300	A ² √s
Low level value of threshold voltage	V _{F(TO)1}	(16.7 % x π x I _{F(AV)} < I < π · I _{F(AV)}), T _J maximum			0.85	0.86	V
High level value of threshold voltage	V _{F(TO)2}	(I > π x I _{F(AV)}), T _J maximum			1.07	1.08	
Low level value of forward slope resistance	r _{f1}	(16.7 % x π x I _{F(AV)} < I < π · I _{F(AV)}), T _J maximum			8.04	7.35	mΩ
High level value of forward slope resistance	r _{f2}	(I > π x I _{F(AV)}), T _J maximum			7.08	6.53	
Maximum forward voltage drop	V _{FM}	I _{pk} = 100 A, T _J = 25 °C, t _p = 400 μs single junction			1.75	1.55	V
RMS isolation voltage	V _{ISOL}	T _J = 25 °C, all terminal shorted f = 50 Hz, t = 1 s			4000		

THERMAL AND MECHANICAL SPECIFICATIONS						
PARAMETER		SYMBOL	TEST CONDITIONS	VALUES 60MT.K	VALUES 70MT.K	UNITS
Maximum junction operating and storage temperature range		T _J , T _{Stg}		-40 to 150		°C
Maximum thermal resistance, junction to case		R _{thJC}	DC operation per module	0.37	0.29	K/W
			DC operation per junction	2.22	1.75	
			120° rect. conduction angle per module	0.40	0.34	
			120° rect. conduction angle per junction	2.42	2.01	
Maximum thermal resistance, case to heatsink per module		R _{thCS}	Mounting surface smooth, flat and greased	0.03		
Mounting torque ± 10 %		to heatsink	A mounting compound is recommended and the torque should be rechecked after a period of 3 hours to allow for the spread of the compound. Lubricated threads.	4 to 6		Nm
		to terminal		3 to 4		
Approximate weight				176		g




Fig. 1 - Current Ratings Characteristics




Fig. 2 - Forward Voltage Drop Characteristics





Fig. 3 - Total Power Loss Characteristics




Fig. 4 - Maximum Non-Repetitive Surge Current




Fig. 5 - Maximum Non-Repetitive Surge Current




Fig. 6 - Current Ratings Characteristics




Fig. 7 - Forward Voltage Drop Characteristics




Fig. 8 - Total Power Loss Characteristics





Fig. 9 - Maximum Non-Repetitive Surge Current





Fig. 10 - Maximum Non-Repetitive Surge Current


Fig. 11 - Thermal Impedance Z_{thJC} Characteristics


ORDERING INFORMATION TABLE

Device code	VS-	7	0	MT	160	K	PbF
	1	2	3	4	5		6
1	-	Vishay Semiconductors product					
2	-	Current rating code: 6 = 60 A (average) 7 = 70 A (average)					
3	-	Three phase diodes bridge					
4	-	Essential part number					
5	-	Voltage code x 10 = V_{RRM} (see Voltage Ratings table)					
6	-	PbF = Lead (Pb)-free					

Note

- To order the optional hardware go to www.vishay.com/doc?95172

CIRCUIT CONFIGURATION




LINKS TO RELATED DOCUMENTS

Dimensions

www.vishay.com/doc?95004

MTK (with and without optional barrier)

DIMENSIONS WITH OPTIONAL BARRIERS in millimeters (inches)



Technical Drawing of the 1000mAh 3.7V Li-ion Battery Pack

Front View Dimensions:

- Overall Width: 94 ± 0.3 mm (3.7 ± 0.01 in)
- Overall Height: 28 ± 1 mm (1.11 ± 0.04 in)
- Terminal Height: 25.5 ± 0.5 mm (1.004 ± 0.02 in)
- Terminal Width: 5 ± 0.3 mm (0.2 ± 0.01 in)
- Internal Width: 75 ± 0.5 mm (2.95 ± 0.02 in)
- Internal Height: 46 ± 0.3 mm (1.81 ± 0.01 in)
- Internal Width (Terminal Area): 80 ± 0.3 mm (3.15 ± 0.01 in)
- Internal Height (Terminal Area): 14 ± 0.3 mm (0.55 ± 0.01 in)
- Internal Width (Terminal Area): 18 ± 0.3 mm (0.71 ± 0.01 in)

Side View Dimensions:

- Overall Width: 35 ± 0.3 mm (1.38 ± 0.01 in)
- Overall Height: 30 ± 0.5 mm (1.17 ± 0.02 in)
- Terminal Height: 8.5 ± 0.5 mm (0.34 ± 0.02 in)
- Terminal Width: 24 ± 0.5 mm (0.94 ± 0.02 in)

Top View Dimensions:

- Overall Width: 94 ± 0.3 mm (3.7 ± 0.01 in)
- Overall Height: 28 ± 1 mm (1.11 ± 0.04 in)
- Terminal Height: 25.5 ± 0.5 mm (1.004 ± 0.02 in)
- Terminal Width: 5 ± 0.3 mm (0.2 ± 0.01 in)
- Internal Width: 75 ± 0.5 mm (2.95 ± 0.02 in)
- Internal Height: 46 ± 0.3 mm (1.81 ± 0.01 in)
- Internal Width (Terminal Area): 80 ± 0.3 mm (3.15 ± 0.01 in)
- Internal Height (Terminal Area): 14 ± 0.3 mm (0.55 ± 0.01 in)
- Internal Width (Terminal Area): 18 ± 0.3 mm (0.71 ± 0.01 in)

Notes:

- Screws M5 x 0.8 length 10
- Fast-on tab 2.8 x 0.8 (type 110)



Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and/or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.

Material Category Policy

Vishay Intertechnology, Inc. hereby certifies that all its products that are identified as RoHS-Compliant fulfill the definitions and restrictions defined under Directive 2011/65/EU of The European Parliament and of the Council of June 8, 2011 on the restriction of the use of certain hazardous substances in electrical and electronic equipment (EEE) - recast, unless otherwise specified as non-compliant.

Please note that some Vishay documentation may still make reference to RoHS Directive 2002/95/EC. We confirm that all the products identified as being compliant to Directive 2002/95/EC conform to Directive 2011/65/EU.

Vishay Intertechnology, Inc. hereby certifies that all its products that are identified as Halogen-Free follow Halogen-Free requirements as per JEDEC JS709A standards. Please note that some Vishay documentation may still make reference to the IEC 61249-2-21 definition. We confirm that all the products identified as being compliant to IEC 61249-2-21 conform to JEDEC JS709A standards.