



|   |                                 |         |          |
|---|---------------------------------|---------|----------|
| G | REVISED (P-DWG<br>REV. A)       | S.O     | 11/18/72 |
| F | REVISED (P-DWG REV. A)          | T.K     | 11/17/72 |
| E | REVISED (P-DWG<br>REV. D)       | Y. J    | 11/17    |
| D | REVISED (P-DWG<br>REV. A)       | P.A     | 11/13/72 |
| C | ADD TIS 2-7 (P-DWG<br>REV. A)   | K.K.    | 11/13/72 |
| B | REVISED (P-DWG<br>REV. A)       | K.K.R.S | 10/26/72 |
| A | DELETE MARK *<br>(P-DWG REV. D) | K.K.    | 11/17/72 |
| O | RELEASED (P-DWG<br>REV. D)      | K.K.    | 11/17/72 |

G1 DELETED MARK @ J84-T160 F.J 4.3 7/17/24

1970 BY THE USSR. ALL RIGHTS RESERVED AND PRODUCTS COVERED BY PATENTS AND/OR PATENTS PENDING.

客户回函  
CUSTOMER COPY  
REFERENCE ONLY

THE MATERIAL 電氣銅

焼なま, 錫めし

28.66-42.92 TOTAL AWG 2

2004 INSULATION DIA.

# WAP

TOKYO, JAPAN

TOLERANCE  
 EXCEPT  
 AS NOTED

LOC 97-08 REV.  
C-170737 6

九型端子