



MAG-MATE TERMINALS WITH MULTISPRING PIN

SAY GOODBYE TO MAGNET WIRE SOLDERING AND PCB SOLDERING

The MAG-MATE terminal with Multispring pin combines two key technologies to eliminate the need to solder in a motor connection. It provides the ability to directly connect magnet wire to a PCB with no solder. Traditionally, the process is to solder magnet wire to a pin, assemble the PCB to the pin, and then solder the PCB to the pin. Not anymore! This product helps to allow solderless magnet wire termination with an insulation displacement contact (IDC) at the bottom and solderless PCB termination through press-fit Multispring pin on the top.

KEY BENEFITS

Features of the Multispring pin

- Large gas-tight contact zone
- High reliability due to stored energy
- Minimum damage to plated-through holes during application
- Especially suited for multi-layer PCBs
- More economic board manufacturing due to larger hole tolerances compared to the use of a solid pin
- Application can be made by the end-user
- High-end TE Connectivity application tooling available
- Extraction force: Pin/PCB min 40N

Features of the MAG-MATE Terminal

- Eliminates need for pre-stripping conductors
- Eliminates need to solder/weld
- Excess magnet wire is automatically trimmed during the termination process
- Simultaneously terminates two magnet wires of the same size in one terminal (for splicing or bi-filing)
- Available in strip form for either semi-automatic or fully-automatic insertions
- High speed, fully-automated integrated systems provide uniform terminations reliably at a very low applied cost
- Clean metal-to-metal interface produces stable, gas-tight electrical terminations free of oxides and other contaminants

APPLICATIONS

Any motor or other magnet wire application that requires a direct PCB connection.

SPECIFICATIONS

Product Specification: [108-74116](#)

Application Specification: [114-74109](#)

MAG-MATE TERMINALS WITH MULTISPRING PIN

COPPER WIRE

Diameter (mm)	Standard PN	Slim Line PN*
0.180-0.265	1247000-2	2120743-2
0.265-0.400	1247001-2	2120744-2
0.400-0.630	1247002-2	2120745-2
0.630-0.850	1247003-2	2120746-2
0.850-1.120	1247004-2	2120747-2
1.20-1.30	2238145-2	-

* For slim line MAG-MATE terminals with Multispring pin for aluminum magnet wire, please consult TE Connectivity.

ALUMINUM WIRE

Diameter (mm)	PN
0.32-0.45	1247001-3
0.57-0.72	1247002-3
0.72-0.91	1247003-3
0.95-1.15	1247004-3
1.30-1.45	2238145-3

Connect With Us

We make it easy to connect with our experts and are ready to provide all the support you need.

Visit te.com/support to chat with a Product Information Specialist.

te.com/mag-mate-terminals

TE Connectivity, TE, TE connectivity (logo), EVERY CONNECTION COUNTS, MAG-MATE and Multispring are trademarks owned or licensed by the TE Connectivity plc family of companies. All other logos, products and/or company names referred to herein might be trademarks of their respective owners. .

While TE has made every reasonable effort to ensure the accuracy of the information in this document, TE does not guarantee that it is error-free, nor does TE make any other representation, warranty or guarantee that the information is accurate, correct, reliable or current. TE reserves the right to make any changes to the information contained herein without prior notice. TE Connectivity's obligations shall only be as set forth in TE Connectivity's Standard Terms and Conditions of Sale for this product and in no case will TE Connectivity be liable for any incidental, indirect, or consequential damages arising out of the sale, resale, use, or misapplication of the product. TE expressly disclaims any implied warranties with respect to the information contained herein, including, but not limited to, implied warranties of merchantability or fitness for a particular purpose. Dimensions, specifications and/or information contained herein are for reference purposes only and are subject to change without notice. Consult TE for the latest dimensions, specifications and/or information. Users of TE Connectivity products must make their own assessment as to whether the respective product is suitable for the respective desired application.

©2025 TE Connectivity. All Rights Reserved.

Published 07-25