

InGaAs PIN photodiode with preamp G9280-14

ROSA type, 1.3/1.55 μm , 156 Mbps



Features

- $\phi 1.25$ mm sleeve type ROSA (Receiver Optical Sub-Assembly)
- High-speed response: 156 Mbps
- High gain with AGC (Auto Gain Control): 26 V/mW (-30 dBm)
- Low power supply voltage: 3.3 V
- Differential output
- Sensitivity: -5 to -37 dBm Typ.

Applications

- SDH/SONET
- Optical fiber communication

■ Absolute maximum ratings (Ta=25 °C)

Parameter	Symbol	Value	Unit
Supply voltage	Vcc	-0.3, +3.8	V
Operating temperature	Topr	-20 to +70 *1	°C
Storage temperature	Tstg	-40 to +85 *1	°C

*1: No condensation

■ Electrical and optical characteristics

(Ta=25 °C, Vcc=3.3 V, Vee=0 V, RL=500 Ω *2, λ =1310 nm, unless otherwise noted)


Parameter	Symbol	Condition	Min.	Typ.	Max.	Unit
Photo sensitivity *2	S	Pin= -30 dBm *3	18	26	-	V/mW
Supply current	Icc	Dark state, RL= ∞	-	25	35	mA
Output bias voltage	Vo	Dark state, RL= ∞	-	1.5	-	V
Cut-off frequency *2	fc	Pin= -30 dBm, -3 dB	85	120	-	MHz
Low cut-off frequency *2	fc-L	Pin= -30 dBm, -3 dB	-	15	-	kHz
Noise equivalent power *2, *3	NEP	Dark state, to 117 MHz	-	21	32	nWrms
Minimum receivable sensitivity	Pmin	156 Mbps, NRZ, PN=23, BER=10 ⁻¹⁰ , Extinction ratio=8.2 dB	-	-37	-	dBm
Maximum receivable sensitivity	Pmax		-	-5	-	

*2: Output: Capacitive coupling

This module should be used with a load resistance larger than 500 Ω .


*3: Single-ended (Vout+) measurement

■ Photo sensitivity vs. average input optical power




KIRDB0290EA

■ Bit error rate




KIRDB0291EA

■ Eye diagram



Bit rate=156 Mbps, PN=23, $\lambda=1310\text{ nm}$
Pin= -20 dBm

■ Dimensional outline (unit: mm, unless otherwise noted: ± 0.15)



KGPDA0020EA

HAMAMATSU

HAMAMATSU PHOTONICS K.K., Solid State Division

1126-1 Ichino-cho, Hamamatsu City, 435-8558 Japan, Telephone: (81) 053-434-3311, Fax: (81) 053-434-5184, <http://www.hamamatsu.com>

U.S.A.: Hamamatsu Corporation: 360 Foothill Road, P.O.Box 6910, Bridgewater, N.J. 08807-0910, U.S.A., Telephone: (1) 908-231-0960, Fax: (1) 908-231-1218

Germany: Hamamatsu Photonics Deutschland GmbH: Arzbergerstr. 10, D-82211 Herrsching am Ammersee, Germany, Telephone: (49) 08152-3750, Fax: (49) 08152-2658

France: Hamamatsu Photonics France S.A.R.L.: 8, Rue du Saule Trapu, Parc du Moulin de Massy, 91882 Massy Cedex, France, Telephone: 33-(1) 69 53 71 00, Fax: 33-(1) 69 53 71 10

United Kingdom: Hamamatsu Photonics UK Limited: 2 Howard Court, 10 Tewin Road, Welwyn Garden City, Hertfordshire AL7 1BW, United Kingdom, Telephone: (44) 1707-294888, Fax: (44) 1707-325777

North Europe: Hamamatsu Photonics Norden AB: Smidesvägen 12, SE-171 41 Solna, Sweden, Telephone: (46) 8-509-031-00, Fax: (46) 8-509-031-01

Italy: Hamamatsu Photonics Italia S.R.L.: Strada della Moia, 1/E, 20020 Arese, (Milano), Italy, Telephone: (39) 02-935-81-733, Fax: (39) 02-935-81-741

Information furnished by HAMAMATSU is believed to be reliable. However, no responsibility is assumed for possible inaccuracies or omissions. Specifications are subject to change without notice. No patent rights are granted to any of the circuits described herein. ©2003 Hamamatsu Photonics K.K.