

High-Performance Surface-Mount TTL Delay Lines

CTTLDL,
BJTTLDL,
GBTTLDL,
BTTLDL

- Five equal taps in 20% increments of total delay.
- Lumped constant, active series.
- Transfer-molded packaging for highest reliability.
- Designed for leading edge timing. Trailing edge timing available.
- Supports Schottky TTL, FAST, and FACT logics.
- Fanout 1 -- 20 loads; logic 0 -- 10 loads.
- Temperature coefficient ± 2 ns or $\pm 4\%$ (whichever is greater) at maximum delay, 0 to 70°C.

- Military models with temperature range -55 to +125°C and ceramic package IC to meet MIL-STD-883C, but not screened to that specification, add suffix "M" to part number.
- Military models as above, but with ceramic package IC screened to MIL-STD 883C and 38510, add suffix "MX" to part number.
- Military models as "MX" above, but with in-house burn-in and thermal shock, add suffix "MY".

LOW PROFILE SURFACE-MOUNT 5-TAP TTL DELAY LINES


TECHNITROL PART NO.	TAP DELAYS (ns)					ALL TAPS	
	T _{D1}	T _{D2}	T _{D3}	T _{D4}	T _{D5}	T _{RO}	T _{FO}
CTTLDL025	5.0	10.0	15.0	20.0	25.0	2.0	2.0
CTTLDL050	10.0	20.0	30.0	40.0	50.0	2.0	2.0
CTTLDL075	15.0	30.0	45.0	60.0	75.0	2.0	2.0
CTTLDL100	20.0	40.0	60.0	80.0	100.0	2.0	5.0
CTTLDL125	25.0	50.0	75.0	100.0	125.0	2.0	5.0
CTTLDL150	30.0	60.0	90.0	120.0	150.0	2.0	6.0
CTTLDL200	40.0	80.0	120.0	160.0	200.0	2.0	7.0

0.175"
MAX
HEIGHT


For TTL delay lines qualified to MIL-D-83532, refer to PSC information sheet entitled "QPL Active Delay Lines."

Delay Characteristics measured at $V_{CC} = 5.0V$, 25°C, no load.
Delay Tolerance ± 2 ns or 5%, whichever is greater.
Rise time measured @ 0.8V to 2.0V levels.
For minimum input pulse width -- contact factory.

SCHEMATIC



MECHANICAL OUTLINE



CTTLDL-19

Notes

- Pin numbers shown are for reference only and are not necessarily marked on unit.
- Lead material is electro tin plated (alloy 42) or solder dipped.
- All specifications are subject to change without notice.



CTTDL,
BJTTDL,
GBTTLDL,
BTTLDL

SURFACE-MOUNT 5-TAP TTL DELAY LINES -- 1/2" SQ.

TECHNITROL PART NO.	PART NO.	PART NO.	TAP DELAYS (ns)					ALL TAPS (Max.)	
			T _{D1}	T _{D2}	T _{D3}	T _{D4}	T _{D5}	T _{RO}	T _{FO}
BJTTLDL025	GBTTLDL025	BTTLDL025	5.0	10.0	15.0	20.0	25.0	2.0	2.0
BJTTLDL050	GBTTLDL050	BTTLDL050	10.0	20.0	30.0	40.0	50.0	2.0	2.0
BJTTLDL075	GBTTLDL075	BTTLDL075	15.0	30.0	45.0	60.0	75.0	2.0	2.0
BJTTLDL100	GBTTLDL100	BTTLDL100	20.0	40.0	60.0	80.0	100.0	2.0	5.0
BJTTLDL125	GBTTLDL125	BTTLDL125	25.0	50.0	75.0	100.0	125.0	2.0	6.0
BJTTLDL150	GBTTLDL150	BTTLDL150	30.0	60.0	90.0	120.0	150.0	2.0	7.0
BJTTLDL200	GBTTLDL200	BTTLDL200	40.0	80.0	120.0	160.0	200.0	2.0	8.0



Delay Characteristics measured at $V_{CC} = 5.0V$, $25^{\circ}C$, no load.

Delay Tolerance ± 2 ns or 5%, whichever is greater.





Rise time measured @ 0.8V to 2.0V levels.

For minimum input pulse width -- contact factory.

SCHEMATICS



MECHANICAL OUTLINES



BJ-19

Notes

- Pin numbers shown are for reference only and are not necessarily marked on unit.
- Lead material is electro tin plated (alloy 42) or solder dipped.
- All specifications are subject to change without notice.