



T.I.P.S. Ribbons


The thermal transfer print technology is based on heating up certain dots in the print head. This transfers the ink very precisely from the ribbon onto the surface of the printed material.

Recommended ribbons for printing on shrinking sleeve

The range of ribbons has been designed to give maximum print clarity and performance. Material can be handled immediately after printing, enabling the printed tubing to be immediately applied without a secondary mark stabilising operation.



Ribbons - TTRA, TTRC+.



ID: The standard inside core diameter is 25.4 mm. Other sizes are available on request.

Specifications please see table page 449 in Appendix.

Technical Table

| Article-No. | Type | Colour | Width (W) | Quantity per pc |
|--|-----------------|--------------------|-----------|-----------------|
| Ribbons for printing on heat shrink tubing | | | | |
| 556-00125 | TTRW 30MM | White (WH) | 30.0 | 300 m |
| 556-00114 | TTRC+ 30MM ** | Black (BK) | 30.0 | 300 m |
| 556-00139 | TTDTHOUT 40MM | Black (BK) | 40.0 | 300 m |
| 556-00115 | TTRC+ 60MM ** | Black (BK) | 60.0 | 300 m |
| 556-00140 | TTDTHOUT 60MM | Black (BK) | 60.0 | 300 m |
| 556-00103 | TTRC+ 100MM ** | Black (BK) | 100.0 | 300 m |
| 556-00133 | TTRW 100MM | White (WH) | 100.0 | 300 m |
| 556-00161 | TT822OUT8 110MM | Silver Grey (SRGY) | 110.0 | 300 m |

All dimensions in mm. Subject to technical changes.

** Patent GB98074362