

S4K5U-5C 6 kVA International On-Line UPS

The new SolaHD S4K5U6K5C Industrial On-Line UPS Series is designed for international usage and provides flexible output voltage, an integrated maintenance bypass switch and internal batteries all in a slim 5U (8.7") enclosure. The S4K5U-5C features true On-Line (double conversion) topology providing the ultimate in protection against a wide range of potential power problems. Flexible output voltages (220/230/240 Volt) are available through the configuration program to allow for international use. One of the three L-N output voltages is selected to match the local voltage. Self diagnostics simplify maintenance and troubleshooting, and the UPS can be serviced by the customer. The standard maintenance bypass switch provides an additional level of protection.

The S4K5U-5C also features a wide input voltage window to support the critical load without having to transfer to the battery. This extends system availability when back-up is truly needed.

Applications

- Industrial Computers
- Robotics and Process Controls
- Industrial Automation Systems
- Network Servers
- Enterprise Telecommunication Systems
- Printing and Publishing Machinery
- Industrial and Commercial Machinery
- Pharmaceutical and Medical Diagnosis Equipment

Features

- True double conversion topology
- Higher power factor of 0.80
- Flexible L-N output voltage (220/230/240V)
- Configurable as a tower or rack mount model
- High density, 6 kVA in only 5U of rack space
- Easily installed in 18" to 32" deep rack using rack mount kit # SRS1832
- User replaceable, hot-swappable internal battery module
- Matching 3U extended battery cabinets
- Includes both automatic and manual maintenance bypass switch
- Automatic frequency detection of either 60 or 50 Hz
- Power factor correction
- Self-diagnostics simplify maintenance and troubleshooting



- Remote Emergency Power Off (REPO)
- Intellislot™, USB, and terminal block communication ports
- Compatible with most standby generators
- Two year limited warranty

Certifications and Compliances

- - IEC62040-1
- ISTA Procedure 1A

Related Products

- Portable MCR Power Conditioners
- Surge Protective Devices
- Active Tracking® Filters

Table 9: UPS Specifications

Parameters		Model Number: S4K5U6K5C
Rating		6000 VA/4800 W
Dimensions, D x W x H, in. (mm)		
Unit		22.40 x 16.90 x 8.70 (570.0 x 430.0 x 220.0)
Shipping		29.30 x 20.90 x 20.30 (745.0 x 530.0 x 516.0)
Weight, lbs. (kg)		
Unit		132.2 (60.00)
Shipping		156.5 (71.00)
Input AC Parameters		
Nominal Operating Frequency		50 or 60 Hz (Factory default is 50 Hz)
Factory Default Vac		230 Vac
User-configurable Vac		220/230/240 Vac (Can be modified using included configuration program)
Operating Voltage Range without Battery Operation		176–280 Vac
Maximum Allowable Vac		280 Vac
Input Frequency without Battery Operation		40–70 Hz
Input Power Connection		S4KPAD2-CEHWMSC Standard (See “3.3 Removable Power Distribution Box”)
Output AC Parameters		
Factory Default Vac		230 Vac
Output Connections		S4KPAD2-CEHWMSC Standard (See “3.3 Removable Power Distribution Box”)
Frequency		50 or 60 Hz, nominal
Wave form		Sine wave
Main Mode Overload		>200% for 5 cycles; 151–200% for 1 second; 131–150% for 10 seconds; 105–130% for 1 minute
Bypass Protection Limits		
Disable Bypass Operation		If input voltage exceeds $\pm 15\%$ of the nominal voltage
Re-enable Bypass Operation		If input voltage returns to within $\pm 10\%$ of nominal output voltage
Disable Bypass Operation		When the input frequency prevents synchronous operation
Environmental Requirements		
Operating Temperature		0°C to +40°C; See Table 12 for Derating Parameters
Storage Temperature		-15°C to +50°C
Relative Humidity		0% to 95%, non-condensing
Operating Elevation		Up to 1,000 m [3,281 ft.] at +30°C without derating
Audible Noise		<55 dBA @ 1 m [3.2 ft.] rear; <50 dBA @ 1 m [3.2 ft.] front & sides
Standards		
EMC		IEC/EN/AS 62040-2 2 nd Edition (Cat 2—Table 6); EN61000-4-2, Level 4, Criteria A, EN61000-4-3, Level 3, Criteria A, EN61000-4-4, Level 4, Criteria A, EN61000-4-5, Level 3, Criteria A

Table 10: UPS Specifications

Parameters	Model Number: S4K5U6K5C
Agency	
Safety	IEC62040-1:2008 Version
EMI/EMC	IEC/EN/AS 62040-2 2 nd Edition (Cat 2—Table 6)
ESD	EN61000-4-2, Level 4, Criteria A
Radiated Susceptibility	EN61000-4-3, Level 3, Criteria A
Electrical Fast Transient	EN61000-4-4, Level 4, Criteria A
Surge Immunity	EN61000-4-5, Level 3, Criteria A
Transportation	ISTA Procedure 1A

Table 11: Operating Temperature Parameters

Ambient Temperature	Model Number: S4K5U6K5C
pf @ 30°C ±3°C	0.8 pf
pf @ 40°C ±3°C	0.8 pf

Table 12: Power Distribution Specifications

Parameters	Model Number: S4KPAD2-CEHWMSC
Used with UPS Model	S4K5U6K5C
Power Distribution Box Includes:	Two (2) IEC320 C19 16 A/250 V Sockets Eight (8) C13 10 A/250 V Sockets Manual bypass switch with indicator lamp
Ampere Rating	32 A
Input/Output Power Connections	3-wire hard wired, 6–10 mm ² (8–10 AWG)
User-supplied Input Branch Circuit Breaker	32 A

Table 13: Internal Battery Specifications

Parameters		Model Number: S4K240INTBATC
Used with UPS Model		S4K5U6K5C
Dimensions, D x W x H, in. (mm)		
Unit		15.40 x 4.40 x 7.20 (390.0 x 113.0 x 184.0)
Shipping		18.40 x 7.00 x 10.30 (467.0 x 178.0 x 262.0)
Weight, lbs. (kg)		
Unit		45.1 (20.46)
Shipping		50.7 (23.00)
Battery Parameters		
Type		Valve-regulated, non-spillable, lead acid
Qty x V x Rating		20 x 12 V x 9.0 Ah
Battery Mfr./Part Number		Yuasa/REW 45-12
Backup Time		See Table 15
Recharge Time		3 hours to 90% capacity after full discharge into 100% load
Environmental Requirements		
Operating Temperature		0°C to +40°C; see Table 9
Storage Temperature		-15°C to +50°C
Relative Humidity		0% to 95%, non-condensing
Operating Elevation		Up to 3,000 m [10,000 ft.] at +40°C without derating

Table 14: External Battery Cabinet Specifications

Parameters	Model Number: S4K240BATC
Used with UPS Model	S4K5U6K5C
Dimensions, D x W x H, in. (mm)	
Unit (with bezel)	22.40 x 16.90 x 5.80 (570.0 x 430.0 x 148.0)
Shipping	29.30 x 20.80 x 16.00 (745.0 x 530.0 x 407.0)
Weight, lbs. (kg)	
Unit	111.0 (50.40)
Shipping	119.0 (54.00)
Battery Parameters	
Type	Valve-regulated, non-spillable, lead acid
Qty x V	1 x 20 x 12 V
Battery Mfr./Part Number	Yuasa/NPH5-12
Backup Time	See Table 15
Environmental Requirements	
Operating Temperature	0°C to +40°C
Storage Temperature	-15°C to +50°C
Relative Humidity	0% to 95%, non-condensing
Operating Elevation	Up to 1,000 m [3,281 ft.] at +40°C

Table 15: Battery Backup Times

Number of Batteries/Cabinets	Load % of Capacity	Model Rating
		6 kVA
		Backup Time in Minutes
Internal battery	10%	97
	20%	47
	30%	33
	40%	22
	50%	17
	60%	14
	70%	11
	80%	9
	90%	8
	100%	6
Internal battery + 1 external battery cabinets	10%	158
	20%	97
	30%	65
	40%	48
	50%	40
	60%	33
	70%	26
	80%	22
	90%	19
	100%	17
Internal battery + 2 external battery cabinets	10%	205
	20%	123
	30%	97
	40%	74
	50%	53
	60%	48
	70%	43
	80%	38
	90%	33
	100%	28
Internal battery + 3 external battery cabinets	10%	223
	20%	158
	30%	110
	40%	97
	50%	78
	60%	66
	70%	52
	80%	48
	90%	44
	100%	41
Internal battery + 4 external battery cabinets	10%	360
	20%	191
	30%	138
	40%	108
	50%	97
	60%	81
	70%	71
	80%	61
	90%	51
	100%	48

The factory default is programmed for internal batteries only. Table 15 shows the estimated battery backup times at different loads. The user may specify the number of external battery cabinets attached to the UPS.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Sola/Hevi-Duty:](#)

[S4K4U6000](#)