No. of Contacts	DIMENSIONS A	DIMENSIONS B
2	2.00	4.00
3	4.00	6.00
4	6.00	8.00
5	8.00	10.00
6	10.00	12.00
7	12.00	14.00
8	14.00	16.00
9	16.00	18.00
10	18.00	20.00
11	20.00	22.00
12	22.00	24.00
13	24.00	26.00
14	26.00	28.00
15	28.00	30.00
16	30.00	32.00
17	32.00	34.00
18	34.00	36.00
19	36.00	38.00
20	38.00	40.00
21	40.00	42.00
22	42.00	44.00
23	44.00	46.00
24	46.00	48.00
25	48.00	50.00
26	50.00	52.00
27	52.00	54.00
28	54.00	56.00
29	56.00	58.00
30	58.00	60.00
31	60.00	62.00
32	62.00	64.00
33	64.00	66.00
34	66.00	68.00
35	68.00	70.00
36	70.00	72.00
37	72.00	74.00
38	74.00	76.00
39	76.00	78.00
40	78.00	80.00

SPECIFICATIONS

Current Rating:	1 Amp
Insulator Resistance:	5000 Mega Ohms min.
Dielectric Withstanding:	AC 500 V
Operating Temperature:	-40 Degrees C. - +105 Degrees C.
Contact Material:	Brass
Insulator Material:	PBT,UL 94V-0
Contact Finish:	Overall Gold or Selective Plating Gold/Tin



Standard Part is:
PBT
Overall Gold Flash plating

Contact Sullins Electronics for additional plating options available.

To complete the part number, replace "xx" with number of contacts. The 3rd letter in the part number designates plating. Insert:

P = Gold flash all over
W = Selective Gold Flash / Tin on tail
Z = 10u" selective Gold / Tin on Tail
X = A30u" selective gold / Tin on tail

A	11-27-02	Added information notes

SULLINS
801 E. MISSION RD.
SAN MARCOS, CA 92069

GENERAL TOLERANCE	
XX. +-	XXX. +-
X. +- 0.20	.XXX +-
.X +- 0.10	X.β +-
.XX +- 0.05	.Xβ +-

SCALE 6:1	DRAWN	DATE	DWG. NO. T0016	TITLE	REV. A
UNIT MM	CHECK	DATE	PARTS NO. PR_Nxx1PAEN		SHEET
SIZE A4	APPROVE	DATE			