

Features

Regulated Converters

- 2:1 and 3:1 Wide Input Voltage Ranges
- 1kVDC, 2kVDC and 3kVDC Isolation
- UL94V-0 Package Material
- Continuous Short Circuit Protection
- Low Ripple and Noise
- Remote On/Off Control
- Efficiency to 83 %

Description

Very high power density, 2:1 or 3:1 input voltage range and a wide operating temperature range -40°C to +71°C and extra features such as On/Off control are just some of the characteristics of this converter which is ideal for highly sophisticated industrial designs. The RS3 is available with 2kV or 3kV isolation options (1kVDC is standard)

Selection Guide

Part Number		Input Voltage Range (VDC)	Rated Output Voltage (VDC)	Output Current Full Load (mA)	Efficiency typ. (%)	Max Capacitive Load ⁽¹⁾
SIP8						
RS3-xx3.3S	(H2/H3)	4.5-9, 9-18 18-36, 36-72	3.3	600	73-75 77-78	4700µF
RS3-xx05S	(H2/H3)	4.5-9, 9-18 18-36, 36-72	5	600	76-79 80-81	4700µF
RS3-xx09S	(H2/H3)	4.5-9, 9-18 18-36, 36-72	9	333	77-80 81-82	3300µF
RS3-xx12S	(H2/H3)	4.5-9, 9-18 18-36, 36-72	12	250	80-81 83	2200µF
RS3-xx15S	(H2/H3)	4.5-9, 9-18 18-36, 36-72	15	200	80-81 83	2200µF
RS3-xx3.3D	(H2/H3)	4.5-9, 9-18 18-36, 36-72	±3.3	±300	73-75 75	±2200µF
RS3-xx05D	(H2/H3)	4.5-9, 9-18 18-36, 36-72	±5	±300	76-80 80-81	±2200µF
RS3-xx09D	(H2/H3)	4.5-9, 9-18 18-36, 36-72	±9	±167	77-81 81	±2200µF
RS3-xx12D	(H2/H3)	4.5-9, 9-18 18-36, 36-72	±12	±125	78-83 83	±1000µF
RS3-xx15D	(H2/H3)	4.5-9, 9-18 18-36, 36-72	±15	±100	79-83 83	±1000µF
RS3-xx3.3SZ	(H2/H3)	9-27 20-60	3.3	600	73 74	4700µF
RS3-xx05SZ	(H2/H3)	9-27 20-60	5	600	76-79 78	4700µF
RS3-xx09SZ	(H2/H3)	9-27 20-60	9	333	77 79	3300µF
RS3-xx12SZ	(H2/H3)	9-27 20-60	12	250	80 80	2200µF
RS3-xx15SZ	(H2/H3)	9-27 20-60	15	200	80 80	2200µF
RS3-xx3.3DZ	(H2/H3)	9-27 20-60	±3.3	±300	73 74	±2200µF
RS3-xx05DZ	(H2/H3)	9-27 20-60	±5	±300	77 78	±2200µF
RS3-xx09DZ	(H2/H3)	9-27 20-60	±9	±167	79 79	±2200µF
RS3-xx12DZ	(H2/H3)	9-27 20-60	±12	±125	80 80	±1000µF
RS3-xx15DZ	(H2/H3)	9-27 20-60	±15	±100	80 80	±1000µF

No suffix is standard isolation (1kVDC) e.g., RS3-0505S

*add suffix /H2 or /H3 for 2kVDC or 3kVDC isolation, e.g., RS3-0505S/H2, RS3-0505DZ/H3

ECONOLINE

DC/DC-Converter

with 3 year Warranty

RECOM

3 Watt SIP8 Isolated Single & Dual Output




UL-60950-1 Certified
EN-60950-1 Certified
EN-60601-1 Certified*
 (* /H suffix)

RS3

Derating-Graph (Ambient Temperature)

RS3-(Z)S_D



2:1 Input
 (RS3-S/D)
 xx = 4.5-9Vin = 05
 xx = 9-18Vin = 12
 xx = 18-36Vin = 24
 xx = 36-72Vin = 48


3:1 Input
 (RS3-SZ/DZ)
 xx = 9-27Vin = 24
 xx = 20-60Vin = 48

Electrical Specifications (measured at $T_A = 25^\circ\text{C}$, at nominal input voltage and rated output current unless otherwise specified)

Input Voltage Range			2:1 and 3:1	
Output Accuracy		Nominal Vin and full load	±2% typ.	
Line Voltage Regulation		LL to HL, full load	±0.5% max.	
Load Voltage Regulation		20% to 100% full load	±0.5% typ.	
Minimum Load			10% ⁽²⁾	
Output Ripple and Noise		20MHz limited	50mVp-p max.	
Switching Frequency		20% to 100% full load	200kHz typ.	
Efficiency at Full Load			see Selection Guide	
Quiescent Current		RS3-05xxS_D	35mA typ.	
Nominal input Voltage		RS3-12xxS_D	25mA typ.	
(Standard, /H2 and /H3)		RS3-24xxS_D, SZ_DZ	20mA typ.	
		RS3-48xxS_D, SZ_DZ	10mA typ.	
Isolation Voltage	Standard	(tested for 1 second)	1000VDC	
		(rated for 1 minute*)	500VAC / 60Hz	
	/H2 Version	(tested for 1 second)	2000VDC	
		(rated for 1 minute*)	1000VAC / 60Hz	
	/H3 Version	(tested for 1 second)	3000VDC	
		(rated for 1 minute*)	1500VAC / 60Hz	
Isolation Capacitance (2:1 and 3:1)		H1	200pF max.	
(tested at 100kHz)		H2/H3	30pF max.	
Isolation Resistance			1GΩ min.	
Short Circuit Protection (see note)			Continuous	
Operating Temperature Range			−40°C to +71°C	
Storage Temperature Range			−55°C to +125°C	
Relative Humidity			95% RH	
Package Weight			4.7g	
Packing Quantity			22 pcs per Tube	
MTBF (+25°C) (+71°C)		Detailed Information see Application Notes chapter "MTBF"	using MIL-HDBK 217F	3303 x10³ hours
			using MIL-HDBK 217F	745 x10³ hours
Certifications				
EN General Safety	Report: SPCLVD1605077-10		EN60950-1, AM2:2013	
EN Medical Safety	Report: MDD1205098-3 + RM1205098-3		IEC/EN 60601-1 3rd Edition	
	Medical Report + ISO14971 Risk Assessment			
UL General Safety	Report: E224736-A34		UL60950-1, 2nd Edition 2014	
	CSA C22.2 60950-1-07, 2nd Edition 2014			

Note: To protect the converter under all fault conditions, an input fuse is required. Quick-blow fuses should be rated at 2x-3x the normal input current, time-delay fuses at 1.5x the normal input current.

Typical Application




**Any data referred to in this datasheet are of indicative nature and based on our practical experience only. For further details, please refer to our Application Notes.

Notes


Note 1:	Maximum capacitive load is defined as the capacitive load that will allow start up in under 1 second without damage to the converter
Note 2:	The RS3 series requires a minimum of 10% load on the output to maintain specified regulation. Operating under no-load conditions will not damage these devices; however, they may not meet all listed specifications.

Typical Characteristics





RS3-0505S





RS3-4805D



Package Style and Pinning (mm)



Recommended Footprint Details



XX.X ± 0.5 mm
XX.XX ± 0.25 mm

Pin Connections

Pin #	Single	Dual
1	-Vin	-Vin
2	+Vin	+Vin
3	CTRL	CTRL
5	NC	NC
6	+Vout	+Vout
7	-Vout	Com
8	NC	-Vout

NC = No Connection

Pin 8 (NC*) This pin is used internally and must have no external connection.


Pin 5 (NC) Not connected internally.

Pin 3 (CTRL)


This pin provides an Off function which puts the converter into a low power mode. When the pin is 'high' the converter is OFF and when the pin is high 'Z' the converter is ON. There is no allowed low state for this pin.

Application Examples

ON/OFF CONTROL



I = 3V
0 = 0.5V or GND



Remote ON/OFF

ON: open or high impedance

OFF: external 5~12 Vdc and 1N4148+ 68Ω resistor