

UP04210/4211/4213/4214/4215/4216

Silicon NPN epitaxial planar transistor

For switching/digital circuits

■ Features

- Two elements incorporated into one package
(Transistors with built-in resistor)
- Reduction of the mounting area and assembly cost by one half

■ Resistance by Part Number


	Marking symbol	(R ₁)	(R ₂)
• UP04210	8Z	47 kΩ	—
• UP04211	9V	10 kΩ	10 kΩ
• UP04213	8S	47 kΩ	47 kΩ
• UP04214	BR	10 kΩ	47 kΩ
• UP04215	8T	10 kΩ	—
• UP04216	8U	4.7 kΩ	—

■ Absolute Maximum Ratings T_a = 25°C


Parameter	Symbol	Rating	Unit
Collector to base voltage	V _{CBO}	50	V
Collector to emitter voltage	V _{CEO}	50	V
Collector current	I _C	100	mA
Total power dissipation	P _T	125	mW
Junction temperature	T _j	125	°C
Storage temperature	T _{stg}	−55 to +125	°C

■ Electrical Characteristics T_a = 25°C ± 3°C

Parameter		Symbol	Conditions	Min	Typ	Max	Unit
Collector to base voltage		V _{CBO}	I _C = 10 μA, I _E = 0	50			V
Collector to emitter voltage		V _{CEO}	I _C = 2 mA, I _B = 0	50			V
Collector cutoff current		I _{CBO}	V _{CB} = 50 V, I _E = 0			0.1	μA
		I _{CEO}	V _{CE} = 50 V, I _B = 0			0.5	
Emitter cutoff current	UP04211	I _{EBO}	V _{EB} = 6 V, I _C = 0			0.5	mA
	UP04214					0.2	
	UP04213					0.1	
	UP04210/4215/4216					0.01	
Forward current transfer ratio	UP04211	h _{FE}	V _{CE} = 10 V, I _C = 5 mA	35			
	UP04213/4214			80			
	UP04210/4215/4216			160		460	
Collector to emitter saturation voltage		V _{CE(sat)}	I _C = 10 mA, I _B = 0.3 mA			0.25	V




Internal Connection






■ Electrical Characteristics (continued) $T_a = 25^{\circ}\text{C} \pm 3^{\circ}\text{C}$



Parameter	Symbol	Conditions	Min	Typ	Max	Unit
High-level output voltage	V_{OH}	$V_{CC} = 5\text{ V}$, $V_B = 0.5\text{ V}$, $R_L = 1\text{ k}\Omega$	4.9			V
Low-level output voltage	V_{OL}	$V_{CC} = 5\text{ V}$, $V_B = 2.5\text{ V}$, $R_L = 1\text{ k}\Omega$			0.2	V
	UP04213	$V_{CC} = 5\text{ V}$, $V_B = 3.5\text{ V}$, $R_L = 1\text{ k}\Omega$				
Input resistance	UP04216		-30%	4.7	+30%	k Ω
	UP04211/4214/4215			10		
	UP04210/4213			47		
Resistance ratio	UP04211/4213	R_1 / R_2	0.8	1.0	1.2	
	UP04214		0.17	0.21	0.25	
Gain bandwidth product	f_T	$V_{CB} = 10\text{ V}$, $I_E = -2\text{ mA}$, $f = 200\text{ MHz}$		150		MHz

Common characteristics chart









Characteristics charts of UP04210







Characteristics charts of UP04211






Characteristics charts of UP04213









Characteristics charts of UP04214











Characteristics charts of UP04215



Characteristics charts of UP04216



Request for your special attention and precautions in using the technical information and semiconductors described in this book

- (1) An export permit needs to be obtained from the competent authorities of the Japanese Government if any of the products or technologies described in this book and controlled under the "Foreign Exchange and Foreign Trade Law" is to be exported or taken out of Japan.
- (2) The technical information described in this book is limited to showing representative characteristics and applied circuits examples of the products. It neither warrants non-infringement of intellectual property right or any other rights owned by our company or a third party, nor grants any license.
- (3) We are not liable for the infringement of rights owned by a third party arising out of the use of the product or technologies as described in this book.
- (4) The products described in this book are intended to be used for standard applications or general electronic equipment (such as office equipment, communications equipment, measuring instruments and household appliances).
Consult our sales staff in advance for information on the following applications:
 - Special applications (such as for airplanes, aerospace, automobiles, traffic control equipment, combustion equipment, life support systems and safety devices) in which exceptional quality and reliability are required, or if the failure or malfunction of the products may directly jeopardize life or harm the human body.
 - Any applications other than the standard applications intended.
- (5) The products and product specifications described in this book are subject to change without notice for modification and/or improvement. At the final stage of your design, purchasing, or use of the products, therefore, ask for the most up-to-date Product Standards in advance to make sure that the latest specifications satisfy your requirements.
- (6) When designing your equipment, comply with the guaranteed values, in particular those of maximum rating, the range of operating power supply voltage, and heat radiation characteristics. Otherwise, we will not be liable for any defect which may arise later in your equipment.
Even when the products are used within the guaranteed values, take into the consideration of incidence of break down and failure mode, possible to occur to semiconductor products. Measures on the systems such as redundant design, arresting the spread of fire or preventing glitch are recommended in order to prevent physical injury, fire, social damages, for example, by using the products.
- (7) When using products for which damp-proof packing is required, observe the conditions (including shelf life and amount of time let standing of unsealed items) agreed upon when specification sheets are individually exchanged.
- (8) This book may be not reprinted or reproduced whether wholly or partially, without the prior written permission of Matsushita Electric Industrial Co., Ltd.