

PMFPB8040XP

20 V, 3.7 A / 440 mV V_F P-channel MOSFET-Schottky combination

21 December 2012

Product data sheet

1. General description

Small-signal P-channel enhancement mode Field-Effect Transistor (FET) using Trench MOSFET technology and ultra low V_F Maximum Efficiency General Application (MEGA) Schottky diode combined in a small and leadless ultra thin DFN2020-6 (SOT1118) Surface-Mounted Device (SMD) plastic package.

2. Features and benefits

- 1.8 V R_{DSon} rated for low-voltage gate drive
- Small and leadless ultra thin SMD plastic package: $2 \times 2 \times 0.65$ mm
- Exposed drain pad for excellent thermal conduction
- Integrated ultra low V_F MEGA Schottky diode

3. Applications

- Charging switch for portable devices
- DC-to-DC converters
- Power management in battery-driven portables
- Hard disk and computing power management

4. Quick reference data

Table 1. Quick reference data

Symbol	Parameter	Conditions		Min	Typ	Max	Unit
MOSFET transistor							
V_{DS}	drain-source voltage	$T_j = 25\text{ }^{\circ}\text{C}$		-	-	-20	V
V_{GS}	gate-source voltage			-12	-	12	V
I_D	drain current	$V_{GS} = -4.5\text{ V}$; $T_{amb} = 25\text{ }^{\circ}\text{C}$; $t \leq 5\text{ s}$	[1]	-	-	-3.7	A
Schottky diode							
I_F	forward current	$T_{sp} \leq 105\text{ }^{\circ}\text{C}$		-	-	2	A
V_R	reverse voltage	$T_{amb} = 25\text{ }^{\circ}\text{C}$		-	-	30	V
MOSFET transistor static characteristics							
R_{DSon}	drain-source on-state resistance	$V_{GS} = -4.5\text{ V}$; $I_D = -2.7\text{ A}$; $T_j = 25\text{ }^{\circ}\text{C}$		-	80	102	m Ω



Scan or click this QR code to view the latest information for this product





Symbol	Parameter	Conditions	Min	Typ	Max	Unit
Schottky diode						
V_F	forward voltage	$I_F = 1\text{ A}$; $T_j = 25\text{ °C}$	-	440	520	mV

[1] Device mounted on an FR4 PCB, single-sided copper, tin-plated, mounting pad for drain 6 cm².

5. Pinning information

Table 2. Pinning information

Pin	Symbol	Description	Simplified outline	Graphic symbol
1	A	anode	 Transparent top view DFN2020-6 (SOT1118)	 aaa-003667
2	n.c.	not connected		
3	D	drain		
4	S	source		
5	G	gate		
6	K	cathode		
7	K	cathode		
8	D	drain		

6. Ordering information

Table 3. Ordering information

Type number	Package		
	Name	Description	Version
PMFPB8040XP	DFN2020-6	plastic thermal enhanced ultra thin small outline package; no leads; 6 terminals; body 2 x 2 x 0.65 mm	SOT1118

7. Marking

Table 4. Marking codes

Type number	Marking code
PMFPB8040XP	1Y

8. Limiting values

Table 5. Limiting values

In accordance with the Absolute Maximum Rating System (IEC 60134).

Symbol	Parameter	Conditions	Min	Max	Unit
MOSFET transistor					
V_{DS}	drain-source voltage	$T_j = 25\text{ °C}$	-	-20	V

20 V, 3.7 A / 440 mV VF P-channel MOSFET-Schottky combination

Symbol	Parameter	Conditions		Min	Max	Unit
V _{GS}	gate-source voltage			-12	12	V
I _D	drain current	V _{GS} = -4.5 V; T _{amb} = 25 °C; t ≤ 5 s	[1]	-	-3.7	A
		V _{GS} = -4.5 V; T _{amb} = 25 °C	[1]	-	-2.7	A
		V _{GS} = -4.5 V; T _{amb} = 100 °C	[1]	-	-1.7	A
I _{DM}	peak drain current	T _{amb} = 25 °C; single pulse; t _p ≤ 10 μs		-	-11	A
P _{tot}	total power dissipation	T _{amb} = 25 °C	[2]	-	485	mW
			[1]	-	1100	mW
		T _{sp} = 25 °C		-	6250	mW
Source-drain diode						
I _S	source current	T _{amb} = 25 °C	[1]	-	-1.1	A
Schottky diode						
V _R	reverse voltage	T _{amb} = 25 °C		-	30	V
I _F	forward current	T _{sp} ≤ 105 °C		-	2	A
I _{FRM}	repetitive peak forward current	t _p ≤ 1 ms; δ ≤ 0.25 ; T _{amb} = 25 °C		-	7	A
I _{FSM}	non-repetitive peak forward current	t _p = 8 ms; T _{j(init)} = 25 °C; square wave		-	18	A
		t _p = 8 ms; T _{j(init)} = 25 °C; half-sine wave	[3]	-	25	A
P _{tot}	total power dissipation	T _{amb} = 25 °C	[2]	-	480	mW
			[1]	-	1190	mW
		T _{sp} = 25 °C		-	6250	mW
Per device						
T _j	junction temperature			-55	150	°C
T _{amb}	ambient temperature			-55	150	°C
T _{stg}	storage temperature			-65	150	°C

[1] Device mounted on an FR4 PCB, single-sided copper, tin-plated, mounting pad for drain 6 cm².

[2] Device mounted on an FR4 PCB, single-sided copper, tin-plated and standard footprint.

[3] Calculated from square-wave measurements.




Fig. 1. MOSFET transistor: Normalized total power dissipation as a function of junction temperature

$$P_{der} = \frac{P_{tot}}{P_{tot(25^{\circ}C)}} \times 100 \%$$





Fig. 2. MOSFET transistor: Normalized continuous drain current as a function of junction temperature

$$I_{der} = \frac{I_D}{I_{D(25^{\circ}C)}} \times 100 \%$$



I_{DM} = single pulse

Fig. 3. MOSFET transistor: Safe operating area; junction to ambient; continuous and peak drain currents as a function of drain-source voltage


9. Thermal characteristics


Table 6. Thermal characteristics

Symbol	Parameter	Conditions		Min	Typ	Max	Unit
MOSFET transistor							
R _{th(j-a)}	thermal resistance from junction to ambient	in free air	[1]	-	225	260	K/W
			[2]	-	99	115	K/W
		in free air; t ≤ 5 s	[2]	-	54	62	K/W
R _{th(j-sp)}	thermal resistance from junction to solder point			-	16	20	K/W
Schottky diode							
R _{th(j-a)}	thermal resistance from junction to ambient	in free air	[1]	-	-	260	K/W
			[2]	-	-	105	K/W
R _{th(j-sp)}	thermal resistance from junction to solder point			-	-	20	K/W

[1] Device mounted on an FR4 PCB, single-sided copper, tin-plated and standard footprint.


[2] Device mounted on an FR4 PCB, single-sided copper, tin-plated, mounting pad for drain 6 cm².






FR4 PCB, mounting pad for drain 6 cm²

Fig. 5. MOSFET transistor: Transient thermal impedance from junction to ambient as a function of pulse duration; typical values



FR4 PCB, standard footprint

Fig. 6. Schottky diode: Transient thermal impedance from junction to ambient as a function of pulse duration; typical values



FR4 PCB, mounting pad for cathode 6 cm²

Fig. 7. Schottky diode: Transient thermal impedance from junction to ambient as a function of pulse duration; typical values

10. Characteristics

Table 7. Characteristics

Symbol	Parameter	Conditions	Min	Typ	Max	Unit
MOSFET transistor static characteristics						
$V_{(BR)DSS}$	drain-source breakdown voltage	$I_D = -250 \mu A$; $V_{GS} = 0 V$; $T_j = 25^\circ C$	-20	-	-	V
V_{GSth}	gate-source threshold voltage	$I_D = -250 \mu A$; $V_{DS} = V_{GS}$; $T_j = 25^\circ C$	-0.4	-0.6	-1	V
I_{DSS}	drain leakage current	$V_{DS} = -20 V$; $V_{GS} = 0 V$; $T_j = 25^\circ C$	-	-	-1	μA
		$V_{DS} = -20 V$; $V_{GS} = 0 V$; $T_j = 150^\circ C$	-	-	-10	μA
I_{GSS}	gate leakage current	$V_{GS} = -12 V$; $V_{DS} = 0 V$; $T_j = 25^\circ C$	-	-	-100	nA
		$V_{GS} = 12 V$; $V_{DS} = 0 V$; $T_j = 25^\circ C$	-	-	100	nA
R_{DSon}	drain-source on-state resistance	$V_{GS} = -4.5 V$; $I_D = -2.7 A$; $T_j = 25^\circ C$	-	80	102	m Ω
		$V_{GS} = -4.5 V$; $I_D = -2.7 A$; $T_j = 150^\circ C$	-	116	148	m Ω
		$V_{GS} = -2.5 V$; $I_D = -2.5 A$; $T_j = 25^\circ C$	-	95	125	m Ω
		$V_{GS} = -1.8 V$; $I_D = -1.1 A$; $T_j = 25^\circ C$	-	120	156	m Ω
g_{fs}	transfer conductance	$V_{DS} = -10 V$; $I_D = -2.7 A$; $T_j = 25^\circ C$	-	15	-	S
MOSFET transistor dynamic characteristics						
$Q_{G(tot)}$	total gate charge	$V_{DS} = -10 V$; $I_D = -2.7 A$; $V_{GS} = -4.5 V$; $T_j = 25^\circ C$	-	5.7	8.6	nC
Q_{GS}	gate-source charge		-	0.7	-	nC
Q_{GD}	gate-drain charge		-	0.96	-	nC

Symbol	Parameter	Conditions		Min	Typ	Max	Unit
C _{iss}	input capacitance	V _{DS} = -10 V; f = 1 MHz; V _{GS} = 0 V; T _j = 25 °C		-	550	-	pF
C _{oss}	output capacitance			-	63	-	pF
C _{rss}	reverse transfer capacitance			-	53	-	pF
t _{d(on)}	turn-on delay time	V _{DS} = -10 V; I _D = -2.4 A; V _{GS} = -4.5 V; R _{G(ext)} = 6 Ω; T _j = 25 °C		-	6	-	ns
t _r	rise time			-	14	-	ns
t _{d(off)}	turn-off delay time			-	120	-	ns
t _f	fall time			-	50	-	ns
MOSFET transistor source-drain diode							
V _{SD}	source-drain voltage	I _S = -1.1 A; V _{GS} = 0 V; T _j = 25 °C		-	-0.8	-1.2	V
Schottky diode							
V _F	forward voltage	I _F = 100 mA; T _j = 25 °C		-	330	390	mV
		I _F = 500 mA; T _j = 25 °C		-	400	460	mV
		I _F = 1 A; T _j = 25 °C		-	440	520	mV
I _R	reverse current	V _R = 5 V; T _j = 25 °C		-	1	3.5	μA
		V _R = 5 V; T _j = 125 °C		-	0.33	1.2	mA
		V _R = 10 V; T _j = 25 °C		-	2	5	μA
		V _R = 20 V; T _j = 25 °C		-	4	15	μA
		V _R = 30 V; T _j = 25 °C		-	8	30	μA
C _d	diode capacitance	V _R = 5 V; f = 1 MHz; T _j = 25 °C		-	45	55	pF




Fig. 8. MOSFET transistor: Output characteristics: drain current as a function of drain-source voltage; typical values




Fig. 9. MOSFET transistor: Subthreshold drain current as a function of gate-source voltage




Fig. 10. MOSFET transistor: Drain-source on-state resistance as a function of drain current; typical values




Fig. 11. MOSFET transistor: Drain-source on-state resistance as a function of gate-source voltage; typical values




Fig. 12. MOSFET transistor: Transfer characteristics: drain current as a function of gate-source voltage; typical values




Fig. 13. MOSFET transistor: Normalized drain-source on-state resistance as a function of junction temperature; typical values

$$a = \frac{R_{DS(on)}}{R_{DS(on)25^{\circ}\text{C}}}$$




Fig. 14. MOSFET transistor: Gate-source threshold voltage as a function of junction temperature




Fig. 15. MOSFET transistor: Input, output and reverse transfer capacitances as a function of drain-source voltage; typical values




Fig. 16. MOSFET transistor: Gate-source voltage as a function of gate charge; typical values




Fig. 17. MOSFET transistor: Gate charge waveform definitions




Fig. 18. MOSFET transistor: Source current as a function of source-drain voltage; typical values




Fig. 19. Schottky diode: Forward current as a function of forward voltage; typical values




Fig. 20. Schottky diode: Reverse current as a function of reverse voltage; typical values





Fig. 21. Schottky diode: Diode capacitance as a function of reverse voltage; typical values



FR4 PCB, mounting pad for cathode 6 cm²
T_j = 150 °C
(1) δ = 1; DC
(2) δ = 0.5; f = 20 kHz
(3) δ = 0.2; f = 20 kHz
(4) δ = 0.1; f = 20 kHz

Fig. 22. Schottky diode: Average forward current as a function of ambient temperature; typical values

11. Test information






Fig. 23. Duty cycle definition

12. Package outline



13. Soldering



14. Revision history

Table 8. Revision history

Data sheet ID	Release date	Data sheet status	Change notice	Supersedes
PMFPB8040XP v.1	20121221	Product data sheet	-	-

15. Legal information

15.1 Data sheet status

Document status [1][2]	Product status [3]	Definition
Objective [short] data sheet	Development	This document contains data from the objective specification for product development.
Preliminary [short] data sheet	Qualification	This document contains data from the preliminary specification.
Product [short] data sheet	Production	This document contains the product specification.

- [1] Please consult the most recently issued document before initiating or completing a design.
- [2] The term 'short data sheet' is explained in section "Definitions".
- [3] The product status of device(s) described in this document may have changed since this document was published and may differ in case of multiple devices. The latest product status information is available on the Internet at URL <http://www.nxp.com>.

15.2 Definitions

Preview — The document is a preview version only. The document is still subject to formal approval, which may result in modifications or additions. NXP Semiconductors does not give any representations or warranties as to the accuracy or completeness of information included herein and shall have no liability for the consequences of use of such information.

Draft — The document is a draft version only. The content is still under internal review and subject to formal approval, which may result in modifications or additions. NXP Semiconductors does not give any representations or warranties as to the accuracy or completeness of information included herein and shall have no liability for the consequences of use of such information.

Short data sheet — A short data sheet is an extract from a full data sheet with the same product type number(s) and title. A short data sheet is intended for quick reference only and should not be relied upon to contain detailed and full information. For detailed and full information see the relevant full data sheet, which is available on request via the local NXP Semiconductors sales office. In case of any inconsistency or conflict with the short data sheet, the full data sheet shall prevail.

Product specification — The information and data provided in a Product data sheet shall define the specification of the product as agreed between NXP Semiconductors and its customer, unless NXP Semiconductors and customer have explicitly agreed otherwise in writing. In no event however, shall an agreement be valid in which the NXP Semiconductors product is deemed to offer functions and qualities beyond those described in the Product data sheet.

15.3 Disclaimers

Limited warranty and liability — Information in this document is believed to be accurate and reliable. However, NXP Semiconductors does not give any representations or warranties, expressed or implied, as to the accuracy or completeness of such information and shall have no liability for the consequences of use of such information. NXP Semiconductors takes no responsibility for the content in this document if provided by an information source outside of NXP Semiconductors.

In no event shall NXP Semiconductors be liable for any indirect, incidental, punitive, special or consequential damages (including - without limitation - lost profits, lost savings, business interruption, costs related to the removal or replacement of any products or rework charges) whether or not such damages are based on tort (including negligence), warranty, breach of contract or any other legal theory.

Notwithstanding any damages that customer might incur for any reason whatsoever, NXP Semiconductors' aggregate and cumulative liability towards customer for the products described herein shall be limited in accordance with the *Terms and conditions of commercial sale* of NXP Semiconductors.

Right to make changes — NXP Semiconductors reserves the right to make changes to information published in this document, including without limitation specifications and product descriptions, at any time and without notice. This document supersedes and replaces all information supplied prior to the publication hereof.

Suitability for use — NXP Semiconductors products are not designed, authorized or warranted to be suitable for use in life support, life-critical or safety-critical systems or equipment, nor in applications where failure or malfunction of an NXP Semiconductors product can reasonably be expected to result in personal injury, death or severe property or environmental damage. NXP Semiconductors and its suppliers accept no liability for inclusion and/or use of NXP Semiconductors products in such equipment or applications and therefore such inclusion and/or use is at the customer's own risk.

Quick reference data — The Quick reference data is an extract of the product data given in the Limiting values and Characteristics sections of this document, and as such is not complete, exhaustive or legally binding.

Applications — Applications that are described herein for any of these products are for illustrative purposes only. NXP Semiconductors makes no representation or warranty that such applications will be suitable for the specified use without further testing or modification.

Customers are responsible for the design and operation of their applications and products using NXP Semiconductors products, and NXP Semiconductors accepts no liability for any assistance with applications or customer product design. It is customer's sole responsibility to determine whether the NXP Semiconductors product is suitable and fit for the customer's applications and products planned, as well as for the planned application and use of customer's third party customer(s). Customers should provide appropriate design and operating safeguards to minimize the risks associated with their applications and products.

NXP Semiconductors does not accept any liability related to any default, damage, costs or problem which is based on any weakness or default in the customer's applications or products, or the application or use by customer's third party customer(s). Customer is responsible for doing all necessary testing for the customer's applications and products using NXP Semiconductors products in order to avoid a default of the applications and the products or of the application or use by customer's third party customer(s). NXP does not accept any liability in this respect.

Limiting values — Stress above one or more limiting values (as defined in the Absolute Maximum Ratings System of IEC 60134) will cause permanent damage to the device. Limiting values are stress ratings only and (proper) operation of the device at these or any other conditions above those given in the Recommended operating conditions section (if present) or the Characteristics sections of this document is not warranted. Constant or repeated exposure to limiting values will permanently and irreversibly affect the quality and reliability of the device.

Terms and conditions of commercial sale — NXP Semiconductors products are sold subject to the general terms and conditions of commercial sale, as published at <http://www.nxp.com/profile/terms>, unless otherwise agreed in a valid written individual agreement. In case an individual agreement is concluded only the terms and conditions of the respective agreement shall apply. NXP Semiconductors hereby expressly objects to applying the customer's general terms and conditions with regard to the purchase of NXP Semiconductors products by customer.

No offer to sell or license — Nothing in this document may be interpreted or construed as an offer to sell products that is open for acceptance or the

grant, conveyance or implication of any license under any copyrights, patents or other industrial or intellectual property rights.

Export control — This document as well as the item(s) described herein may be subject to export control regulations. Export might require a prior authorization from competent authorities.

Non-automotive qualified products — Unless this data sheet expressly states that this specific NXP Semiconductors product is automotive qualified, the product is not suitable for automotive use. It is neither qualified nor tested in accordance with automotive testing or application requirements. NXP Semiconductors accepts no liability for inclusion and/or use of non-automotive qualified products in automotive equipment or applications.

In the event that customer uses the product for design-in and use in automotive applications to automotive specifications and standards, customer (a) shall use the product without NXP Semiconductors' warranty of the product for such automotive applications, use and specifications, and (b) whenever customer uses the product for automotive applications beyond NXP Semiconductors' specifications such use shall be solely at customer's own risk, and (c) customer fully indemnifies NXP Semiconductors for any liability, damages or failed product claims resulting from customer design and use of the product for automotive applications beyond NXP Semiconductors' standard warranty and NXP Semiconductors' product specifications.

Translations — A non-English (translated) version of a document is for reference only. The English version shall prevail in case of any discrepancy between the translated and English versions.

15.4 Trademarks

Notice: All referenced brands, product names, service names and trademarks are the property of their respective owners.

Adelante, Bitport, Bitsound, CoolFlux, CoReUse, DESFire, EZ-HV, FabKey, GreenChip, HiPerSmart, HITAG, I²C-bus logo, ICODE, I-CODE, ITEC, Labelution, MIFARE, MIFARE Plus, MIFARE Ultralight, MoReUse, QLPAK, Silicon Tuner, SiliconMAX, SmartXA, STARplug, TOPFET, TrenchMOS, TriMedia and UCODE — are trademarks of NXP B.V.

HD Radio and **HD Radio** logo — are trademarks of iBiquity Digital Corporation.

16. Contents

1 General description 1

2 Features and benefits 1

3 Applications 1

4 Quick reference data 1

5 Pinning information 2

6 Ordering information 2

7 Marking 2

8 Limiting values 2

9 Thermal characteristics 5

10 Characteristics 7

11 Test information 12

12 Package outline 13

13 Soldering 13

14 Revision history 13

15 Legal information 14

15.1 Data sheet status 14

15.2 Definitions 14

15.3 Disclaimers 14

15.4 Trademarks 15

© NXP B.V. 2012. All rights reserved

For more information, please visit: <http://www.nxp.com>

For sales office addresses, please send an email to: salesaddresses@nxp.com

Date of release: 21 December 2012