


REV.	DESCRIPTION/ECO NO.	DATE
	RELEASED	2/4/03
A	OPERATING SPEC. CHANGE	11/15/04



NO.	PIN NUMBER		JKL MATING WIRE HARNESS
CN1	1	INPUT (+12V)	BXC-10549
	2	INPUT (GND)	
	3	SW1 INHIBIT (+V OR OPEN = OFF / GND = ON)	
	4	VR1	
	5	VR1 POTENTIOMETER (10K)	
CN2	1	OUTPUT (HV)	BXC-10643
	2	NO CONNECTION	
	3	OUTPUT (GND)	

NOTE:
 MATING CONNECTORS ARE NOT INCLUDED WITH INVERTER.
 JKL WIRE HARNESS BXC-10549 AND BXC-10643 CAN BE ORDERED SEPARATELY.

OPERATING SPECIFICATIONS

CHARACTERISTICS	MIN	TYP	MAX
INPUT VOLTAGE: (vdc)	8.0	12.0	16.0
INPUT CURRENT: (mA)	-	320	-
OUTPUT VOLTAGE: (Vrms)	-	1200	-
OUTPUT CURRENT (mA)	4.0	5.0	6.0
OUTPUT FREQUENCY: (kHz)	45	55	65
DIMMING RANGE (%)	33	-	100
OPERATING TEMP: (CELSIUS)	0		60

METRIC THIRD ANGLE PROJECTION	DIMENSIONS ARE IN MILLIMETERS TOLERANCE UNLESS OTHERWISE SPECIFIED 1 PL +/- 0.3 2 PL +/- 0		JKL COMPONENTS CORPORATION				
			TITLE SINGLE OUTPUT DIMMING INVERTER				
	DRAWN BY L. WENGSTROM	APPVD BY J.K.	DATE 11/15/04	SIZE A	FSCM NO. 55335	DRAWING NO. BXA-12598-5M	
- CAD DRAWING - MANUAL REVISIONS NOT PERMITTED			SCALE NONE	RELEASED DATE 2/4/03	REVISION DATE 11/15/04	REV. NO. A	SHEET OF