


Molded, Dual-In-Line Resistor Networks




Actual Size

Vishay Thin Film offers two standard circuits in a 14 and 16 pin molded dual-in-line over a 100 Ω to 100 k Ω resistance range. The networks feature ratio tolerance to 0.05 % with a TCR tracking of 5 ppm/ $^{\circ}$ C.

SCHEMATIC

Schematic TDP01



Models: TDP1401 and TDP1601
13 or 15 resistors with one pin common

FEATURES

- Lead (Pb)-free available
- Standard Rugged, molded case construction (14 and 16 Pin)
- Highly stable thin film (500 ppm at + 70 $^{\circ}$ C at 2000 hours)
- Low temperature coefficient (± 25 ppm/ $^{\circ}$ C)
- Compatible with automatic insertion equipment
- Standard isolated pin one common schematic




RoHS*
COMPLIANT

TYPICAL PERFORMANCE

	ABS	TRACKING
TCR	25	5
	ABS	RATIO
TOL	0.1	0.05

Schematic TDP03




Models: TDP1403 and TDP1603
7 or 8 isolated resistors

STANDARD ELECTRICAL SPECIFICATIONS


TEST	SPECIFICATIONS	CONDITIONS
SCHEMATIC	TDP01, TDP03	
Resistance Range	100 Ω to 100 k Ω	
TCR:	Ratio	± 5 ppm/ $^{\circ}$ C
	Absolute	± 25 ppm/ $^{\circ}$ C
Tolerance:	Ratio	± 0.05 % to ± 0.5 %
	Absolute	± 0.1 %
Power Rating:	Resistor	01 Circuit = 0.05 W/resistor 03 Circuit = 0.10 W/resistor
	Package	0.8 W/package
Stability:	ΔR Absolute	500 ppm
	ΔR Ratio	150 ppm
Voltage Coefficient	< 1 ppm/Volt typical	
Working Voltage	100 Volts	
Operating Temperature Range	- 55 $^{\circ}$ C to + 125 $^{\circ}$ C	
Storage Temperature Range	- 55 $^{\circ}$ C to + 150 $^{\circ}$ C	
Noise	< - 30 dB	
Thermal EMF	0.08 μ V/ $^{\circ}$ C	
Shelf Life Stability:	Absolute	100 ppm
	Ratio	20 ppm

* Pb containing terminations are not RoHS compliant, exemptions may apply

DIMENSIONS AND IMPRINTING in inches and millimeters



DIMENSION	INCHES	MM
A	0.755	19.18
B	0.250	6.35
C	0.075	1.91
D	0.100	2.54
E	0.018	0.46
F	0.060	1.52
G	0.025	0.64
H	0.190	4.83
J	0.130	3.30
K	0.320	8.13
L	0.310	7.87
M	0.010	0.25



DIMENSION	INCHES	MM
A	0.755	19.18
B	0.250	6.35
C	0.025	0.64
D	0.100	2.54
E	0.018	0.46
F	0.060	1.52
G	0.025	0.64
H	0.190	4.83
J	0.130	3.30
K	0.320	8.13
L	0.310	7.87
M	0.010	0.25

MECHANICAL SPECIFICATIONS

Resistive Element	Passivated Nichrome
Substrate Material	Silicon or Alumina
Body	Molded Epoxy
Terminals	Copper Alloy #42
Plating	Sn60
Marking Resistance to Solvents	Per MIL-PRF-83401
Lead (Pb)-free Option	100 % Sn Matte
Lead (Pb)-free Finish	Plated

GLOBAL PART NUMBER INFORMATION

New Global Part Numbering: TDP14031002BUF (preferred part number format)

	T	D	P	1	4	0	3	1	0	0	2	B	U	F
T	D	P	T	1	6	0	3	1	0	0	3	A	U	F

GLOBAL MODEL
(3 or 4 digits)

PINS

SCHEMATIC

RESISTANCE

TOLERANCE AND
RATIO TOLERANCE

PACKAGING

TDP
(Tin Lead)**14****01** = 13 or 15
resistors with
1 common pin

03 = 7 or 8
isolated resistorsFirst 3 digits are
significant figures and
the last digit specifies
the number of zeroes
to follow.Example:
1001 = 1K
1002 = 10K

Abs. Tol.	Ratio
*A = $\pm 0.1\%$	$\pm 0.05\%$
B = $\pm 0.1\%$	$\pm 0.1\%$
C = $\pm 0.25\%$	$\pm 0.1\%$
D = $\pm 0.5\%$	$\pm 0.1\%$
F = $\pm 1\%$	$\pm 0.5\%$

* Tol. available on 1 k Ω
and up only R1 is
reference resistors**UF** = TUBED

Historical Part Number example: TDP14031001F (will continue to be accepted)

TDP**14****03****1001****F**

SERIES

PINS

SCHEMATIC

RESISTANCE

TOLERANCE AND
RATIO TOLERANCE

THROUGH HOLE



Disclaimer

All product specifications and data are subject to change without notice.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product.

Vishay disclaims any and all liability arising out of the use or application of any product described herein or of any information provided herein to the maximum extent permitted by law. The product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein, which apply to these products.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications unless otherwise expressly indicated. Customers using or selling Vishay products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify Vishay for any damages arising or resulting from such use or sale. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

Product names and markings noted herein may be trademarks of their respective owners.