

AN7318/S


Dual Recording and Playback Pre-Amplifier Circuit with ALC

■ Description


The AN7318/S are monolithic integrated circuits designed for dual pre-amplifier circuit with ALC for record/playback amplifier of cassette tape recorder.

■ Features

- High open loop gain (typically 100dB)
- Incorporates ALC detector circuit
- Low noise (typically 0.7μV)
- Low current consumption (typical I_{CQ} is 4.5mA)
- Less EMI achievable via external RC network
- Low power ON shock noise



■ Block Diagram



■ Absolute Maximum Ratings (Ta=25°C)

Item	Symbol	Rating	Unit
Supply Voltage	V _{CC}	14	V
Supply Current	I _{CC}	50	mA
Power Dissipation (Ta = 75°C)	P _D	200	mW
Operating Ambient Temperature	T _{opr}	-20 ~ +75	°C
Storage Temperature	T _{stg}	-55 ~ +125	°C

Operating Supply Voltage Range: V_{CC} = 5.0V ~ 12.0V

■ Electrical Characteristics (V_{CC}=6V, f=1kHz, R_L=5.1kΩ Ta=25±2°C)

Item	Symbol	SW1	SW2	Condition	min.	typ.	max.	Unit
Quiescent Current	I _{CQ}	B	B	V _{in} = 0mV	2.5	4.5	8.0	mA
Close Circuit Voltage Gain	G _{VC}	B	A	V _O = 0.5V	66	70	72	dP
Total Harmonic Distortion	THD	B	A	V _O = 0.5V		0.5	1.0	%
Maximum Output Voltage	V _O	B	A	THD = 1%	1.2	1.6		V
Output Noise Voltage	V _{no}	B	B	R _g = 0Ω DIN/AUDIO		2.0	4.2	mV
ALC Voltage	V _{ALC}	A	A	V _{in} = 400μV	0.55	0.63	0.7	V
ALC Width	W _{ALC}	A	A	Starting point 3dB up	35	47		dB
Channel Balance	CB	B	A	V _O = 0.5V, CB = Gv1 - Gv2	-1	0	+1	dB

■ Pin

Pin No.	Pin Name	Pin No.	Pin Name
1 ①	GND	9	NC
2 ②	ALC Time Constant	10 ⑧	Channel 2 Input
3 ③	Channel 1 ALC Input	11 ⑨	Channel 2 Negative Feedback
4 ④	Channel 1 Output	12 ⑩	Reference Pin 2
5 ⑤	Reference Pin 1	13 ⑪	Channel 2 Output
6 ⑥	Channel 1 Negative Feedback	14 ⑫	Channel 2 ALC Input
7 ⑦	Channel 1 Input	15 ⑬	Ripple Filter
8	N.C	16 ⑭	V _{CC}




Show the pin of AN7318

■ Comparison of AN7318/S with AN7312


AN7318/S has the following modification over AN7312

- 1) Both input resistors R₁ and R₂ (1.5kΩ) are short-circuited.
- 2) Both feedback resistors R₅ and R₆ (56kΩ) are open-circuited.
- 3) DC Bias resistor R₄₇ (54kΩ) is open-circuited. Externally, R₄₇ is to be connected between pin 5 and pin 12.
- 4) Gvo at 10kHz is increased to 78dB.

Test Circuit



■ Application Circuit



■ 6932852 0013960 109 ■

341

Panasonic