

Industries

Solutions

.

Services

Software

Partners

Support

, ,

About Us

-Search-

Entire Site

▼ GO

Search Results

Evaluate

- FAQ's

Design a Solution

- Part Drawings
- PDF-Pre-Terminat ...

How to Buy

- Bill of Material
- Favorite Products List
- Locate Distributor

Home > Product On-Line Catalog > Search Results >

Products

Your search criteria matched only one product, shown below

F66D3-NM2Y



Fan-Out Cords - Multimode 62.5/125µm (OM1)

- Pass all TIA/EIA-568-B.3 performance requirements
- Insertion loss per connection: 0.10dB typical; 0.30dB maximum
- Pigtailed (open) end allows quick high performance field fusion splice during installation to provide the lowest installed cost
- 900µm tight-buffered fibers break out to terminated colored buffers for quick and easy identification of separate channels for accurate installations
- Factory terminated and 100% tested for insertion loss
- Insertion loss data recorded for every multimode fan-out cord
- Lifetime traceability of test data to a Q.C. number on each fan-out cord
- Highest quality flame retardant fiber optic cable with tight-buffered coating on each optical fiber

Part Number	F66D3-NM2Y
 RoHS Compliancy Status 	Intended for use in fixed installations which are outside the scope of RoHS
Note	F66D3-NM2Y replaces F66D3-NM2
Part Description	SC to pigtail 6-fiber fan-out cord (six SC connectors on one end and open on the other end on distribution cable) – 62.5/125µm.
Product Type	Fan-Out Cords
Length (m)	2
Fiber Compatibility	62.5/125µm
Fiber Type	Multimode
Cable Color	Orange
Cable Type	Duplex
CE Compliant	No
Connector 1 Type	SC Connector
Connector 2 Type	Pigtail
End Configurations	SC to Pigtail
Fiber Count	6
Flammability Rating	Riser (OFNR)
Pricing Description	PC 6-Fiber mm 6 SC-Open 62.5µm 2m
Min. Order UOM	PC
Min. Order Qty.	1
BOM Gty. (# of Pkgs.)	0
Add to Favorite Product List	

Please register to utilize the 'Bill of Materials', 'Submit Quotes' and 'Favorite Product List' features.