

ALL RIGHTS RESERVED. NO PORTION OF THIS PUBLICATION, WHETHER IN WHOLE OR IN PART CAN BE REPRODUCED WITHOUT THE EXPRESS WRITTEN CONSENT OF SPC TECHNOLOGY.

REVISIONS			DOC. NO. SPC-F005 * Effective: 7/8/02 * DCP No: 1398					
DCP #	REV	DESCRIPTION	DRAWN	DATE	CHECKD	DATE	APPRVD	DATE
1868	Α	RELEASED	BYF	11/21/05	НО	11/28/05	JWM	11/29/05

SPC-F005.DWG Nut RoHS Lock Washer Compliant Insulation Washer Centering Washer -Bolt 2.0 Bracket 0.063 0.438 0.875 **Brackets Dimensions** SPECIFICATIONS: - Sturdy plated steel brackets, allow for secure mounting of 300 Wirewound type resistors. Includes: (2pcs) 90° brackets (2pcs) Thru-bolts, lock washers and nuts

DISCLAIMER

ALL STATEMENTS AND TECHNICAL INFORMATION CONTAINED HEREIN ARE BASED UPON INFORMATION AND/OR TESTS WE BELIEVE TO BE ACCURATE AND RELIABLE. SINCE CONDITIONS OF USE ARE BEYOND OUR CONTROL, THE USER SHALL DETERMINE THE SUITABILITY OF THE PRODUCT FOR THE INTENDED USE AND ASSUME ALL RISK AND LIABILITY WHATSOEVER IN CONNECTION THEREWITH.

**TOLERANCES:** 

UNLESS OTHERWISE SPECIFIED, Angles  $\pm 0.5^{\circ}$  .XX  $\pm 0.010$  .XXX  $\pm 0.005$  Features On CL  $\pm 0.010$ 

DRAWN BY:	DATE:
BASAM YOUSIF	11/21/05
CHECKED BY:	DATE:
HISHAM ODISH	11/28/05
APPROVED BY:	DATE:
JEFF MCVICKER	11/29/05

(4pcs) Centering washers (4pcs) Insulating washers

DRAWING TITLE:

Thru—Bolt Mounting Bracket, For Two 300W Wirewound Resistor

	SIZE	DWG. NO.			TRONIC FILE	REV
05	Α	MC1	14762	33	3K3839.DWG	Α

SCALE: NTS U.O.M.: INCHES SHEET: 1 OF 1