




SLI-343 8 Series

EXCELED™

Features

- Viewing angle 2θ 1/2 : 40°
- High brightness
- Low current consumption
- Competent to direct mount

Color Type V U D Y M P


Specifications

Viewing angle 2θ 1/2 : 40°: EXCELED™


Part No.	Chip Structure	Emitting Color	Absolute Maximum Ratings (Ta=25°C)						Electrical and Optical Characteristics (Ta=25°C)									
			Power Dissipation Pd (mW)	Forward Current If (mA)	Peak Forward Current Ifp (mA)	Reverse Voltage Vr (V)	Operating Temperature Topr (°C)	Storage Temperature Tstg (°C)	Forward Voltage Vf Typ. (V)		Reverse Current Ir Max. (μA)	Vr (V)	Dominant Wavelength λ D Typ. (nm)		Luminous Intensity Iv Min. (mcd)		Typ. (mcd)	Iv (mA)
■ SLI-343V8RC	AlGaInP on GaAs	Red												630		150	330	
■ SLI-343U8RC														620				
■ SLI-343D8C		Orange												605		330	680	
■ SLI-343Y8C		Yellow												590				
■ SLI-343M8C		Yellowish Green												572		68	150	
■ SLI-343P8C		Green	54	20	100*	9	-30 to +85	-40 to +100	2.2	20	10	9	560	20	10	22	20	
■ SLI-343V8R		Red													630	100		220
■ SLI-343U8R														620				
■ SLI-343D8U		Orange												605		220	470	
■ SLI-343Y8Y		Yellow												590				
■ SLI-343M8G		Yellowish Green												572		68	150	
■ SLI-343P8G		Green												560		10	22	

*: Duty 1/10, 1kHz


Dimensions



Recommended Solder Pattern




Viewing Angle




* EXCELED™ is ROHM's pending trademark.

Electrical Characteristics Curves


Forward Current-Forward Voltage




Luminous Intensity-Atmosphere Temperature



Luminous Intensity-Forward Current



Derating



Rank Reference of Brightness

Red (V, U)

(Ta=25°C, If=20mA)

	Viewing angle (2θ1/2)	High Brightness Rank Brightness (mcd)	XA	XB	XC	XD	XE	XF	XG	XH	XJ	XK	XL	XM	XN	XP	XQ	XR	XS	XT	XU
		Resin Color	10 to 15	15 to 22	22 to 33	33 to 47	47 to 68	68 to 100	100 to 150	150 to 220	220 to 330	330 to 470	470 to 680	680 to 1000	1000 to 1500	1500 to 2200	2200 to 3300	3300 to 4700	4700 to 6800	6800 to 10000	10000 to 15000
φ3 Circular type	40°	Transparent Colored											SLI-343U8RC								
													SLI-343V8RC								
		Diffused Colored											SLI-343U8R								
													SLI-343V8R								

Orange (D)

(Ta=25°C, If=20mA)

	Viewing angle (2θ1/2)	High Brightness Rank Brightness (mcd)	XA	XB	XC	XD	XE	XF	XG	XH	XJ	XK	XL	XM	XN	XP	XQ	XR	XS	XT	XU
		Resin Color	10 to 15	15 to 22	22 to 33	33 to 47	47 to 68	68 to 100	100 to 150	150 to 220	220 to 330	330 to 470	470 to 680	680 to 1000	1000 to 1500	1500 to 2200	2200 to 3300	3300 to 4700	4700 to 6800	6800 to 10000	10000 to 15000
φ3 Circular type	40°	Transparent Colored												SLI-343D8C							
														SLI-343D8U							
		Diffused Colored																			

Yellow (Y)

(Ta=25°C, If=20mA)


	Viewing angle (2θ1/2)	High Brightness Rank Brightness (mcd)	XA	XB	XC	XD	XE	XF	XG	XH	XJ	XK	XL	XM	XN	XP	XQ	XR	XS	XT	XU
		Resin Color	10 to 15	15 to 22	22 to 33	33 to 47	47 to 68	68 to 100	100 to 150	150 to 220	220 to 330	330 to 470	470 to 680	680 to 1000	1000 to 1500	1500 to 2200	2200 to 3300	3300 to 4700	4700 to 6800	6800 to 10000	10000 to 15000
φ3 Circular type	40°	Transparent Colored												SLI-343Y8C							
														SLI-343Y8Y							
		Diffused Colored																			

Green (M, P)

(Ta=25°C, If=20mA)

	Viewing angle (2θ1/2)	High Brightness Rank Brightness (mcd)	XA	XB	XC	XD	XE	XF	XG	XH	XJ	XK	XL	XM	XN	XP	XQ	XR	XS	XT	XU
		Resin Color	10 to 15	15 to 22	22 to 33	33 to 47	47 to 68	68 to 100	100 to 150	150 to 220	220 to 330	330 to 470	470 to 680	680 to 1000	1000 to 1500	1500 to 2200	2200 to 3300	3300 to 4700	4700 to 6800	6800 to 10000	10000 to 15000
φ3 Circular type	40°	Transparent Colored												SLI-343M8C							
														SLI-343P8C							
		Diffused Colored												SLI-343M8G							
														SLI-343P8G							

Part No. Construction



* Concerning the Brightness rank

- Please refer to the rank chart above for luminous intensity classification.
- Part name is individual for each rank.
- When shipped as sample, the part name will be a representative part name.

General products are free of ranks. Please contact sales if rank appointment is needed.

Notes

No copying or reproduction of this document, in part or in whole, is permitted without the consent of ROHM Co.,Ltd.

The content specified herein is subject to change for improvement without notice.

The content specified herein is for the purpose of introducing ROHM's products (hereinafter "Products"). If you wish to use any such Product, please be sure to refer to the specifications, which can be obtained from ROHM upon request.

Examples of application circuits, circuit constants and any other information contained herein illustrate the standard usage and operations of the Products. The peripheral conditions must be taken into account when designing circuits for mass production.

Great care was taken in ensuring the accuracy of the information specified in this document. However, should you incur any damage arising from any inaccuracy or misprint of such information, ROHM shall bear no responsibility for such damage.

The technical information specified herein is intended only to show the typical functions of and examples of application circuits for the Products. ROHM does not grant you, explicitly or implicitly, any license to use or exercise intellectual property or other rights held by ROHM and other parties. ROHM shall bear no responsibility whatsoever for any dispute arising from the use of such technical information.

The Products specified in this document are intended to be used with general-use electronic equipment or devices (such as audio visual equipment, office-automation equipment, communication devices, electronic appliances and amusement devices).

The Products specified in this document are not designed to be radiation tolerant.

While ROHM always makes efforts to enhance the quality and reliability of its Products, a Product may fail or malfunction for a variety of reasons.

Please be sure to implement in your equipment using the Products safety measures to guard against the possibility of physical injury, fire or any other damage caused in the event of the failure of any Product, such as derating, redundancy, fire control and fail-safe designs. ROHM shall bear no responsibility whatsoever for your use of any Product outside of the prescribed scope or not in accordance with the instruction manual.

The Products are not designed or manufactured to be used with any equipment, device or system which requires an extremely high level of reliability the failure or malfunction of which may result in a direct threat to human life or create a risk of human injury (such as a medical instrument, transportation equipment, aerospace machinery, nuclear-reactor controller, fuel-controller or other safety device). ROHM shall bear no responsibility in any way for use of any of the Products for the above special purposes. If a Product is intended to be used for any such special purpose, please contact a ROHM sales representative before purchasing.

If you intend to export or ship overseas any Product or technology specified herein that may be controlled under the Foreign Exchange and the Foreign Trade Law, you will be required to obtain a license or permit under the Law.



Thank you for your accessing to ROHM product informations.
More detail product informations and catalogs are available, please contact us.

ROHM Customer Support System

<http://www.rohm.com/contact/>