


DASH NO.	M CODE	MADE FROM
----------	--------	-----------

GSD

M39012/30-0118

REVISIONS	
ISSUE	CHANGES
2	ER 34778 E REDRAWN KH 07/14/93
3	CN 38246 C BDH 03/12/01
4	CN 39923 C DCT 5/9/7



NOTES:

- FOR USE WITH RG-316 & 174/U CABLES.
- FOR CABLING INSTRUCTIONS SEE CP-1050.
- INTERFACE PER MIL-STD-348, FIG. 313-1.
- MATERIALS:
INSULATORS-TEFLON, ASTM-D4894
GASKETS-SILICONE RUBBER, A-A-59588
OUTER CONTACT } BER. COP., ASTM-B-196
CENTER CONTACT F }
ALL OTHER METAL PARTS-BRASS, ASTM-B16
- FINISHES:
CENTER CONTACTS-GOLD PLATE PER ASTM-B488
ALL OTHER METAL PARTS-SILVER PLATE PER ASTM-B700
- ELECTRICAL CHARACTERISTICS:
NOMINAL IMPEDANCE-50 OHMS
FREQUENCY RANGE-DC TO 11 GHZ
WORKING VOLTAGE-500 VRMS

GSD

SCALE 4:1	
APPROX SURFACE AREA	
KA-59-348	
USED ON	
REF:	
PLUG, ANG, TNC	
DRAWN KH	DATE 07/14/93
DESIGN JT	DATE 07/15/93
APPR.	DATE
KINGS ELECTRONICS CO., INC. ROCK HILL, SOUTH CAROLINA 29730	
M39012/30-0118	