

- 1.VESA 75 standard for IOVU-751R product.
- 2.Enhance charger and battery status by network remote management software



Low Battery/High Temperature Alarm

Special event Pop-up :



iE1000 Board Configuration

Board Configuration

You page shows the configuration of the board's network settings.

CAUTION: Recovery settings may cause the board to lose network connectivity. Recovery actions will be available on the next page.

Enter the new settings for the board below:

MAC Address: 00:00:00:00:00:00
Host Name: 00

IP Address: 192.168.1.1
Gateway: 192.168.1.1
Subnet Mask: 255.255.255.0
Primary DNS: 192.168.1.1
Secondary DNS: 192.168.1.1

[illegible]

The screenshot shows the iM Technology Group website. The header includes the company logo and name. A navigation menu on the left lists 'Home', 'About Us', 'Contact Us', 'Download Us', and 'File Uploads'. The 'File Uploads' section is highlighted in red. The main content area is titled 'File Uploads' and contains a paragraph explaining that the iM777 program can process file uploads via POST. It mentions that the application can allow users to upload multiple files, and the application must be restarted to process the upload. A sample calculation is provided: 1000 files * 100 KB = 100,000 KB. Below the text is a form with a label 'Upload a File', a text input field, and two buttons: 'Upload' and 'Cancel'.

Specification

Ordering Information

Packing List

www.ieiworld.com