




Distributed by:




www.Jameco.com ♦ 1-800-831-4242

The content and copyrights of the attached
material are the property of its owner.

LIGITEK

SINGLE DIGIT LED DISPLAY (0.3 Inch)		LSD321X/2X series	Page 1/2		
PACKAGE DIMENSION		INTERNAL CIRCUIT DIAGRAM			
		 			
<p>NOTE: All Dimension Are In Millimeters And (Inch) Tolerance Is $\pm 0.25(0.01")$ Unless Otherwise Noted</p>					
<ul style="list-style-type: none"> • Connection To Electrical Schematic 					
Electrical Connection					
PIN NO.	LSD321X-XX	PIN NO.	LSD322X-XX		
1	Anode F	1	Cathode A		
2	Anode G	2	Cathode F		
3	No Pin	3	Common Anode		
4	Common Cathode	4	No Pin		
5	No Pin	5	No Pin		
6	Anode E	6	Cathode LDP		
7	Anode D	7	Cathode E		
8	Anode C	8	Cathode D		
9	Anode DP	9	Cathode RDP		
10	No Pin	10	Cathode C		
11	No Pin	11	Cathode G		
12	Common Cathode	12	No Pin		
13	Anode B	13	Cathode B		
14	Anode A	14	Common Andoe		



• Part Selection And Application Information (Ratings At 25°C Ambient)

PART NO	CHIP		common cathode or anode	λ_P (nm)	$\Delta\lambda$ (nm)	Electrical					IV-M
						Vf(v)			Iv(mcd)		
	material	emitted				Min	Typ.	Max	Min	Typ.	
LSD3215-XX	GaAlAs	Red	Common Cathode	660	20	1.5	1.7	2.4	5.9	9.8	2:1
LSD3211-XX	GaP	Red		697	90	1.7	2.1	2.8	1.5	2.5	2:1
LSD3212-XX	GaP	Green		565	30	1.7	2.1	2.8	2.2	3.7	2:1
LSD3213-XX	GaAsP/GaP	Yellow		585	35	1.7	2	2.8	4.2	7.0	2:1
LSD3214-XX	GaAsP/GaP	Orange		635	45	1.7	2	2.8	4.5	7.5	2:1
LSD3225-XX	GaAlAs	Red	Common Anode	660	20	1.5	1.7	2.4	5.9	9.8	2:1
LSD3221-XX	GaP	Red		697	90	1.7	2.1	2.8	1.5	2.5	2:1
LSD3222-XX	GaP	Green		565	30	1.7	2.1	2.8	2.2	3.7	2:1
LSD3223-XX	GaAsP/GaP	Yellow		585	35	1.7	2	2.8	4.2	7.0	2:1
LSD3224-XX	GaAsP/GaP	Orange		635	45	1.7	2	2.8	4.5	7.5	2:1

• Absolute Maximum Rating (Ta=25°C)

Parameter	Red		Green		Yellow		Orange		Unit	Remark	
	SR	R	H	PG	G	PY	Y	A	I	E	
Forward Current Per Chip	40	40	15	30	30	20	20	20	30	30	mA
Peak Current Per Chip (Duty 1/10, 0.1MS Pulse Width)	200	200	60	120	120	80	80	80	120	120	mA
Power Dissipation Per Chip	110	45	100			85			100		mW
Derating Linear From 25°C Per Chip	0.45	0.25	0.45			0.45			0.45		mA/°C
Reverse Current Per Any Chip	10		10			10			10		μA
Operating Temperature						-25°C TO +85°C					
Storage Temperature						-25°C TO +85°C					

Solder Temperature 1/16 Inch Below Seating Plane For 3 Seconds At 260°C

• Test Condition For Each Parameter

Parameter	Symbol	Unit	Test Condition
Forward Voltage Per Chip	Vf	volt	If=20mA
Luminous Intensity Per Chip	Iv	mcd	If=10mA
Peak Emission Wavelength	λ_P	nm	If=20mA
Spectral Line Half-Width	$\Delta\lambda$	nm	If=20mA
Reverse Current Any Chip	Ir	μA	Vr=5V
Luminous Intensity Matching Ratio	IV-M		

