

SOT223 PNP SILICON PLANAR MEDIUM POWER TRANSISTOR

ISSUE 3 – AUGUST 1995 


FEATURES

- * Suitable for AF drivers and output stages
- * High collector current and Low $V_{CE(sat)}$

COMPLEMENTARY TYPE – BCP54

PARTMARKING DETAILS – BCP51
BCP51 – 10
BCP51 – 16

BCP51



ABSOLUTE MAXIMUM RATINGS.

PARAMETER	SYMBOL	VALUE	UNIT
Collector-Base Voltage	V_{CBO}	-45	V
Collector-Emitter Voltage	V_{CEO}	-45	V
Emitter-Base Voltage	V_{EBO}	-5	V
Peak Pulse Current	I_{CM}	-1.5	A
Continuous Collector Current	I_C	-1	A
Power Dissipation at $T_{amb}=25^{\circ}C$	P_{tot}	2	W
Operating and Storage Temperature Range	$T_j; T_{stg}$	-55 to +150	$^{\circ}C$

ELECTRICAL CHARACTERISTICS (at $T_{amb} = 25^{\circ}C$ unless otherwise stated).

PARAMETER	SYMBOL	MIN.	TYP.	MAX.	UNIT	CONDITIONS.
Collector-Base Breakdown Voltage	$V_{(BR)CBO}$	-45			V	$I_C = -100\mu A$
Collector-Emitter Breakdown Voltage	$V_{(BR)CEO}$	-45			V	$I_C = -10mA$ *
Emitter-Base Breakdown Voltage	$V_{(BR)EBO}$	-5			V	$I_E = -10\mu A$
Collector Cut-Off Current	I_{CBO}			-100 -10	nA μA	$V_{CB} = -30V$ $V_{CB} = -30V, T_{amb} = 150^{\circ}C$
Emitter Cut-Off Current	I_{EBO}			-10	μA	$V_{EB} = -5V$
Collector-Emitter Saturation Voltage	$V_{CE(sat)}$			-0.5	V	$I_C = -500mA, I_B = -50mA$ *
Base-Emitter Turn-On Voltage	$V_{BE(on)}$			-1.0	V	$I_C = -500mA, V_{CE} = -2V$ *
Static Forward Current Transfer Ratio	h_{FE}	40 25 63 100	100 160	250 160 250		$I_C = -150mA, V_{CE} = -2V$ * $I_C = -500mA, V_{CE} = -2V$ * $I_C = -150mA, V_{CE} = -2V$ * $I_C = -150mA, V_{CE} = -2V$ *
Transition Frequency	f_T		125		MHz	$I_C = -50mA, V_{CE} = -10V, f = 100MHz$

*Measured under pulsed conditions. Pulse width=300 μs . Duty cycle $\leq 2\%$

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Diodes Incorporated:](#)

[BCP5110TA](#) [BCP5110TC](#) [BCP5116TA](#) [BCP5116TC](#) [BCP51TA](#) [BCP51TC](#)