


JKL PART NUMBER	-A- LENGTH	LCD HIGH OUTPUT WHITE RGB COLOR	STARTING CIRCUIT VOLTAGE VS (Vrms)	OPERATING LAMP VOLTAGE VL (Vrms)	OPERATING LAMP CURRENT IL (mA rms)	BRIGHTNESS (CANDELA/m ²)	*RATED LIFE (HRS) MINIMUM
BF2661-24B	61±1.0**	9,400°k x = .285 ± .03 y = .283 ± .03	490 @ 0°C	195	5 ± 1	30,000 TYP.	20,000
BF26180-24B	180±3.0		975 @ 0°C	390			
BF26188-24B	188±3.0		1115 @ 0°C	405			
BF26214-24B	214±2.0**		1150 @ 0°C	445			
BF26230-24B	230±3.0		1240 @ 0°C	495			
BF26240-24B	240±3.0		1290 @ 0°C	515			
BF26250-24B	250±1.5		1350 @ 0°C	540			

NOTES:

* RATED LIFE IS DEFINED AS THE POINT WHICH THE INTENSITY BECOMES 50% OF THE INITIAL RATING.

** LEAD LENGTH 15±3.0.

RATINGS AT 25°C UNLESS OTHERWISE SPECIFIED.

			METRIC  THIRD ANGLE PROJECTION		DIMENSIONS ARE IN MILLIMETERS TOLERANCE UNLESS OTHERWISE SPECIFIED 1 PL +/- REF. 2 PL +/- REF. ANGLE +/- 0		JKL COMPONENTS CORPORATION													
					TITLE															
					MINIATURE COLD CATHODE FLUORESCENT LAMP															
D RATED LIFE HRS MINIMUM & 20,000 - & MARKUP 8/5/09			DRAWN BY		APPV'D BY		SIZE	FSCM NO.	DRAWING NO.											
C CORRECT x & y TOLERANCE 7/5/06			L. WENGSTROM		L.R.		A	55335	BF 26-24B											
B LENGTH TOLERANCE CHANGE ON BF26250-24B 2/3/06																				
A ELECTRICAL CHANGES & ADD PART BF2661-24B 10/20/04																				
RELEASED TO CAD MULTI LIST 8/14/03																				
REV. NO.			DESCRIPTION/ECO NUMBER			APPV'D DATE			- CAD DRAWING - MANUAL REVISIONS NOT PERMITTED		SCALE		RELEASED DATE		REVISION DATE		REV. NO.		SHEET	
									NONE		8/14/03		8/5/09		D		1 OF 1			