

## DeoxIT® D100 Spray, D-Series Contact Cleaner & Rejuvenator

**Part No.:** D100S-2 with optional stainless steel extension tube (Part No. ACT-SS-2OZ)

**Container Size:** 57 g

### Product Description:

Unique contact cleaner, rejuvenator, conductivity enhancer and lubricant. Dissolves oxidation and corrosion on metal surfaces. Fills in microscopic gaps and reseals surface for better contact to enhance flow of electricity. Chemically improves metal-to-metal connections and contacts. Improves connector performance/reliability. Temperature range: -34 to +200°C.



### Features/Benefits:

**100% Spray, metered one shot valve - No Solvents, Non-Drip, Safe on Plastics.**

DeoxIT® D100L concentrate has approximately 20% chemical cleaning action.

Excellent cleaning/deoxidizing, good protection, no ozone depletion.

Improves conductivity and reduces intermittent connections.

Reduces arcing, RFI, wear and abrasion.

**Cleaner Audio - Clearer Video - Reliable Data.**

### Formulation:

|        |                             |
|--------|-----------------------------|
| 10-20% | DeoxIT® D100L, D-Series     |
| 80-90% | 1,1-DIFLUOROETHANE (R-152a) |



### Which DeoxIT® product do I Use:

- ▶ Use **DeoxIT® D-Series** contact cleaner on surfaces that have been in service or have visual signs of oxidation. Contains 20% active cleaner.
- ▶ Use **DeoxIT® Gold G-Series** conditioner on new surfaces, and gold plated surfaces. Ideal for preventing dendrite/fretting corrosion. Protects both surface and base metals. Ideal for critical applications. Contains >1% active cleaner.
- ▶ Use **DeoxIT® Shield S-Series** to protect surfaces from severe environments (humidity, salts, pollutants, sulfur, etc.). Use on clean surface. Contains 0% active cleaner.

### Directions for Use:

1. Turn off, unplug the device.
2. Apply one short burst of DeoxIT® D-Series contact cleaner to contact/connector surface.

Operate the part/device to help break up oxides and contamination. Wait a few seconds, reapply one short burst. Wait two minutes before turning on equipment. **Test for compatibility before use.**

3. In extreme cases (severe oxidation or corrosion), you may need to leave DeoxIT® on overnight. If that is necessary; apply, then the following day remove any contaminants lifted by DeoxIT® with a lint free swab or cloth on accessible surfaces (If surface is not accessible, repeat step two above.). When surface is clean (no residue on the swab/cloth), finish with a short burst of DeoxIT®, then remove excess leaving a thin layer.
4. If you notice a green or black coloration on the surface (may take a few days) after applying DeoxIT®, this indicates dissolved oxidation (surface was severely oxidized). Follow step “2” above one more time.
5. **For extended protection:** After surface is clean, apply DeoxIT® Gold G-Series for indoor applications or DeoxIT® Shield S-Series for outdoor applications.
6. **NOTE:** To prevent overspray or spraying in unwanted areas, you can always spray onto a lint-free swab or cloth first and then using the swab/cloth apply the DeoxIT® to the connector/contact surface(s).

## Other Applicators:

| Part No.                 | % DeoxIT® | VOC (%) | Applicator       | Size/Amount | Flammable/Nonflammable |
|--------------------------|-----------|---------|------------------|-------------|------------------------|
| D5S-6                    | 5%        | 75%     | spray            | 142 g       | flammable              |
| DN5S-6N                  | 5%        | 75%     | mini-spray       | 163 g       | nonflammable           |
| DN5MS-15                 | 5%        | 0%      | spray            | 57g         | nonflammable           |
| D100P                    | 100%      | 0%      | pen              | 6 mL        | nonflammable           |
| D100L-P6C                | 100%      | 0%      | oiler pen        | 6 mL        | nonflammable           |
| D50W                     | 100%      | 0%      | wipes            | 50 count    | nonflammable           |
| D1W                      | 100%      | 0%      | wipes            | individual  | nonflammable           |
| D100L-2C                 | 100%      | 0%      | tube             | 2 mL        | nonflammable           |
| D100L-2DB                | 100%      | 0%      | brush bottle     | 7.4 mL      | nonflammable           |
| D100L-25C                | 100%      | 0%      | needle dispenser | 25 mL       | nonflammable           |
| D100L (bulk, many sizes) | 100%      | 0%      | bottle/drum      | assort.     | nonflammable           |
| D5L-A (bulk, many sizes) | 5%        | 75%     | bottle/drum      | assort.     | flammable              |

## Product Selection Guides:

### DeoxIT® - Product Selection Guide

|                                   | DeoxIT®   | DeoxIT®<br>GOLD | DeoxIT®<br>GOLD 6xL | DeoxIT®<br>GOLD 6x2 | DeoxIT®<br>SHIELD | DeoxIT®<br>FaderLube |
|-----------------------------------|-----------|-----------------|---------------------|---------------------|-------------------|----------------------|
| New Surfaces                      |           | ✓               | ✓                   | ✓                   | ✓                 | ✓                    |
| * In Service / Used               | ✓         |                 |                     |                     |                   | ✓                    |
| Gold surfaces                     |           | ✓               | ✓                   | ✓                   |                   |                      |
| Oxidation / corrosion visible     | ✓         |                 |                     |                     |                   |                      |
| Conductive plastics               |           |                 |                     |                     |                   | ✓                    |
| ** Outdoor / Severe environments  | ✓         |                 |                     |                     |                   | ✓                    |
| Deoxidizing / cleaning properties | 20%       | 0.1%            | 0.1%                | 0.0%                | 0.0%              | 0.0%                 |
| Metal / Plastic surfaces          | Yes       | Yes             | Yes                 | Yes                 | Yes               |                      |
| Plastics compatibility            | Excellent | Excellent       | Excellent           | Excellent           | Excellent         | Excellent            |
| Temperature range (°C)            | -34/200   | -45/240         | -45/310             | -45/500             | -34/210           | -26/150              |
| Stationary & moving surfaces      | Yes       | Yes             | Yes                 | Yes                 | Yes               | Yes                  |
| Seals & protects base metals      | Good      | Excellent       | Excellent           | Excellent           | Good              | No                   |

✓ All products are Nonflammable and RoHs Compliant

\* In Service: Clean with DeoxIT®. For added protection, follow with DeoxIT® GOLD (indoors), DeoxIT® SHIELD (outdoors) or DeoxIT® Grease (additional barrier).

\*\* Severe environments: Pre-clean with DeoxIT®, Follow with DeoxIT® SHIELD or DeoxIT® Grease.

### DeoxIT® - Spray Selection Guide

| Product Series                                                    | FP | QD | NF | PC | VOC |
|-------------------------------------------------------------------|----|----|----|----|-----|
| Standard - 5% solution                                            | ✓  |    |    | ✓  | 75  |
| D5S-6, D5MS-15, G5S-6, G5MS-15,<br>S5S-6, S5MS-15, F5S-6, F5MS-15 |    |    |    |    |     |
| N Series - 5% solution                                            |    | ✓  | ✓  | ✓  | 20  |
| DN5S-6N, DN5MS-15, GN5S-6N,<br>GN5MS-15, SN5S-6, SN5MS-15         |    |    |    |    |     |
| X Series - 5% solution                                            |    | ✓  | ✓  | ✓  | 20  |
| GX5S-6N                                                           |    |    |    |    |     |
| 100 Series - 100% solution                                        |    |    | ✓  | ✓  | 0   |
| D100S-2, G100S-2, F100S-2                                         |    |    |    |    |     |

FP = Flushing properties QD = Quick dry / non drip NF = Nonflammable  
PC = Plastics compatibility VOC = VOC (%)

## Materials Compatibility (Plastics, Rubber, Elastomeric and Metals):

(Rating: Not compatible, Poor, Fair, Good, Excellent), (N/A = Not applicable (no solvents and propellants))

(\* If the product is not 100% DeoxIT® then the package is rated before and after the solvents/propellants are applied to materials. Compatibility testing is always recommended)

| Material Name      | Rating (*100% DeoxIT®) | Rating (*with solvents & propellants) |
|--------------------|------------------------|---------------------------------------|
| ABS                | Excellent              | Excellent                             |
| Nylon              | Excellent              | Excellent                             |
| Lexan              | Excellent              | Excellent                             |
| HDPE               | Good                   | Good                                  |
| LDPE               | Good                   | Good                                  |
| C.E.Phenolic       | Excellent              | Excellent                             |
| Epoxy              | Excellent              | Excellent                             |
| Polycarbonate      | Excellent              | Excellent                             |
| PMMA               | Fair                   | Fair                                  |
| POM                | Excellent              | Excellent                             |
| PP                 | Excellent              | Excellent                             |
| PS                 | Fair                   | Fair                                  |
| PTFE               | Excellent              | Excellent                             |
| PVC                | Excellent              | Excellent                             |
| TPE/Rubber/Varnish | Poor                   | Poor                                  |

**IMPORTANT:** Even though the DeoxIT® D100S-2 contains a propellant, since it is a metered valve, only the 100% DeoxIT® is sprayed onto the surfaces, therefore we treat it like a 100% DeoxIT® application. Any of the above that fall into the "Fair" and "Poor" categories should be thoroughly tested for compatibility. They may be compatible, however, it will depend on the manufacturing process of the materials. Acrylics, ABS, and polycarbonate, if under stress, may show slight cracking or crazing damage. Test for compatibility before use. On porous materials; i.e. wood, rubber, cloth, some phenolics, semi-cured materials, no liquid or solvents should be used. Occasionally, DeoxIT® will get onto unwanted surfaces, quickly wipe off surface and usually no damage will occur.

## DeoxIT® Essential Reference:

**DeoxIT® D-Series** - Brings old systems back to life!

**DeoxIT® Gold G-Series** - Maintains new system performance!

**DeoxIT® Shield S-Series** - Maintains new system performance for severe environments!

**DeoxIT® Fader F-Series** - Clean, lubricate & protect conductive plastic and carbon compound faders!

## Shipping and Additional Information:

Hazardous: ORMD

VOC (%): Part No. D100S-2      None

## Other Information:

RoHS Compliant: YES

VOC Compliant: YES

**MSDS Link, D100S-2** <http://store.caig.com/s.nl/sc.18/category.3545/f>

DeoxIT® Product Sheet: <http://store.caig.com/s.nl/sc.18/category.236/f>

MentorCard Link: <http://store.caig.com/s.nl/it.l/id.73/f>

WHY DeoxIT® is Different: <http://store.caig.com/s.nl/it.l/id.22/f>

<http://store.caig.com/s.nl/it.l/id.64/f>

## MANUFACTURER DISCLAIMER:

---

To the best of our knowledge, the information contained herein is accurate. However, neither CAIG Laboratories, Inc., or any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. All materials may present unknown hazards and should be used with caution. In particular, improper use of our products and their inappropriate combination with other products and substances may produce harmful results which cannot be anticipated. Final determination of the suitability of any material is the sole responsibility of the user. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that may exist. All service performed on internal parts and equipment should be provided by qualified technicians.

## Contact Information:

---



**Website:** [www.caig.com](http://www.caig.com)  
[www.deoxit.com](http://www.deoxit.com)

**General email:** [info@caig.com](mailto:info@caig.com)

**Technical email:** [tech@caig.com](mailto:tech@caig.com)

### North America (Headquarters):

#### **CAIG Laboratories, Inc.**

12200 Thatcher Court  
Poway, CA 92064 USA  
Tel: (858) 486-8388  
Fax: (858) 486-8398

### Distributors (Domestic & International):

<http://store.caig.com/s.nl/sc.15/f>