

a**Precision Low Noise JFET
Operational Amplifiers****Preliminary Technical Data****AD8510/AD8512/AD8513****FEATURES**

Low Offset Voltage: 400 μ V max
Low TcVos: 2 μ V/ $^{\circ}$ C typ
Low input bias current: 30pA max.
Dual-Supply Operation: $\pm$ 5V to $\pm$ 15V Volts
Low Noise: 8 nV/ $\sqrt{\text{Hz}}$
Fast settling: 10V step to 0.01% in 600ns
No Phase Reversal
Unity Gain Stable

APPLICATIONS

Instrumentation
 Multi-pole filters
 Precision current measurement
 Photo-diode amplifiers
 Sensors
 Audio







GENERAL DESCRIPTION

The AD8510, AD8512 and AD8513 are single, dual and quad precision JFET amplifiers featuring low offset voltage, low input bias current and low input voltage and current noise.

The combination of low offsets, low noise and very low input bias currents make these amplifiers especially suitable for high impedance sensor amplification and precise current measurements using shunts. Unlike many older JFET amplifiers these parts do not suffer from output phase reversal when input voltages exceed the maximum common mode voltage range.

The AD8510, AD8512 and AD8513 are specified over the extended industrial (-40° to $+125^{\circ}\text{C}$) temperature range. The AD8510, single, and AD8512, dual, are available in the 8 lead MSOP and narrow SOIC surface mount packages. The

AD8513 is available in the 14 lead TSSOP and narrow SOIC packages. MSOP and TSSOP versions are available in tape and reel only.

PIN CONFIGURATIONS**8-Lead MSOP
(RM-8)****8-Lead SO
(R-8)****8-Lead MSOP
(RM-8)****8-Lead SO
(R-8)****14-Lead TSSOP
(RU-14)****14-Lead SO
(R-14)**

Information furnished by Analog Devices is believed to be accurate and reliable. However, no responsibility is assumed by Analog Devices for its use, nor for any infringements of patents or other rights of third parties which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of Analog Devices.

PRELIMINARY TECHNICAL DATA

AD8510/AD8512/AD8513

ELECTRICAL CHARACTERISTICS ($V_S = \pm 5V$, $V_{CM} = 0V$, $T_A = +25^\circ C$ unless otherwise noted)

Parameter	Symbol	Conditions	Min	Typ	Max	Units
INPUT CHARACTERISTICS						
Offset Voltage (A Grade)	V_{OS}	$-40^\circ < T_A < +125^\circ C$			1	mV
					1.8	mV
Offset Voltage (B Grade)	V_{OS}	$-40^\circ < T_A < +125^\circ C$			.4	mV
					0.8	mV
Input Bias Current	I_B	$-40^\circ < T_A < +85^\circ C$			30	pA
		$-40^\circ < T_A < +125^\circ C$			2	nA
					30	nA
Input Offset Current	I_{OS}	$-40^\circ < T_A < +85^\circ C$			25	pA
		$-40^\circ < T_A < +125^\circ C$			1.6	nA
					13	nA
Input Voltage Range			-4		3.2	V
Common-Mode Rejection Ratio	CMRR	$V_{CM} = -3.5V$ to $3V$	86			dB
Large Signal Voltage Gain	A_{VO}	$R_L = 2\text{ k}\Omega$ $V_O = -3V$ to $3V$	150	200		V/mV
Offset Voltage Drift (A Grade)	$\Delta V_{OS}/\Delta T$			3	10	$\mu V/^\circ C$
Offset Voltage Drift (B Grade)	$\Delta V_{OS}/\Delta T$			2	10	$\mu V/^\circ C$
OUTPUT CHARACTERISTICS						
Output Voltage High	V_{OH}	$I_L = 1mA$ $-40^\circ C < T_A < +125^\circ C$	3.5 3.4			V V
Output Voltage Low	V_{OL}	$I_L = 1mA$ $-40^\circ C < T_A < +125^\circ C$			-4 -3.4	V V
Output Current	I_{OUT}		± 25	± 35		mA
Closed Loop Output Impedance	Z_{OUT}	$f = 10\text{ kHz}$, $A_V = 1$		tbd		Ω
POWER SUPPLY						
Power Supply Rejection Ratio	PSRR	$V_S = 2.7\text{ V}$ to 5.5 V	86			dB
Supply Current/Amplifier	I_{SY}	$V_O = 0V$ $-40^\circ < T_A < +125^\circ C$		1.8	3 4	mA mA
DYNAMIC PERFORMANCE						
Slew Rate	SR	$R_L = 2\text{ k}\Omega$		20		V/ μs
Gain Bandwidth Product	GBP			7.5		MHz
Settling Time	t_s	to 0.01%, 0V to 4V step		.3		μs
THD+Noise	THD+N			.0001		%
Phase Margin	$\angle \phi_o$			60		degrees
NOISE PERFORMANCE						
Voltage Noise Density	e_n	$f = 1\text{ kHz}$		8		nV/ $\sqrt{\text{Hz}}$
Voltage Noise Density	e_n	$f = 10\text{ kHz}$		8		nV/ $\sqrt{\text{Hz}}$
Current Noise Density	i_n	$f = 1\text{ kHz}$		0.01		pA/ $\sqrt{\text{Hz}}$

PRELIMINARY TECHNICAL DATA

AD8510/AD8512/AD8513

ELECTRICAL CHARACTERISTICS (@ $V_S = \pm 15.0V$, $V_{CM} = 0V$, $T_A = +25^\circ C$ unless otherwise noted)

Parameter	Symbol	Conditions	A Grade			Units
			Min	Typ	Max	
INPUT CHARACTERISTICS						
Offset Voltage (A Grade)	V _{OS}	-40°< T _A < +125°C			1	mV
					1.8	mV
Offset Voltage (B Grade)	V _{OS}	-40°< T _A < +125°C			.4	mV
					0.8	mV
Input Bias Current	I _B	-40°< T _A < +85°C			30	pA
		-40°< T _A < +125°C			2	nA
					30	nA
Input Offset Current	I _{OS}	-40°< T _A < +85°C			25	pA
		-40°< T _A < +125°C			1.6	nA
					13	nA
Input Voltage Range			-13.5		13	V
Common-Mode Rejection Ratio	CMRR	V _{CM} = -12.5V to 12.5V	86			dB
Large Signal Voltage Gain	A _{VO}	V _O = -13V to 13V, R _L = 2 kΩ , V _{CM} = 0V	150	200		V/mV
Offset Voltage Drift (A Grade)	ΔV _{OS} /ΔT			3	10	μV/°C
Offset Voltage Drift (B Grade)	ΔV _{OS} /ΔT			2	10	μV/°C
OUTPUT CHARACTERISTICS						
Output Voltage High	V _{OH}	I _L = 1mA	13.5			V
		I _L = 10mA	13			V
		-40°C to +125°C	12			V
Output Voltage Low	V _{OL}	I _L = 1mA			-13.5	V
Output Voltage High	V _{OL}	I _L = 10mA			-13	V
		-40°C to +125°C			-12	V
Output Current	I _{OUT}			±50		mA
Closed Loop Output Impedance	Z _{OUT}	f=10 kHz, A _V = 1		tbd		Ω
POWER SUPPLY						
Power Supply Rejection Ratio	PSRR	V _S = 2.7 V to 5.5 V	86			dB
Supply Current/Amplifier	I _{SY}	V _O = 0V		1.8	3.5	mA
		-40°< T _A < +125°C			4.5	mA
DYNAMIC PERFORMANCE						
Slew Rate	SR	R _L =2 kΩ		20		V/μs
Gain Bandwidth Product	GBP			7.5		MHz
Settling Time	t _s	to 0.01%, 0V to 10V step		.9		μs
THD+Noise	THD+N			.0001		%
Phase Margin	∅ _o			60		degrees

PRELIMINARY TECHNICAL DATA

AD8510/AD8512/AD8513

NOISE PERFORMANCE				
Voltage Noise Density	e_n	$f=1\text{kHz}$	8	nV/ $\sqrt{\text{Hz}}$
Voltage Noise Density	e_n	$f=10\text{kHz}$	8	nV/ $\sqrt{\text{Hz}}$
Current Noise Density	i_n	$f=1\text{kHz}$	0.015	pA/ $\sqrt{\text{Hz}}$

ABSOLUTE MAXIMUM RATINGS¹

Supply voltage	$\pm 18\text{V}$
Input Voltage	$\pm V_s$
Output Short-Circuit Duration to Gnd ² ... Observe Derating Curves	
Storage Temperature Range	
R, RM, RU Package	-65°C to $+150^\circ\text{C}$
Operating Temperature Range	
AD8510/AD8512/AD8513	-40°C to $+125^\circ\text{C}$
Junction Temperature Range	
R, RM, RU Package	-65°C to $+150^\circ\text{C}$
Lead Temperature Range (Soldering, 60 Sec)	$+300^\circ\text{C}$
Electrostatic Discharge (HBM)	2000V

Package Type	θ_{JA}	θ_{JC}	Units
8-Pin MSOP (RM)	210	45	$^\circ\text{C/W}$
8-Pin SOIC (R)	158	43	$^\circ\text{C/W}$
14-Pin TSSOP (RU)	158	43	$^\circ\text{C/W}$
14-Pin SOIC (R)	158	43	$^\circ\text{C/W}$

NOTES

¹ Absolute maximum ratings apply at 25°C , unless otherwise noted.

² θ_{JA} is specified for the worst case conditions, i.e., θ_{JA} is specified for device soldered in circuit board for surface mount packages.


ORDERING GUIDE

Model	Temperature Range	Package Description	Package Option	Marking Code
AD8510ARM	-40°C to $+125^\circ\text{C}$	8-Pin MSOP	RM-8	B7A
AD8510AR	-40°C to $+125^\circ\text{C}$	8-Pin SOIC	R-8	
AD8510BR	-40°C to $+125^\circ\text{C}$	8-Pin SOIC	R-8	
AD8512ARM	-40°C to $+125^\circ\text{C}$	8-Pin MSOP	RM-8	B8A
AD8512AR	-40°C to $+125^\circ\text{C}$	8-Pin SOIC	R-8	
AD8512BR	-40°C to $+125^\circ\text{C}$	8-Pin SOIC	R-8	
AD8513ARU	-40°C to $+125^\circ\text{C}$	14-Pin TSSOP	RU-14	R-14
AD8513AR	-40°C to $+125^\circ\text{C}$	14-Pin SOIC	R-14	


PRELIMINARY TECHNICAL DATA

AD8510/AD8512/AD8513


8-Lead ■SOIC
(RM-8)



8-Lead SO
(R-8)



14-Lead TSSOP
(RU-14)



14-Lead SO
(R-14)

