

# JJN Limitron™ 300Vac, 1-1200A, fast-acting Class T fuses

RoHS



## Catalog Symbol:

- JJN-(amp)

## Description:

Eaton's Bussmann™ series Limitron™ advanced protection Class T current-limiting, fast-acting fuses.

## Specifications:

### Ratings

- Volts
  - 300 Vac (1-10 A)
  - 300 Vac, 160 Vdc (15-600 A)
  - 300 Vac, 170 Vdc (700-1200 A)
- Amps — 1-1200 A
- IR
  - 200kA Vac RMS Sym.
  - 20kA Vdc (15-600 A)
  - 100kA Vdc (700-1200 A)

## Agency Information

- cULus Listed file No. JDDZ.E4273
  - UL 248-15 – Class T Fuses
  - CSA C22.2 No. 248.15 – Class T Fuses
- CE
- RoHS compliant

## Catalog numbers (amps)

|        |         |         |          |
|--------|---------|---------|----------|
| JJN-1  | JJN-35  | JJN-110 | JJN-400  |
| JJN-2  | JJN-40  | JJN-125 | JJN-450  |
| JJN-3  | JJN-45  | JJN-150 | JJN-500  |
| JJN-6  | JJN-50  | JJN-175 | JJN-600  |
| JJN-10 | JJN-60  | JJN-200 | JJN-700  |
| JJN-15 | JJN-70  | JJN-225 | JJN-800  |
| JJN-20 | JJN-80  | JJN-250 | JJN-1000 |
| JJN-25 | JJN-90  | JJN-300 | JJN-1200 |
| JJN-30 | JJN-100 | JJN-350 |          |

## Carton quantity:

| Amp rating | Carton qty. |
|------------|-------------|
| Up to 60   | 10          |
| 70-100     | 5           |
| 110-1200   | 1           |

## Features:


- Provides 10X better current limitation to help prevent equipment damage caused by short-circuit events.
- 200 kA interrupting rating complies with NEC® Section 110.9 for today's large capacity systems.
- Fast-acting fuse helps prevent equipment damage caused by short-circuit events.
- Small, space-saving fuses provide a high degree of current limitation on short-circuits for excellent component protection.
- Ideal for critical industrial or commercial applications that have specific current limitation requirements.

## Recommended fuse blocks\*

| Fuse amps | 1-pole    | 2-pole    | 3-pole    | 4-Pole    |
|-----------|-----------|-----------|-----------|-----------|
| up to 30  | —         | T30030-2_ | T30030-3_ | T30030-4_ |
| 35-60     | —         | T30060-2_ | T30060-3_ | T30060-4_ |
| 70-100    | —         | T30100-1_ | T30100-2_ | T30100-3_ |
| 110-200   | T30200-1_ | —         | —         | —         |
| 200       | 1B0083    | —         | —         | —         |
| 225-400   | T30400-1_ | —         | —         | —         |
| 450- 600  | T30600-1_ | —         | —         | —         |

\* For additional information, see data sheet no. 1115.


Dimensions – in



Custom designs


Printed circuit board versions available up to 60 amps. Consult your Bussmann series product representative details.

JJN-XXL Dimensions - in




| Fuse amps/catalog number | A     | B     |
|--------------------------|-------|-------|
| JJN-(1-30)L              | 0.406 | 0.125 |
| JJN-(35-60)L             | 0.563 | 0.125 |
| JJN-(35-60)L-01          | 0.563 | 0.165 |

JJN-XXLS Dimensions - in




The JJN-XXL and JJN-XXLS products are UL Component Recognized under Guide JFHR2, File E56412. Contact your Bussmann series product representative for RoHS status.

## Time-current curves - average melt



Current-limitation curves



Current-limiting effects

| Prosp. S.C.C. Let-through current (apparent RMS Sym. vs. fuse rating) |      |      |      |       |       |       |        |        |        |        |
|-----------------------------------------------------------------------|------|------|------|-------|-------|-------|--------|--------|--------|--------|
|                                                                       | 15 A | 30 A | 60 A | 100 A | 200 A | 400 A | 600 A  | 800 A  | 1200 A |        |
| 500                                                                   | 1000 | 1000 | 1000 | 1000  | 1000  | 1000  | 1000   | 1000   | 1000   | 1000   |
| 1000                                                                  | 1000 | 1000 | 1000 | 1000  | 1000  | 1000  | 1000   | 1000   | 1000   | 1000   |
| 5000                                                                  | 1000 | 1000 | 1000 | 1000  | 1000  | 2000  | 3000   | 5000   | 5000   | 5000   |
| 10,000                                                                | 1000 | 1000 | 1000 | 1000  | 2000  | 2000  | 4000   | 6000   | 7000   | 9000   |
| 15,000                                                                | 1000 | 1000 | 1000 | 1000  | 2000  | 3000  | 4000   | 6000   | 9000   | 10,000 |
| 20,000                                                                | 1000 | 1000 | 1000 | 1000  | 2000  | 3000  | 5000   | 7000   | 10,000 | 11,000 |
| 25,000                                                                | 1000 | 1000 | 1000 | 2000  | 2000  | 3000  | 5000   | 7000   | 10,000 | 12,000 |
| 30,000                                                                | 1000 | 1000 | 2000 | 2000  | 3000  | 5000  | 8000   | 11,000 | 13,000 |        |
| 35,000                                                                | 1000 | 1000 | 2000 | 3000  | 4000  | 6000  | 8000   | 11,000 | 13,000 |        |
| 40,000                                                                | 1000 | 1000 | 2000 | 3000  | 4000  | 6000  | 9000   | 11,000 | 13,000 |        |
| 50,000                                                                | 1000 | 1000 | 2000 | 3000  | 4000  | 7000  | 9000   | 12,000 | 15,000 |        |
| 60,000                                                                | 1000 | 1000 | 2000 | 3000  | 4000  | 7000  | 10,000 | 13,000 | 16,000 |        |
| 70,000                                                                | 1000 | 1000 | 2000 | 3000  | 5000  | 7000  | 10,000 | 14,000 | 17,000 |        |
| 80,000                                                                | 1000 | 2000 | 2000 | 3000  | 5000  | 8000  | 11,000 | 15,000 | 17,000 |        |
| 90,000                                                                | 1000 | 2000 | 2000 | 3000  | 6000  | 8000  | 11,000 | 15,000 | 18,000 |        |
| 100,000                                                               | 1000 | 2000 | 2000 | 4000  | 6000  | 8000  | 12,000 | 16,000 | 19,000 |        |
| 150,000                                                               | 1000 | 2000 | 3000 | 4000  | 6000  | 9000  | 13,000 | 17,000 | 22,000 |        |
| 200,000                                                               | 2000 | 2000 | 3000 | 4000  | 7000  | 9000  | 15,000 | 19,000 | 23,000 |        |

The only controlled copy of this data sheet is the electronic read-only version located on the Eaton network drive. All other copies of this document are by definition uncontrolled. This bulletin is intended to clearly present comprehensive product data and provide technical information that will help the end user with design applications. Eaton reserves the right, without notice, to change design or construction of any products and to discontinue or limit distribution of any products. Eaton also reserves the right to change or update, without notice, any technical information contained in this bulletin. Once a product has been selected, it should be tested by the user in all possible applications.

Eaton  
1000 Eaton Boulevard  
Cleveland, OH 44122  
Eaton.com  
  
Bussmann Division  
114 Old State Road  
Ellisville, MO 63021  
United States  
Eaton.com/bussmannseries

© 2023 Eaton  
All Rights Reserved  
Printed in USA  
Publication No. 1025 — BU-SB13734  
July 2023

Eaton, Bussmann and Limitron are valuable trademarks of Eaton in the U.S. and other countries. You are not permitted to use the Eaton trademarks without prior written consent of Eaton.

CSA is a registered trademark of the Canadian Standards Group.  
NEC is a registered trademark of the National Fire Protection Association, Inc.  
UL is a registered trademark of the Underwriters Laboratories, Inc.

For Eaton’s Bussmann series product information, call 1-855-287-7626 or visit: [Eaton.com/bussmannseries](https://Eaton.com/bussmannseries)

Follow us on social media to get the latest product and support information.

