





# CIRCUIT DIAGRAMED



1. MATERIALS  
CONNECTOR  
INSULATOR: HIGH TEMP THERMOPLASTIC 94V-0, BLACK.  
CONTACT: COPPER ALLOY, GOLD PLATED OVER NICKEL ON CONTACT AREA  
LATCH: STAINLESS STEEL
- 1.2 SERIAL ATA WIRESEE CABLE VENDOR  
WIRE: 2PAIR 26AWG 100 OHM.  
JACKET: PVC
- 1.3 HOOD: PE, COLOR BLACK

2. THE PRODUCT IS NOT INTENDED TO BE EXPOSED TO A MANUFACTURING SOLDER PROCESS
3. PRODUCT SPEC: GS-12-200  
PACKING SPEC: GS-14-866

4. PRODUCT NUMBERING  
10072706-XXX-XX LF - LEAD FREE

ADDITIVE CODE  
0: WIRE 26AWG

CABLE VENDOR  
A: COPARTNER (RED)

LENGTH CODE (DIM. A)

06	- 6.0	±2.50cm
13	- 13.0	±2.50cm
15	- 15.0	±2.50cm
16	- 16.0	±2.50cm
18	- 18.0	±2.50cm
20	- 20.0	±2.50cm
26	- 26.0	±2.50cm
30	- 30.0	±2.50cm
35	- 35.0	±2.50cm
50	- 50.0	±2.50cm
60	- 60.0	±2.50cm
A0	- 100.0	±2.50cm

PLATING CODE  
5-15 u' GOLD

mat'l. code				tolerances unless otherwise specified		CUSTOMER COPY	 www.fciconnect.com		
ltr	ecn no	dr	date						
A	T07-1114	S.Lin	7/16/07	linear	.X ± 0.38	projection	title S-ATA 7P SIGNAL CABLE WITH LATCH		
B	T08-1079	S.Lin	04/23/08		.XX ± 0.25				
C	T09-1070	Roger	05/10/09	angles	.XXX ± 0.10		product family S-ATA size dwg no A4 10072706		
				dr	0' ± 2"	scale N/A			
				enr	Sterling Lin 7/16/07		code TWN sheet 1 of 1		
				chr	Sterling Lin 7/16/07				
				appd	Minerva Wang 7/16/07		cage code		
sheet index	revision	C	1						

ACAD