

CUSTOMER TERMINAL	RoHS	LEAD(Pb)-FREE
Sn96%, Ag4%	Yes	Yes

more than you expect




ELECTRICAL SPECIFICATIONS @ 25°C unless otherwise noted:

PARAMETER	TEST CONDITIONS	VALUE
D.C. RESISTANCE	1-3 @20°C	0.020 ohms max.
D.C. RESISTANCE	8-11 @20°C	0.520 ohms max.
INDUCTANCE	1-3 200kHz, 100mVAC, Ls	14.00uH ±10%
SATURATION CURRENT	20% rolloff from initial	>15A
LEAKAGE INDUCTANCE	1-3 tie(8+11), 200kHz, 100mVAC, Ls	200nH max.
DIELECTRIC	1-11 1875VAC, 1 second	1500VAC, 1 minute
URNS RATIO	(8-11):(1-3)	4.42:1, ±1%

GENERAL SPECIFICATIONS:

OPERATING TEMPERATURE RANGE: -40°C to +125°C including temp rise.



Wire insulation & RoHS status not affected by wire color.
Wire insulation color may vary depending on availability.

REV.	DATE	Packaging Specifications	CONVENTION PLACEMENT	Tolerances unless otherwise specified: Angles: ±1° Fractions: ±1/64	Decimals: ±.005 [.13] Footprint: ±.005 [.13]	DRAWING TITLE	PART NO.
6B	1/11	Method: Tape & Reel PKG-0605 www.we-online.com/midcom				TRANSFORMER	750310988
6A	9/10	SEE REVISION SHEET FOR	REVISION LEVEL	This drawing is dual dimensioned. Dimensions in brackets are in millimeters.		eiSos p/n: 750310988	SPECIFICATION SHEET 1 OF 1

