X9DRD-7LN4F

Key Features

1. Dual socket R (LGA 2011) supports Intel® Xeon® processor E5-2600 and **E5-2600 v2** family†
2. Intel® C602J chipset; QPI up to 8.0GT/s
3. Up to 1TB ECC DDR3, up to 1866MHz; 16x DIMM slots
4. Expansion slots: 6 (x8) PCI-E 3.0
5. Intel® i350 GbE LAN (4 ports)
6. 4x SATA2 and 2x SATA3 ports
7. 8x SAS2 (6Gb/s) ports via LSI 2308
8. Integrated IPMI 2.0 and KVM with Dedicated LAN
9. 9x USB 2.0 ports (4 rear, 4 via header + 1 Type A)

Links & Resources

- Tested Memory List
- Tested HDD / SSD List
- Motherboard Manual
- Update Your BIOS
- IPMI Firmware
- Download the Latest Drivers and Utilities
- Download Driver CD
- Heat Sink Compatibility
- OS Compatibility
- Product Intro Video

Specifications

Product SKUs	
MBD-X9DRD-7LN4F -O	X9DRD-7LN4F (Standard Retail Pack)
MBD-X9DRD-7LN4F -B	X9DRD-7LN4F (Bulk Pack)

Physical Stats	
Form Factor	E-ATX
Dimensions	12" x 13" (30.5cm x 33.0cm)

Processor/Cache	
CPU	Dual Socket R (LGA 2011) Intel® Xeon® processor E5-2600 and **E5-2600 v2** family† (up to 135W TDP **)
Note	† BIOS version 3.0 or above is required
Note	** Motherboard supports this maximum TDP. Please verify your system can thermally support.
Cache	Up to 30MB
System Bus	QPI up to 8 GT/s

System Memory	
Memory Capacity	16x 240-pin DDR3 DIMM slots Up to 1TB DDR3 ECC LRDIMM Up to 512GB DDR3 ECC RDIMM Up to 128GB DDR3 ECC/non-ECC UDIMM
Memory Type	1866/1600/1333/1066/800MHz* ECC DDR3 SDRAM 72-bit, 240-pin gold-plated DIMMs Support ECC and non-ECC UDIMMs * Maximum memory speed may be capped by CPU. Please verify that the chosen CPU can support desired memory speed.
DIMM Sizes	32GB, 16GB, 8GB, 4GB, 2GB, 1GB, 64GB LRDIMM
Memory Voltage	1.5 V, 1.35 V
Error Detection	Corrects single-bit errors Detects double-bit errors (using ECC memory)

On-Board Devices	
Chipset	Intel® C602J chipset
SATA	SATA 2.0 3Gb/s with RAID 0, 1, 5, 10 SATA 3.0 6Gb/s with RAID 0, 1, 5, 10
SAS	SAS2 (6Gb/s) via LSI 2308 SW RAID 0, 1, 10 support
IPMI	Support for Intelligent Platform Management Interface v.2.0 IPMI 2.0 with virtual media over LAN and KVM-over-LAN support Nuvoton WPCM450 BMC
Network Controllers	Intel® i350 Quad Port Gigabit Ethernet Virtual Machine Device Queues reduce I/O overhead Supports 10BASE-T, 100BASE-TX, and 1000BASE-T, RJ45 output 1x Realtek RTL8201N PHY (dedicated IPMI)
Video	Matrox G200eW

Input / Output	
SATA	2 SATA 3.0 ports (6Gb/s) 4 SATA 2.0 ports (3Gb/s)
SAS	8 SAS2 ports (6Gb/s)
LAN	4 RJ45 Gigabit Ethernet LAN ports 1 RJ45 Dedicated IPMI LAN port
USB	9 USB 2.0 ports total (4 rear + 4 via header + 1 Type A)
Video	1 VGA port
Serial Port / Header	1 Fast UART 16550 port / 1 Header
DOM	1 DOM (Disk on Module) power connector
TPM	1 TPM 1.2 20-pin Header

Chassis (Optimized for X9DRD-7LN4F)	
1U Chassis	CSE-815TQ-600CB
2U Chassis	CSE-825TQ-R740LPB CSE-826BA-R1K28LPB CSE-826BA-R920LPB CSE-826BE16-R1K28LPB CSE-826BE16-R920LPB CSE-826BE26-R1K28LPB CSE-826BE26-R920LPB
3U Chassis	CSE-835TQ-R920B
Tower / 4U Rackmount	CSE-846BA-R1K28B CSE-846BE16-R1K28B CSE-846BE26-R1K28B CSE-847A-R1400B CSE-847A-R1K28LPB CSE-847E16-R1400B CSE-847E16-R1K28LPB CSE-847E26-R1400B CSE-847E26-R1K28LPB
Important Chassis Notes	To support the new generation Intel® Xeon® processor-based motherboards, **Revision M** chassis is recommended. Please talk to your sales representative for details. Please use optional I/O shield MCP-260-00041-0N in Supermicro 1U chassis

SuperServer(s) with X9DRD-7LN4F	
Model(s)	SYS-1027R-73DAF SYS-1027R-73DARF SYS-1027R-73DBRF SYS-6027R-73DARF

Expansion Slots	
PCI-Express	6 (x8) PCI-E 3.0 slots (Both CPUs need to be installed for full access to PCI-E slots and onboard controllers. See manual block diagram for details.)

System BIOS	
BIOS Type	128Mb SPI Flash EEPROM with AMI BIOS
BIOS Features	Plug and Play (PnP) APM 1.2 DMI 2.3 PCI 2.3 ACPI 1.0 / 2.0 / 3.0 / 4.0 BIOS rescue hot keys USB Keyboard support SMBIOS 2.7.1 UEFI 2.3.1

Management	
Software	SuperDoctor® III Watch Dog NMI IPMI 1.5 / 2.0
Power Configurations	ACPI / APM Power Management CPU Fan auto-off in sleep mode Power-on mode for AC power recovery

PC Health Monitoring	
Voltage	Monitors for CPU Cores, +1.1V, +1.5V, +3.3V, +5V, +12V, +3.3V Standby, +5V Standby, VBAT, Memory Voltages. 5+1 Phase-switching voltage regulator
FAN	8x 4-pin fan headers 8x fans with tachometer monitoring Status monitor for speed control Status monitor for on/off control Low noise fan speed control Pulse Width Modulated (PWM) fan connectors
Temperature	Monitoring for CPU and chassis environment CPU thermal trip support I^2C temperature sensing logic Thermal Monitor 2 (TM2) support PECI
LED	CPU / System Overheat LED Suspend static indicator LED UID/Remote UID
Other Features	Chassis intrusion detection Chassis intrusion header SDDC Support RoHS

Operating Environment	
Operating Temperature Range	10°C - 35°C (50°F - 95°F)
Non-Operating Temperature Range	-40°C - 70°C (-40°F - 158°F)
Operating Relative Humidity Range	8% - 90% (non-condensing)
Non-Operating Relative Humidity Range	5% - 95% (non-condensing)

Note: For optimized or compatible chassis, additional parts may be required, please check with Supermicro sales rep

Parts List

Parts List (retail)

	Part Number	Qty	Description
X9DRD-7LN4F	MBD-X9DRD-7LN4F	1	X9DRD-7LN4F Motherboard
I/O Cables	CBL-0044L	2	SATA CABLE 61CM FLAT S-S PBF
I/O Cables	CBL-0097L-03	2	30AWG 50CM Ipass to 4 SATA, W/50cm SB, S
I/O Shield	MCP-260-00042-0N	1	STD I/O shield for X9 socket R server MB with Gasket.

Optional Parts List

	Part Number	Qty	Description
Heat Sink (optional, not included)	-	-	CPU Heat Sink reference
TPM security module (optional, not included)	AOM-TPM-9655V AOM-TPM-9655H	-	TPM module with Infineon 9655, RoHS/REACH,PBF; Vertical or Horizontal depends on the server
SuperDOM	-	-	Supermicro SATA DOM Solutions [Details]

Copyright © 2015 Super Micro Computer, Inc.
Information in this document is subject to change without notice.
Other products and companies referred to herein are trademarks or registered trademarks of their respective companies or mark holders.