

TLM4036DC-0700

Description:

The TLM4036DC-0700 is a compact and lightweight Constant Current Switch Mode Power Supply. Waterproof design - IP66, NEMA 4 suitable for dry and damp locations. Convection cooled plastic housing. Some typical applications include LEDs, Lighting, etc.

Specifications (@25°C)

Electrical Specifications:

Input Voltage:	See Table
Power Factor:	>0.9 at full load, 115Vac
Output*:	.700A \pm 5%, Vout range: See Table
Efficiency:	90% Typical at full load
Maximum power:	26W
Output Current Regulation:	\pm 5%
Protection:	Short circuit protection: Auto-recovery *Subject to Max power limitations



Environmental Specifications:

Operating Temperature:	-40 to 60°C (De-rating: 1%/°C from 60-70°C)
Storage Temperature:	-40 to 80°C
Operating Humidity:	5 to 95% RH (non-Condensing)
Cooling:	Convection cooling
Vibration:	5 to 50Hz
MTBF:	>100,000 Hours at full load and 25°C ambient conditions

General Specifications:


Connections:	4in leads - Input: 18 AWG; Output: 18 AWG
Dimensions (WxLxH):	32.0x31.0x15.0mm
Weight:	25g
Warranty:	3 years @ 40°C, 100% Load

Performance Graphs:



RoHS Compliance: This power supply meets the requirements 2002/95/EC, known as the RoHS initiative.

* Upon printing, this document is considered **uncontrolled**. Please contact Triad Magnetics website for the most current version.



Vin (DC)	Vout (DC)	IDC (A)	Max Watts
40	2-32	0.700	22.4
36	2-30	0.700	21.0
32	2-28	0.700	19.6
30	2-26	0.700	18.2
28	2-24	0.700	16.8
24	2-22	0.700	15.4
15	2-12	0.700	8.4
12	2-10	0.700	7.0
10	2-8	0.700	5.6

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Triad Magnetics:](#)

[TLM4036DC-0700](#)