

A

B

C


D

A

B

C

D



spec ref	dr	Delhy Liu	2010/09/28	projection	MM	size	A4	scale	0.600
tolerance std	eng	Andy Zhuang	2017/02/28			ecn no	ELX-N-26208-1		
X	chr	-	-			rel level	Released		
X	appr	Caspar Lin	2017/02/28	product family	C&A				
surface	linear	0.X	±	Amphenol FCi	title	PwrProfile+ to Mate-N-Lok C&A	dwg no	10093606	rev
✓		0.XX	±	www.fci.com		214F-PwrProfile+ Cable Assembly			F
X	angular	0°	±°		cat. no.	-	Product - Customer Drw	sheet 1 of -	

A


B

C

D

PRODUCT NUMBER

SEE TABLE I

LABEL PRINT EXAMPLE
SEE NOTE 5

P/N AND DIMENSION TABLE I (SEE NOTE 3)

No.	FCI P/N	CUSTOMER P/N	R-STATE	DIM L	TOLERANCE
1	I0093606-40I20YYLF	TSR49334/I200 R2A	R2A	1.2 METER	+12/-0 MM
2	I0093606-40I80YYLF	TSR49334/I800 R2A	R2A	1.8 METER	+18/-0 MM
3	I0093606-40220YYLF	TSR49334/2200 R2A	R2A	2.2 METER	+22/-0 MM
4	I0093606-40300YYLF	TSR49334/3000 R2A	R2A	3 METER	+30/-0 MM
5	I0093606-40600YYLF	TSR49334/6000 R2A	R2A	6 METER	+/-60 MM

A

B

C

D

8	MATE-N-LOK TERMINAL	EA	2
7	MATE-N-LOK RECEPT. 2P HOUSING	EA	1
6	LABEL WITH PRINTING	EA	1 SEE NOTE 4
5	LABEL WITH PRINTING	EA	1
4	POWER CABLE REF P/N TFL252 I06/8	M	AR
3	H.S.T W/ADHESIVE OD:9.5MM 3:I BLACK	M	AR
2	SHRINK SLEEVE OD:9.0MM 3:I GREY	M	AR
1	PWR PROFILE+ CC CONNECTOR KITS	EA	1
No.	DESCRIPTION	UNIT	Q'TY

spec ref	dr	Delhy Liu	2010/09/28	projection	MM	size	A4	scale	0.600
tolerance std	eng	Andy Zhuang	2017/02/28			ecn no	ELX-N-26208-1		
X	chr	-	-			rel level	Released		
X	appr	Caspar Lin	2017/02/28	product family	C&A				
surface	linear	0.X	±	Amphenol FCi	title	PwrProfile+ to Mate-N-Lok C&A	dwg no	10093606	rev
		0.XX	±			2I4F-PwrProfile+ Cable Assembly			F
		0.XXX	±	www.fci.com	cat. no.	-	Product - Customer Drw	sheet 2 of 3	
X	angular	0°	±°						

2

3

PDS: Rev :F

STATUS:Released

Printed: Feb 28, 2017

A

B

C

D

PRODUCT NUMBER

SEE TABLE I

NOTES:

- END "P1" MATES WITH FCI HEADER PART NUMBER: 10089872-101LF
END "P2" MATES WITH FCI HEADER PART NUMBER: N/A
- UNLESS OTHERWISE SPECIFIED ASSEMBLED LENGTH TOLERANCE =
< 1 METER: +10.0mm / -0
1 METER TO 4 METER: +1% / -0 OF ALL LENGTHS
> 4 METER: ±1% OF ALL LENGTHS
- PART NUMBER DESCRIPTION:

BASE NUMBER

DASH NUMBER

1 0 0 9 3 6 0 6 - 4 0 X 0 0 Y Y LF

LEAD FREE (SEE NOTE 9)

SPECIAL FEATURES

Y NO APPLICABLE TO THIS ASSEMBLY

HARDWARE TYPE

Y NO HARDWARE REQUIRED

LENGTH (DIM L)

XXXX: XX METERS, XX CENTIMETERS
0300: 03 METERS, 00 CENTIMETERS
0600: 06 METERS, 00 CENTIMETERS

- LABEL POSITION SHALL BE APPROXIMATELY 50MM FROM REAR OF SHRINK SLEEVING. IF THE CABLE LENGTH IS MORE THAN 3 METER A SECOND IDENTITY LABEL SHALL BE PLACED IN END P2

WIRE SIZE(MM ²)
4 6.00 MM ²

NOTES CONTINUED:

5. LABELING SHALL BE CONTAIN:

- ERICSSON P/N AND REV
- DESCRIPTION ("POWER CABLE"), T.A. (T.A. STANDS FOR TEST APPROVED), PLACED IN RIGHT MARGIN
- MANUFACTURING WEEK, BATCH INCLUDING FACTORY CODE
- COUNTRY OF ORIGIN, ERICSSON LOGO (RIGHT MARGIN)

FONT SHALL BE CLEARLY VISABLE AND BLACK IN COLOR.

- ALL CABLE ASSEMBLIES SHALL BE TESTED 100% FOR CONTINUITY AS DEFINED IN WIRING LIST.

- UNLESS OTHERWISE SPECIFIED ALL CABLE ASSEMBLIES SHALL BE 100% HI-POT TESTED BY APPLYING 300V DC FOR MINIMUM OF 10ms, UNLESS ACTIVE COMPONENTS ARE USED IN THIS ASSEMBLY.

- THIS DIMENSION IS A FINISHED PRODUCT LENGTH.

- LEAD FREE PRODUCTS MEET EUROPEAN UNION DIRECTIVES AND OTHER COUNTRY REGULATIONS AS DESCRIBED IN GS-22-008.

- ASSEMBLY SHOWN IS FOR REFERENCE ONLY AND MAY NOT SHOW ALL PART DETAIL. REFERENCE CONNECTOR ASSEMBLY DRAWING FOR COMPLETE DETAILS.

- CABLES SHALL BE PROTECTED BY ESD PLASTIC BAG, THEN WE NEED TO PASTE A 2D LABEL ON THE BAG (THE CONTENT INCLUDE: E/// P/N AND REV, QUANTITY, BATCH NO., MAN. WEEK, COUNTRY OF ORIGIN, FACTORY CODE, ERICSSON LOGO (RIGHT MARGIN)). PACKAGING SPECIFICATIONS SHALL BE ACCORDING TO GS-14-1340.

- MATERIALS:
CABLE: UL/IEC RECONIZED, TEMP. RATING 90°C, 300V, COLOR GRAY
HOUSING: PPA, UL94V-0 GLASS FILLED, COLOR: BLACK
POWER CONTACTS: COPPER ALLOY WITH CRIMPING TYPE

- A "△" SYMBOL WILL BE NEXT TO ANY DIMENSION, VIEW, OR NOTE WHICH HAD BEEN MODIFIED WITH THE CURRENT DRAWING REVISION.

spec ref	dr	Delhy Liu	2010/09/28	projection	MM	size	A4	scale	0.600
tolerance std	eng	Andy Zhuang	2017/02/28			ecn no	ELX-N-26208-1		
X	chr	-	-	product family	C&A	rel level	Released		
X	appr	Caspar Lin	2017/02/28						
surface	linear	0.X	±	Amphenol FCI	title	PwrProfile+ to Mate-N-Lok C&A	dwg no	10093606	rev
		0.XX	±			214F-PwrProfile+ Cable Assembly			F
		0.XXX	±						
X	angular	0°	±°	www.fci.com	cat. no.	-	Product - Customer Drw	sheet 3 of 3	

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[FCI / Amphenol:](#)

[10093606-40300YYLF](#)