

Maxim > Products > Power and Battery Management > MAX1788EVSYS

MAX1788EVSYS

Evaluation System for the MAX1788

Overview

Technical Documents

Ordering Info

Related Products

User Comments (0)

All

Status

Part Number	Status
MAX1788EVKIT	Active: In Production. See Ordering Information for details.

Data Sheet

[Request Full Data Sheet](#)
[Custom Order](#)

Description

The MAX1788 evaluation system (EV system) demonstrates the capabilities of the MAX1788 advanced smart battery-pack controller. The EV kit includes multiple component networks to utilize the functionality of the PORT A (PA) I/O, high-voltage (HV) outputs, SMBus interface, and battery cell terminals. Each network can be configured to provide proper evaluation of the programmed device. An on-board low-dropout (LDO) linear regulator is also included to provide a +3.3V rail voltage and up to a 0.2A load current.

The MAX1788 EV system includes the MAX1788 EV kit and the MINIQUSB command module. The MINIQUSB provides both an SPI and SMBus interface to a PC. The supplied command module allows the kit to be evaluated with Maxim's multipurpose SMBus software (MSS), prebuilt with the MAX1788 user interface framework.

Key Features


- MINIQUSB Connectivity (SPI and SMBus Interface)
- On-Board Protection Fuse
- On-Board LDO (+3.3V, 0.2A)
- GPIO LEDs and Jumpers
- Standalone Operation
- 9V, 200mA Adapter
- Battery-Cell String Emulation
- RoHS Compliant
- Proven PCB Layout
- Fully Assembled and Tested

Software/Models

none

Ordering Information

Filters: Part Number: Package: Temperature: ☐ Tape and Reel ☐ Sample

Part Number	Free Sample	Buy	Status 	Package: TYPE PINS FOOTPRINT DRAWING CODE/VAR *	Temp	RoHS/Lead-Free? Materials Analysis
MAX1788EVKIT+		N/A	No Longer Available	KIT; Land Pattern: Not Available		See data sheet
MAX1788EVMINIQU#		<input type="button" value="Buy"/>	Active: Data sheet on request only	KIT; Land Pattern: Not Available	-40°C to +85°C	See data sheet
MAX1788EVMINIQUUSB#		N/A	No Longer Available	KIT; Land Pattern: Not Available	-40°C to +85°C	See data sheet

- Notes:
1. Other options and links for purchasing parts are listed at: <http://www.maxim-ic.com/sales>.
 2. [Didn't Find What You Need?](#) Ask our applications engineers. Expert assistance in finding parts, usually within one business day.
 3. Part number suffixes: T or T&R = tape and reel; + = RoHS/lead-free; # = RoHS/lead-exempt; -D = drypack; -U/+U on DS parts = cut tape. More: See [Full Data Sheet](#) or [Maxim Product Naming Conventions](#).
 4. * Some packages have variations, listed on the drawing. "PkgCode/Variation" tells which variation the product uses. Note that "+", "#", "-" in the part number suffix describes RoHS status. Package drawings may show a different suffix character.

Products with Similar Part Numbers

MAX1788 Advanced Smart Battery-Pack Controller

Didn't Find What You Need?

[Next Day Product Selection Assistance from Applications Engineers](#)
[Parametric Search](#)
[Applications Help](#)

Information Index

Overview

[Description](#)
[Key Features](#)
[Applications/Uses](#)
[Key Specifications](#)
[Diagram](#)
[Notes and Comments](#)

Technical Documents

[Data Sheet](#)
[Technical Documents](#)
[Evaluation Kits](#)
[Reliability Reports](#)
[Software/Models](#)

Ordering Info

[Price and Availability](#)
[Samples](#)
[Buy Online](#)
[Package Information](#)
[Lead-Free Information](#)

Related Products

[Similar Products by Function](#)
[Similar Products by Application](#)
[Evaluation Kits](#)
[Products with Similar Part Numbers](#)
[Products Used With This](#)