

MICRO SWITCH
a Honeywell Division

FED. MFG. CODE 91929

SWITCH – BASIC

CATALOG LISTING

V3-119

CK-B1900

CATALOG LISTING
V3-119
PAGE 1 OF 1

ISSUE
13

REVISIONS
A OBS
C082209
CSL
11 NOV 96
B RE-INST
PR22527
DCS
18 DEC 96

REPLACES

RELEASE NO.

CHECK



CHECK

CHECK

CHECK

CHECK

CHECK




NOTE
1 – TERMINALS ARE PLATED FOR SOLDERING

ANSI Y14.5M-1982 APPLIES

THIS DRAWING COVERS A PROPRIETARY ITEM AND IS THE PROPERTY OF MICRO SWITCH, A DIVISION OF HONEYWELL. THIS DRAWING IS NOT TO BE COPIED OR USED WITHOUT THE APPROVAL OF MICRO SWITCH.

THIRD ANGLE PROJECTION



CHARACTERISTICS	ELECTRICAL DATA	SCALE FULL	DO NOT SCALE PRINT
OPERATING FORCE — — — — 8 OZ MAX	CONTACT ARRANGEMENT S P D T	UNLESS OTHERWISE SPECIFIED TOLERANCES ARE	
RELEASE FORCE — — — — 2 OZ MIN	L156 11A 1/3HP 125, 250 OR 277 VAC 1/2A 125 VDC, 1/4A 250 VDC 4A 125 VAC "L"	ONE PLACE (.0)	±.030
DIFFERENTIAL TRAVEL — — — .006-.016		TWO PLACE (.00)	±.015
OVERTRAVEL — — — — .040 MIN		THREE PLACE (.000)	±.005
FREE POSITION — — — — .625 MAX		ANGLES	±
RELEASE TRAVEL — — — — .007 MIN	WEIGHT .016 LB		



DDM/CAD

DRAWN

18 DEC 96

DCS