


# ALUMINUM ELECTROLYTIC CAPACITORS

nichicon

**ZD** 3.0mmL Chip Type  
series



- Chip type with 3.0mmL height.
- Designed for surface mounting on high density PC board.
- Applicable to automatic mounting machine fed with carrier tape.
- Compliant to the RoHS directive (2011/65/EU).




## ■ Specifications


Item	Performance Characteristics												
Category Temperature Range	-40 to +85°C												
Rated Voltage Range	4 to 25V												
Rated Capacitance Range	2.2 to 100μF												
Capacitance Tolerance	±20% at 120Hz, 20°C												
Leakage Current	After 2 minutes' application of rated voltage, leakage current is not more than 0.01 CV or 3 (μA), whichever is greater.												
Tangent of loss angle (tan δ)	Rated voltage (V)	4	6.3	10	16	25	120Hz 20°C						
	tan δ (MAX.)	0.50	0.40	0.30	0.24	0.19							
Stability at Low Temperature	Rated voltage (V)	4	6.3	10	16	25	120Hz						
	Impedance ratio ZT / Z20 (MAX.)	Z-25°C / Z+20°C Z-40°C / Z+20°C	7 15	4 8	3 8	2 4							
Endurance	The specifications listed at right shall be met when the capacitors are restored to 20°C after the rated voltage is applied for 1000 hours at 85°C.				Capacitance change	Within ±30% of the initial capacitance value							
					tan δ	300% or less than the initial specified value							
					Leakage current	Less than or equal to the initial specified value							
Shelf Life	After storing the capacitors under no load at 85°C for 1000 hours and then performing voltage treatment based on JIS C 5101-4 clause 4.1 at 20°C, they shall meet the specified values for the endurance characteristics listed above.												
Resistance to soldering heat	The capacitors are kept on a hot plate for 30 seconds, which is maintained at 250°C. The capacitors shall meet the characteristic requirements listed at right when they are removed from the plate and restored to 20°C.				Capacitance change	Within ±10% of the initial capacitance value							
Marking					tan δ	Less than or equal to the initial specified value							
					Leakage current	Less than or equal to the initial specified value							
Marking													
Black print on the case top.													

## ■ Chip Type

Voltage (C : 16V)	Series	Capacitance
Lot No.		
+	A2	10C
-	ZD	
Voltage		
V	4	6.3
Code	g	j
	A	C
	C	E



## Type numbering system (Example : 16V 10μF)



## ■ Dimensions

Cap. (μF)	V	4	6.3	10	16	25
	Code	0G	0J	1A	1C	1E
2.2	2R2					4
3.3	3R3					7
4.7	4R7					4
5.6	5R6					11
6.8	6R8					4
10	100					16
22	220	4	20	5	28	5
33	330	5	28	5	37	23
47	470	5	33	6.3	45	6.3
100	101	6.3	56	6.3	70	27
						Case size φD (mm)
						Rated ripple mAmps

Rated ripple current (mAmps) at 85°C 120Hz

## ■ Frequency coefficient of rated ripple current

Frequency	50 Hz	120 Hz	300 Hz	1 kHz	10 kHz or more
Coefficient	0.70	1.00	1.17	1.36	1.50

- Taping specifications are given in page 23.
- Recommended land size soldering by reflow are given in page 18,19.
- Please refer to page 3 for the minimum order quantity.