

Glenair Connector
Designator E

MIL-DTL-26500

MS27291-401

Basic Part No.

Dash No.

**INACTIVE FOR
NEW DESIGN OR
MODIFICATION
OF EXISTING
EQUIPMENT**




TABLE I

Dash No. For Use With Class Connectors			Shell Size Ref.	A Thread Class 2B	C Max	E		F Max	G Dia	
R and F	G					±.015	(.4)		±.005	(.1)
1	101	10		.562 - 24 UNEF	.731 (18.6)	.935	(23.7)	.914 (23.2)	.270	(6.9)
2	201	12		.750 - 20 UNEF	.919 (23.3)	.935	(23.7)	1.026 (26.1)	.400	(10.2)
3	301	14		.812 - 20 UNEF	.981 (24.9)	1.170	(29.7)	1.090 (27.7)	.460	(11.7)
4	401	16		.938 - 20 UNEF	1.106 (28.1)	1.170	(29.7)	1.250 (31.8)	.610	(15.5)
5	501	18		1.062 - 18 UNEF	1.231 (31.3)	1.170	(29.7)	1.358 (34.5)	.690	(17.5)
6	601	22		1.312 - 18 UNEF	1.481 (37.6)	1.170	(29.7)	1.604 (40.7)	.940	(23.9)
13	701	8		.438 - 28 UNEF	.606 (15.4)	.935	(23.7)	.789 (20.0)	.186	(4.7)
14	801	20		1.188 - 18 UNEF	1.356 (34.4)	1.170	(29.7)	1.481 (37.6)	.816	(20.7)
15	901	24		1.438 - 18 UNEF	1.606 (40.8)	1.170	(29.7)	1.729 (43.9)	1.066	(27.1)

1. For complete dimensions see applicable Military Specification.
2. Metric dimensions (mm) are indicated in parentheses.
3. Finish: Anodize.