




NOTES:	31-70257		REVISIONS			
	DRAWING NO.	REV	DESCRIPTION	DATE	ECO	APPR
	THIRD ANGLE PROJ.	A	RELEASE TO MFG.	3/6/02	43986	CPM


1. MATERIALS OF CONSTRUCTION:
SHELL, BODY, BARREL, FERRULE & RETAINER RING = BRASS (ASTM-B16 H02, C36000), NICKEL PLATED (.000100 MIN THICK)
CONTACT PIN = BRASS (ASTM-B16 H02, C36000), GOLD PLATED (.000030 MIN THICK)
WASHER = BRASS (QQ-B-613), NICKEL PLATED (.000100 MIN THICK)
SPRING = COPPER ALLOY, NICKEL PLATED (.000200 MIN THICK)
INSULATOR = PTFE (ASTM D 1710 OR EQUIV.)
GASKET = SILICONE RUBBER, COLOR RED

2. CRIMPED FERRULE = HEX CRIMP SIZE .278




SCALE 2.000





RECOMMENDED CABLE STRIPPING DIMENSIONS
SCALE 3.000



CUSTOMER OUTLINE DRAWING
ALL OTHER SHEETS ARE FOR INTERNAL USE ONLY

UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN INCHES AND TOLERANCES ARE: 0.5 - 6mm ±0.2mm 6 - 30mm ±0.4mm 30 - 120mm ± 0.6mm	MATERIAL	DRAWN C. McGRATH	DATE 3/5/02	TITLE MINI BNC CRIMP PLUG (FOR 1694A CABLE)			Amphenol Amphenol Corporation Communication and Network Products Division Danbury, CT U.S.A. 06810		
		ENGINEER O. BARTHELMES	DATE 3/5/02						
NOTICE - These drawings, specifications, or other data (1) are, and remain the property of Amphenol Corp. (2) must be returned upon request; and (3) are confidential and not to be disclosed to any person other than those to whom they are given by Amphenol Corp. The furnishing of these drawings, specifications, or other data by Amphenol Corp., or to any other person to anyone for any purpose is not to be regarded by implication or otherwise in any manner licensing, granting rights or permitting such holder or any other person to manufacture, use or sell any product, process or design, patented or otherwise, that may in any way be related to or disclosed by said drawings, specifications, or other data.	REFERENCE EAR 537 GEN# 31-70260_ASSY	APPROVED O. BARTHELMES	DATE 3/6/02				SCALE: 4.0:1		
		CAD FILE I:\BNC75\31-70257			CODE ID 74868	DWG SIZE B	DRAWING NO. 31-70257		REV A